



Case	Load	Unit	LF1	LF2	LF3	LF4
Difference absolute	40%	deg	-0.06	-0.12	-0.23	-0.03
	60%	deg	-0.08	-0.15	-0.32	-0.14
	80%	deg	-0.10	-0.13	-0.41	-0.21
	100%	deg	-0.13	-0.11	-0.51	-0.30
Difference relative	40%	%	30.5	20.2	43.8	3.9
	60%	%	26.1	15.6	41.4	15.0
	80%	%	22.9	9.8	39.0	16.4
	100%	%	22.7	6.6	38.7	19.4

Case	Load	Unit	LF1	LF2	LF3	LF4
Difference absolute	40%	deg	-0.06	-0.16	-0.53	-0.75
	60%	deg	-0.07	-0.20	-0.60	-1.01
	80%	deg	-0.08	-0.24	-0.59	-1.25
	100%	deg	-0.09	-0.28	-0.50	-1.46
Difference relative	40%	%	44.0	44.8	35.4	59.3
	60%	%	32.9	35.6	25.0	51.5
	80%	%	27.0	32.0	17.7	47.1
	100%	%	24.9	30.0	11.7	43.7

Case	Load	Unit	LF1	LF2	LF3	LF4
Difference absolute	40%	deg	-0.04	-0.03	-0.18	-1.26
	60%	deg	-0.04	-0.01	-0.14	-1.50
	80%	deg	-0.05	0.01	-0.10	-1.63
	100%	deg	-0.05	0.03	-0.05	-1.68
Difference relative	40%	%	36.1	9.4	17.0	45.5
	60%	%	24.1	2.0	9.1	34.7
	80%	%	19.4	-1.5	4.7	27.9
	100%	%	15.8	-3.7	1.8	22.8