

Interactive comment on “Aero-elastic Wind Turbine Design with Active Flaps for AEP Maximization” by Michael K. McWilliam et al.

Michael K. McWilliam et al.

mimc@dtu.dk

Received and published: 1 February 2018

In response to p1. "The state-of-the-art reference is 8 years old (Barlas and Kuik)." and " p1. Barlas eta al Barlas et al (repetition)" _____

The following articles will be added:

Johnson, Scott J. et al. “An Overview of Active Load Control Techniques for Wind Turbines with an Emphasis on Microtabs.” Wind Energy 13.2-3 (2010): 239–253.

Bernhammer, L. O., G. A. M. van Kuik, and R. De Breuker. “How Far Is Smart Rotor Research and What Steps Need to Be Taken to Build a Full-Scale Prototype?” Journal of Physics. Conference Series 555.1 (2014): 012008.

Chen, Z. J., K. A. Stol, and S. R. Mace. "Wind Turbine Blade Optimisation with Individual Pitch and Trailing Edge Flap Control." *Renewable Energy* 103 (2017): 750–765.

Smit, Jeroen et al. "Sizing and Control of Trailing Edge Flaps on a Smart Rotor for Maximum Power Generation in Low Fatigue Wind Regimes." *Wind Energy* 16.4 (2016): 607–624.

Repetition is addressed by adding more articles to the revised manuscript

"p3.25-30 The loads of this design were used as constrained: Do the authors mean the ultimate and the fatigue loads or the loads per wind speed?" _____

The fatigue loads are ignored in this optimization due to the added difficulties of optimization with turbulence. This optimization did not consider the use of flaps for fatigue reduction, so it was not considered important to assess quasi-static actuation of flaps. In the revised manuscript, this clarification will be made.

More details on the load cases:

We use a reduced DLB similar to the one that was developed by Pavese:

Pavese, C.; Tibaldi, C.; Larsen, T. J.; Kim, T. & Thomsen, K. Reduced Design Load Basis for Ultimate Blade Loads Estimation in Multidisciplinary Design Optimization Frameworks *Journal of Physics: Conference Series*, 2016, 753, 062005

For this work the following load cases are used:

DLC 1.2 Regular Operation - Note: without turbulence to acquire steady state response,

DLC 1.3 Extreme Turbulence - Note: this is performed with an extreme gust to mimic the elevated loads seen from turbulence

[Printer-friendly version](#)

[Discussion paper](#)



DLC 2.1 Grid Loss

DLC 2.2b Blade Stuck

DLC 5.1 Emergency Shutdown

DLC 6.1 Parked in extreme winds

DLC 6.2 Parked grid loss

DLC 6.3 Parked with large yaw error

We constrained the root bending loads, tower top thrust, tower bottom moment, then the sectional forces in the blades are used to calculate the ultimate stress in the cross section.

These are typically the load cases that produce the highest loads. The load cases are simplified by not including turbulence. When turbulence is included, local minima occur and the optimization does not progress far. A consequence of this simplification is that the simulated loads are lower in this simplified DLB than in a Full DLB. This discrepancy is resolved by constraining relative increases instead of absolute values. In other words the loads are not allowed to increase. In practice this has proven reliable in a number of projects including the recent re-design of the DTU 10MW that was published in Torque 2016

p3.35 The flaps are controlled with respect to the wind speed. Do the authors mean the hub height inflow or the local sectional wind speed where the flaps operate? _____

The flaps are controlled based on the low-pass filtered inflow wind speed. So this would correspond to the hub-height inflow. This will be clarified in the revised manuscript.

p4.5 industrial industrial (repetition) _____

[Printer-friendly version](#)

[Discussion paper](#)



This will be corrected in the revised manuscript

p6. Table 5 The optimizer finds a very high tip speed for the blades. This can lead to leading edge erosion (and noise, which would be a lesser issue offshore). Did the authors study how limiting the tip speed would change the optimized design? _____

We agree that the high tip-speed-ratio is unrealistic due to erosion and noise issues. Of course it would be more realistic to have a noise model or an erosion model in the optimization to push the tip speed down. Otherwise the next option is to constrain the tip speed explicitly. However we chose not to include these options to see where the optimization would go. The drag from the large deflections in the flap may push the optimization to lower tip-speed ratios, which we see in the co-design.

In the revised manuscript, we will mention the erosion and noise issues of such a high tip-speed-ratio and state that these considerations were ignored.

p6.15-17 The authors mention profile drag. For the operation of (discrete) flaps also induced drag of the flaps should be taken into account. A reference to the near wake model would be good. _____

Induced drag was not included in this analysis. However, we feel this is a secondary effect and can be safely ignored.

In the revised manuscript it will be stated that the near-wake model of HAWC2 was not used in this work and thus induced drag ignored.

p6. The co-optimization finds higher deflection angles for the flaps without increasing the power. Is there a benefit that is hidden to the reviewer that could point towards using a combined optimization or are the results from the baseline with flap more realistic for actual applications? _____

[Printer-friendly version](#)[Discussion paper](#)

One of the goals of the study was to investigate whether an "add-on" application was sub-optimal compared to fully integrated design. So we were approaching this research question without any assumptions or insights.

There could be benefits to co-design but they are also hidden from the authors. By the fact that the benefits are not obvious in the optimization results, it indicates that those benefits are smaller than the combined error in the models and the optimization, thus, not revealed with these tools. Thus, for this particular design problem, it seems that a sequential optimization is at least sufficient if not better since it is easier and the blade is still optimal in non-flap applications.

Additional interactions may arise that may lead to a better co-design solutions if the flap is used for more functions and/or more flap design variables (width, length, position, etc.) are exposed. So we think further investigation is needed. We intend on performing further studies, however, we have to address some additional challenges in optimization first.

On page 9, line 10, we state that there are only small benefits to co-design. Thus, it seems nothing should be added to the manuscript to address this comment.

Summary of proposed revisions to the manuscript _____

- More references will be added to the manuscript
- It will be clarified that the ultimate loads were constrained but not fatigue for two reasons. Turbulence effects are difficult to include in optimization and turbulence was not considered important for evaluating the quasi-static actuation of flaps.
- It will be clarified that the flaps were actuated according to the hub-height wind speed.
- repeated word industrial deleted.
- State that the high tip-speed-ratio would lead to greater noise and erosion issues and

[Printer-friendly version](#)

[Discussion paper](#)



that these issues were ignored in the optimization.

- State that induced drag was ignored.

Interactive comment on Wind Energ. Sci. Discuss., <https://doi.org/10.5194/wes-2017-50>, 2017.

Printer-friendly version

Discussion paper

