

Is the Blade Element Momentum Theory overestimating Wind Turbine Loads? – An Aeroelastic Comparison between OpenFAST’s AeroDyn and QBlade’s Lifting Line Free Vortex Wake Method

Perez-Becker Sebastian¹, Papi Francesco², Saverin Joseph¹, Marten David¹, Bianchini Alessandro², and Paschereit Christian Oliver¹

¹Chair of Fluid Dynamics, Hermann Föttinger Institute, Technische Universität Berlin, Berlin, Germany

²Department of Industrial Engineering, Università degli Studi di Firenze, Florence, Italy

Correspondence: Sebastian Perez-Becker (s.perez-becker@fd.tu-berlin.de)

Abstract. Load calculations play a key role in determining the design loads of different wind turbine components. To obtain the aerodynamic loads for these calculations, the industry relies heavily on the Blade Element Momentum (BEM) theory. BEM methods use several engineering correction models to capture the aerodynamic phenomena present in Design Load Cases (DLCs) with turbulent wind. Because of this, BEM methods can overestimate aerodynamic loads under challenging conditions when compared to higher-order aerodynamic methods – such as the Lifting Line Free Vortex Wake (LLFVW) method – leading to unnecessarily high design loads and component costs. In this paper, we give a quantitative answer to the question of load overestimation of a particular BEM implementation by comparing the results of aeroelastic load calculations done with the BEM-based OpenFAST code and the QBlade code which uses a particular implementation of the LLFVW method. We compare extreme and fatigue load predictions from both codes using 66 ten-minute load simulations of the DTU 10 MW Reference Wind Turbine according to the IEC 61400-1 power production DLC group.

Results from both codes show differences in fatigue and extreme load estimations for the considered sensors of the turbine. LLFVW simulations predict 9% lower lifetime Damage Equivalent Loads (DELs) for the out-of-plane blade root and the tower base fore-aft bending moments, when compared to BEM simulations. The results also show that lifetime DELs for the yaw bearing tilt- and yaw moments are 3% and 4% lower when calculated with the LLFVW code. An ultimate state analysis shows that extreme loads of the blade root out-of-plane bending moment predicted by the LLFVW simulations are 3% lower than the moments predicted by BEM simulations. For the maximum tower base fore-aft bending moment, the LLFVW simulations predict an increase of 2%. Further analysis reveals that there are two main contributors to these load differences. The first is the different way both codes treat the effect of the non-uniform wind field on the local blade aerodynamics. The second is the higher average aerodynamic torque in the LLFVW simulations. It influences the transition between operating modes of the controller and changes the aeroelastic behavior of the turbine, affecting the loads.

1 Introduction

Load calculations are an essential process when designing large modern wind turbines. With the help of such simulations, turbine designers are able to derive the design loads for each of the turbine's components. International guidelines and standards prescribe for each load calculation loop a large number of aeroelastic simulations of the complete turbine (IEC 61400-1 Ed. 3).
5 These simulations, or Design Load Cases (DLCs), are required in order to cover many possible situations that the wind turbine might encounter in its lifetime and hence calculate realistic loads. In the case of turbulent wind simulations, several repetitions of individual DLCs with different wind realizations are required to limit the effect of statistical outliers and obtain converged results. The current industry trend is to design ever larger wind turbines with increasingly long and slender blades. As the wind turbines become larger, the design loads of each component scale accordingly (Jamieson, 2018). This leads to increased
10 material requirements and ultimately to higher component costs. Given this fact, there is a large incentive to calculate the components' loads as accurately as possible. Differences in load estimations on these large, multi MW scales can result in a considerable reduction in material use and consequently component costs.

Current aeroelastic codes rely mostly on the Blade Element Momentum (BEM) aerodynamic model (Hansen, 2008; Burton et al., 2011) to calculate aerodynamic loads. BEM models are computationally inexpensive but require a series of engineering
15 corrections to model the more challenging unsteady aerodynamic phenomena usually present in the DLCs. This can lead to inaccurate predictions of the turbine's design loads. The advantages of BEM methods have become less compelling because of the increase in available computational power. For the same reason, methods with higher-order representations of the unsteady aerodynamics have become more attractive. Vortex methods such as the Lifting Line Free Vortex Wake (LLFVW) aerodynamic model are able to model the turbine wake and its interaction with the turbine directly instead of relying on momentum
20 balance equations – as BEM models do. Therefore, LLFVW models are able to calculate unsteady aerodynamics with far less assumptions than BEM models (Hauptmann et al., 2014; Perez-Becker et al., 2018). Using more accurate aerodynamic methods lowers model uncertainty, potentially lowering design loads and safety factors and ultimately leading to more competitive turbine designs.

Over the past years, there have been several studies comparing BEM models with higher-order vortex models. In (Madsen
25 et al., 2012), Madsen et al. compare the predictions of several BEM-based codes, vortex-based codes and CFD-based codes. They find that under uniform conditions, the considered codes predict similar power and thrust. This changes when sheared inflow conditions are simulated. Here, the differences in the predicted power, thrust and load variation between the codes are larger. In (Qiu et al., 2014), the authors present a LLFVW method and analyze the unsteady aerodynamic loads in yawing and pitching procedures. In (Marten et al., 2015), Marten et al. use the LLFVW method implemented in the aeroelastic code
30 QBlade (Marten et al., 2013b, a) to simulate the MEXICO (Snel et al., 2009) and the NREL Phase IV (Simms et al., 2001) experiments. They compare the results to experimental data and to predictions from other BEM and vortex codes, showing good agreement with the experimental results.

Several authors have also done aeroelastic comparative studies. In (Voutsinas et al., 2011), Voustinas et al. analyze the aeroelastic effect of sweeping a turbine blade backwards. For the NREL/UPWIND 5 MW Reference Wind Turbine (RWT)

(Jonkman et al., 2009), they compare the loads predicted with a BEM method and GENUVP – a lifting surface method coupled with a vortex particle representation of the wake (Voutsinas, 2006). Jeong et al. extended the study from (Madsen et al., 2012) by considering flexibility in their turbine model as well as inflow conditions with turbulent wind (Jeong et al., 2014). They find that for lower wind speeds (i.e. optimal tip speed ratios and higher), there are noticeable differences in the predicted loads from
5 BEM and LLFVW methods. For higher wind speeds though (i.e. low tip speed ratios), these differences decrease due to the overall smaller axial induction factors.

Other comparisons of vortex and BEM methods are done in (Hauptmann et al., 2014; Boorsma et al., 2016). Here, the authors compare the aeroelastic predictions of LLFVW and BEM methods for several load cases. Both studies conclude that for their considered cases the LLFVW method predicts lower load fluctuations. Chen et al. perform a study of the NREL 5
10 MW RWT considering yawed and shared inflow using a free wake lifting surface model and a geometrically exact beam model (Chen et al., 2018). Saverin et al. couple in (Saverin et al., 2016a) the LLFVW method from QBlade to the structural code of FAST (Jonkman and Buhl, 2005). The authors use the NREL 5 MW RWT and compare the loads predicted by the LLFVW method and AeroDyn – the BEM code used in FAST (Moriarty and Hansen, 2005) – showing significant differences in loading and controller behavior. Large differences can also be seen in (Saverin et al., 2016b). Here, Saverin et al. combine QBlade’s
15 LLFVW method and a structural model with a geometrically exact beam model for the rotor blade. Load case simulations are also performed by Perez-Becker et al. in (Perez-Becker et al., 2018). Here, the authors simulate the DTU 10 MW RWT (Bak et al., 2013) in power production DLCs as defined in (IEC 61400-1 Ed. 3) including wind shear, yaw error and turbulent inflow conditions. They conclude that for wind speeds above rated wind, the BEM-based aeroelastic code FAST predicts higher fatigue loading and pitch activity than the LLFVW-based code QBlade.

20 A hybrid implementation of BEM method for the far wake and a lifting line vortex method for the near wake is presented in (Pirrung et al., 2017). Here, Pirrung et al. compare the predictions of their hybrid near-wake model to a pure BEM method and the lifting-surface free-wake method GENUVP. Results from pitch step responses and prescribed vibration cases for the NREL 5 MW RWT show that the near-wake method agrees much better with the lifting-surface free-wake method than with the pure BEM method.

25 So far, most of the studies comparing loads have focused on specific scenarios, simulating turbines under idealized inflow conditions or using a small number of turbulent load cases. If we wish to answer quantitatively how the results of load calculations differ when we use BEM-based and LLFVW-based methods, we need a large number of turbulent DLCs to level out statistical biases of individual realizations. Many of the mentioned studies also do not include the direct interaction with the turbine controller. Wind turbine load calculations are aero-servo-elastic in nature and the predicted loads are a result of
30 the interaction of the aerodynamics with the turbine structure and controller. Not taking this interaction into account gives an incomplete picture of the effect that different aerodynamic models have on the design loads of the wind turbine.

In this paper, we compare the results of aero-servo-elastic load calculations for the DTU 10 MW RWT. The turbine is simulated according to the IEC 61400-1 ed.3 DLC groups 1.1 and 1.2 using two different aeroelastic codes: NREL’s BEM-based OpenFAST v.2.2.0 (OpenFAST) and TU Berlin’s LLFVW-based QBlade. Fatigue and extreme loads of key turbine
35 sensors, derived from 66 ten-minute simulations covering a wind speed range between 4 m/s and 24 m/s, are compared and

analyzed. Section 2 gives an overview of the aerodynamic and structural codes as well as the controller used in this study. A baseline comparison of the codes under idealized inflow conditions is done in Sect. 3, where we compare the performance of our turbine when calculated with both codes. Sections 4 to 6 contain the main contribution of this paper: a comparison and analysis of the results of load calculations with turbulent wind using both codes. Section 4 presents the considered sensors and gives an overview of the results. Section 5 presents, analyses and discusses the fatigue loads. An ultimate load analysis including discussion is presented in Sect. 6 and the conclusions are drawn in Sect. 7.

2 Methods

For this study, we chose to use the DTU 10 MW RWT. It is representative of the new generation of wind turbines and has been used in several research studies. The complete description of the turbine can be found in (Bak et al., 2013).

The following subsections briefly present the methods used for aerodynamic and structural modeling, the turbine controller and the setup used for the load simulations.

2.1 Aerodynamic Models

OpenFAST and QBlade are set up so that their only difference is the implemented aerodynamic model. OpenFAST uses AeroDyn – an implementation of the BEM method – and QBlade uses an implementation of the LLFVW method. The following subsections describe the details of these two particular implementations of the BEM and LLFVW methods.

2.1.1 Blade Element Momentum-Method

The BEM method calculates the aerodynamic loads by combining the blade element theory and the momentum theory of an actuator disc to obtain the induced velocities on every discretized element of the blades (Moriarty and Hansen, 2005). The turbine rotor is divided into independently-acting annuli. For each annulus, the thrust and torque obtained from 2D airfoil polar data of the blade element is equated to the thrust and torque derived from the momentum theory of an actuator disc (Burton et al., 2011). This set of equations can be solved iteratively to obtain the forces and moments on each blade element. This theory is only valid for uniform aligned flows in equilibrium. Several correction models have been developed to extend the BEM method so that more challenging aerodynamic situations can be modelled. The correction models are summarized in Table 1. Details for the implementation of the tip- and root-loss model, the turbulent wake state model, the oblique inflow model, the dynamic stall model and the tower shadow model in OpenFAST can be found in (Moriarty and Hansen, 2005). The other correction models are briefly mentioned below.

– **Wake memory effect:** This correction is needed to model the additional time required by the flow to adapt when sudden changes in pitch angle, rotational speed or wind speed occur at the rotor plane. This additional time comes from the interaction of the flow with the rotor wake. OpenFAST recently introduced this feature via the optional Dynamic BEM Theory (DBEMT) module. It is the model by Øye presented in (Snel and Schepers, 1995) that filters the induced velocities via two first-order differential equations.

– **Stall delay:** Blade Element Theory assumes no interaction between the blade elements. For rotating airfoils in the inner part of a wind turbine blade there is a significant amount of radial flow. This phenomenon delays the effective angle of attack at which the airfoil stalls (when compared to the 2D airfoil polar data). OpenFAST does not have an explicit model for stall delay. Instead, the airfoil polar data has to be pre-processed using an appropriate model before it is implemented in the code. For this study we used the 3D-corrected airfoil polar data presented in (Bak et al., 2013). The corrected airfoil data was obtained using the method described in (Bak et al., 2006).

2.1.2 Lifting Line Free Vortex Wake-Method

The LLFVW-method is based on inviscid potential flow theory and a vortex representation of the flow field (Van Garrel, 2003; Marten et al., 2015). In the implementation found in QBlade, the rotor blade is discretized into elements represented by bound ring vortices. These bound vortices are located the quarter chord position and their sum make up a lifting line. By using the Kutta-Joukowski theorem and the airfoil polar data corresponding to the blade element we can calculate the circulation of the bound vortices:

$$\Gamma = \frac{L}{|\mathbf{V}_{tot}|\rho} = C_l(\alpha) \frac{1}{2} |\mathbf{V}_{tot}| \cdot c. \quad (1)$$

In this equation, Γ is the circulation of the blade element, L is the lift per unit length, ρ the density, \mathbf{V}_{tot} the total velocity, C_l the lift coefficient, α the angle of attack and c the local chord. The total velocity is the sum of the incoming velocity \mathbf{V}_∞ , the velocity due to the motion of the blade (rotation / deflection) \mathbf{V}_{mot} and the induced velocity from the wake \mathbf{V}_Γ :

$$\mathbf{V}_{tot} = \mathbf{V}_\infty + \mathbf{V}_{mot} + \mathbf{V}_\Gamma. \quad (2)$$

The induced velocity from all the vortex elements in the wake can be calculated by applying the Biot-Savart Law at each blade element:

$$\mathbf{V}_\Gamma(\mathbf{x}_p) = -\frac{1}{4\pi} \int \Gamma \frac{(\mathbf{x}_p - \mathbf{x}) \times d\mathbf{l}}{|\mathbf{x}_p - \mathbf{x}|^3}. \quad (3)$$

Here, \mathbf{x}_p is the control point where the Biot-Savart Law is evaluated (e.g. the blade element), \mathbf{x} is the position of each of the wake vortices and $d\mathbf{l}$ their vectorized length.

Equations (1 – 3) can be solved iteratively to obtain the circulation, the induced velocity and the forces at each blade element. At each time step, the circulation is shed to the wake creating trailing and shed vortices. The former arise from the spanwise variation of the circulation and the latter from the temporal variation. By applying Eq. (3) to the wake vortices, the free convection of the wake can be modelled.

In order to avoid a singularity when evaluating Eq. (3) at the vortex centers, the vortex core model proposed by van Garrel was used (Van Garrel, 2003; Marten et al., 2015). The initial vortex core size was set to be 0.3 times the local chord length of the blade element and was used for bound and wake vortices. This initial value was determined based on a preliminary sensitivity study with idealized wind conditions. Figure 1 shows a closeup of a wind turbine blade during a LLFVW simulation using the aero-servo-elastic code QBlade. It includes the concepts explained in this section.




Figure 1. Representation of the LLFVW method and concepts on a wind turbine blade.

While capturing the flow physics of a wind turbine rotor much more accurately, LLFVW methods still use some correction models to account for all the aerodynamic phenomena present in turbulent load calculations, briefly explained here:

- **Dynamic stall:** Because of the potential flow assumption and the use of airfoil polar data, a model is needed to account for the flow separation phenomenon. QBlade’s LLFVW method uses the ATEFlap unsteady aerodynamic model (Bergami and Gaunaa, 2012), modified so that it excludes contribution of the wake in the attached flow region (Wendler et al., 2016).
- **Tower shadow:** The effect of the tower on the blade aerodynamics also has to be taken into account explicitly in the LLFVW simulations via an engineering model. QBlade uses the same potential flow model that is also used in OpenFAST (Bak et al., 2001).
- **Stall delay:** As with the BEM method, the stall delay phenomenon is included via modified airfoil polar data using an appropriate model. We used the same 3D-corrected airfoil polar data in both codes. The data was obtained with the method described in (Bak et al., 2006).

2.1.3 Comparison between the Aerodynamic Models

Table 1 summarizes the differences between the two aerodynamic models. The LLFVW method explicitly includes most of the phenomena present in DLC simulations with turbulent wind conditions. Usual DLC configurations include sheared and oblique inflow as well as temporal and spatial variations of the incoming wind speed. Unlike the BEM method that solves for the axial and tangential induction factors at each blade element, the LLFVW method solves for the complete flow around the rotor.

Turbine configurations can have coned blades. Including cone angles, as well as the blade pre-bend and blade deflections in the case of aeroelastic calculations, violates the assumption made in many BEM methods that the momentum balance takes place in independent acting annuli in the rotor plane. Recently, Madsen et al. proposed in (Madsen et al., 2020) a

Table 1. Modeling differences of the two aerodynamic codes. I = Intrinsic; EM = Engineering Model

Aerodynamic Phenomenon	BEM	LLFVW
Axial/Tangential induction	I	I
Radial induction	-	I
Tip- and root-loss	EM	I
Oblique inflow	EM	I
Turbulent wake state	EM	I
Wake memory effect	EM	I
Stall delay	EM	EM
Dynamic stall	EM	EM
Tower shadow	EM	EM

BEM method that can model the effect of coned blades and radial induction. These corrections are not included in other BEM implementations such as AeroDyn. Thus, aerodynamic load predictions for the turbulent load cases obtained from the considered LLFVW method are expected to be more accurate compared to predictions from the considered BEM method. The radial induction mentioned in Table 1 comes from the effect of the trailing vortices in the wake.

5 2.2 Structural Model

The structural model used for this study in both OpenFAST and QBlade is ElastoDyn (Jonkman, 2014). It uses a combined multi-body and modal dynamics representation that is able to model the wind turbine with flexible blades and tower (Jonkman, 2003). The modal representation of blades and tower uses an Euler-Bernoulli beam model to calculate deflections. It also includes corrections to account for geometrical non-linearities. The structural model allows for four tower modes: the first two fore-aft and side-side modes respectively. As for the blade, three modes are modelled in ElastoDyn: the first and second flapwise modes and the first edgewise mode. The structural model does not take into account shear deformation, axial and torsional degrees of freedom.

Both OpenFAST and QBlade have additional models that allow for a more accurate representation of the wind turbine structural dynamics. The module BeamDyn in OpenFAST is able to model the blade as a geometrically exact beam (Wang et al., 2016) and QBlade has a structural solver based on the open source multi-physics library CHRONO (Tasora et al., 2016). The latter uses a multi-body representation which includes Euler-Bernoulli beam elements in a co-rotational formulation. More accurate representations of the structural deflection of the wind turbine – in particular blade torsional deflection – have a significant influence on the loads. Torsional deflection changes the local angle of attack of a blade section and hence the lift force. This can lead to very different blade dynamics when compared to a model that does not include this degree of freedom. Nonetheless, we decided to use ElastoDyn as the structural model for our study. It is shared by both aeroelastic codes so by

using it, we keep the modeling differences only in the aerodynamic module and ensure that the latter is the only source of the load differences.

2.3 Controller

To enable aero-servo-elastic studies, we implemented a wind turbine controller that is compatible with both codes. The controller is based on the DTU Wind Energy Controller (Hansen et al., 2013), which features pitch and torque control. It has been extended with a supervisory control based on a report by Iribas et al. (Iribas et al., 2015). The supervisory control enables the controller to run a full load analysis. The controller parameters were taken from the report (Borg et al., 2015). Only the optimal torque-speed gain was recalculated based on the maximum power coefficient obtained from OpenFAST calculations.

The controller parameters were obtained via BEM calculations, so it is expected that the controller will behave differently if used in LLFVW calculations. We deliberately did not re-tune the controller parameters for the LLFVW simulations. This way, load differences arise not only from the different aerodynamic models themselves but also from the interaction of identical turbine controllers with these aerodynamic models. This procedure mimics to some extent current industry standards, in which wind turbine controllers are often pre-tuned using BEM-based aero-servo-elastic codes before they are implemented in real wind turbines.

2.4 Practical Considerations for Load Calculations

In order to use the presented methods in load calculations, several practical considerations had to be taken into account. Given that Eq. (3) has to be evaluated for each vortex element in the wake, calculating the convection of the wake can be computationally costly, slowing down the LLFVW calculations. In order to increase the calculation speed of these simulations, we implemented two wake coarsening methods. The first one follows a similar method as the one described in (Boorsma et al., 2018). Instead of skipping or removing vortices, the method implemented in QBlade lumps the wake elements together after a given number of rotor revolutions. The method reduces the number of vortex elements in the wake while conserving the total vorticity. This is done in two stages, giving us three wake regions: the near-wake, the mid-wake and the far-wake. The number of vortices lumped together is given by a lumping factor. So QBlade uses two lumping factors: the mid-wake factor for the transition from near-wake to mid-wake and the far-wake factor for the transition from mid-wake to far-wake.

The second method is the wake cut-off. After a given amount of rotor revolutions, the wake is cut off. The influence of these far-wake vortex elements on the velocity in the rotor plane is negligible. Removing these elements helps speeding up the calculations. Figure 2 shows the combination of the two implemented wake coarsening methods. The wake coarsening methods are a function of rotor revolutions. Because the effect of the vortex elements on the induced velocity is a function of the distance, the parameters for these methods will be dependent on the wind speed. The latter has an impact on the rotor speed and on the convection speed of the vortex elements. The wake coarsening parameters that we used for our simulations are given in Table A1.




Figure 2. Wake coarsening methods for the LLFVW simulations: The wake is split into three regions with decreasing amount of wake elements. After a given number of revolutions, the wake is cut off.




Figure 3. Performance coefficients for aerodynamic simulations with idealized conditions: (a) Thrust coefficient; (b) Power coefficient.

3 Baseline Comparison and Performance under Idealized Conditions

To do a baseline comparison of our aerodynamic models, we ran a series of idealized aerodynamic simulations. The parameters for these simulations are summarized in Table 2 under the column 'Aerodynamic calculations'. With these settings the flow is axis-symmetric on the rotor and no elasticity is taken into account. Under these conditions, many of the engineering correction models do not affect the rotor aerodynamics. Table 1 shows that under these conditions the only BEM engineering correction models that affect the rotor aerodynamics are the tip- and root-loss model and the turbulent wake state for high tip speed ratios (i.e. low wind speeds).

Figure 3 shows the steady state performance coefficients for aerodynamic calculations when done with the BEM and LLFVW codes. In general, the performance coefficients from both calculations agree well. The thrust coefficient from LLFVW calcu-

Table 2. Simulation parameters for aerodynamic and aeroelastic simulations

Parameter	Aerodynamic calculations	Aeroelastic calculations	
		Sensitivity study	Turb. calculations
Mean V_{Hub}	4 - 25 m/s	4 - 24 m/s	
Wind model	steady uniform	steady uniform	IEC NTM
Elasticity	off	on	
Rotor cone / Shaft tilt angles	$0^\circ / 0^\circ$	$2.5^\circ / 5^\circ$	
Wind shear exponent	0	0	0.2
Upflow angle	0°	0°	8°
Nacelle yaw angle	0°	0°	$-8^\circ, 0^\circ, 8^\circ$
Wake coarsening		See Table A1	
Rotor azimuth step / Time step	5°	0.04 s	

lations follows the thrust coefficient from BEM calculations very closely (Fig. 3 (a)). It is only at a wind speed of 11 m/s that the values visibly differ. As for the power coefficient (Fig. 3 (b)), the LLFVW code predicts higher values for wind speeds below rated wind speed. Above rated wind speed, the power coefficients in both codes almost perfectly match. This behavior can be explained from the fact that at higher wind speeds, the turbine controller pitches the blades out to keep the power output of the turbine constant. The controller logic is identical in both codes. Additionally, at higher wind speeds the rotor speed is kept constant by the controller while the convection speed of the wake increases. This decreases the influence of the wake on the turbine's thrust and power and hence the differences in the aerodynamic models become smaller. If we compare numerical values at 8 m/s, the difference between the thrust and power coefficients from both codes is 1.1% and 4.6% respectively. Similar differences of power and thrust between BEM and LLFVW codes for 8 m/s and ideal inflow conditions were also reported in (Madsen et al., 2012).

Figure 3 also contains data from three calculations done with other codes. The data is taken from (Bak et al., 2013), where the performance coefficients of the rigid DTU 10 MW RWT are calculated with the BEM-based code HAWCStab2 and the CFD-based code EllipSys3D. For the latter, two different boundary layer models were used. The OpenFAST and HAWCStab2 calculations predict very similar performance coefficients except for low wind speeds. QBlade predicts thrust coefficients that are closer to the BEM-based codes and power coefficients that are closer to the CFD-based codes.

The turbulent load calculations described in Sect. 4 used the full aeroelastic turbine model. The simulation parameters for the full aeroelastic model are summarized in Table 2 under the column 'Aeroelastic calculations'. Because of the long simulation time of each load case, we applied more aggressive wake coarsening parameters for the aeroelastic calculations than for the aerodynamic calculations. These are also summarized in Table A1. These simulation parameters are the result of a sensitivity study we performed to make sure that our chosen, wind dependent, wake parameters for the aeroelastic LLFVW simulations predicted similar steady state values compared to the idealized aerodynamic calculations with long wakes.




Figure 4. Comparison of aerodynamic and aeroelastic calculations on turbine performance: (a) Rotor thrust; (b) Rotor power; (c) Pitch angle; (d) Rotor speed.

Figure 4 shows the comparison of the rotor thrust, rotor power, pitch angle and rotor speed for the aerodynamic and aeroelastic calculations. Using the parameters from column 'Sensitivity study' in Table 2 has only a small influence on the steady state values of the rotor thrust and power (Figs. 4 (a) and 4 (b)). For both OpenFAST and QBlade, the rotor thrust from aeroelastic calculations is slightly higher than the thrust from purely aerodynamic calculations (as defined in column 'Aerodynamic calculations' from Tab. 2). For the wind speeds between 9 m/s and 12 m/s, the difference in thrust between aeroelastic and aerodynamic calculations in QBlade is more marked than the difference in OpenFAST.

The rotor speeds and pitch angles for the aerodynamic and aeroelastic calculations are shown in Figs. 4 (c) and 4 (d) respectively. In these subfigures we can see that there is also little difference in the controller signals if the turbine is simulated aeroelastically. The pitch angle coincides for all simulations. The reason for this probably comes from the fact that the structural model does not include the blade torsional degree of freedom. As for the rotor speed, QBlade predicts higher rotor speeds than OpenFAST for wind speeds between 7 and 11 m/s. Particularly for 11 m/s wind speed, QBlade simulations already reach the rated rotor speed while OpenFAST predict a steady state rotor speed of 9.1 rpm. This fact explains the higher thrust (Fig. 4 (a)) and thrust coefficient (Fig. 3 (a)) for this wind speed.

An important result from Fig. 4 is that using the wake coarsening parameters from Table A1 has only a small effect on the accuracy of the aeroelastic steady state results compared to the aerodynamic results. Therefore, the coarsening parameters can be used to speed up the turbulent load calculations in the next section.

Table 3. Considered sensors and analysis type for turbulent load calculations. C.S. = Coordinate System; F = Fatigue; U = Ultimate.

Sensor Name	OpenFAST Coord. Sys.	Symbol	Analysis Type
Blade root in-plane / out-of-plane bending moment	Coned C.S. c	M_X^{BR} / M_Y^{BR}	F / U
Yaw bearing roll / tilt / yaw moment	Nacelle C.S. n	$M_X^{YB} / M_Y^{YB} / M_Z^{YB}$	F / U
Tower base side-side / fore-aft / torsional bending moment	Tower-base C.S. t	$M_X^{TB} / M_Y^{TB} / M_Z^{TB}$	F / U
Blade tip out-of-plane / in-plane deflection	Coned C.S. c	D_X^{BT} / D_Y^{BT}	U
Tower top fore-aft / side-side deflection	Tower-top C.S. p	D_X^{TT} / D_Y^{TT}	U
Blade pitch angle / Rotor speed	N.A.	θ / Ω	F / U

4 Design Load Calculations with Turbulent Wind

The turbulent wind load cases were performed following the DLC groups 1.1/1.2 from the IEC61400-1 standard (IEC 61400-1 Ed. 3). The turbine setup for these load cases is listed in Table 2 in the third column. In this study, we considered wind speed bins (defined by the mean V_{Hub}) between 4 m/s to 24 m/s in 2 m/s steps. For each wind speed bin, six simulations were performed using two turbulence seeds per yaw angle. The same wind fields were used for BEM and LLFVW calculations. In total we did 66 simulations with 600 s simulation time for both the BEM and LLFVW codes. To give time for the wake to develop in the LLFVW calculations, we included an extra 100 s simulation time that was discarded in the load analysis. These discarded 100 s wake build-up time were also included in the BEM-simulations to make sure that for both codes we had the same incoming wind conditions.

4.1 Considered Sensors

For the analysis of the turbulent wind load calculations, we considered a selection of load sensors that is representative of the dynamics and load level of the entire turbine. The sensors include the blade root bending moments, the yaw bearing moments and the tower base bending moments. In addition, we considered the blade tip and tower top deflections. As for the controller signals, we analyzed the collective pitch angle and the rotor speed. Table 3 lists all considered sensors for this study and their corresponding symbol. For each sensor group, we used the coordinate systems defined in (Jonkman and Buhl, 2005) for both OpenFAST and QBlade calculations. The coordinate systems are listed in Tab. 3. In addition, the table also lists the type of post-processing analysis that we performed for each sensor group. F stands for fatigue load analysis and U for ultimate load analysis. Figure 2 shows exemplary the tower-base coordinate system **t**.

4.2 Statistical Overview

Figure 5 shows an overview of the statistical values of rotor thrust, electrical power, pitch angle and rotor speed for the turbulent wind calculations of both codes. The markers joined with lines represent the median of all values of the six 600 s simulations in each wind bin. The shaded area represents the Inter-Quartile Range (IQR) of the time series data– the range in which 50%




Figure 5. Comparison of statistical values for turbulent calculations: (a) Rotor thrust; (b) Electrical power; (c) Pitch angle; (d) Rotor speed. IQR = Inter-quartile range.

of the simulation values of each wind speed bin lie. The error bars represent the extrema of all values recorded at one wind speed bin.

Let us consider the rotor thrust in Fig. 5 (a) first. We can see that for wind speeds lower than the rated wind speed the values of the rotor thrust calculated with the LLFVW code tend to be higher than the values from the BEM code. This tendency inverts for wind speed between 12 and 18 m/s. Here, the medians and IQRs from the BEM calculations are slightly higher than the corresponding values from LLFVW calculations. For wind speeds higher than 18 m/s, the medians and IQRs between both codes almost match. This behavior of the thrust as a function of the wind speed is also seen for the steady state values in Fig. 4 (a).

The comparison of electrical power from the turbulent wind simulations – Fig. 5 (b) – also shows similarities with the comparison in ideal situations (Fig. 4 (b)). For below rated wind speeds, the LLFVW simulations show higher medians of the electrical power than results from BEM simulations. In contrast, the IQRs are lower for the LLFVW simulations. For the 12 m/s wind speed bin, the median electrical power for the LLFVW calculation is already practically 10 MW while the median power of the BEM simulations is still 9.8 MW. Also, we can see from the IQRs that at 12 m/s wind speed a higher percentage of time the power from BEM simulations lies below rated power.

The rotor speed signal (Fig. 5 (d)) is closely linked to the power signal (Fig. 5 (b)). The most observations made for the electrical power also hold true for the rotor speed. The exception being the IQRs of the signal for the 8 m/s wind bin. Here the IQR of the rotor speed is smaller in the BEM simulations than in the LLFVW simulations.




Figure 6. Normalized averaged standard deviations vs. wind speed. (a) Rotor speed Ω ; (b) Pitch angle θ

Finally, Fig. 5 (c) shows a comparison of the pitch angles between both codes. For wind speeds between 4 m/s and 8 m/s, there is practically no difference between the statistical values from the BEM and the LLFVW simulations. For higher wind speeds, we can see that the LLFVW simulations have slightly higher median, first quartile and third quartile values than BEM simulations. This behavior was not seen in the idealized aeroelastic simulations – Fig. 4 (c) – where the steady state values of the pitch angles were almost identical.

Differences in the IQRs shown in Fig. 5 reveal that the variability of the signals changes if we use different aerodynamic models. Particularly in the wind speeds from 8 m/s to 14 m/s, the IQR of the pitch angle, the rotor speed and the electrical power from the BEM calculations is visibly larger than the IQR of these signals from the LLFVW calculations. A quantitative analysis of these variations and their effect on the loads is done in the subsequent sections.

10 5 Fatigue Analysis of the Design Load Calculation Results

In this section, we discuss the influence of the aerodynamic models on the variability of controller signals and fatigue loads of different turbine sensors. The analysis is based on the results of the turbulent load calculations described in the previous section. In this and the following sections, the subscripts $(\cdot)_{\text{BEM}}$ and $(\cdot)_{\text{LLFVW}}$ denote values obtained from BEM and LLFVW simulations, respectively.

15 5.1 Controller Signals

To quantify the variability of the control signals, we used the standard deviation $\sigma(\cdot)$ as our metric. For each of the six simulations in one wind speed bin, we calculate σ for the rotor speed Ω and the pitch angle θ . We then average all six standard deviations for each control signal to get a representative quantity for the signal’s variability for that wind speed bin. These averaged standard deviations are denoted $\bar{\sigma}(\theta)$ for the pitch angle and $\bar{\sigma}(\Omega)$ for the rotor speed.

Figure 6 shows the normalized $\bar{\sigma}(\theta)$ and $\bar{\sigma}(\Omega)$ for the all the simulated wind speed bins. The normalization is with respect to the values from the BEM simulations, so the normalized $\bar{\sigma}(\theta)_{\text{BEM}}$ and $\bar{\sigma}(\Omega)_{\text{BEM}}$ are always 1.

If we consider the rotor speed (Fig. 6 (a)), we see that for all wind speed bins except 8 m/s, the normalized $\bar{\sigma}(\Omega)_{\text{LLFVW}}$ is lower than 1. The largest deviations can be seen at wind speed bins of 4 and 12 m/s. Here, the normalized $\bar{\sigma}(\Omega)_{\text{LLFVW}}$ are 0.35 and 0.55. When we consider wind speed bins of 16 m/s and above, we see the normalized value of $\bar{\sigma}(\Omega)_{\text{LLFVW}}$ increase monotonically towards 1.

Why do we have these differences in the wind speed bins 4 m/s, and 12 m/s? In the case of the 4 m/s wind bin, this difference can be explained if we look at Fig. 5 (d). For very low wind speeds, the value of Ω is almost always Ω_{min} . Yet in the BEM simulations, there are load cases where Ω_{BEM} drops below Ω_{min} and reaches a lower value than Ω_{LLFVW} . Because of the small absolute value of $\bar{\sigma}(\Omega)$ at those wind speeds, those excursions of Ω_{BEM} have a higher relative effect on $\bar{\sigma}(\Omega)_{\text{BEM}}$ and also on the normalized $\bar{\sigma}(\Omega)_{\text{LLFVW}}$.

As for $\bar{\sigma}(\Omega)$ at the wind speed bin of 12 m/s, the large difference comes from the fact that the LLFVW simulations predicted higher aerodynamic torque and hence higher values of Ω_{LLFVW} compared Ω_{BEM} at below-rated wind speed. For example, Ω_{LLFVW} is already Ω_R at wind speed 11 m/s in Fig. 4 (d) while Ω_{BEM} is slightly above 9 rpm. For turbulent calculations, the variation of Ω_{LLFVW} in Fig. 5 (d) is smaller than the variation of Ω_{BEM} mainly because the turbine has reached Ω_R at more time instants in the LLFVW simulations and the pitch controller is keeping the power and rotor speed constant.

For the pitch angle signal we can see that the normalized $\bar{\sigma}(\theta)_{\text{LLFVW}}$ behaves differently as a function of wind speed than $\bar{\sigma}(\Omega)_{\text{LLFVW}}$, while generally having values below 1 (Fig. 6 (b)). For wind speed bins between 10 and 16 m/s, $\bar{\sigma}(\theta)_{\text{LLFVW}}$ drops to values significantly lower than 1, reaching a value of 0.85 for the 14 m/s wind speed bin. For low wind speed bins, $\bar{\sigma}(\theta)_{\text{LLFVW}}$ is practically 1. For the wind speed bins of 18 m/s and above, the normalized values of $\bar{\sigma}(\theta)_{\text{LLFVW}}$ are above 0.95.

5.2 Loads

The fatigue loads are quantified using the Damage Equivalent Loads (DELs) metric. DELs are derived from the time series of the load sensor using a rain-flow counting algorithm. In this algorithm, the time-varying signal is broken down into individual cycles by matching local minima and maxima in the time series (Hayman, 2012). The rain-flow counting was performed using NREL's post-processing software Crunch (Buhl). We used the Palmgren-Miner linear damage accumulation hypothesis to obtain the DELs. Two types of fatigue loads were calculated. The first type are the short-term 1 Hz DELs – noted $\text{DEL}_{1\text{Hz}}(\cdot)$ – which give us the equivalent fatigue damage of one simulation. The second type are the lifetime DELs – noted $\text{DEL}_{\text{Life}}(\cdot)$ – which give us the equivalent loading for the entire turbine lifetime. The lifetime DELs were obtained following the method described in (Hayman, 2012). We used the wind distribution corresponding to wind class IA turbine with 20 years design life and an equivalent cycle number of 10^7 . For the blade root fatigue loads, we used an inverse S-N curve-slope of $m = 10$ to calculate the DELs. For all other loads, the inverse S-N curve-slope used is $m = 4$.

Figure 7 shows the normalized lifetime DELs for the considered turbine load sensors. We can see from this figure that performing the simulations with different aerodynamic models has an impact on the lifetime DELs of almost all considered load sensors. Let us start with the blade root. For these loads we see that the normalized $\text{DEL}_{\text{Life}}(M_X^{\text{BR}})_{\text{LLFVW}}$ and




Figure 7. Normalized lifetime DELs for the considered turbine load sensors. Sensor notation is given in Tab. 3.

$DEL_{Life}(M_Y^{BR})_{LLFVW}$ are 0.98 and 0.89, respectively. The finding that the fatigue loads of M_Y^{BR} are lower than $M_Y^{BR}_{BEM}$ has also been reported by other studies, e.g. (Perez-Becker et al., 2018; Boorsma et al., 2016). The studies report normalized values of $DEL_{1Hz}(M_Y^{BR})_{LLFVW}$ between 1.006 and 0.77 for turbulent wind simulations, depending on the wind speed. It should be noted that previous studies considered one simulation per wind speed and less time per simulation. This makes a direct comparison of lifetime fatigue loading with the cited literature difficult. Qualitatively though, the results agree.

When considering the yaw bearing, Fig. 7 shows that the normalized $DEL_{Life}(M_X^{YB})_{LLFVW}$ has an even lower value than the blade root fatigue loads: 0.87. If we look at the other bending moments, we see a smaller difference between the LLFVW and BEM codes. The normalized values of $DEL_{Life}(M_Y^{YB})_{LLFVW}$ and $DEL_{Life}(M_Z^{YB})_{LLFVW}$ are 0.96 and 0.97, respectively. For the tower loads, the largest difference in the lifetime DELs occurs in the tower base fore-aft bending moment. The normalized value of $DEL_{Life}(M_Y^{TB})_{LLFVW}$ is 0.89. The normalized values of $DEL_{Life}(M_X^{TB})_{LLFVW}$ and $DEL_{Life}(M_Z^{TB})_{LLFVW}$ are 0.92 and 0.97.

When calculating the lifetime fatigue loads, we take into account the loading of all the wind speed bins. In different wind speed bins, the turbine can see qualitatively different loading scenarios leading to significant differences in fatigue loading when simulated with different aerodynamic models. To further understand which phenomena are contributing to the differences in fatigue loads, we also analyzed the contribution of the individual wind speed bins to the lifetime fatigue loading of the sensors. As we can see in Fig. 8, the contribution of the wind speed bins to the lifetime fatigue loads is strongly dependent on the wind speed. To limit the extent of the fatigue analysis, we will concentrate four load sensors: M_Y^{BR} , M_X^{YB} , M_Y^{YB} and M_Y^{TB} .

Figure 8 (a) shows the normalized average 1 Hz DEL for M_Y^{BR} as a function of the wind speed bin. The average, noted $\overline{DEL}_{1Hz}(\cdot)$, was taken from the 1Hz DELs of each of the 6 realizations in one wind speed bin. The normalization was done with respect to the values of the BEM simulations. We can see in this subfigure that the value of the normalized $\overline{DEL}_{1Hz}(M_Y^{BR})_{LLFVW}$




Figure 8. Normalized averaged 1 Hz DEL as a function of the wind speed bin. (a) Blade root out-of-plane bending moment M_Y^{BR} ; (b) Yaw bearing roll moment M_X^{YB} ; (c) Tower base fore-aft bending moment M_Y^{TB} ; (d) Yaw bearing tilt moment M_Y^{YB} .

is lower than 1 for all wind speed bins except 4 m/s. For the rest of the wind speed bins, $\overline{DEL}_{1Hz}(M_Y^{BR})_{LLFVW}$ takes values around 0.9.

A different behavior can be seen for the M_Y^{TB} sensor in Fig. 8 (c). Where $\overline{DEL}_{1Hz}(M_Y^{TB})_{LLFVW}$ increase from about 0.7 to just over 0.9 with increasing wind speed. After rated wind speed, $\overline{DEL}_{1Hz}(M_Y^{TB})_{LLFVW}$ remains fairly constant.

- 5 The behavior of the fatigue damage on the yaw bearing sensors is also qualitatively different from the tower base fore-aft and the blade root out-of-plane bending moments. Figure 8 (b) and (d) show the values of $\overline{DEL}_{1Hz}(M_X^{YB})_{LLFVW}$ and $\overline{DEL}_{1Hz}(M_Y^{YB})_{LLFVW}$ for all the simulated wind speed bins. For these sensors, the highest differences are seen in wind speed bins between 8 and 12 m/s.

5.3 Discussion

- 10 To better understand the differences in the fatigue loads and the variability of the controller signals, we can categorize the wind speed bins into three qualitatively different wind speed regions: Regions A, B and C.

- Region A includes wind speed bins between 4 and 10 m/s. In this region, the turbine is below rated wind speed and hence the controller seeks to maximize energy capture. The pitch controller is largely inactive and the tip speed ratio of the turbine is above or close to the turbine’s optimal tip speed ratio. For the aerodynamic loads this means that the axial induction factor is relatively large. Therefore, the differences in the aerodynamic modeling will be large and their influence on the turbine loads significant.
- 15

- Region B encompasses wind speed bins between 10 m/s and 16 m/s. In this region, the transition between below-rated power and above-rated power operations of the controller occurs. Small differences in aerodynamic loads can trigger this transition and significantly affect the turbine loading. This is because around rated wind the thrust on the rotor is highest (Fig. 4 (a)) and the activation of the pitch controller influences the thrust considerably. In this region, the tip speed ratio of the turbine is still close to the optimum. Hence the axial induction is still large making differences in aerodynamic models relevant for turbine loading.
- Region C covers wind speed bins between 18 m/s and 24 m/s. Here, the blade pitch angle is relatively high and the rotor speed is close to the rated rotor speed Ω_R . With higher wind speeds the wake is convected faster downstream, effectively reducing the effect of its induced velocity on the rotor plane. This translates into smaller values of axial induction factors on the blade elements and on the rotor as a whole. Hence, the global effect of the different aerodynamic models on the controller behavior decreases. This in turn reduces the loading differences for certain turbine loads.

Because we are analyzing turbulent load calculations with varying wind speed, the limits between the regions cannot be exactly defined. We will consider one wind speed bin for each region as a representative set of simulations for that region. For each chosen wind speed bin, the qualitative turbine behavior will be the same as in the corresponding region described above. For Region A the chosen wind speed bin is 8 m/s, for Region B the wind speed bin is 14 m/s and for Region C, the wind speed bin is 20 m/s. We will concentrate on the same turbine loads as in Fig. 8 to limit the extension of this section.

It should be stressed here that the analysis done in this section is valid only for the two particular aerodynamic codes considered in this study. The LLFVW implementation of QBlade does not take into account the interaction between the vorticity of the wind shear and the vorticity due to the wake. This affects the shape of the turbine wake and influences the loading on the turbine (Branlard et al., 2015). The choices of the engineering correction models used in AeroDyn are also particular for this code. Other BEM codes implement engineering models and the coupling between them differently (Madsen et al., 2020).

5.3.1 Blade Root Out-of-Plane Bending Moment

Figure 9 shows the Power Spectral Density (PSD) plots of M_Y^{BR} for several BEM and LLFVW simulations. Each row of the subplots in the figure corresponds to one of the aforementioned regions. The left column shows PSD plots of the results from turbulent wind load calculation. The right column shows the PSDs of 200 s simulations with steady inflow conditions. The latter column will help us understand the source of the differences in the fatigue loads between both codes. As with the turbulent calculations, additional 100 s were simulated and discarded in the analysis to allow the wake in the steady LLFVW simulations to build up.

Figures 9 (a) and 9 (b) show the PSD plots of M_Y^{BR} for simulations in the 8 m/s wind speed bin – i.e. Region A. In Fig. 9 (a) the solid lines represent turbulent wind simulations with a 0° yaw error while the dashed lines represent simulations with 8° yaw error. For Fig. 9 (b), the solid lines represent results from steady wind simulations without yaw error but with a 0.2 wind shear exponent while the dashed lines represent results from simulations with 8° yaw error and a wind shear exponent of 0.




Figure 9. Power Spectral Density plots for M_Y^{BR} at different wind speeds. (a) Turbulent calculations at 8 m/s wind speed; (b) Steady calculations at 8 m/s wind speed; (c) Turbulent calculations at 14 m/s wind speed; (d) Steady calculations at 14 m/s wind speed; (e) Turbulent calculations at 20 m/s wind speed; (f) Steady calculations at 20 m/s wind speed

The idea of the simulations in Fig. 9 (b) is to isolate different aerodynamic phenomena to see their individual contribution to the fatigue loading. Apart from the tip- and root-loss model, the major difference of the aerodynamic models in the solid line simulations is the treatment of the non-homogeneous wind speed distribution on the rotor disk. In contrast, the major difference of the aerodynamic models in the dashed line simulations is the treatment of the oblique inflow.

- 5 When we consider the PSDs of the turbulent load calculations (Fig. 9 (a)) we can see that there are two main peaks at different frequencies in the PSD. One peak is at a low, below once-per-revolution (1P) frequency. This is the frequency region where the controller is active.

The second peak is at the 1P frequency. If we compare the amplitudes between the aerodynamic codes at that frequency we can see that, for both the 8° and 0° yaw error simulations, the amplitude of the 1P peak in the PSD of the BEM simulations is visibly larger than the corresponding peak in the LLFVW simulations. The main source of this difference between both codes is the effect that the non-homogeneous wind field – arising for example from the wind shear – has on the local blade aerodynamics. As Fig. 9 (b) shows, simulating the turbine in sheared inflow leads to the largest differences between both

10

codes in the load prediction at the 1P frequency of $\text{PSD}(M_Y^{\text{BR}})$. The reason for this difference has already been identified and explained by other authors – e.g. (Madsen et al., 2012; Boorsma et al., 2016; Madsen et al., 2020) – and will only be briefly mentioned here. According to (Moriarty and Hansen, 2005), AeroDyn calculates the local thrust coefficient using the average inflow wind speed from the rotor; a procedure also done in other BEM codes (Madsen et al., 2012). This choice has an averaging effect on the local axial induced velocity when the turbine is simulated with sheared inflow. As a result, the local angle of attack sees a higher amplitude in the 1P variations compared to when the scenario simulated with a LLFVW code. In the latter, the local three-dimensional induction field is implicitly modelled through the induced velocities from the bound and wake vortices. The result is a better tracking of the local axial induced velocity with the LLFVW simulations. Having higher angle of attack variations in BEM simulations leads to higher 1P variations in the local lift forces and ultimately to higher 1P variations in $M_{Y-\text{BEM}}^{\text{BR}}$ (compared to $M_{Y-\text{LLFVW}}^{\text{BR}}$).

These loading differences are also seen between different implementations of BEM codes. In (Madsen et al., 2020), Madsen et al. implement a BEM model on a polar grid. This code also allows for a better tracking of the local induction variations on the blades compared to an annular averaged BEM approach. This polar implementation of a BEM-type code leads to a significant reduction in M_Y^{BR} fatigue loads when compared to the more common annular-averaged BEM approach. They also show that, for large wind turbines, the rotational sampling of the turbulent inflow is an important contributor to load differences between the different BEM implementations. This rotational sampling also contributes to the loading differences at the 1P frequency in Fig. 9 (a).

The behavior of the PSD plots changes when we compare simulations in Region B (Fig. 9 (c)). There are still two major peaks in the PSD: again one is at the low frequency of the controller and the other at the 1P frequency. In contrast to Region A, the 1P peak is now much more pronounced than the low frequency peak. Also, there are differences between the aerodynamic codes at both frequency peaks in Region B. The reasons for the differences at the 1P frequency are the same as in Region A (Fig. 9 (d)). We can understand the differences at the low frequency region of the controller if we recall Fig. 5 (d). In Region B the turbine controller is often transitioning between below-rated power and above-rated power operations, thereby reaching maximum thrust. Because of the slightly higher aerodynamic torque from the LLFVW simulations, the turbine controller is able to keep Ω_R and rated power for a higher percentage of time compared to the BEM simulations. The smaller variations of Ω_{LLFVW} (Figs. 5 (d) and 6 (a)) also lead to smaller variations of rotor thrust, and hence smaller variations of $M_{Y-\text{LLFVW}}^{\text{BR}}$. The higher aerodynamic torque and smaller variation of Ω_{LLFVW} also lead to smaller variations of θ_{LLFVW} (Figs. 5 (c) and 6 (b)). Again, this lowers the variation of rotor thrust and ultimately the variation of $M_{Y-\text{LLFVW}}^{\text{BR}}$.

We finally consider Region C in Figs. 9 (e) and 9 (f). Here, the 1P frequency peak dominates the PSD and is still the frequency where the differences between the codes lie. The reason for the differences is again the different treatment of the non-homogenous wind field in both codes. The variation of the controller signals in this region is comparable between both codes (Fig. 6). The same holds true for the effect of the controller action on M_Y^{BR} . Yet this load contribution to the $\text{PSD}(M_Y^{\text{BR}})$ is overshadowed by the load contribution from the 1P frequency.




Figure 10. Power Spectral Density plots for M_Y^{TB} at different wind speeds. (a) Turbulent calculations at 8 m/s wind speed; (b) Steady calculations at 8 m/s wind speed; (c) Turbulent calculations at 14 m/s wind speed; (d) Steady calculations at 14 m/s wind speed; (e) Turbulent calculations at 20 m/s wind speed; (f) Steady calculations at 20 m/s wind speed

5.3.2 Tower Base Fore-Aft Bending Moment

Like M_Y^{BR} , the tower base fore-aft bending moment also shows large differences in the lifetime DELs. Figure 10 shows the PSD plots for the M_Y^{TB} sensors in Regions A, B and C. The rows and columns are organized in the same way as in Fig. 9.

For turbulent wind speed calculations in Region A (Fig. 10 (a)), we can see that the main differences in $\text{PSD}(M_Y^{\text{TB}})$ from both aerodynamic codes lie close to the 3P frequency. The source of this difference comes mostly from the treatment of the non-homogeneous wind field, as can be seen in Figure 10 (b). The reason for this is as follows. Since the amplitude of the 1P frequency component of $M_{Y-\text{LLFVW}}^{\text{BR}}$ in sheared flow is lower than for $M_{Y-\text{BEM}}^{\text{BR}}$ (Fig. 9 (b)), the amplitude of the PSD at the tower passing frequency – i.e. 3P – will also be lower for the LLFVW simulations. The fact that the differences in Fig. 10 (a) do not lie exactly on the 3P frequency comes from the varying rotor speed in the simulations. The normalization of the frequencies was done using the average rotor speed of each simulation.

If we now concentrate on Region B simulations, we can see in Fig. 10 (c) that the dominant frequencies in $\text{PSD}(M_Y^{\text{TB}})$ for all simulations are the low, sub-1P frequencies. It is also this frequency range of the PSD that contains the largest differences between both codes. While there are some differences in the PSD at the 3P frequencies due to wind shear (Fig. 10 (d)), the contribution of this frequency is significantly smaller than the contribution of the low frequency range. As in the case of M_Y^{BR} ,
 5 the reason for this loading difference can be traced back to the higher aerodynamic torque from the LLFVW simulations. It leads to lower variations of $\sigma(\Omega_{\text{LLFVW}})$ and $\sigma(\theta_{\text{LLFVW}})$ in this region (Fig. 6) and ultimately lower variations in rotor thrust.

For simulations in Region C the $\text{PSD}(M_Y^{\text{TB}})$ of both codes is comparable and at the same time more complicated (Fig. 10 (e)). There are several frequency regions in which the PSD of the BEM simulations is higher than the PSD of the LLFVW simulations. For the 3P frequency, the difference is due to the treatment of the non-homogenous wind field (Fig. 10 (f)) but its
 10 contribution to the PSD is small compared to the lower frequencies.

We note in Fig. 10 (e) a large difference in peaks of $\text{PSD}(M_Y^{\text{TB}})$ at about 1.5P frequency. This peak is also present in Figs. 10 (d) and 10 (f). The frequency corresponds to an absolute frequency of 0.25 Hz, which is the natural frequency of the 1st tower fore-aft and side-side mode of the turbine (Bak et al., 2013). In the simulations we saw that the mode was lowly damped in the side-side direction and contributed to the oscillations of M_X^{TB} . As for the tower fore-aft mode, its contribution to $\text{PSD}(M_Y^{\text{TB}})$ is
 15 also significant in Region C and the peak for the BEM simulations is consistently higher. This indicates that the aerodynamic damping of the 1st tower fore-aft mode is higher for the LLFVW simulations than for the BEM simulations.

5.3.3 Yaw Bearing Roll Moment

In absolute terms, M_X^{YB} is the load sensor with the smallest variation in amplitude. So small differences in loading will have a large influence on the relative contribution to the fatigue loads of this sensor. This load component is affected by the generator
 20 torque and by the side-side force acting on the rotor hub. The latter force causes a roll moment due to the vertical offset of the rotor hub to the yaw bearing. A similar analysis was performed for this sensor as it was done for M_Y^{BR} and M_Y^{TB} , although for brevity only the results will be stated here.

For turbulent simulations in Region A, the main difference in $\text{PSD}(M_X^{\text{YB}})$ lies in the low frequency range where the controller is active. It is therefore the variability of the generator torque that is the source of the load differences in this region. It could be
 25 argued that the variability of Ω for this particular wind speed bin is larger in the LLFVW simulations (see Fig. 6 (a)). Yet the higher variability of the electrical power in Region A for the BEM simulations seen in Fig. 5 (b) indicates that in this region there is a higher fluctuation in the generator torque which causes the higher fatigue loads of M_X^{YB} . It is also this phenomenon that is the source of the differences in Region B.

When we consider Region C, we can see in Fig. 8 (b) that the normalized $\overline{\text{DEL}}_{1\text{Hz}}(M_X^{\text{YB}})_{\text{LLFVW}}$ is close to 1, indicating that
 30 the fatigue loads derived from the LLFVW simulations are almost the same as the ones derived from the BEM simulations. Yet the $\text{PSD}(M_X^{\text{YB}})$ reveals that at different frequencies there are different loading peaks for BEM and LLFVW simulations. As in Regions A and B, there is a slightly higher peak at the low frequencies of the controller in the BEM simulations. At the 0.25 Hz frequency though, there is a higher peak for the LLFVW simulations. The reason for this is the lowly damped oscillations of the 1st tower side-side mode mentioned above. This side-side oscillation of the tower top is not directly influenced by the

aerodynamics. While the relative contribution of the 1st tower fore-aft mode to $\text{PSD}(M_Y^{\text{TB}})$ is moderate (Fig. 10 (f)), the relative contribution of the 1st tower side-side mode to $\text{PSD}(M_X^{\text{YB}})$ is much higher. Because of the small absolute variations of this load signal, the side-side forces present in the hub contribute significantly to the fatigue loads. In our study, BEM simulations show higher oscillations for certain wind speeds and turbulent seeds while in other cases the LLFVW show higher oscillations. For higher wind speeds in particular, the side-side oscillations of the tower top tend to have a higher amplitude in the LLFVW simulations, explaining the higher 1Hz DELs of M_X^{YB} for the latter aerodynamic code seen in this region.

5.3.4 Yaw Bearing Tilt Moment

The last sensor analyzed in this section is M_Y^{YB} . As with the yaw bearing roll moment, we will only include the results of the discussion in this section.

For Region A, there are two peaks where $\text{PSD}(M_Y^{\text{YB}})_{\text{BEM}}$ is higher than $\text{PSD}(M_Y^{\text{YB}})_{\text{LLFVW}}$. One is at the 3P frequency and the other at the below-1P frequencies. The latter region corresponding to the frequencies of the time varying turbulent wind and the resulting controller reaction. These peaks can be explained by the fact that one source of M_Y^{YB} – measured in a non-rotating frame of reference – is the non-uniform distribution of M_Y^{BR} from the three blades, which is measured in a rotating frame of reference (Burton et al., 2011). In particular, amplitude changes at the 1P frequency of $\text{PSD}(M_Y^{\text{BR}})$ contribute to amplitude changes at the 0P frequency (or very low frequencies in case of varying wind speed) of $\text{PSD}(M_Y^{\text{YB}})$. Changes at the 1P frequency of $\text{PSD}(M_Y^{\text{BR}})$ also contribute to amplitude changes at the 2P frequency of $\text{PSD}(M_Y^{\text{YB}})$, although the contribution of the loads at this frequency to the fatigue loads of M_Y^{YB} is negligible for three-bladed turbines. Changes at the 2P frequency in the $\text{PSD}(M_Y^{\text{BR}})$ contribute to changes at the 1P and 3P frequencies in $\text{PSD}(M_Y^{\text{YB}})$. Again, only the 3P frequency in $\text{PSD}(M_Y^{\text{YB}})$ has an important load contribution for this sensor in the case of a three-bladed turbine. As we can see in Figures 9 (a) and (b), the 1P and 2P peaks in the PSD of $M_Y^{\text{BR}}_{\text{BEM}}$ have a higher amplitude than the peaks from $M_Y^{\text{BR}}_{\text{LLFVW}}$. The reason for these differences comes from the effect of the non-homogenous wind field on the local blade aerodynamics. This is also an important contributor to the differences in the case of M_Y^{YB} .

This phenomenon is also responsible for the fatigue load differences in Regions B and C. As we can see in Figs. 9 (c) and 9 (e), the load peak at the 1P frequency becomes more dominant in $\text{PSD}(M_Y^{\text{BR}})$, increasing the contribution of the low frequency peak of $\text{PSD}(M_Y^{\text{YB}})$ to the fatigue loads. While the normalized values of $\overline{\text{DEL}}_{1\text{Hz}}(M_Y^{\text{BR}})_{\text{LLFVW}}$ remain fairly constant for higher wind speed bins (Fig. 8 (a)), the normalized values of $\overline{\text{DEL}}_{1\text{Hz}}(M_Y^{\text{YB}})_{\text{LLFVW}}$ increase and get closer to 1. The cause of this apparent discrepancy can be explained if we consider a second source of yaw bearing tilt moment: the axial force on the rotor hub from the rotor thrust. Because of the vertical offset between the hub and the yaw bearing, variations in rotor thrust will lead to variations in M_Y^{YB} . Recalling Fig. 6 (b), we can see that for wind speed bins of 16 m/s and above, $\overline{\sigma}(\theta)_{\text{LLFVW}}$ increases towards a normalized value of 1. This leads to the result that the differences in rotor thrust variations between BEM and LLFVW simulations decrease, in turn reducing the differences in amplitude of M_Y^{YB} variations.




Figure 11. Normalized extreme values of deflections and controller signals. (a) Maxima; (b) Minima

6 Ultimate State Analysis of the Design Load Calculation Results

In the previous section, we discussed the contribution of the periodic oscillations on the turbine loading. This section considers the extreme events that the turbine sensors experienced in the turbulent wind load calculations. The ultimate state analysis was done for all the sensors listed in Table 3. We analyze the deflection and control signals in the first subsection and the load sensors in the second subsection. The last subsection discusses the differences of the extrema and the reasons behind these differences.

The extreme values presented in this subsection are obtained by taking the maximum and minimum occurring values in the time series of all the simulations. In addition, the extreme values of the blade related sensors – i.e. M_X^{BR} , M_Y^{BR} , D_X^{BT} , D_Y^{BT} and θ – are obtained from one blade only. The same blade was considered in the analysis of the BEM and the LLFVW simulations. For this study, it is considered that the extreme events-analysis of one blade is representative of all three blades.

Analogously to the fatigue analysis, we will use the notation $\text{Max}(\cdot)_{\text{BEM}}$ / $\text{Min}(\cdot)_{\text{BEM}}$ for the maximum and minimum of a sensor in the BEM simulations. The extrema for the LLFVW simulations will have the corresponding subscript. Although we present the results for all sensors, we will concentrate our discussion and analysis on the out-of-plane related sensors. These sensors are the most directly affected by the differences in the aerodynamic models.

6.1 Deflections and Controller Signals

Figure 11 shows the normalized extreme values of the blade tip and tower top deflections as well as the pitch angle and rotor speed. It is clear from this figure that using different aerodynamic models in load calculations also affects the extrema of the considered sensors.

When looking at the blade deflections, it is remarkable to see that the extrema of D_X^{BT} are very similar in both calculations. From the higher 1Hz DELs of M_Y^{BR} in the BEM simulations at wind speeds close to the rated wind speed, we would expect to




Figure 12. Normalized extreme values of turbine load sensors. (a) Maxima; (b) Minima

see blade deflections with higher amplitudes in the BEM simulations and hence larger extrema of D_X^{BT} . While on average the amplitude of D_X^{BT} in the BEM simulations is larger than in the LLFVW calculations, the normalized value of $\text{Max}(D_X^{BT})_{\text{LLFVW}}$ is 0.99.

The tower top deflections show larger differences in extreme values from the different calculations than the blade tip deflections. If we consider the extrema of the fore-aft deflection, we see that the normalized values of $\text{Max}(D_X^{TT})_{\text{LLFVW}}$ and $\text{Min}(D_X^{TT})_{\text{LLFVW}}$ are 0.96 and 0.51, respectively.

Finally, Fig. 11 also shows the normalized extreme values of the pitch angle and rotor speed. The extrema of the pitch angle θ are very similar in both codes. The rotor speed Ω also shows a small differences in the extrema. The normalized $\text{Max}(\Omega)_{\text{LLFVW}}$ is 0.99.

10 6.2 Loads

Performing load calculations with different aerodynamic models also has an impact on practically all the considered extreme loads of the turbine, as Fig. 12 shows.

Let us start with the blade root loads. We can see in Fig. 12 that the normalized extrema of M_Y^{BR} are very similar in both calculations. This correlates with the fact that the extreme values of D_X^{BT} in Fig. 11 were also very similar between both codes. The normalized $\text{Max}(M_Y^{BR})_{\text{LLFVW}}$ and $\text{Min}(M_Y^{BR})_{\text{LLFVW}}$ are 0.97 and 0.84, respectively.

In the case of the yaw bearing, the most notable difference in extreme loads occurs for the tilting moment. The normalized $\text{Max}(M_Y^{YB})_{\text{LLFVW}}$ is 0.88.

For the tower base loads we see large differences in the extrema of the fore-aft bending moment. The normalized values of $\text{Max}(M_Y^{TB})_{\text{LLFVW}}$ and $\text{Min}(M_Y^{TB})_{\text{LLFVW}}$ are 1.02 and 0.45. A deeper analysis of these differences in the extreme loads is presented in the next section.




Figure 13. Time series of extreme tower event. (a) Wind speed at hub height; (b) Rotor speed; (c) Pitch angle; (d) Tower base fore-aft bending moment; (e) Tower top fore-aft deflection

6.3 Discussion

As with the fatigue loads, the reason for these differences in the extreme loads must ultimately come from the different aerodynamic models.

In order to limit the extension of this analysis, we will only consider a selection of the sensors. These are: M_Y^{TB} , D_X^{TT} , M_Y^{BR} , D_X^{BT} and M_Y^{YB} since they show large deviations and are directly influenced by the aerodynamic loads. While doing the ultimate load analysis, we noted that the extrema of BEM and LLFVW simulations did not necessarily occur in the same simulation or even the same wind speed bin. In the following analysis we will always present the load case where the highest (absolute) extreme value of the sensors occurred, whether it happened for the BEM calculations or the LLFVW calculations. So for example if the maximum of D_X^{TT} was higher for the BEM code, we will include the time series analysis of the BEM load case and show the corresponding LLFVW load case as a comparison. The load case where the maximum of D_X^{TT} in the LLFVW simulations occurred will not be analyzed.

6.3.1 Tower Loads and Deflections

For the extreme values of the tower sensors, we see in Figs. 11 and 12 that $\text{Max}(D_X^{\text{TT}})_{\text{BEM}} > \text{Max}(D_X^{\text{TT}})_{\text{LLFVW}}$ but $\text{Max}(M_Y^{\text{TB}})_{\text{BEM}} < \text{Max}(M_Y^{\text{TT}})_{\text{LLFVW}}$. These extreme values result from different events happening at different time instants. Curiously, these events share the same load case that comes from the 12 m/s wind speed bin.

A selection of the load case time series is shown in Fig. 13. The time instant where $\text{Max}(D_X^{\text{TT}})_{\text{BEM}}$ occurs is around 450 s of simulation time. The time instant where $\text{Max}(M_Y^{\text{TB}})_{\text{LLFVW}}$ occurs is around 650 s of simulation time.

Let us focus on $\text{Max}(D_X^{\text{TT}})_{\text{BEM}}$ first. As we can see in Fig. 13 (a), there is an increase of the hub wind speed from just above 5 m/s to about 12 m/s in the simulation time interval between 400 s and 450 s. For that time interval, Ω_{BEM} takes values that are roughly 1 rpm lower than Ω_{LLFVW} (Fig. 13 (b)). When the hub wind speed increases to about 12 m/s both Ω_{BEM} and Ω_{LLFVW} reach Ω_R , which activates the pitch controller. The rotational acceleration of the rotor is smaller in the LLFVW simulations, allowing more time for the controller to increase θ_{LLFVW} (Fig. 13 (c)) and limit the effect of the aerodynamic thrust on $M_{Y-\text{LLFVW}}^{\text{TB}}$ (Fig. 13 (d)) and $D_{X-\text{LLFVW}}^{\text{TT}}$ (Fig. 13 (e)). For the BEM simulation on the other hand, we see that the rotational acceleration is higher. This gives the controller less time to increase θ_{BEM} and hence the wind speed increase generates a higher rotor thrust. This leads to higher values of $M_{Y-\text{BEM}}^{\text{TB}}$ and the recorded maximum of $D_{X-\text{BEM}}^{\text{TT}}$

If we now consider on $\text{Max}(M_Y^{\text{TB}})_{\text{LLFVW}}$, we can see that there is a similar turbine configuration between 600 s and 650 s that leads to the differences in maxima between BEM and LLFVW simulations. This time, a sudden wind gust at around 650 s increases the hub wind velocity from about 10 m/s to 15 m/s. There is again a difference of around 1 rpm between Ω_{BEM} and Ω_{LLFVW} . Yet in this event, the rotational accelerations from both simulations have very similar values. Because Ω_{LLFVW} is almost 9 rpm just before the gust, the wind velocity jump leaves Ω_{LLFVW} at a higher value compared to Ω_{BEM} at the time instant the pitch controller is activated to feather out the overshoot. The higher value of Ω_{LLFVW} increases the tip speed ratio and hence the axial induction of the rotor, compared to the axial induction in the BEM simulation. An increase in the instantaneous induction results in a higher thrust on the rotor. This leads to the recorded maximum of $M_{Y-\text{LLFVW}}^{\text{TB}}$.

The difference in the controller behavior affecting the maxima of the tower sensors can be traced back to the higher aerodynamic torque of the LLFVW simulations (Fig. 3 (b)) that lead to higher values of Ω_{LLFVW} in the below-rated power wind regime (Figs. 4 (d) and 5 (d)). Especially for wind speeds around rated wind speed, small differences in rotor speed cause the transition between below-rated power and above-rated power operations of the controller, influencing significantly the loading on the turbine.

6.3.2 Out-of-Plane Root Bending Moment and Tip Deflection of the Blade

A similar analysis as in the previous subsection was also carried out for M_Y^{BR} and D_X^{BT} . For brevity, only the findings will be presented here.

For the BEM simulations, $\text{Max}(M_Y^{\text{BR}})_{\text{BEM}}$ and $\text{Max}(D_X^{\text{BR}})_{\text{BEM}}$ occurred for a load case simulation at the wind speed bin of 12 m/s. Similar to Fig. 13, the differences in the blade root loading and tip deflection come from a lower θ_{BEM} at the moment the wind turbine encountered a small wind gust. As with the tower sensors, there is again a difference of around 1 rpm between Ω_{BEM} and Ω_{LLFVW} just before the gust, leading to the lower values of θ_{BEM} . This difference can be traced back to the higher aerodynamic torque from the LLFVW simulations, affecting the transition of the controller operation modes.

6.3.3 Yaw Bearing Tilt Moment

From Fig. 12 we see that the normalized value of $\text{Max}(M_Y^{\text{YB}})_{\text{LLFVW}}$ is 0.88. We will again only present the results of the analysis to limit the extend of this section.

The maxima of M_Y^{YB} occurred in a load case simulation with 24 m/s average wind speed for both the BEM and LLFVW simulations. In this load case, the controller behavior is almost identical. The most relevant difference is that – because of the higher aerodynamic torque in the LLFVW simulations – the average value of θ_{LLFVW} is slightly higher than the one of θ_{BEM} , a behavior also seen in Fig. 5 (c). As a consequence the average rotor thrust in the BEM simulation is also slightly higher and – due to the vertical offset between rotor hub and yaw bearing – so is the average value of $M_{Y-\text{BEM}}^{\text{YB}}$. It should be noted that for this simulation Ω_{BEM} and Ω_{LLFVW} are practically identical, leading to coinciding rotor azimuth angles in both codes. The extreme event occurs at an azimuth angle of 65° , meaning that the turbine is close to the Y-configuration in which one blade is in front of the tower. This is the configuration of maximum M_Y^{YB} . Because of different treatment of the non-homogenous wind field between the codes, the $M_{Y-\text{BEM}}^{\text{YB}}$ also has a higher energy content in the 3P frequency (see Sec. 5.3.4). The higher average value due to the thrust and the higher 3P oscillation of $M_{Y-\text{BEM}}^{\text{YB}}$ lead to a higher maximum peak of $M_{Y-\text{BEM}}^{\text{YB}}$ which also becomes the extreme value of this sensor of all simulations.

7 Conclusions

In this paper we analyzed the effect of two different aerodynamic models on the performance and especially on the loads of the DTU 10 MW RWT. The first aerodynamic model – used in the aeroelastic simulation software OpenFAST – is an implementation of the BEM method, the standard method used in the industry. The second aerodynamic model – used in TU Berlin’s aeroelastic software QBlade – is an implementation of the LLFVW method.

We did a baseline comparison of both codes by calculating the performance of the turbine under constant uniform wind speeds, where many of the engineering correction models do not contribute to the aerodynamic loads. The performance coefficients of the turbine simulated with both codes were similar for all relevant wind speeds where the turbine is in power production. The largest differences were seen at wind speeds below rated wind speed, where the axial induction factor plays an important role. Including measures to speed up the LLFVW simulations as well as elasticity did not have a significant impact on the performance of the wind turbine.

We also simulated the wind turbine under turbulent wind conditions following the requirements of the IEC 61400-1 ed.3 DLC groups 1.1 and 1.2. The average performance of the turbine in the turbulent wind simulations is comparable to the performance in the idealized simulations with constant uniform wind speed. Yet there is considerable variation in the thrust and power of the turbine due to the unsteady aerodynamic phenomena present in the turbulent wind load calculations. Those variations are more marked in the BEM simulations than in the LLFVW simulations, with the former showing a higher activity in the controller signals – i.e. the rotor speed and the pitch angle. This leads to considerable differences in the fatigue and extreme loads of the turbine.

In order to quantify the differences in the fatigue loads, we carried out a fatigue analysis that includes the lifetime DELs and the per wind bin-averaged 1 Hz DELs of selected load sensors of the turbine. For the lifetime DELs, the LLFVW simulations show a 9% decrease in $DEL_{Life}(M_Y^{BR})$ and $DEL_{Life}(M_Y^{TB})$ compared to the BEM simulations. Analyzing the averaged 1Hz DELs, we found that the wind speed bins below rated wind speed contribute the most to the decrease in the sensors' fatigue loads in the LLFVW simulations. For bins with higher wind speeds, the differences in fatigue loads of M_Y^{BR} remain roughly constant and the differences in M_Y^{TB} fatigue loads diminish. Further analysis showed that the main contributors to the differences in the fatigue loads of the sensors are the different way the non-homogenous wind field affects the local blade aerodynamics in each code and the higher average aerodynamic torque seen in the LLFVW calculations. The latter influenced the values of Ω_{LLFVW} and – for wind speeds around rated wind speeds – affected the transition of the controller between below-rated power and above-rated power operations. This had a significant effect on the turbine loading.

For the yaw bearing moment, we found that the LLFVW simulations predicted a decrease of 4% and 3% in $DEL_{Life}(M_Y^{YB})$ and $DEL_{Life}(M_Z^{YB})$, respectively. Analyzing the contributions of individual wind speed bins on the 1Hz DELs of M_Y^{YB} revealed that the load differences for this sensor arose from the same aerodynamic differences that contributed to the differences of M_Y^{BR} and M_Y^{TB} .

We also did an ultimate state analysis on the results of the turbulent wind load calculations. For the out-of-plane loads and deflections of the blade, we found that the BEM simulations predicted higher extrema than the LLFVW simulations. The maxima of D_{X-BEM}^{BT} and M_{Y-BEM}^{BR} are 1% and 3% higher than their respective maxima in the LLFVW simulations. As for the tower sensors, we found that $Max(D_X^{TT})_{BEM}$ is 4 % higher and $Max(M_Y^{TB})_{BEM}$ 2 % lower than their respective maxima in the LLFVW simulations. The reason for these differences could be traced back to the higher average aerodynamic torque in the LLFVW simulations, which caused differences in the transition of turbine controller between operating modes and hence the loading. The higher aerodynamic torque in the LLFVW simulations and the different treatment of the non-homogeneous wind field were the reasons for the differences in $Max(M_Y^{YB})$ between both codes. In the case of this sensor, the results from LLFVW simulations predicted a decrease of $Max(M_Y^{YB})$ by 12%.

The results of this paper show that there are significant differences in the fatigue and extreme loads if we use a higher order aerodynamic model in the load calculations. In order to improve our quantification of the load differences, future work will include simulations with a higher-order representation of the structural dynamics. By including the torsional degree of freedom, we will be able to model the flap-twist coupling that greatly influences the loads on the turbine. In order to better quantify the differences in extreme loads, more DLC groups from the current guidelines and standards should be included. Performing an ultimate state analysis of the IEC 64100-1 DLC 1.1 and 1.2 groups gave us some insight into the influence of the aerodynamic codes on the extreme loads. Including DLC groups that are known to induce design driving extreme loads on the turbine will help us to better understand and quantify the effect of higher-order aerodynamic models on the extreme loads.

Code and data availability. Both OpenFAST and QBlade are open source codes available online. The latest version of OpenFAST is available at <https://github.com/OpenFAST>. The latest version of QBlade is available at <https://sourceforge.net/projects/qblade/>. The version of

Table A1. Wake coarsening parameters for aerodynamic and aeroelastic LLFVW simulations

Simulation type	Wind speed range	Near-wake	Mid-wake	Far-wake	Wake cut-off	Mid-wake factor	Far-wake factor
Aerodynamic	4-25 m/s	10 revs	10 revs	1 rev	21	2	3
Aeroelastic	4 m/s	0.5 revs	5.5 revs	12 revs	18 revs	3	3
	6 m/s	3 revs	5 revs	10 revs	18 revs	2	2
	8 - 10 m/s	1 rev	2 revs	7.7 revs	10.7 revs	3	4
	12 m/s	0.5 revs	0 revs	8 revs	8.5 revs	2	2
	14 - 20 m/s	0.5 revs	0 revs	7.5 revs	8 revs	2	2
	20 - 24 m/s	0.5 revs	0 revs	6.5 revs	7 revs	2	2

QBlade used in this paper that includes the structural model will be made available soon. The time series for the BEM and LLFVW calculations used in this paper are stored in the OpenFAST binary format. They can be made available upon request. The figures described but not shown in sections 5 and 6 can be made available upon request.

Appendix A: Wake Coarsening Parameters for the LLFVW Simulations

- 5 This appendix contains the wake coarsening parameters we used in our LLFVW simulations. They are summarized in Table A1.

Author contributions. S. Perez-Becker prepared the manuscript with the help of all co-authors. D. Marten is the main developer of QBlade and developed the aerodynamic code. J. Saverin developed the structural code. S. Perez-Becker and F. Papi performed the calculations and the analysis of the results. A. Bianchini and C.O. Paschereit provided assistance with the paper review.

- 10 *Competing interests.* The authors declare that they have no conflict of interest.

Acknowledgements. S. Perez-Becker wishes to thank WINDnovation Engineering Solutions GmbH for supporting his research.

References

- Bak, C., Madsen, H. A., and Johansen, J.: Influence from Blade-Tower Interaction on Fatigue Loads and Dynamics, in: Proceedings of the 2001 European Wind Energy Conference and Exhibition, pp. 394–397, Copenhagen, Denmark, 2001.
- Bak, C., Johansen, J., and Andersen, P. B.: Three-Dimensional Corrections of Airfoil Characteristics based on Pressure Distributions, in: Proceedings of the European Wind Energy Conference and Exhibition, pp. 1–10, Athens, Greece, 2006.
- Bak, C., Zahle, F., Bitsche, R., Kim, T., Yde, A., Henriksen, L. C., Andersen, P. B., Natarajan, A., and Hansen, M. H.: Design and Performance of a 10 MW Wind Turbine, Tech. Rep. I-0092, DTU Wind Energy, Roskilde, Denmark, 2013.
- Bergami, L. and Gaunaa, M.: ATEFlap Aerodynamic Model, a Dynamic Stall Model Including the Effects of Trailing Edge Flap Deflection, Tech. Rep. Risø-R-1792, DTU Wind Energy, Risø, Denmark, 2012.
- Boorsma, K., Hartvelt, M., and Orsi, L.: Application of the Lifting Line Vortex Wake Method to Dynamic Load Case Simulations, Journal of Physics: Conference Series, 753, 022 030, <https://doi.org/10.1088/1742-6596/753/2/022030>, 2016.
- Boorsma, K., Greco, L., and Bedon, G.: Rotor Wake Engineering Models for Aeroelastic Applications, in: Journal of Physics: Conference Series, vol. 1037, p. 062013, Milan, <https://doi.org/10.1088/1742-6596/1037/6/062013>, 2018.
- Borg, M., Mirzaei, M., and Bredmose, H.: LIFES50+ Deliverable D1.2: Wind Turbine Models for the Design, Tech. Rep. E-101, DTU Wind Energy, Risø, Denmark, 2015.
- Branlard, E., Papadakis, G., Gaunaa, M., Winckelmans, G., and Larsen, T. J.: Aeroelastic Large Eddy Simulations Using Vortex Methods: Unfrozen Turbulent and Sheared Inflow, Journal of Physics: Conference Series, 625, 012 019, <https://doi.org/10.1088/1742-6596/625/1/012019>, 2015.
- Buhl, M. L. J.: Crunch Software, <https://nwtc.nrel.gov/Crunch>, [Online; accessed 2018-01-27].
- Burton, T., Jenkins, N., Sharpe, D., and Bossanyi, E. A.: Wind Energy Handbook, John Wiley & Sons Ltd., West Sussex, United Kingdom, 2nd edn., 2011.
- Chen, J., Shen, X., Zhu, X., and Du, Z.: Influence of Wake Asymmetry on Wind Turbine Blade Aerodynamic and Aeroelastic Performance in Shear/Yawed Wind, Journal of Renewable and Sustainable Energy, 10, 053 309, <https://doi.org/10.1063/1.5030671>, 2018.
- Hansen, M. H., Henriksen, L. C., Hartvig, M., and Christian, L.: Basic DTU Wind Energy Controller, Tech. Rep. E-0028, DTU Wind Energy, Risø, Denmark, 2013.
- Hansen, M. O. L.: Aerodynamics of Wind Turbines, Earthscan, London, United Kingdom, 2nd edn., 2008.
- Hauptmann, S., Bülk, M., Schön, L., Erbslöh, S., Boorsma, K., Grasso, F., Kühn, M., and Cheng, P. W.: Comparison of the Lifting-Line Free Vortex Wake Method and the Blade-Element-Momentum Theory regarding the simulated Loads of Multi-MW Wind Turbines, Journal of Physics: Conference Series, 555, 012 050, <https://doi.org/10.1088/1742-6596/555/1/012050>, <http://stacks.iop.org/1742-6596/555/i=1/a=012050>, 2014.
- Hayman, G. J.: MLife Theory Manual for Version 1.00, Tech. rep., NREL, Golden, Colorado, 2012.
- IEC 61400-1 Ed. 3: IEC 61400-1: Wind Turbines - Part 1: Design Requirements, Standard, International Electrotechnical Commission, Geneva, Switzerland, 2005.
- Iribas, M., Morten, H. H., Mahmood, M., Tibaldi, C., Natarajan, A., Bossanyi, E., Stock, A., Jamieson, P., Leithead, W., and Schlipf, D.: INNWIND Deliverable 1.42: Methodology for Feed-Forward Control Strategies using Nacelle or Blade Based Sensors and Distributed Control, Tech. rep., INNWIND.eu, 2015.
- Jamieson, P.: Innovation in Wind Turbine Design, John Wiley & Sons Ltd., West Sussex, United Kingdom, 2nd edn., 2018.

- Jeong, M., Kim, S., Lee, I., and Yoo, S.: Wake Impacts on Aerodynamic and Aeroelastic Behaviors of a Horizontal Axis Wind Turbine Blade for Sheared and Turbulent Flow Conditions, *Journal of Fluids and Structures*, 50, 66–78, <https://doi.org/10.1016/j.jfluidstructs.2014.06.016>, <http://dx.doi.org/10.1016/j.jfluidstructs.2014.06.016>, 2014.
- Jonkman, J.: Modeling of the UAE Wind Turbine for Refinement of FAST_AD, Tech. Rep. TP-500-34755, NREL, Golden, Colorado, 2003.
- 5 Jonkman, J., Butterfield, S., Musial, W., and Scott, G.: Definition of a 5-MW Reference Wind Turbine for Offshore System Development, Tech. Rep. TP-500-38060, NREL, Golden, Colorado, 2009.
- Jonkman, J. M.: Overview of the ElastoDyn Structural-Dynamics Module, in: NREL Wind Turbine Modeling Workshop, Bergen, Norway, https://wind.nrel.gov/public/jjonkman/Presentations/WindTurbineModelingWorkshop_1409_NORCOWE_BergenNorway/3_ElastoDyn_Jonkman.pdf, 2014.
- 10 Jonkman, J. M. and Buhl, M. L. J.: FAST User's Guide, Tech. Rep. EL-500-38230, NREL, Golden, Colorado, <https://doi.org/10.2172/15020796>, <http://www.osti.gov/servlets/purl/15020796-vtWXa3/>, 2005.
- Madsen, H. A., Riziotis, V., Zahle, F., Hansen, M. O. L., Snel, H., Larsen, T. J., Politis, E., and Rasmussen, F.: Blade Element Momentum Modeling of Inflow with Shear in Comparison with Advanced Model Results, *Wind Energy*, 15, 63–81, <https://doi.org/https://doi.org/10.1002/we.493>, <https://onlinelibrary.wiley.com/doi/full/10.1002/we.493>, 2012.
- 15 Madsen, H. A., Larsen, T. J., Pirrung, G. R., Li, A., and Zahle, F.: Implementation of the Blade Element Momentum Model on a Polar Grid and its Aeroelastic Load Impact, *Wind Energy Science*, 5, 1–27, <https://doi.org/10.5194/wes-5-1-2020>, 2020.
- Marten, D., Wendler, J., Nayeri, C. N., and Paschereit, C. O.: Development and Application of a Simulation Tool for Vertical and Horizontal Axis Wind Turbines, in: Proceedings of the ASME Turbo Expo, San Antonio, Texas, <https://doi.org/10.1115/GT2013-94979>, 2013a.
- Marten, D., Wendler, J., Pechlivanoglou, G., Nayeri, C. N., and Paschereit, C. O.: QBlade: An Open Source Tool for Design and Simulation
20 of Horizontal and Vertical Axis Wind Turbines, *International Journal of Emerging Technology and Advanced Engineering*, 3, 264–269, 2013b.
- Marten, D., Lennie, M., Pechlivanoglou, G., Nayeri, C. N., and Paschereit, C. O.: Implementation, Optimization and Validation of a Nonlinear Lifting Line-Free Vortex Wake Module within the Wind Turbine Simulation Code QBlade, *ASME Journal of Engineering for Gas Turbines and Power*, 138, 072 601, <https://doi.org/10.1115/GT2015-43265>, 2015.
- 25 Moriarty, P. and Hansen, A.: AeroDyn Theory Manual, Tech. Rep. EL-500-36881, Golden, Colorado, <https://doi.org/10.2172/15014831>, <http://www.nrel.gov/docs/fy05osti/36881.pdf>, 2005.
- OpenFAST: OpenFAST, <https://github.com/OpenFAST/openfast>, [Online; accessed 2019-05-28].
- Perez-Becker, S., Saverin, J., Marten, D., Alber, J., Pechlivanoglou, G., and Paschereit, C. O.: Investigations on the Fatigue Load Reduction Potential of Advanced Control Strategies for Multi-MW Wind Turbines using a Free Vortex Wake Model, in: Proceedings of ASME Turbo
30 Expo 2018, p. V009T48A008, Oslo, Norway, <https://doi.org/10.1115/GT2018-76078>, 2018.
- Pirrung, G., Riziotis, V., Madsen, H., Hansen, M., and Kim, T.: Comparison of a Coupled Near- and Far-Wake Model with a Free-Wake Vortex Code, *Wind Energy Science*, 2, 15–33, <https://doi.org/10.5194/wes-2-15-2017>, <http://www.wind-energ-sci.net/2/15/2017/>, 2017.
- Qiu, Y. X., Wang, X. D., Kang, S., Zhao, M., and Liang, J. Y.: Predictions of Unsteady HAWT Aerodynamics in Yawing and Pitching using the Free Vortex Method, *Renewable Energy*, 70, 93–106, <https://doi.org/10.1016/j.renene.2014.03.071>, <http://dx.doi.org/10.1016/j.renene.2014.03.071>, 2014.
- 35 Saverin, J., Marten, D., Pechlivanoglou, G., Nayeri, C. N., and Paschereit, C. O.: Coupling of an Unsteady Lifting Line Free Vortex Wake Code to the Aeroelastic HAWT Simulation Suite FAST, in: Proceedings of ASME Turbo Expo 2016: Turbine Technical Conference and Exposition GT2016, vol. 9, p. V009T46A002, Seoul, South Korea, <https://doi.org/10.1115/GT2016-56290>, 2016a.

- Saverin, J., Peukert, J., Marten, D., Pechlivanoglou, G., Paschereit, C. O., and Greenblatt, D.: Aeroelastic Simulation of Multi-MW Wind Turbines using a free Vortex Model coupled to a geometrically exact Beam Model, *Journal of Physics: Conference Series*, 753, 082015, <https://doi.org/10.1088/1742-6596/753/8/082015>, <http://stacks.iop.org/1742-6596/753/i=8/a=082015?key=crossref.0cb9428c1433bb9b530c066d245312b6>, 2016b.
- 5 Simms, D., Schreck, S., Hand, M., and Fingersh, L. J.: NREL Unsteady Aerodynamics Experiment in the NASA-Ames Wind Tunnel: A Comparison of Predictions to Measurements, Tech. Rep. TP-500-29494, NREL, Golden, Colorado, <https://doi.org/10.2172/783409>, <https://www.nrel.gov/docs/fy01osti/29494.pdf>{% }0Ahttp://arc.aiaa.org/doi/abs/10.2514/6.2001-35, 2001.
- Snel, H. and Schepers, J.: Joint Investigation of Dynamic Inflow Effects and Implementation of an Engineering Method, Tech. Rep. ECN-C-94-107, ECN, Petten, Netherlands, <https://publications.ecn.nl/E/1995/ECN-C--94-107>, 1995.
- 10 Snel, H., Schepers, G., and Siccama, N.: MEXICO Project: The Database and Results of Data Processing and Interpretation, in: *Proceedings of the 47th AIAA Aerospace Sciences Meeting*, pp. 2009–1217, Orlando, Florida, <https://doi.org/10.2514/6.2009-1217>, 2009.
- Tasora, A., Serban, R., Mazhar, H., Pazouki, A., Melanz, D., Fleischmann, J., Taylor, M., Sugiyama, H., and Negrut, D.: Chrono: An Open Source Multi-Physics Dynamics Engine, in: *Proceedings of the International Conference on High Performance Computing in Science and Engineering*, pp. 19–49, Solan, Czech Republic, https://doi.org/10.1007/978-3-319-40361-8_2, 2016.
- 15 Van Garrel, A.: Development of a Wind Turbine Aerodynamics Simulation Module, Tech. Rep. ECN-C-03-079, ECN Wind Energy, <https://doi.org/10.13140/RG.2.1.2773.8000>, 2003.
- Voutsinas, S.: Vortex Methods in Aeronautics: How to Make Things Work, *International Journal of Computational Fluid Dynamics*, 20, 3–18, <https://doi.org/10.1080/106185600566059>, 2006.
- Voutsinas, S., Riziotis, V., and Manolis, D.: Advance Aeroelastic Modeling of Swept Rotor Blades, in: *Proceedings of European Wind Energy Conference and Exhibition*, Brussels, Belgium, 2011.
- 20 Wang, Q., Jonkman, J. M., Sprague, M., and Jonkman, B.: BeamDyn User’s Guide and Theory Manual, Tech. rep., NREL, Golden, Colorado, <https://nwtc.nrel.gov/BeamDyn>, 2016.
- Wendler, J., Marten, D., Pechlivanoglou, G., Nayeri, C. N., and Paschereit, C. O.: An Unsteady Aerodynamics Model for Lifting Line Free Vortex Wake Simulations of HAWT and VAWT in QBlade, in: *Proceedings of ASME Turbo Expo: Turbine Technical Conference and Exposition GT2016*, p. V009T46A011, Seoul, South Korea, <https://doi.org/10.1115/GT2016-57184>, 2016.
- 25