Scaling effects of rigid wing ground-generation airborne wind energy systems

Markus Sommerfeld¹, Martin Dörenkämper², Jochem De Schutter³, and Curran Crawford¹

¹Institute for Integrated Energy Systems, University of Victoria, British Columbia, Canada

²Fraunhofer Institute for Wind Energy Systems, Oldenburg, Germany

²Systems Control and Optimization Laboratory IMTEK, Freiburg, Germany

Correspondence: Markus Sommerfeld (msommerf@uvic.ca)

Abstract. While some Airborne Wind Energy System (AWES) companies aim at small, temporary or remote off-grid markets, others aim at utility-scale, multi-megawatt integration into the electricity grid. This study investigates the scaling effects of single-wing, ground-generation Airborne Wind Energy Systems from small to utility-scale systems, subject to realistic 10-minute, onshore and offshore wind conditions derived from the numerical mesoscale weather research and forecasting (WRF)

- 5 model. To reduce computational cost, wind velocity profiles are grouped into k = 10 clusters using k-means clustering. Three representative profiles from each cluster are implemented into a nonlinear AWES optimal control model, to determine poweroptimal trajectories. We compare the effects of three different aircraft masses and two sets of nonlinear aerodynamic coefficients for aircraft with wing areas ranging from 10 m^2 to 150 m^2 , on operating parameters and trajectories. We predict size- and weight-dependent AWES power curves, annual energy production (AEP) and capacity factor (cf) and compare them to a quasi-
- 10 steady state reference model. Instantaneous force, tether speed and power fluctuations as well as power losses associated with tether drag and system mass are quantified.

1 Introduction

45

Airborne wind energy systems (AWESs) harvest wind energy from the stronger and less turbulent winds at mid-altitude, here defined as heights above 100 m and below 1500 m. These beneficial conditions promise more reliable and stable wind power

- 15 generation compared to the conventional wind turbines (WTs) at lower altitudes. The light, tower-less design allows for mobile deployment and reduces the capital cost of AWESs (Lunney et al., 2017). These kite inspired systems consist of one or more autonomous aircraft which are connected to a ground station via one or more tethers. While various designs are investigated, two major crosswind concepts are currently considered by industry: the ground-generation also referred to as pumping-mode, and on-board-generation also referred to as drag-mode. This study focuses on the two-phase, ground-generation concept, as
- 20 it is currently the main concept pursued by industry. On-board-generation AWES carry additional weight with the on-board generator and propeller mass, as well as the heavier, conductive tether.

Ground-generation AWES generate power during the reel-out phase^s while the wing generates large lift forces and pulls the tether from a drum. During the following reel-in phase^s a fraction of the energy is consumed to return the aircraft back to its initial position and restart the cycle (Luchsinger, 2013). As a result, the power generated by such systems is inherently

25 oscillating which could be offset using multiple devices in a wind farm setup or buffering the energy before feeding it into the grid (Malz et al., 2018).

Over the last years, two main AWES applications emerged. The first makes use of the mobile nature of the technology which allows the deployment in inaccessible or remote places such as temporary mines or remote off-grid communities as these locations often rely on expensive diesel generators. Second is the grid-scale integration of AWES, which requires upscaling the

- 30 systems to compete with fossil and renewable energy sources in the energy market. One example is Ampyx Power (Ampyx, 2020) which aims to re-power decommissioned offshore wind farms or deploy floating platforms (offshorewind.biz, 2018), expecting higher energy yield due to better wind conditions, which in combination with design choices lead to lower levelized cost of electricity. Additionally, setting up AWES offshore allows for safer operation and is likely to be socially more accepted (Ellis and Ferraro, 2016).

We therefore investigate the scalability and design space of small to large-scale AWES, both offshore and onshore. De-40 pending on the aircraft wing surface area, aerodynamic coefficients and the tether diameter, rated power ranges from $\overline{P}_{rated} =$ 145 kW to 199 kW for $A_{wing} = 10 \text{ m}^2$ and $\overline{P}_{rated} = 2010 \text{ kW}$ to 3430 kW.

In comparison to the commonly used logarithmic wind speed profile, this WRF-derived set of wind data includes the wind direction rotation with height and the complex range of profile shapes emerging from atmospheric stability. This includes almost constant wind velocity profiles associated with unsteady stratification, high sheer wind velocity profiles resulting from stable conditions, as well as non-monotonic wind velocity profiles including low level jets (LLJs). The power output of an AWES not only depends on the wing size, but also the prevalent wind velocity profile shape and magnitude which result in distinct trajectories and operating altitudes. Therefore, a representative wind data set up to mid-altitudes, here defined as heights above 100 m and below 1500 m, is necessary to determine realistic AWES performance. This study relies on mesoscale numerical

- 50 weather prediction models such as the Weather Research and Forecasting (WRF) model, which is well known for conventional WT siting applications (Salvação and Guedes Soares, 2018; Dörenkämper et al., 2020), as measuring wind conditions at mid-altitudes is difficult due to reduced data availability aloft (Sommerfeld et al., 2019a). To reduce the computational cost, 10-minute average wind speed profiles were clustered using the k-means clustering method described in (Sommerfeld, 2020). We compare AWES performance for an onshore location in northern Germany near Pritzwalk (Sommerfeld et al., 2019b) and
- 55 an offshore location at the FINO3 research platform in the North Sea. These wind clustered wind conditions were implemented into the awebox (awebox, 2020) optimization framework which computes periodic flight trajectories that maximize average mechanical power output.

In comparison to our previous studies, which derived onshore and offshore AWES power curves, this paper explores the AWES design space from small to to utility-scale. We aim at setting up-scaling design and mass targets, instead of a detailed

- 60 system design. While other studies rely on simplified logarithmic wind speed profiles De Schutter et al., (2019), high resolution Large eddy simulation (LES) Haas et al. (2019) or reanalysis data sets Schelbergen et al. (2020) to investigate general behavior, performance, trajectory or wake effects, we optimize AWES trajectory subject to realistic 10 minute mesoscale wind data, which allows better optimal performance prediction.
- The main contribution is the presentation of aerodynamic, mass and size scaling effects on representative ground-station AWES subject to realistic wind conditions and operating constraints. The here described results inform decision-making regarding location-specific design, power estimation and scaling limitations.

The structure of the paper is as follows. Section 2 summarizes the onshore and offshore wind resource as well as the clustering results. For a detailed description of the WRF model and clustering algorithm see (Sommerfeld, 2020). Section 3 briefly introduces the AWES model and optimization method as well as the implemented constraints and initialization. Section 4 compares the results for six AWES

70 sizes with three different mass scaling assumptions and two sets of non-linear aerodynamic coefficients. We present, inter dight alia, trajectories, power curves and annual energy production estimates for a representative onshore and offshore location. Finally, Section 5 concludes the article with an outlook and motivation for future work to continue to advance AWES towards commercial reality.

2 Wind data

This study considers representative 10 min onshore (northern Germany, lat: $53^{\circ}10'47.00''$ N, lon: $12^{\circ}11'20.98''$ E) and offshore wind data (FINO3 research platform, lat: $55^{\circ}11,7'$ N, lon: $7^{\circ}9,5'$ E) derived from 12 months of WRF simulations each. Both locations are highlighted by a black dot in figure 1.



Figure 1. Topography-map of northern Germany with the representative onshore (Pritzwalk) and offshore (FINO3) locations highlighted with a black dot.⁸

Both horizontal velocity components of the resulting mesoscale wind data set are clustered using a **k**-means clustering algorithm (Pedregosa et al., 2011). According to previous investigations (Sommerfeld, 2020), a small number of clusters with few representative profiles per cluster yield good power and AEP estimates at reasonable computational cost. Therefore, the wind velocity profiles were grouped into k = 10 clusters from which the 5th, 50th and 95th percentile (sorted by wind speed at 200 m) were implemented into the optimization algorithm as design points to cover the entire annual wind regime.

The resulting average wind velocity profiles for each of the ten clusters, also known as centroids, are shown in the top row of figure 2. For presentation purposes, only each centroid's wind speed magnitude, colored according to average wind speed up to 500 m, is shown. The complete set of clustered profiles profiles are shown in grey. The cluster average wind profile shapes show wind shears typically associated with unstable and stable conditions. They follow expected location-specific trends

4

with lower wind shear and higher wind speeds offshore (right) in comparison to onshore (left). The associated, color-coded annual centroid frequency is shown in the center. The bottom subfigures summarize the wind speed probability distribution at a reference height of $100 \le z \le 400$ m. We chose this reference height as a proxy for wind speed at operating altitude, because an a priori estimation is impossible, and onshore and offshore power curves are almost identical using this reference wind speed. For a detailed description of the WRF model and setup, the clustering process as well as the correlation between clusters and stability conditions see (Sommerfeld, 2020).

90



Figure 2. Onshore (left) and offshore (right) annual cluster average wind speed profiles (centroids) resulting from the k-means clustering process for k = 10 (top). Underlying WRF simulated wind speed profiles depicted in grey. The centroids are sorted, labeled and colored in according to average wind speed up to 500 m. The corresponding cluster frequency f for each cluster C is shown in the center. The bottom in the bottom row figures show the wind speed probability distribution at a reference height of $100 \le z \le 400$ m.

3 **AWES** trajectory optimization model



- 95 AWES power production, which is intrinsically linked to the aircraft's flight dynamics, as the AWES never reaches a steady state over the course of a power cycle. Hence, power output estimation based on steady-state simplifications only give a rough estimate, but can not describe the variation of system parameters or operating trajectory which determine power production. particularly for realistic, non-monotonic wind profiles. Therefore we make use of optimal control methods to compute poweroptimal, dynamically feasible flight trajectories that satisfy operation constraints such as flight envelope and structural system
- 100 limits. We compare the optimization results to a simplified quasi steady-state (QSS) engineering AWES model (sub-section 3.2 to verify our results and to highlight the difference between both models.

3.1 Model overview

We compute ground-generation AWES power cycles by solving a periodic optimal control problem which maximizes the cycle-average AWES power output \overline{P} . In periodic optimal control, the system state at the initial and final time of the trajectory

105 must be equal, but are chosen freely by the optimizer. This methodology, implemented in the open-source software framework awebox (awebox, 2020), is used to generate power-optimal trajectories for single-wing ground-generation AWES sizes with various wing area, mass and aerodynamic performance. Table 1 summarizes the imposed constraints for each system design.

The AWES model considers a 6 degree of freedom (DOF) rigid-wing aircraft model with pre-computed quadratic lift, drag and pitch moment coefficients, which is controlled via aileron, elevator and rudder deflection rates. For this scaling study, the

110 Ampyx AP2 reference model (Ampyx, 2020; Malz et al., 2019) serves as a base from which the aircraft size and mass as well as aerodynamic coefficients were scaled (see sections 3.4 and 3.6).

While the ground station dynamics are not explicitly modeled, constraints on tether speed, acceleration and jerk are implemented to ensure a realistic operating envelope. For this study a reel-out to reel-in ratio of $\frac{2}{3} \left(\frac{v_{\text{out}}}{v_{\text{in}}} = \frac{10 \text{ ms}^{-1}}{15 \text{ ms}^{-1}} \right)$ was chosen. Tether acceleration $\ddot{l}_{\text{max}} = 10 \text{ ms}^2$ and tether jerk $\ddot{l}_{\text{max}} = 100 \text{ ms}^3$ were limited to simulate generator torque constraints. Tether

115 tension is defined by its diameter and maximum strain. The tether diameter has been chosen such that maximum average cycle power is achieved at an approximate wind speed of 10 ms.

For a more detailed description of the model and the optimization algorithm see (Sommerfeld, 2020; Leuthold et al., 2018; De Schutter et al., 2019; Bronnenmeyer, 2018; Horn et al., 2013; Haas et al., 2019).

3.2 Quasi-steady state reference model

120 To contextualize the optimization results, a quasi-steady state model (QSS) based on Loyd's-crosswind approximation Loyd (1980) is introduced. This model has been adapted by Schmehl et al. (2013) to include misalignment losses. It neglects aircraft and tether mass and assumes a quasi-steady state, with the wing moving directly cross-wind with zero azimuth angle $\phi = 0$ relative to the wind direction. Tether speed v_t is non-dimensionalized as the reeling factor ($f = v_t/U$) with an optimal value of $f_{opt} = 1/3\cos\theta\cos\phi$. Equation 1 estimates optimal power P_{opt} as a function of wind speed U at altitude z and the resultant aerodynamic force coefficient $c_{\rm R}$ (see equation 2), which is calculated from the aerodynamic lift $c_{\rm L}$ and total drag coefficient $c_{\rm D,total}$. Tether drag is included in the total AWES drag coefficient $c_{\rm D,total}$ according to a simplified estimation **3** Houska and Diehl (2007); Argatov and Silvennoinen (2013); van der Vlugt et al. (2019); Schmehl et al. (2013).

Maximizing P_{opt} is mainly a function of c³_R/c²_{D,total} and wind speed U at height z as well as tether length l_{tether} which determine the elevation angle θ = arcsin(z/l_{tether}). A linear approximation of the standard atmosphere yields air density ρ_{air}(z)
 130 at altitude z Champion et al. (1985) (ρ_{air}(z) = 1.225 kgm⁻³ - 0.00011 kgm⁻⁴z).

$$P_{\rm opt} = \frac{\rho_{\rm air}(z)}{2} U(z)^3 c_{\rm R} \left(\frac{c_{\rm R}}{c_{\rm D,total}}\right)^2 f_{\rm opt} \left(\cos\theta\cos\phi - f_{\rm opt}\right)^2 \tag{1}$$

$$c_{\rm R} = \sqrt{c_{\rm L}^2 + c_{\rm D,total}^2} \tag{2}$$

The total drag coefficient $c_{D,total}$ determines the air resistance of the entire AWES in crosswind motion. It depends on the tether diameter d_{tether} and length l_{tether} , as well as the wing area A_{wing} . The aerodynamic drag coefficient of the wing $c_{D,wing}$ depends on the angle of attack and the shape of is defined by the wing shape. We consider a cylindrical tether with constant diameter and an aerodynamic tether drag coefficient $c_{D,tether} = 1.0$. The tether drag coefficient could even be higher for braided tethers. For the sake of simplicity, tether slope is not considered in the drag calculation, which leads to an over estimation of tether drag. A more accurate tether model would further include the wind speed variation with height. Assuming a uniform wind, the line integral along the tether results in a total effective drag coefficient of Houska and Diehl (2007); Argatov and Silvennoinen (2013); van der Vlugt et al. (2019):

140
$$c_{\rm D,total} = c_{\rm D,wing} + \frac{1}{4} \frac{d_{\rm tether} l_{\rm tether}}{A_{\rm wing}} c_{\rm D,tether}$$
 (3)

Both the QSS and optimization model are subject to the same constraints (table 1). Optimal power of the QSS model is estimated by varying tether length up to 2000 m for every given wind profile (section 3.3) and applying the above described tether drag and elevation losses. The same minimal operating altitude as for the optimization model is enforced. The QSS-predicted power used for reference in sub-section 4.3 are the highest power for a given wind profile. Therefore, optimial operating height is the height at which the highest power is calculated, see previous publication (Sommerfeld, 2020).

3.3 Wind profile implementation

 \bigcirc

150

145

The 2D horizontal wind velocity profiles were clustered into k = 10 clusters, where representative profiles from each cluster as well as each cluster's centroid, rotated such that the main wind direction u points in positive x direction and the deviation v from it points in positive y direction, were implemented. This assumes omnidirectional AWES operation, which simplifies the comparison of results. We interpolate the u and v components using Lagrange polynomials to obtain a twice continuously differentiable function representation of the wind velocity profiles, which is necessary formulate an optimal control problem that can be solved with the gradient-based nonlinear programming (NLP) solver IPOPT (Waechter and Laird, 2016).

3.4 Aircraft scaling

Aircraft mass m and inertia J are scaled relative to the Ampyx AP2 reference model (Malz et al., 2019; Ampyx, 2020)

- 155 according to simplified geometric scaling laws relative to wing span *b* (see equation (4)). The mass scaling exponent κ ranges from 2.7 to 3.3. An exponent of 3 represents pure geometric scaling, while $\kappa = 2.7$ implies positive scaling effects and weight savings with size, while $\kappa = 3.3$ assumes negative scaling. A review of available literature shows that anticipated AWES scaling exponents vary between $\kappa = 2.2 - 2.6$ (grey area), shown in 3. We assume more conservative mass scaling for the purpose of this investigation.
- Makani's openly published technical reports describe their "M600 SN6" as well as their MX2 (*Oktoberkite*) design, which is a redesign of redesigned the M600 airframe to overcome some of its shortcomings and produce P_{MX2} = 600kW at a wind speed of U_{MX2-ref} = 11ms⁻¹ at operating height (Echeverri et al., 2020). Note that Makani's on-board-generation concept is inherently heavier than the ground-generation concept considered here, because of propellers, generators and supporting structures. The intended M600 design specified-a mass of 919 kg, which corresponds to an AP2 mass scaling exponent of κ = 2.72. The
 as built M600 had a wing area of A_{wing} = 32.9m² and a mass fm_{M600} = 1730.8kg. If we scale the AP2 reference aircraft to
- the same wing area and mass, the corresponding mass scaling exponent is $\kappa = 3.23$. The airframe of the improved MX2 design aimed at $m_{MX2} = 1852$ kg for a wing area of $A_{MX2} = 54$ m², equivalent to $\kappa = 2.719$ relative to the AP2 reference. Similarly, WT mass scales with an exponent slightly below 3 based on rotor diameter (Fingersh et al., 2006).



Figure 3. Curve fit of published sizing study AWES aircraft mass Haas et al. (2019); Kruijff and Ruiterkamp (2018); Eijkelhof et al. (2020); Ampyx (2020); Echeverri et al. (2020). For these data mass scales within a scaling exponent range of $\kappa = 2.2 - 2.6$ (grey area). The investigated, more conservative, mass scaling exponents between $\kappa = 2.7 - 3.3$ are depicted by dashed, dash-dotted and dotted lines.





170 3.5 Tether model

The tether is modeled as a straight, cylindrical solid rod with constant diameter which can not support compressive forces. This is a reasonable sympton when tether tension is high during the power production phase of the power cycle. Total tether drag is proportional to tether diameter d_{tether} and tether length l_{tether} . Both scale with tether tension, assuming a constant tensile strength, and therefore aircraft size and wind speed (see subsection 4.5). The tether drag is approximated by dividing the tether

175 into multiple elements (here $n_{\text{tether}} = 10$) and calculating the apparent wind speed at each element individually, assuming a constant tether drag coefficient of $C_D^{\text{tether}} = 1$, which could even be higher for braided tethers. Each elements tether drag is then equally divided between the two endpoints and finally transferred to either the aircraft or ground station. This leads to an underestimation of total tether drag at the aircraft (Leuthold et al., 2018).

Similarly, the total tether weight W_{tether} , calculated with a constant material density of $\rho_{\text{tether}} = 970 \text{ kgm}^{-3}$, is distributed 180 evenly between the aircraft and ground station.

Tether force constraints are chosen such that the system's rated power is achieved for a logarithmic wind speed profile with $U_{\rm sizing}(z = 200 \text{ m}) \approx 10 \text{ms}^{-1}$ ($U_{\rm sizing}(100 \le z \le 400 \text{ m}) \approx 10 \text{ms}^{-1}$), similar to wind at hub height for conventional wind turbines. Therefore, the tether diameter of every AWES design (table 1) is derived from the maximum tether stress $\sigma_{\rm tether} = 3.6 \cdot 10^9 \text{ Pa}$ and a safety factor $SF_{\rm tether} = 3$.

The Ground station is not explicitly modeled, instead hypothetical tether speed and acceleration constraints are imposed, mimicking motor torque and rotational speed limitations. Maximum reel-out speed is limited to $v_{out} = 15 \text{ ms}^{-1}$ and reel-in speed to $v_{out} = 10 \text{ ms}^{-1}$. This limits the mechanical, instantaneous power that each ground-generation AWES can generate $P_{\text{inst.}}^{\text{max}} = F_{\text{tether}}^{\text{max}} v_{out}$. A maximum tether acceleration of $\ddot{l} = 10 \text{ ms}^{-2}$ is imposed to comply with generator torque limits.

3.6 Aerodynamic scaling

Figure 4 compares the aerodynamic performance of AP2 wing with and without a 500m tether to a high lift wing. Lift $C_{\rm L}$ (a), drag $C_{\rm D}$ (b) and pitch moment $C_{\rm m}$ coefficients (c) and glide ratio are depicted as a function of angle of attack (e). Lift over Drag is shown in (d). The bottom right figure (f) displays the $\frac{C_{\rm R}^2}{C_{\rm D}^2}$ ratio (equation 1) which determines the theoretical maximum power of any crosswind AWES (Loyd, 1980; Diehl, 2013). Makani's reports mention two shortcomings of their original

M600 design were the overestimation of $C_{\rm L}^{\rm max}$ and underestimation of $C_{\rm D}$, further justifying this comparison and prompting a more conservative estimation of practical aerodynamic coefficients. The aerodynamic coefficients of the AP2 reference model

were identified in AVL (Drela and Youngren, 2016), CFD analyses by Ampyx Power and during unter the dest flights (Malz et al., 2019) Modifications to the AP2 aerodynamic reference model were implemented to assess the impact of improved aerodynamics on AWES performance (labeled HL for high lift). This is achieved by shifting the $C_{\rm L}$, $C_{\rm D}$ and $C_{\rm m}$ as if high lift devices, such as fixed trailing-edge flaps and fixed leading-edge slots, were attached Kermode et al. (2006); Lee and Su (2010);

200 Hurt (1965); Scholz (2016). Lift and drag at zero angle of attack are increased, stall is delayed, and pitch moment decreased. While both airfoils have comparable optimal glide ratios, the Loyd's optimal power ratio is almost twice as high for the high lift airfoil. Stall effects were implemented for both the AP2 reference model (blue) as well as the high lift (HL - orange) model by formulating a quadratic lift coefficient function (see figure 4). As a result, the lift coefficients deviate slightly in the linear lift region at lower angle of attack.



Figure 4. Aerodynamic lift $C_{\rm L}$ (a), drag $C_{\rm D}$ (b), pitch moment $C_{\rm m}$ coefficients (c) and with (dashed line) and without tether drag (solid diagrams) line) as a function of angle of attack for AP2 (blue) (Malz et al., 2019) and high-lift (HL) (orange) configuration. The bottom sub-figures display lift over drag (d), lift to drag ratio over angle of attack (e) and $c_{\rm R}^3/c_{\rm D,total}^2$ over angle of attack according to Level Loyd (1980). HL coefficients are derived by modifying the AP2 reference model as if high-lift devices, e.g. flaps and slats were attached.

205 3.7 Constraints

As previously mentioned, the AWES model solves a constrained optimal control problem to maximize average cycle-power of a single 6 DOF tethered aircraft connected to the ground station via a single rigid tether. Each run optimizes the trajectory during apply to the production cycle of an AWES at a fixed size subject to varying wind conditions. Constraints include system dynamics, material properties, aircraft (sub-section 3.6) and ground station hardware constraints as well as flight envelope limitations therein

210 listed in table 1. More information on the model and constraints can be found under a webox (2020) and the referenced publications. These limitations include minimum and maximum operating heights ($z_{operation}^{min}$ and $z_{operation}^{max}$), maximum acceleration measured as multiples of g $a_{\text{flight}}^{\text{max}}$ as well as a maximum tether length $l_{\text{tether}}^{\text{max}}$ to maintain safe operation. The number of loops n_{loop} within each cycle is fixed to 5. The maximum tether stress and force, from which the tether diameter is calculated, together with the periodicity constraint

215 are some of the most important path constraints. Ground station hardware limitations such as torque and acceleration dynamics are not explicitly modeled, but implemented as tether speed and acceleration constraints. A fixed angle of attack α and the slip angle β of the wing angle β range ensures operation within realistic bounds. However, neither angular constraint is active during flight, because the optimizer tries to achieve an angle of attack close to the maximum of $C_{\rm L}$, $C_{\rm D}$ and $C_{\rm m}$ figure 4). Due to weight and drag effects, actual angle of attack is closer to $\alpha \approx 10^{\circ}$ during reel-out for the majority of wind speeds.

220 3.8 Initialization

The AWES dynamics are highly non-linear and therefore result in a non-convex optimal control problem which possibly has multiple local optima. Therefore, the particular results generated by a numerical optimization solver can only guarantee local optimality, and usually depend on the chosen initialization The optimization is initialized with a circular trajectory based on a fixed number of $n_{\text{loop}} = 5$ loops at a 30° elevation angle and an estimated aircraft speed of $v_{\text{init}} = 10 \text{ ms}^{-1}$. Previous analyses showed that the convergence of large AWES highly depends on initial tether length. Larger systems become less sensitive to tether drag and hence can drag along a longer tether, because lift to tether drag ratio scales linearly with wing span. Therefore, initial tether length is increased linearly with aircraft wing area (see table 1).

In order to solve the highly nonlinear optimization problem, an appropriate initial guess is generated using a homotopy method similar to those detailed in (Gros et al., 2013; Malz et al., 2020). This technique gradually relaxes the problem from

- 230 simple tracking of circular loops to the original nonlinear path optimization problem where the previous result serves as an initial guess for the following problem. An initial circular path, which is determined from the tether length guess and estimated flight speed, is transformed into a periodic helix-like trajectory. Several initial tether lengths were investigated to determine a feasible initial path depending on system mass, system size and wind speed. Initial tether lengths needs to increase with system size and wind speed. The resulting problem is formulated in the symbolic modeling framework CasADi for Python (CasADi,
- 235 2016; Andersson et al., 2012) and solved using the NLP solver IPOPT (Wächter and Biegler, 2006) in combination with the linear solver MA57 (HSL, 2020).

Table 1. List of invest	st of investigated AWES design parameters and selected, important system constraints for	and ts for HL and AP2 ret	six HL designs ference <mark>aerodynamic</mark>
coefficients			

Parameter		AP2	design 1	design 2	design 3	design 4	design 5	design 6		
$A_{ m wing} \ [m^2]$		3	10	20	50	80	100	150		
	$c_{\rm wing}$ [m]	0.55	1.00	1.41	2.24	2.83	3.16	3.87		
	$b_{\rm wing}$ [m]	5.5	10	14.1	22.4	28.3	31.6	38.7		
Aircraft	AR [-]	10	10	10	10	10	10	10		
	$m_{\rm kite}(\kappa=2.7)$ [kg]	36.8	185	471	1,624	3,062	4,139	7,155		
	$m_{\rm kite}(\kappa=3.0)$ [kg]	36.8	221	626	2,473	5,005	6,995	12,850		
	$m_{\rm kite}(\kappa=3.3)$ [kg]	36.8	265	830	3,767	8,180	11,821	23,079		
	α [°]	[-10:30]								
	β [°]		[-15 : 15]							
	$l_{\rm tether}^{\rm max}$ [m]	2000								
Tether	$\dot{l}_{\rm tether} \ [{\rm ms}^{-2}]$	[-15 : 10]								
	$\ddot{l}_{\rm tether} [{\rm ms}^{-2}]$	[-15 : 10]								
	$\ddot{l}_{\rm tether}^{\rm max} [{\rm ms}^{-3}]$	[-20 : 20]								
	$\rho^{\text{tether}} [\text{kgm}^{-3}]$	970								
	$\sigma_{\max}^{\text{tether}}$ [Pa]	3.6 [×] 10 ⁹								
	SF^{sigma} [-]	3								
	$d_{\text{tether}}(\text{AP2}) \text{ [mm]}$		5.5	7.8	12.3	15.5	20	21.7		
	$d_{\rm tether}({ m HL})$ [mm]		7.2	10.2	16.1	20.6	23	28.3		
	$F_{\text{tether}}^{\text{max}}(\text{AP2})$ [kN]		34	60	136	241	377	456		
	$F_{\rm tether}^{\rm max}({\rm HL})$ [kN]		46	94	241	416	499	738		
	$z_{ m operating}^{ m min}$ [m]		55	60	75	90	100	125		
flight envelope	$z_{ m operating}^{ m max}$ [m]				10	00				
	$v_{\rm flight}^{\rm max} [{\rm ms}^{-1}]$	80								
	$a^{\max}\left[rac{m{g}}{m{g}} ight]$	12								
	$n_{ m loop}$ [-]	5								
Initialization	N _{loops}	5								
muanzation	ε [°]	30								
	$l_{\mathrm{tether}}^{\mathrm{init}} [\mathrm{m}]$		500	535	643	750	821	1000		

4 Results and Discussion

We compare $\overset{\text{blue}}{6}$ AWES sizes with three different mass properties and two sets of nonlinear aerodynamic coefficients each to investigate the AWES design space and upscaling potential. Furthermore, we contrast $\overset{\text{the}}{AWES}$ performance at representative onshore (Pritzwalk in northern Germany) and offshore locations (FINO3 research platform in the North Sea) based on one year

of WRF simulated and k-means clustered wind data. To that end, we show representative optimized trajectories (subsection 4.1) and compare typical operating altitudes and tether lengths (subsection 4.2). Subsection 4.3 analyses AWES power curves for each design and determines an AWES power coefficient based on swept area and wing chord. From this we derive the annual energy production (AEP) in subsection 4.4 for each location and system configuration. We examine the predicted power losses

245 (subsection 4.6) due to tether drag. Finally, we establish an upper limit of the weight to lift ratio and compare tether drag forces in subsection 4.5.

4.1 Flight trajectory and time series results

250

Figures 5(b) and 5(d) The trajectories in sub-figure b) and d) of Figure 5 depict the local optima of the highly non-linear model and optimization problem for AWESs with a wing area of $A_{\text{wing}} = 50 \text{ m}^2$, both AP2 (solid lines) and HL (dashed lines) aerodynamic coefficients and $\kappa = 3$. The trajectories seem reasonable, are within the set constraints and are consistent with other studies (De Schutter et al., 2019; Sommerfeld, 2020) which use the same model.

Sub-figure a) of Figure 5^(a) shows the wind speed profiles U over altitude \approx with the operating region highlighted in color. Any deviation from the WRF data in grey is caused by the interpolation with Lagrange polynomials during the implementation process described in subsection 3.3. The hodographs in sub-figure c) show a top view of the rotated wind velocity components

255 u and v up to a height of 1000 m which follow the expected clockwise rotation with altitude (Stull, 1988). The average wind speed between 100 m $\leq z \leq 400$ m is used as reference wind speed U_{ref} it is a good enough proxy for conditions at operating height (Sommerfeld, 2020).

Trajectories at higher wind speeds and above rated power deviate noticeably from the expected trajectory, which manifest at optimization algorithm the aircraft it lower wind speeds. The system tries to de-power by moving out of the wind window, either upwards or perpendicular to the as can be seen from Equation (1) main wind direction; to stay within the tether force, tether speed and flight speed constraints, while still maximizing average power. Subsection 4.2 further analyzes the trend towards longer tethers and higher operating altitude with increasing wind

speed, which can be seen here as distance from the origin.

Figure 6 describes the time dependent attitue of the previously analyzed trajectories during the operating cycle. Cycle time varies with wind speed and system configuration. A possible explanation is that better aerodynamics lead to higher flight speed and therefore shorter time to complete the cycle, as can be seen for lower wind speeds ($\overline{U}_{ref} = 5.5 \text{ ms}^{-1}$, blue). At higher wind the HL configuration needs to reduce the flight speed to stay within constraints and also requires a much longer reel-in phase, both speeds however, the system reduces its flight speed to stay within constraints, leading to a longer cycle time. The algorithm maintains a fixed number of loops, resulting in unnecessary and probably less optimal trajectories during the same model, showed that AWES power output seems to be fairly insensitive to both number of loops (here $n_{loop} = 5$ for all setups) and fight time. However, this paeds to be variefied and compared to other models and real experiments.

270 flight time. However, this needs to be verified and compared to other models and real experiments.

The optimizer aims to achieve a constant, maximum tether force F_{tether} (a) during the reel-out period and vary tether speed (Figure 4(c)) (Figure 4(e)) (Figure 4(e)) (Figure 4(e)) (Figure 4(d)) (Figure



Figure 5. Optimization results of ground-generation AWES with a wing area of $A_{wing} = 50 \text{ m}^2$, mass scaling exponent $\kappa = 3$ for both AP2 reference (solid lines) and high-lift HL (dashed lines) aerodynamic coefficients at various WRF-generated wind conditions. Sub-figures⁶(a) and (c) depict representative horizontal onshore wind speed profiles and their hodographs of wind velocity up to 1000 m. The deviation of the colored lines is caused by the implementation of discrete WRF-simulated data points using Lagrange polynomials. Sub-figures⁶(b) and (d) show the optimized trajectories in side and top view.

275 the tether reels out and the aircraft follows an almost circular pattern, which leads to deceleration of the aircraft during the ascent and acceleration during the descent. To maintain tether tension, tether speed decreases to zero. At lower wind speeds the aircraft can not produce sufficient lift force to pull the tether and overcome gravity during the ascent within each loop of the production cycle. As a result, tether force decreases together with apparent wind speed $v_{app}^{(Figure 6(c))}$ reeling instantaneous power $P_{eurrent}^{(Figure 6(a))}$ (see $U_{ref} = 5.5$ (ms⁻¹) blue). Even at higher wind speeds (see $U_{ref} = 11.5$ [ms⁻¹], orange) the tether speed drops to zero at during the ascent. As a consequence, the generated power also drops to zero and ramps up again (figure 6 (e)), leading to feed-in challenges.

reel-i

Additionally, aerodynamic loads drop to almost zero during the recovery phase as the aircraft returns to its initial position and the tether is reeled in. To reduce the power losses and decrease the reel-in time, tether speed quickly reaches its minimum of $v_{\text{tether}} = 15 \text{ms}^{-1}$. To alleviate this inherent intermittency, buffering the energy or coupling multiple, phase-shifted AWES in a wind farm setup would be beneficial (Malz et al., 2018).

285

At lower wind speeds, aerodynamic forces oscillate about a constant base load (figure 6) during the reel-out phase. With increasing wind speed, aerodynamic forces saturate due to tether tension constraints (table 1), leading to increasing periods of constant, maximum tension. However, tether force troughs decrease even further with tether length, due to increased total



Figure 6. Time series of optimized ground-generation AWES with a wing area of $A_{\text{wing}} = 50 \text{ m}^2$, mass scaling exponent $\kappa = 3$ for both AP2 reference (solid lines) and high-lift HL (dashed lines) aerodynamic coefficients at various WRF-generated wind conditions. The corresponding trajectories are shown in Figure 5. The sub-figures show tether force F_{tether} (a), tether speed v_{tether} (c) and instantaneous power $P_{\text{instruct}}^{\text{inst}}$ (e), as well as apparent wind speed v_{app} (b), angle of attack α (d) and tether length l_{tether} (f).

system weight. Figure 7 gives an insight into the tether load cycles during the reel-out phase of an AWES with a wing area
of A_{wing} = 50 m², both AP2 and HL aerodynamic coefficients and mass scaling of κ = 2.7, 3.0, 3.3. Average time between troughs (a) slightly increases with κ due to increased aircraft inertia, but remains almost constant with wind speed U_{ref}(100 m ≤ z ≤ 400 m). The relative reduction of tether tension troughs (b) ΔF_{tether}/F_{tether,max} = |F_{trough} - F_{tether,max}|/F_{tether,max} decreases with wind speed as the apparent wind speed at the wing increases. As expected, this decrease is more pronounced for heavier AWES. Higher aerodynamic efficiency (HL circular marker and dotted line) increases performance and smooths out
the troughs. The lightest configuration achieves constant reel-out tension at around rated wind speed of U_{ref} = 10ms⁻¹, while the heaviest design requires higher wind speeds of about 15ms⁻¹.

4.2 Tether length and operating altitude

One of the major value propositions of AWESs is that they can tap into wind resources beyond the reach of conventional wind turbines. However, the choice of optimal operating height highly dependents on the wind speed profile and system design. Two

300 opposing effects influence the optimal operating height. On the one hand, an increase in altitude is generally associated with an increase in wind speed and therefore produced power. On the other hand, higher altitudes require a longer tether which results in higher drag losses or increase the elevation angle which increase "cosine" losses (Diehl, 2013) ,or both.



Figure 7. Average time between tether tension troughs (a) and relative decrease in tether tension (b) during the production phase of optimized ground-generation AWES with a wing area of $A_{\text{wing}} = 50 \text{ m}^2$. The figures show results for mass scaling exponents $\kappa = 2.7, 3.0, 3.3$ (blue, red, green) and both sets of aerodynamic coefficients AP2 reference (square, dashed line) and high-lift HL (circle, dashed lines).

Figure 8 shows a trend towards longer average tether lengths \overline{l}_{tether} (top) and higher average operating altitudes $\overline{z}_{operating}$ (senter) with increasing system size for a representative scaling exponent of $\kappa = 3$ (see $\frac{E}{e}$ quation (4)) and wind speed. We chose U_{ref} to be the average wind speed between 100 m $\leq z \leq 400$ m as we previously found that this range is a good proxy for conditions at operating height (Sommerfeld, 2020). Lighter aircraft and higher lift wings results in slightly higher operating altitudes, a longer tether and higher elevation angle.

Outliers, e.g. for high wind speed profiles (compare $\frac{1}{10}$ gure 2), are likely local optima of the highly nonlinear trajectory optimization problem described in $\frac{s}{s}$ ection 3.

As wind speed increases beyond rated power ($U_{ref} \approx 10 \text{ ms}^{-1}$, see figures 5 and 6), the aircraft moves out of the wind window to de-power. This is seen as rising average elevation angles ε (bottom) above $U_{ref} = 10 \text{ms}^{-1}$. Results for both offshore (right) and onshore (left) follow the same trends, but operating heights below rated wind speed are lower offshore because of lower wind shear and higher wind speeds.

It is important to keep in mind that even though the operating height exceeds 500 m for wind speeds of more than $U_{\rm ref} \approx$

315 15 ms⁻¹ such wind speeds occur only about 10 % of the time (see figure 2). Between 5 and 15 ms⁻¹, the most likely wind speed range, operating heights both onshore and offshore are between 200 to 300 m. For smaller system sizes these heights are even lower. While this is slightly above the hub-height of current conventional wind turbines, it rebuts the argument of harvesting wind energy beyond this altitude. These findings are consistent with current offshore WT trends, whose rotor diameter increased



Figure 8. Average tether length \overline{l}_{tether} (top), average operating altitude $\overline{z}_{operating}$ (center) and average elevation angle $\overline{\varepsilon}$ (bottom) over reference wind speed $\overline{U}_{ref}(100 \le z \le 400 \text{ m})$. Results for wing areas between $A_{wing} = 10 - 150 \text{ m}^2$ scaled with a mass scaling exponent of $\kappa = 3$, AP2 reference aerodynamic coefficients for both onshore (left) and offshore (right) location.

significantly while hub height only increased marginally over the last years. However, it is likely that offshore hub heights will
 increase as technology improves, making the argument for the deployment of AWES particularity challenging as both operate at comparable heights and WT are the more proven and established technology. However, this might be different for multiple kite systems which could benefit from longer tethers, due to reduced tether motion (De Schutter et al., 2019).

4.3 Power curve, annual energy distribution and power harvest factor

¹ⁿ the following, we This sub-section compares average power \overline{P} , annual energy production distribution E and power harvest factor ζ (equation Figures 9(a) and 10(a) 325 5) of optimized trajectories to the quasi steady-state model (QSS) described in sub-section 3.2. The top Sub figures (a) of figure 9 and 10 compare the effect of aerodynamic efficiency and location on cycle-average power in the form of a power curve for AWESs with a wing area of $A_{\text{wing}} = 50 \text{ m}^2$ and a mass scaling exponent of $\kappa = 2.7$. The data are derived from $\frac{10}{2}$ representative profiles from each of the 10 wind velocity clusters. Average wind speed between 100 and 400 m has been chosen as reference wind speed, because these are typical operating heights for these AWES. As of now, no standard reference wind speed at hub height for conventional WT, has been agreed upon for AWES. Furthermore, using this altitude range results in comparable power curve trends onshore and offshore. Offshore AWES could benefit from a larger tether diameter as wind speeds are generally higher (see figure 2) which would result in higher rated power and AEP. Higher lift coefficients result in higher rated power and a steeper power increase up to rated power. Power variations are caused by local optima mostly occurring above rated wind speed as the system de-powers to stay within tether force and flight speed constraints (see subsection 3.7).

335



Figure 9. Representative AWES power curves (top) for both sets of HL (circle) and AP2 (square) reference aerodynamic coefficients for both onshore (blue) and offshore (orange) location. The masses of the $A_{\text{wing}} = 50 \text{ m}^2$ wing area aircraft are scaled according to equation (4) with a mass exponent of $\kappa = 2.7$. Cycle-average power \overline{P} is derived from p5, p50, p95 wind velocity profiles within each of the k = 10 WRF-simulated clusters. A reference height of $100 \le z_{\text{ref}} \le 400$ m is used as a proxy for wind speed at operating altitude to calculate the annual wind speed probability distribution (bottom). The integral over the annual Energy production distribution (bottom) which is the product of power and wind speed probability distribution, yields the AEP (legend).

Rated power, here defined as the maximum, almost constant average cycle power, which is constrained by instantaneous tether force and speed, is summarized in Table 2. Tether reel-in and reel-out are kept constant for all designs, simulating drum speed constraints. Tether diameter is kept constant for both locations, but adjusted according to aircraft area and aerodynamic efficiency so that all system sizes reach rated power at about $U_{\rm ref} = 10 \,\mathrm{ms}^{-1}$ (see subsection 3.5). Therefore, the HL configuration achieves higher rated power. No cut-out wind speed limitations were implemented. Therefore, wind power is only limited by each location's maximum wind speed, which is significantly higher offshore (compare figure 2). Table 2 also shows the estimated equivalent WT rotor diameter $D_{\rm WT}^{\rm equiv}$, for an assumed power coefficient of $c_{\rm p}^{WT} = 0.4$ and a rated wind speed of



Figure 10. QSS model-based AWES power curves (top) for an AWES wing area of $A_{\text{wing}} = 50 \text{ m}^2$, both sets of HL (circle) and AP2 (square) reference aerodynamic coefficients and both onshore (blue) and offshore (orange) location. Optimal power $\overline{P}_{\text{Loyd}}$ is derived from p5, p25, p50, p75, p95 wind speed profiles within each of the k=10 WRF-simulated clusters. A reference height of $100 \le z_{\text{ref}} \le 400 \text{ m}$ is used as a proxy for wind speed at operating altitude to calculate the annual wind speed probability distribution (enterplacement). The integral over the annual energy production distribution (bottom) which is the product of power and wind speed probability distribution, yields the AEP (legend)

 10ms^{-1} . The system size and therefore material cost benefits of AWES become obvious when comparing AWES wing span b_{wing} to WT rotor diameter $D_{\text{WT}}^{\text{equiv}}$. AWES wing span is about 30 (HL) to 40 % (AP2) of the equivalent rotor diameter.

345

AEP and *cf* almost doubles for HL in comparison to the AP2 reference, highlighting the importance of exploring high lift configurations. The QSS modeled power curves (see figure 10), which use the same wind velocity profiles and tether diameter as the optimization model, achieve rated power at around $U_{\text{rated}}(100 < z_{\text{ref}} < 400) \approx 8ms^{-1}$. This is caused by the fact that the engineering model neglects mass and predicts optimal power production, whereas the dynamic optimization model resolves the flight trajectory and the varying forces and power within each production cycle. Deviation between QSS onshore and offshore power are due to variation in wind conditions.

350

The annual wind speed probability distribution f (b) represents the average annual wind speed between $100 \le z \le 400$ m which stands in as a proxy for wind at operating altitude (see section 2). As expected, higher wind speeds are more likely to occur offshore (FINO3) than onshore (Pritzwalk). However, very high wind speeds above $U_{ref} > 18 - 20 \text{ms}^{-1}$, beyond the

Table 2. Rated power of AWES with a mass scaling exponent of $\kappa = 2.7$ and equivalent wind turbine rotor diameter

$A_{\rm wing}[{\rm m}^2]$	10		20		50		80		100		150	
$b_{ m wing}[{ m m}]$	10		14.1		22.4		28.3		31.6		38.7	
aerodynamic coeff.	AP2	HL	AP2	HL	AP2	HL	AP2	HL	AP2	HL	AP2	HL
$\overline{P}_{\text{rated}} [\text{kW}]$	145	200	265	420	575	1030	1045	1800	1600	2225	2000	3400
$D_{\rm WT}^{\rm equiv}$ [m]	27	32	37	47	55	73	74	97	91	108	102	132

cut-off speed of realistic wind energy converters, have a very low chance occurrence at both locations. The resulting annual average energy production distributions \overline{E} (c) reveal a clear difference between the offshore and onshore energy potential.⁸ Better wind conditions offshore result in higher AEP and cf (sub-section 4.4).

Estimated energy production distributions E_{QSS} , AEP and cf (Figure 10) of the QSS reference model are based on the same wind speed distribution as the optimization model. Here the QSS model data has been interpolated to be compatible with the annual wind speed probability distribution f (b). The QSS model predicts a higher energy production distribution (c) up to

360 rated wind speed than the optimization model, because of the lack of a defined cut-in wind speed and a sooner rated power. Beyond rated power, E_{QSS} is similar to optimized results, as predicted power is very similar, except some small variation. This leads to a higher AEP and cf predictions (Figure 11). Figures 9(d) and 10(d)

Sub-figure (d) in figures 9 and 10 presents the power harvest factor ζ Diehl (2013), which sets cycle-average AWES power \overline{P} in relation to the total wind power of a cross sectional area of the same size as a given wing A_{wing} .

365
$$\zeta = \frac{P}{P_{\text{area}}} = \frac{\overline{P}}{\frac{1}{2}\rho_{\text{air}}A_{\text{wing}}U(z)^3} \le \frac{4}{27}c_{\text{R}}\left(\frac{c_{\text{R}}}{c_{\text{D}}}\right)^2$$

U(z) is the wind speed and $\rho_{air}(z)$ the air density at operating altitude. The power harvest factor decreases steadily for both the optimization and QSS model. The QSS model predicts an almost constant ζ at low wind speeds ($U_{ref} < 5 \text{ ms}^{-1}$)

(5)

4.4 Annual energy production and capacity factor

The previously described power curves \overline{P} (a) and annual wind speed probability distributions f (b) allow the investigation of the annual energy production distribution E (c) and therefore annual energy production (AEP) as well as capacity factor (cf):

In Figure 11 AEP and cf are compared The left side of figure 11 compares onshore AEP (a,b) and ef (c,d) for all system sizes scaled with a mass scaling exponent Figures 11(a) and 11(c) describe onshore conditions, while Figures 11(b) and 11(d) describe offshore conditions of $\kappa = 2.7$ to QSS data, while the right side compares offshore results. AEP increases almost linearly with wing area, because power, which is the product of tether force scales linearly with wing area and the maximum tether speed is kept constant 375 throughout all optimization runs. As expected HL aerodynamic coefficients (circle) outperform the AP2 reference (square).

Offshore (orange) AEP and cf is generally higher than onshore (blue) because of the higher likelihood of higher wind speeds. The QSS model predicts higher AEP, because of the previously described differences in power up to rated wind speed (subsection 4.3), but follows the same trends. The optimization model predicts lower average AEP at $A_{\rm wing} = 150 \text{ m}^2$, due to the high number of infeasible solutions at lower wind speeds. Overall cf (c,d) remains almost unchanged up to $A_{\text{wing}} = 100 \text{ m}$ and sharply declines for $A_{\text{wing}} = 150 \text{ m}$. Onshore AEP and cf seems to outperform offshore for wing areas larger than 100m^2 . 380 This is likely caused by outliers, or wind velocity profile specific local minima, in the power curve before rated wind speed $(v_{\text{rated}} = 10 \text{ ms}^{-1})$, where the system seemingly over-performs. The QSS model predicts very high cf values at both locations, while offshore AEP always outperforms onshore AEP. The relatively high cf values are the result of relativity low rated wind speed. This location specific design trade-off between generator size, wing area and tether diameter needs to be further investigated.

385



Figure 11. Representative AWES AEP (a,b) and cf (c,d) over aircraft wing area A_{wing} scaled according to equation (4) with a mass exponent diagrams of $\kappa = 2.7$. OSS model (solid lines) results are included for reference (sub-section 3.2). These figures summarizes data for both sets of HL (circle) and AP2 (square) aerodynamic coefficients as well as both onshore (left, blue) and offshore (right, orange) location. Results are based on the cycle-average power \overline{P} derived from p5, p50, p95 wind velocity profiles within each of the k = 10 WRF-simulated clusters and wind speed probability distribution between $100 \le z_{ref} \le 400$ m, used as a proxy for wind speed at operating height.

Figure 12 compares AEP for a mass scaling exponents of $\kappa = 2.7$ to scaling with $\kappa = 3$ and $\kappa = 3.3$, both onshore and offshore. Heavy configurations with no feasible trajectory at any wind speed result in missing data. While smaller systems seem almost unaffected by aircraft weight, mass scaling effects lead to significant reduction in AEP for larger AWES. This is particularly true for wings with aerodynamic reference coefficients (AP2, square) and onshore wind conditions. Combining

results from both figure 11, which already shows diminishing returns in AEP and cf with increasing wing area for the lightest, 390 idealized aircraft mass scaling, and figure 12, which predicts that AEP will only decline for heavier mass scaling, conveys that upscaling AWES is only beneficial with significant weight reduction. These results hint at the existence of an upper limit of AWES weight relative to AWES size or lift (see subsection 4.5), which is plausible since mass scales with aircraft volume and lift scales with aircraft area. Therefore and for compensating power fluctuation caused by the cyclic nature of groundgeneration AWES, it is likely better to deploy multiple smaller scale devices rather than a single large-scale system. The ideal, 395 site-specific AWES size needs to be determined by realistic mass scaling and the local wind resource.



Figure 12. AEP ratio for mass scaling exponent $\kappa = 3$ (dashed lines) and $\kappa = 3.3$ (dotted lines) relative to AEP of $\kappa = 2.7$ over aircraft wing area A_{wing} . Figure summarizes data for both onshore (blue) and offshore (orange) location^s as well as both sets $\overset{\text{of}}{\text{aerodynamic coefficients HL}}$ (circle) and AP2 (square). Results are based on the cycle-average power \overline{P} derived from p5, p50, p95 wind velocity profiles within each of the k = 10 WRF-simulated clusters. Missing data points indicate that no feasible solution for any wind velocity profile was found.

4.5 Impact of weight and drag

400

The ground-generation crosswind AWES concept benefits from increased apparent wind speed (Loyd, 1980). Such trajectories, whether circular or figure-of-eight, always include an ascent during every loop where the aircraft needs to overcome gravity to gain altitude. This leads to a deceleration and therefore reduction of aerodynamic lift. AWESs with excess mass fail to overcome weight and drag and can no longer climb. during these phases

rated by the flight motion of the tethered aircraft

With an increased wing area, the entire aircraft, particularly the load carrying structures such as the wing box, need to increase in size and weight in order to withstand increased aerodynamic loads produced by a larger wing. Aircraft mass scales with volume ($\kappa = 3$), assuming pure geometric scaling without design improvements, while lift force and therefore power only scales with the area ($F_{\text{lift}} \sim b^2$). However, when tether drag is considered AWES power scales faster than b^2 , because tether drag losses are proportional to the tether diameter, which scales relative to the square root of the wing area. Similarly,

conventional WT power and AEP scales with the rotor diameter square, while theoretic WT mass scales with the cube of the rotor diameter. However, comparing both wind energy converters under these assumptions. AWES perform worse with size as their flight path degrades. This can be attributed to the fact that AWES need to produce enough lift to carry their own weight

410 to maintain operational, while WT are supported by a tower.

415

420

These facts limit AWES size, as the prevailing wind resource does not improve enough to produce sufficient aerodynamic lift to overcome the increased system drag and weight. An increase of operating altitude only comes with a marginal wind speed increase especially offshore (compare figure 2). Furthermore, higher operating altitudes also lead to increased cosine losses, unless offset by a longer tether which in turn results in more drag and weight. Better aerodynamics or lighter, more durable aircraft and tether materials can only push this boundary, but not overcome it.

A comparison of tether weight W_{tether} during the production phase (reel-out) to total system weight $(W_{\text{total}} = W_{\text{aircraft}} +$ $\frac{F_{i}}{W_{tother}}$ in figure 13 (top) shows that the tether makes up 10 to 30 % of the entire system weight. Note that the tether cross sectional area is sized with a safety factor of 3. Tether cross sectional area mostly scales with aerodynamic force and therefore wing area while the aircraft weight scales with a mass scaling exponent $\kappa > 2.7, 3.0$ which results in decreasing trend lines. This value is higher for high lift airfoils (circle) as the tether diameter is larger to withstand higher aerodynamic forces. For

lighter aircraft, scaled with $\kappa = 2.7$ (dash-dotted), the portion of tether weight is higher because the tether diameter remains constant while the aircraft mass is lighter.

Figure 13(bottom) The bottom sub-figure reveals that tether drag makes up about 18 to 40 % of the entire system drag during the production phase. Tether diameter d_{tether} and therefore face area $(A_{\text{tether}}^{\text{face}} = d_{\text{tether}})$ scales beneficially with wing area, leading to 425 the downward trend lines. As descried in Sub-section 3.5, the total tether drag is divided up evenly between the top and bottom node at every tether segment, resulting in half the tether drag being attributed to the aircraft and the other half to the ground station. Implementing more detailed tether models could explore the impact of tether dynamics and tether drag in more detail.

It is critical for crosswind AWES to ascend during each loop of the production or reel-out phase. The aircraft needs to produce enough aerodynamic lift, which decreases as the aircraft slows down during ascent (compare 6), to overcome gravity. During

- the ascent, the aircraft increases angle of attack (figure 6) to compensate for the decreased apparent wind speed. However, 430 this is not enough to maintain aerodynamic force and tether tension during times of lower wind speeds, especially for larger Figure 14(top) and heavier systems. The top sub figure in figure 14 contrasts the aeronautic load factor defined as the ratio of average lift force \overline{L}_{wing} to total AWES weight \overline{W}_{total} , including tether with a safety factor of 3 and aircraft, during the reel-out phase for all aircraft sizes $A_{\text{wing}} = 10 - 150 \text{m}^2$, mass scaling exponents $\kappa = 2.7, 3.0, 3.3$ and aerodynamic coefficients HL, AP2. The
- average load factor decreases from about 10 20 to $\frac{10-5}{10-5}$, depending on aerodynamic performance and mass scaling, which 435 is approximately the maneuvering load factor of an acrobatic airplane $n_{\text{acrobatic}} = 6.0$ (Federal Aviation Agency, 2017). For utility airplanes this value is about $n_{\rm acrobatic} = 4.4$. The beneficial effect of better aerodynamics and mass scaling are clearly visible in a lower weight to lift ratio. High system mass with insufficient lift on the other hand leads to infeasible solutions and missing data.



Figure 13. Percentage of cycle-average tether weight $\overline{W}_{\text{tether}}$ to total weight $\overline{W}_{\text{total}}$ (top) and tether drag $\overline{D}_{\text{tether}}$ to total drag $\overline{D}_{\text{total}}$ (bottom) during production phase (reel-out) for all aircraft sizes $A_{\text{wing}} = 10 - 150 \text{ m}^2$, sets of aerodynamic coefficients AP2, HL and mass scaling exponents $\kappa = 2.7, 3, 3.3$ for wind data at the offshore location.

440 The bottom sub-figure 14 shows a slight reduction of total average drag \overline{D}_{total} to average lift \overline{L}_{wing} ratio with increasing wing area. Overall however, this ratio remains almost constant between 6 to 8 %. The increase for $A_{wing} = 100,150 m^2$, $\kappa = 3$ and AP2 aerodynamics is likely caused by local optimization minima and few feasible wind speed profiles.

For a large-scale aircraft with an area of $A_{\text{wing}} = 150 \text{ m}^2$, scaled with the lightest mass scaling exponent of $\kappa = 2.7$, and AP2 reference aerodynamic coefficients, no feasible solution could be found for low wind speeds $U_{\text{ref}} < 5 \text{ms}^{-1}$. This can be seen in figure 15 which shows the total weight $\overline{W}_{\text{total}}$, including tether and aircraft, divided by average lift $\overline{L}_{\text{wing}}$ for all aircraft

seen in figure 15 which shows the total weight \overline{W}_{total} , including tether and aircraft, divided by average lift \overline{L}_{wing} for all aircraft sizes with AP2 reference aerodynamic scaled with $\kappa = 2.7$. Weight to lift ratio increases up to $U_{ref} \approx 5 \text{ms}^{-1}$, above which it remains almost constant. This can likely be attributed to the applied apparent flight speed constraint of $U_{add}^{max} = 80 \text{ms}^{-1}$ which

seems to already be achieved at this reference wind speed.
From this, together with time series data shown in ^{fig}/_{fig}ure 6, it is possible to to estimate the minimum cut-in wind speed or
minimum viable aerodynamic load factor (lift to weight ratio). For the investigated design and constraints, the minimum viable aerodynamic load factor seems to be about 5 which is equivalent to a maximum viable weight to lift ratio of 20 %. No feasible solutions were ^{found}/_{fund} for lower wind speeds.

The bottom sub-figure of figure 15 shows the total AWES drag \overline{D}_{total} , including tether drag, to lift ratio \overline{L}_{wing} over reference wind speed for all aircraft sizes scaled with $\kappa = 2.7$ and AP2 reference aerodynamic coefficients. Data for all aircraft sizes show a similar trend with the drag proportion doubling from about 5 to 10 % with wind speed. This increase is primarily caused

455



Figure 14. Load factor or lift \overline{L}_{wing} to \overline{W}_{total} ratio (top) and cycle-average total lift \overline{L}_{wing} to drag \overline{D}_{total} , including tether drag, (bottom) during production phase (reel-out) for all aircraft sizes $A_{wing} = 10 - 150 \text{ m}^2$, sets of aerodynamic coefficients AP2, HL and mass scaling exponents $\kappa = 2.7, 3, 3.3$ for wind data at the offshore location. Large-scale results for $A_{wing} = 100, 150 \text{ m}^2$ might be misleading because only high wind speeds result in feasible solutions (compare figures 15).

weight also leads to an angle of attack α increase as the aircraft needs to produce more lift while staying within the flight speed constraint.

4.6 Power losses

460 ^{An}Increased aircraft wing area not only leads to increased power potential, but is also accompanied by increased tether losses due to weight and drag. Tether mass scales with aircraft wing size because the higher aerodynamic forces require a larger tether diameter, assuming constant tether strength. Tether length increases with AWES size and wind speed (see ^Ssubsection 4.2) which further increases tether drag and weight.

Figure 16 compares the average tether power losses $\overline{P}_{\text{tether}}^{\text{drag}}$, calculated from the tether drag assigned to the aircraft node and its flight speed, relative to average cycle power \overline{P} for all aircraft wing sizes $A_{\text{wing}} = 10 - 150 \text{ m}^2$, mass scaling exponents $\kappa = 2.7, 3.0, 3.3$ and both sets of aerodynamic coefficients (HL, AP2). This power loss can be interpreted as how much of the harvested wind power is dissipated by the tether. The relative tether drag loss decreases with wing area, because tether diameter scales beneficially with the square root of the tether force which scales linearly with wing area. This scaling trend is



Figure 15. Ratio of cycle-average total weight $\overline{W}_{\text{total}}$ to lift $\overline{L}_{\text{wing}}$ (top) and cycle-average total drag $\overline{D}_{\text{total}}$, including tether drag, to lift $\overline{L}_{\text{wing}}$ (bottom) during production phase (reel-out) for all aircraft sizes $A_{\text{wing}} = 10 - 150 \text{ m}^2$ for AP2 reference aerodynamic coefficients and a mass scaling exponent of $\kappa = 2.7$ over reference wind speed offshore.

encouraging, but is counteracted and dominated by mass increases with size highlighted in earlier sections. As expected, the
high lift airfoil HL (dotted lines) experiences less relative drag loss than the AP2 reference airfoil (dashed lines) due to higher average cycle power.

5 Summary and conclusion



This study presents AWES scaling trends and explores the AWES design space subject to representative onshore (Pritzwalk in nothern Germany) and offshore (FINO3 research platform in the North Sea) wind conditions. Tether speed range and tether diameter of every design (size and aerodynamic coefficients) were fixed. This can be interpreted as generator limitations on speed, torque and power which result in a constant maximum AWES power and a power curve as a function of wind speed. We evaluate^d the impact of wing area and mass scaling as well as nonlinear aerodynamic properties on optimal trajectories, reaction forces and moments, power generation and AEP, based on the awebox power and trajectory optimization model. Our analyses estimate a maximum average weight to average lift ratio (equivalent to a load factor of about 5) to allow viable AWES

480 operation of about 20%. Our results imply the existence of an upper limit of AWES weight relative to AWES size or lift, which is plausible since mass scales with aircraft volume and lift scales with aircraft area. In comparison, conventional WT power scales with the square and mass with the cube of the rotor diameter. Under the same assumptions AWES performance scales worse because the aircraft needs to carry the entire increasing system weight (including tether mass), instead of being supported



Figure 16. Ratio of cycle-average power losses due to tether drag $\overline{P}_{\text{tether}}^{\text{drag}}$ to produced power \overline{P} over aircraft size A_{wing} for both sets of aerodynamic coefficients AP2, HL, all mass scaling exponent of $\kappa = 2.7, 3.0, 3.3$ and wind data at the offshore location.

by a tower. Therefore, the optimal AWES size is always defined by the maximum weight, including tether and aircraft, which the aircraft can support, subject to local wind conditions.

In this work we described and analyzed ground-generation AWES scaling effects subject to realistic wind velocity profiles for a set of representative AWES. We compare the impact of several design parameters based on the Ampyx AP2 reference model. We analyze AWES performance for two sets of nonlinear aerodynamic coefficients, the AP2 reference and a high lift configuration where AP2 coefficients were adjusted as if high lift devices were attached. To assess AWES scaling potential, several wing areas between $A_{wing} = 10 - 150$ m, with mass properties scaled according to a geometric scaling law with three

- different mass scaling exponents $\kappa = 2.7, 3.0, 3.3$, were implemented into the awebox power and trajectory optimization toolbox. A representative set of k-means clustered onshore and offshore wind velocity profiles, derived from the mesoscale WRF model, were used to define wind inflow conditions.
- We discussed the impact of mass and system size on typical trajectories and time series data which confirms that instantaneous power can drop to zero during the reel-out phase. This is caused by insufficient lift as the aircraft tries to overcome gravity and maintain tether tension. The minimum wind speed to sustain positive power production during the reel-out phase as well as tether length and average operating altitude increase with system size and weight. However, operating heights beyond 500 m are rare and mostly occur as the system de-powers above rated wind speed to stay within tether force and flight speed constraints. Therefore, it could be reasonable to keep the maximum tether length and operating altitude below those values
- 500 to reduce costs and permitting burdens. As these constraints become active, the resulting trajectory deforms and diverge from the expected paths seen for lower wind speeds. This is especially true for high lift configurations as they reach these limits faster. er losses, Since detailed design and stress analysis is beyond the scope of this paper, we limit ourselves to the estimation

of maximum mechanical wing loads, assuming an elliptical lift distribution. Shear force scales linearly with wing area, while bending moment increases nonlinearly with wing area and wing span.

- Analyzing the AWES power curve we determine that rated power scales linearly with wing area, assuming that tether speed constraint^s are kept constant and the tether diameter is adjusted appropriately. We chose to size the tether diameter so that rated power is achieved at about $U_{ref} = 10 m s^{-1}$, independent of size, mass and location. A larger tether diameter would increase rated power and shift rated speed towards higher wind speeds, which might be beneficial for faster offshore wind conditions, but would impact tether drag and weight. Improving aerodynamic efficiency increases power production. For the
- 510 sets of aerodynamic coefficients used in this study, average power increased by approximately 30% to 80 %, depending on wing area. We proposed the nonlinear AWES power coefficient $c_{\rm p}^{\rm AWES}c_{\rm wing}^{-1}$ from the aircraft path length and wing area to collapse power curves.

We estimate AEP and cf based on the power curve analysis and wind speed probability distribution at reference height between $100 \le z_{ref} \le 400$ m. Offshore AEP is generally higher than onshore, while the power curves are almost identical even though clustered profiles differ, due to higher wind speeds. Increased aircraft mass leads to significant reduction in AEP, as

- lower wind speeds become infeasible to fly in until finally no feasible solutions, even at higher wind speeds, can be found. This is particularly true for the onshore location and AP2 reference aerodynamics, as these conditions can not produce sufficient lift force to overcome system weight. Wind farm setups might therefore benefit from the deployment of multiple smaller AWES rather than few large-scale AWES. This could also reduce the overall power loss when synchronizing the flight trajectories of
- 520 AWESs within a farm. Determining the ideal, site-specific AWES size needs to be determined subject to realistic mass scaling, the available area and the local wind resource.

Furthermore, we describe the tether contribution to total weight and drag relative to aircraft wing size as well as tetherassociated power losses. Our results show that even though relative tether power losses decrease with wing size, they still use up a significant portion (20 - 60 %) of the average mechanical AWES power.

525 Lastly, we try to determine the maximum AWES weight to lift ratio. Our data shows that total AWES weight, including tether and aircraft, should not exceed 20 % of the produced aerodynamic lift to operate. The limitation of crosswind AWES operations seems to be the upward climb within each loop. During this ascent the aircraft decelerates by approximately 20%-25%, which reduces aerodynamic lift by about 35% - 45%, which could be offset by the deployment of additional high-lift devices. As a result the system can not produce enough lift to overcome gravity and maintain tether tension, leading to a reduction in tether speed and produced power up until a complete drop to zero for lower wind speeds.

6 Future work

Defining the AWES design space subject to realistic wind conditions and operating constraints is crucial for scaling this technology for large-scale deployment of grid-integration. We therefore propose to build upon this study and further investigate the design space using design optimization. A possible approach is to utilize the already existing AWES power and trajectory optimization toolbox awebox and implement it into a design optimization framework that varies parameters such as aspect

535

515

ratio, wing area and wing box dimensions. Adding a cost model would allow to optimize for levelized cost of electricity or AEP. Analyzing the dynamic aircraft wing loads caused by the cyclic nature of crosswind AWES and turbulence could improve AWES durability and further explore AWES design by considering fatigue loads to explore wing concepts to minimize κ . Ultimately, AWES must compete with conventional wind. Scaling and moving offshore are logical goals for both technologies.

540 The relative merits of large-scale AWES must be further explored to set design and development targets, particularly since this study highlighted that offshore AWES are not particularly beneficial relative to conventional wind, given the generally lower sheer offshore. This further highlights that the advantage of ground-generation AWES, in particularly offshore, does not lie in higher altitudes, but in reduced material and associated benefits such as easier transportation.

Code availability. TEXT

545 Data availability. TEXT

Author contributions. Markus Sommerfeld evaluated the data and wrote the manuscript in consultation and under the supervision of Curran Crawford. Martin Dörenkämper set up the numerical offshore simulation, contributed to the meteorological evaluation of the data. Jochem De Schutter co-developed the optimization model and helped writing and reviewed this manuscript.

Competing interests. We declare that neither the author nor any co-author can identify any conflict of interest regarding the subject matter or materials discussed in this manuscript.

Acknowledgements. The authors thank the BMWi for funding of the "OnKites I" and "OnKites II" project [grant number 0325394A] on the basis of a decision by the German Bundestag and project management Projektträger Jülich. We thank the PICS, NSERC and the DAAD for their funding.

awebox has been developed in collaboration with the company Kiteswarms Ltd. The company has also supported the awebox project
 through research funding. The awebox project has received funding from the European Union's Horizon 2020 research and innovation program under the Marie Sklodowska-Curie grant agreement No 642682 (AWESCO)

We thank the Carl von Ossietzky University of Oldenburg and the Energy Meteorology research group for providing access to their High Performance Computing cluster *EDDY* and ongoing support.

We further acknowledge Rachel Leuthold (University of Freiburg, SYSCOP) and Thilo Bronnenmeyer (Kiteswarms Ltd.) for their helped in writing this article and great technical awebox support.

References

575

Ampyx: Ampyx Power BV, https://www.ampyxpower.com/, 2020.

- Andersson, J., VAAkesson, J., and Diehl, M.: CasADi: A Symbolic Package for Automatic Differentiation and Optimal Control, in: Recent Advances in Algorithmic Differentiation, edited by Forth, S., Hovland, P., Phipps, E., Utke, J., and Walther, A., pp. 297–307, Springer
- 565 Berlin Heidelberg, Berlin, Heidelberg, 2012.

Argatov, I. and Silvennoinen, R.: Efficiency of Traction Power Conversion Based on Crosswind Motion, pp. 65-79, Springer Berlin Heidel-

berg, Berlin, Heidelberg, https://doi.org/10.1007/978-3-642-39965-7_4, https://doi.org/10.1007/978-3-642-39965-7_4, 2013.

awebox: awebox: Modelling and optimal control of single- and multiple-kite systems for airborne wind energy, https://github.com/awebox,

2020. Last accessed on dd-mm-yyyy

570 Bronnenmeyer, T.: Optimal Control for Multi-Kite Emergency Trajectories, Master's thesis, University of Stuttgart, https://cdn.syscop.de/ publications/Bronnenmeyer2018.pdf, 2018.

CasADi: CasADi, https://github.com/casadi/casadi, 2016.

Champion, K. S. W., Cole, A. E., and Kantor, A. J.: Chapter 14 Standard and Reference Atmospheres, 1985.

De Schutter, J., Leuthold, R., Bronnenmeyer, T., Paelinck, R., and Diehl, M.: Optimal control of stacked multi²kite systems for utility-scale airborne wind energy, in: 2019 IEEE 58th Conference on Decision and Control (CDC), pp. 4865–4870, 2019.

Diehl, M.: Airborne Wind Energy: Basic Concepts and Physical Foundations, in: Airborne Wind Energy, edited by Ahrens, U., Diehl, M., and Schmehl, R., pp. 3–22, Springer Berlin Heidelberg, Berlin, Heidelberg, https://doi.org/10.1007/978-3-642-39965-7_1, https://doi.org/ 10.1007/978-3-642-39965-7_1, 2013.

Dörenkämper, M., Olsen, B. T., Witha, B., Hahmann, A. N., Davis, N. N., Barcons, J., Ezber, Y., García-Bustamante, E., González-Rouco,

580 J. F., Navarro, J., Sastre-Marugán, M., Sīle, T., Trei, W., Žagar, M., Badger, J., Gottschall, J., Sanz Rodrigo, J., and Mann, J.: The Making of the New European Wind Atlas – Part 2: Production and Evaluation, Geosci. Model Dev. Discuss., 2020, 1–37, https://doi.org/10.5194/gmd-2020-23, 2020.

Drela, M. and Youngren, H.: AVL, http://web.mit.edu/drela/Public/web/avl/, 2016.

Echeverri, P., Fricke, T., Homsy, G., and Tucker, N.: The Energy Kite - Selected Results From the Design, Development and Testing of

- 585 Makani's Airborne Wind Turbines Part 1, Technical Report 1, Makani Power, https://storage.googleapis.com/x-prod.appspot.com/files/ Makani_TheEnergyKiteReport_Part1.pdf, 2020.
 - Eijkelhof, D., Rapp, S., Fasel, U., Gaunaa, M., and Schmehl, R.: Reference Design and Simulation Framework of a Multi-Megawatt Airborne Wind Energy System, Journal of Physics: Conference Series, 1618, 032 020, https://doi.org/10.1088/1742-6596/1618/3/032020, 2020.
- 590 Ellis, G. and Ferraro, G.: The Social Acceptance of Wind Energy: Where we stand and the path ahead., Eur- scientific and technical research reports, European Commission, https://doi.org/10.2789/696070, 2016.

Federal Aviation Agency: Part 23 - AIRWORTHINESS STANDARDS: NORMAL, UTILITY, ACROBATIC, AND COMMUTER CATE-GORY AIRPLANES,

https://www.govinfo.gov/content/pkg/CFR-2017-title14-vol1/xml/CFR-2017-title14-vol1-part23.xml#seqnum23.337, 2017.

595 Fingersh, L., Hand, M., and Laxson, A.: Wind Turbine Design Cost and Scaling Model, Tech. rep., NREL, https://doi.org/10.2172/897434, 2006. Gros, S., Zanon, M., and Diehl, M.: A relaxation strategy for the optimization of airborne wind energy systems, in: Control Conference (ECC), 2013 European, pp. 1011–1016, IEEE, http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=6669670, 2013.

Haas, T., De Schutter, J., Diehl, M., and Meyers, J.: Wake characteristics of pumping mode airborne wind energy systems, in: Journal of

- Physics: Conference Series, vol. 1256, p. 012016, IOP Publishing, 2019.
 Horn, G., Gros, S., and Diehl, M.: Numerical trajectory optimization for airborne wind energy systems described by high fidelity aircraft models, in: Airborne wind energy, pp. 205–218, Springer, http://link.springer.com/chapter/10.1007/978-3-642-39965-7_11, 2013.
 - Houska, B. and Diehl, M.: Optimal control for power generating kites, in: Control Conference (ECC), 2007 European, pp. 3560–3567, IEEE, http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=7068861, 2007.
- 605 HSL: The HSL Mathematical Software Library ONLINE, http://www.hsl.rl.ac.uk/, 2020. Hurt, H. J.: Aerodynamics for naval aviators, Naval Air Systems Command, https://www.faa.gov/regulations_policies/handbooks_manuals/ aviation/media/00-80t-80.pdf, 1965.
 - Kermode, A., Barnard, R., and Philpott, D.: Mechanics of Flight, Pearson Prentice Hall, <u>https://books.google.co.jp/books?id-op7CQgAACAAJ</u>, 2006.
- 610 Kruijff, M. and Ruiterkamp, R.: A Roadmap Towards Airborne Wind Energy in the Utility Sector, pp. 643–662, Springer Singapore, Singapore, https://doi.org/10.1007/978-981-10-1947-0_26, https://doi.org/10.1007/978-981-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-10-1947-1

Lee, T. and Su, Y.: Lift enhancement and flow structure of airfoil with joint trailing-edge flap and Gurney flap, Experiments in Fluids, https://doi.org/10.1007/s00348-010-1024-8, 2010.

Leuthold, R., De Schutter, J., Malz, E., Licitra, G., Gros, S., and Diehl, M.: Operational Regions of a Multi-Kite AWE System, in: 2018
European Control Conference (ECC), pp. 52–57, https://doi.org/10.23919/ECC.2018.8550199, 2018.

Loyd, M. L.: Crosswind kite power (for large-scale wind power production), Journal of Energy, 4, 106–111, https://doi.org/10.2514/3.48021, https://doi.org/10.2514/3.48021, 1980.

Luchsinger, R. H.: Pumping Cycle Kite Power, pp. 47–64, Springer Berlin Heidelberg, Berlin, Heidelberg, https://doi.org/10.1007/978-3-642-39965-7_3, https://doi.org/10.1007/978-3-642-39965-7_3, 2013.

- 620 Lunney, E., Ban, M., Duic, N., and Foley, A.: A state-of-the-art review and feasibility analysis of high altitude wind power in Northern Ireland, Renewable and Sustainable Energy Reviews, 68, 899 – 911, https://doi.org/https://doi.org/10.1016/j.rser.2016.08.014, 2017.
 - Malz, E., Koenemann, J., Sieberling, S., and Gros, S.: A reference model for airborne wind energy systems for optimization and control, Renewable Energy, 140, 1004 – 1011, https://doi.org/https://doi.org/10.1016/j.renene.2019.03.111, http://www.seieneedirect.com/seienee/ article/pii/S0960148119304239, 2019.
- 625 Malz, E., Verendel, V., and Gros, S.: Computing the power profiles for an Airborne Wind Energy system based on large-scale wind data, Renewable Energy, 162, 766 – 778, https://doi.org/10.1016/j.renene.2020.06.056, http://www.seieneedirect.com/seienee/ article/pii/S0960148120309666, 2020.

Malz, E. C., Zanon, M., and Gros, S.: A Quantification of the Performance Loss of Power Averaging in Airborne Wind Energy Farms, in: 2018 European Control Conference (ECC), pp. 58–63, 2018.

- 630 offshorewind.biz: Ampyx Power Taking First Steps Towards MW-Scale Kite, Online, https://www.offshorewind.biz/2018/12/04/ ampyx-power-taking-first-steps-towards-mw-scale-kite/, 2018.
 - Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., and Duchesnay, E.: Scikit-learn: Machine Learning in Python, Journal of Machine Learning Research, 12, 2825–2830, 2011.

- 635 Salvação, N. and Guedes Soares, C.: Wind resource assessment offshore the Atlantic Iberian coast with the WRF model, Energy, 145, 276 287, https://doi.org/https://doi.org/10.1016/j.energy.2017.12.101, http://www.sciencedirect.com/science/article/pii/S0360544217321448, 2018.
 - Schelbergen, M., Kalverla, P. C., Schmehl, R., and Watson, S. J.: Clustering wind profile shapes to estimate airborne wind energy pro-Volume 5, issue 3WES, 5, 1097–1120, https://doi.org/10.5194/wes-5-1097-2020 duction, Wind Energy Science Discussions, 2020, 1–34, https://doi.org/10.5194/wes-2019-108, https://www.wind-energ_sei-discuss.net/wes-2019-108/, 2020.
 - Schmehl, R., Noom, M., and van der Vlugt, R.: Traction Power Generation with Tethered Wings, in: Airborne Wind Energy, chap. 2, pp. 23–45, Springer Berlin Heidelberg, Berlin, Heidelberg, https://doi.org/10.1007/978-3-642-39965-7 2, 2013.
 - Scholz, D.: Aircraft Design an Open Educational Resource (OER) for Hamburg Open Online University (HOOU), http://HOOU.ProfScholz. de, last accessed: 11.10.2021, 2016.
- 645 Sommerfeld, M.: Power curve characterization for ground-generation AWES, Wind Energy Science, 2020.
 - Sommerfeld, M., Crawford, C., Monahan, A., and Bastigkeit, I.: LiDAR-based characterization of mid-altitude wind conditions for airborne wind energy systems, Wind Energy, 0, https://doi.org/10.1002/we.2343, 2019a.
 - Sommerfeld, M., Dörenkämper, M., Steinfeld, G., and Crawford, C.: Improving mesoscale wind speed forecasts using lidar-based observation nudging for airborne wind energy systems, Wind Energy Science, 4, 563–580, https://doi.org/10.5194/wes-4-563-2019, https://www.
- 650 wind energ sci.net/4/563/2019/, 2019b.

640

- Stull, R.: An Introduction to Boundary Layer Meteorology, Atmospheric and Oceanographic Sciences Library, Springer Netherlands, https:///books.google.ca/books?id=eRRz9RNvNOkC, 1988.
 - van der Vlugt, R., Bley, A., Noom, M., and Schmehl, R.: Quasi-steady model of a pumping kite power system, Renewable Energy, 131, 83 99, https://doi.org/10.1016/j.renene.2018.07.023, http://www.sciencedirect.com/science/article/pii/S0960148118308206, 2019.
- 655 Waechter, A. and Laird, C.: Ipopt (Interior Point OPTimizer), https://github.com/coin-or/Ipopt, 2016.
 Wächter, A. and Biegler, L. T.: On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming,
 Mathematical Programming, 106, 25–57, https://doi.org/10.1007/s10107-004-0559-y, https://doi.org/10.1007/s10107-004-0559-y,