New strategies for optimized structural monitoring of wind farms: experimental campaign

João Pacheco¹, Silvina Guimarães², Carlos Moutinho¹, Miguel Marques², José Carlos Matos², Filipe Magalhães¹

⁵ ¹CONSTRUCT- VIBEST, Faculty of Engineering, University of Porto, Porto, 4200-465, Portugal ²INEGI, Porto, 4200-465, Portugal

Correspondence to: João Pacheco (ec11142@fe.up.pt)

Abstract. The main goal of the recently started WindFarmSHM research project is the development, validation and optimization of monitoring strategies to be applied at the level of the wind farm, which should be able to evaluate the structural condition of a set of wind turbines and their consumed fatigue life, using the response to operation loads. In this context, a quite extensive experimental campaign is being performed in Tocha wind farm, an onshore wind farm located in Portugal, which includes the simultaneous instrumentation of several wind turbines adopting strain gages, clinometers and accelerometers distributed in the tower and blades. This paper introduces the Tocha wind farm, presents the different layouts adopted in the instrumentation of the wind turbines and shows some initial results from the already fully instrumented wind

15 turbine. At this preliminary stage, the capabilities of the very extensive monitoring layout will be demonstrated. The results presented in this paper demonstrate the ability of the different monitoring components to track the modal parameters of the system composed by tower and rotor and to characterize the internal loads at the tower base and blade roots.

1 Introduction

10

Wind energy is one of the most promising renewable energy sources, having registered a truly remarkable evolution in the last
two decades. This evolution, practically worldwide, is verified both in terms of installed capacity, as well as in terms of
technological evolution. In the EU, wind was the fastest growing energy source between 2005 and 2017, surpassing coal in
2016 as the second largest total installed power generation capacity (EWEA, 2018). Future forecasts are equally optimistic. It
is expected that cumulative capacity of wind energy in the EU will continue to grow and that it will even double in a minimum
interval of 10 years, considering the most optimistic forecast (EWEA, 2017). Thus, based on this scenario, it is possible to
identify several challenges that will arise in the coming years. Among them, the following stand out:

- Costs of energy production: the reduction of the unit cost of wind energy is a major factor to guarantee the competitiveness and growth of the wind sector. The reducing operation risk through monitoring is one away;
 - The extension of the lifespan of the existing wind turbines: wind turbines were designed to operate 20 years, so it is estimated that about one half of the accumulated capacity currently installed in the EU will reach the end of design

- life in 2030 (EWEA, 2017). It is therefore essential to create a regulatory framework that defines the rules for the actions to be taken when the expected design life of the structures is exhausted;
 - Limited technical knowledge: the increase in the size of wind turbines and the exploration of offshore sites still involve a certain degree of uncertainty.

Considering this background and previous research (Weijtjens, Noppe et al., 2016, Lorax and Brühwiler, 2016, Weijtjens,

- 35 Verbelen, et al. 2017), the main goal of the WindFarmSHM research project is the development, validation and optimization of new methodologies to continuously assess the structural elements of wind turbines: tower, blades and foundation. The monitoring strategy is being designed to be applied in the context of a wind farm, adequate for onshore and floating solutions (the two types of foundation being used in Portugal), using optimized instrumentation layouts at a subgroup of wind turbines, and taking profit from the data provided by the acquisition systems already available in all wind turbines (SCADA), for the
- 40 use of extrapolation techniques to assess all the wind turbines of the same wind farm (Figure 1). The research project will include three monitoring layouts of wind turbines of an onshore wind farm, comprehending accelerometers, strain gages and clinometers and the development of numerical models for the generation of virtual monitoring data to validate the monitoring strategy in floating wind turbines.

The data processing will be based on the continuous evaluation of the parameters that drive the structure dynamic behaviour

45 (vibration frequencies and damping) estimated from the structure response to ambient excitation (wind, waves, currents, soil vibrations) and advanced statistical modelling, having in mind two main goals: detection of stiffness reductions motivated by the appearance of damage (as performed in (Oliveira, Magalhães, et al. 2018a)) and evaluation of the remaining fatigue life of the main structural components (Figure 1).

In the project a very extensive instrumentation is being deployed in order evaluate different monitoring layout alternatives, but

50 the final goal is to propose a minimal optimized monitoring layout based on reduced number of sensors that can be easily installed.



Figure 1. Monitoring strategy. Meaning of the horizontal bars at the bottom: the colour bars represent in a simplistic fashion the structural health, the green/white bars represent the consumed fatigue life.

2 Tocha Wind Farm

- 55 The Tocha wind farm is owned by EDP Renewables and started its operation in May 2012. It is located in the central region of Portugal approximately 3 km from the coastline. It consists of five Vestas wind turbines, model V100 with 1.8 MW of rated power, totalling 9.0 MW of installed power. Figure 2 presents a geographic location of the wind farm and the distribution of the five wind turbines, identified with numbers that will be used throughout this work. This figure also identifies a substation position, as well as a meteorological mast.
- 60 It is important to note that the wind farm fits into a coastal area, with very soft orography of the terrain and where the foundation's soil is predominantly sandy, which is why deep foundations are used in all wind turbines. Thus, the steel tower of the turbines is connected to a 14-by-14 m concrete slab with variable height (1.50 m at the ends and 3.00 m in the central area). In turn, sixteen concrete piles with 1 m diameter support the slab.



Figure 2. Tocha wind farm: a) Geographic location in Portugal (Google, n.d.-a); b) Identification of wind turbines and auxiliary structures (Google, n.d.-b); c) Characterization of the wind conditions observed during 2017 (SCADA data of wind turbine 1).

Figure 2 c) shows a wind rose, which characterizes the wind speed and direction for the year 2017 at the Tocha wind farm. The predominant wind direction is approximately north. Thus, considering the very smooth terrain and the proximity of the coast, wind turbines 1, 2 and 3 are exposed to slightly disturb offshore winds, while the remaining generators are exposed to wind with additional turbulence caused by the wake effects.

70 Vestas V100-1.8MW wind turbine is an onshore turbine model with a 100 m diameter rotor. It is a variable speed, 3 blades rotor with individual pitch control for each blade. The hub is placed at a height of 95 m and is supported by a steel tower, with a hollow circular cross-section with variable diameter and thickness, composed of four segments that are linked on site with bolted connections. The wind turbines operate for wind speeds between 4 and 20 m/s and achieve the rated power for wind speeds of about 12 m/s (Figure 3 c).

3 Preliminary evaluation of the modal properties of the wind turbines

In order to obtain an initial estimate of the wind turbine dynamic properties before the installation of the monitoring systems, a set of ambient vibration tests was performed in four of the five wind turbines in operating and non-operating conditions. Additionally, a numerical model of the wind turbines was deployed. In the next sections, the preliminary evaluation of the modal properties of the wind turbines will be described.

3.1 Numerical Models

80

In order to better interpret the experimental results, a numerical model of the wind turbine was developed using ROBOT STRUCTURAL ANALYSIS software (Autodesk, 2016), following the technical drawings provided by the manufacturer. It is a simplified model, in which the operation of the turbine is not modelled. Rotational movement of the rotor and all control

85 systems are disregarded, being the main purpose of the numerical model the simulation of the dynamic behaviour of the tower under the test conditions presented in the following section.

It is considered that the foundation does not allow any kind of relative movements and is not considered the opening of the door (a specific numerical model for this detail has shown that it has a reduced influence on global behaviour). Thus, for the modelling of the tower was based on 3D bar elements to which the corresponding cross sections were assigned.

- 90 Regarding blade modelling, at the time very detailed information was not available. Alternatively, starting from the NREL 5 MW reference wind turbine (Jonkman, Butterfield et al., 2009), the characteristics of the blades were scaled to be compatible with the wind turbine under study. The blades are modelled by 3D bar elements, divided into multiple sections to which the average mass, stiffness and inertia characteristics have been attributed. Since there is no rotation of the rotor, the blades were modelled with the pitch angle observed during the ambient vibration tests.
- 95 The nacelle and hub are represented by concentrated loads applied at their centres of gravity. The connection between the tower, blades and the geometric centres of the nacelle and hub is modelled with rigid links of negligible mass. Still, it is important to note that advanced models are currently being developed in FAST (Sprague, Jonkman et al., 2015) using some structural information that was derived from the previously described model. All the details of the FAST model are presented in (Pimenta, Branco et al., 2019).

100 3.2 Ambient Vibration Tests

The set of ambient vibration tests was divided into two campaign. In the first campaign, the main goal was to accurately identify the natural frequencies and the configuration of the tower vibration modes, considering two different situations: wind turbine in operating conditions and wind turbines in non-operating conditions (the rotor was stopped or idling). At this stage, only the wind turbine 1 was tested. Several 10 minutes of accelerations time series were measured (sample rate of 100 Hz)

105 with 4 standalone seismographs (Figure 3 a), with internal tri-axial force balance sensors, that were placed in the horizontal platforms of the tower (Figure 3 b).

In the second campaign, the main objective is to identify the natural frequencies of all wind turbines of the wind farm, in order to characterize the variability of the natural frequencies. The same equipment was used and with the same data acquisition parameters, but only the two highest sections of the towers were instrumented. It should be noted that in this second tests the

110 rotor of the wind turbines was stopped.

The collected acceleration time series were first analysed in the frequency domain and then processed with Covariance driven Stochastic Subspace Identification method (SSI-COV) (Magalhães and Cunha, 2011). The operating scenarios observed during the performance of the ambient vibration tests are shown in Figure 3 c) (1st campaign: red circles, 2nd campaign: green triangle). It can be seen that the wind conditions observed during the two test are quite different. The owner of the wind farm provides

115 SCADA data with the mean, maximum and minimum value from 10 minutes period, important information for the accelerations processing.



Figure 3. Ambient vibration tests: a) Sensors; b) Section instrumented; c) Operating scenarios and power curve of Vestas V100 wind turbine (https://en.wind-turbine-models.com).

- Figure 4 shows some of the results obtained from the first campaign in non-operating condition. The top left plot shows two averaged normalized spectra (ANPSD): one for the for-aft direction, FA, (perpendicular to the rotor plane) and another for the side-side direction, SS, (parallel to the rotor plane). It is possible to identify several abscissa in correspondence with the most relevant peaks of the spectrum, which represent good estimates of natural frequencies. Among the various peaks identified, there are two that clearly stand out: one near 0.25 Hz and another near 1.80 Hz. Comparing the experimental results with numerical ones (Figure 5), it is confirmed that these peaks correspond to the first and second pairs of tower bending modes. In
- 125 the stabilization diagram covering the full frequency range under analysis, the position of the first three pairs of tower bending modes is marked. The two zooms presented at the bottom of the figure show that with the SSI-COV method it is possible to separate the very close modes within the first two pairs of frequencies. There are still other stable pole alignments relevant to the dynamic characterization of the structure, however they are probably associated with vibration modes dominated by the rotor, which can only be identified and characterized using the more detailed instrumentation, which will be described in the
- 130 next section.



Figure 4. Ambient Vibration test results for wind turbine 1: a) average power spectra for FA and SS directions;, b) stabilization diagram produced by the SSI-COV method; c) two zooms of this diagram for first (left) and second (right) pairs of tower bending modes.

Figure 5 presents the identified mode shapes and natural frequencies, which are compared to numerical results obtained from

135 a preliminary simple numerical model. There is an excellent relationship between numerical results (blue line) and experimental results (red circles).



Figure 5. Mode shapes and natural frequencies identified with the ambient vibration test and numerical model of wind turbine 1.

Still, for the first test campaign, it is important to understand the influence that the normal operation of the rotor has on the dynamic characteristics of the structure. Thus, Figure 6 compares ANPSD (average normalized auto-spectral density function) obtained for stopped rotor and in operation. It should be noted that the represented ANPSD were calculated considering

together the signals measured along the FA and SS directions. The dashed vertical lines represent the harmonic frequencies associated with the rotor operation (Ω , 3Ω , 6Ω , ...). The results obtained in terms of natural frequencies (f) are also compared for the identified vibration modes for the two analysed situations (environment and operational parameters shown at the table on bottom). For the first tower bending modes there are two very pronounced peaks for the two considered operating conditions. For the second pair of tower bending modes only in non-operating conditions there is a clear peak in ANPSD. In

145





Figure 6. Ambient Vibration test results for wind turbine 1 in operating and non-operating conditions: average power spectra and natural frequencies (results obtained from 10 minutes single observation setups with very low variance of the environment and operational parameters).

150 Figure 7 compares the results obtained for the four tested wind turbines. All of them present quite similar natural frequencies, but wind turbine 5 seams to present a slightly different behaviour expressed by the differences observed at the values of the natural frequencies of the first and second tower bending modes associated with the side-side direction (1SS lower than the others and 2SS higher than the others). For this reason and because this is the wind turbine where higher turbulence is expected the monitoring camping will be focused on wind turbines 1 and 5.



155 Figure 7. Comparison of the natural frequencies of four wind turbines in non-operational conditions (1st and 2nd pairs of bending modes).

4 Monitoring Systems and Preliminary Monitoring Results

The experimental campaign in Tocha wind farm involves the simultaneous monitoring of several wind turbines during a period of about two years. In order to obtain data representative of the dynamic behavior of all wind turbines and based on the results of the ambient vibration tests described above, the experimental campaign includes the following three instrumentation layouts:

- An extended monitoring layout installed on wind turbine 1;
- An intermediate monitoring layout installed on wind turbine 5;
- A simple monitoring layout to be installed on the other wind turbines, considering shorter instrumentation periods;

The distribution of the alternative monitoring layouts in the wind turbines of the farm was conditioned by the available time

165 slot for installation of equipment (usually scheduled during other maintenance operations) and our will to instrument the rotor of one wind turbine that for the predominance wind direction (north) is loaded by an unperturbed flow and another one the is influenced by the wakes of the other turbines (see Figure 2). For this reason, wind turbine 1 was instrumented according to the complete layout, while the intermediate layout was applied in wind turbine 5.

The simple monitoring layout has two main objectives: i) to characterize and identify differences in the dynamic behavior of wind turbines; ii) to understand the interaction of the wake effects between nearby wind turbines. This simple layout will be applied to all other structures, considering time periods limited to two or three months. If justified or atypical behaviors are identified, these wind turbines can be instrumented by adopting a complementary layout, suitable for each situation that is intended to be analysed.

The complete monitoring layout includes the following components:

- 175 o Two alternative systems to characterize accelerations at the tower: a commercial system based on a set of very low noise accelerometers and a customized low-cost system based on MEMs (micro electromechanical systems) accelerometers designed and assembled in FEUP (Moutinho and Cunha, 2019);
 - Strain gages at the tower base to characterize the stresses during different operating conditions;
 - Clinometers to characterize the rotations and, indirectly, the bending moments at the base of the tower;
- 180

160

• A set of fiber optic strain gages to estimate bending moments at the blades roots;

o MEM accelerometers placed at the blades (10 m from the root) to characterize their dynamics.

The intermediate layout includes the characterization of the accelerations at the tower through the optimized low-cost MEM accelerometer system and the characterization of the rotor dynamic behavior through fiber optic strain gauges and MEM accelerometers installed on the blades.

185 Finally, the simple monitoring layout consists solely of using the MEM accelerometer system to collect data regarding tower vibrations. As mentioned, this system will be applied to all other wind turbines and may be supplemented as appropriate. It should be noted that data on the environmental and operational conditions of each wind turbine is being obtained through the SCADA system (10 minutes averages and sampled at 15 seconds). The meteorological mast is also important to

characterize the history of environmental conditions in the wind farm (wind direction and wind speed) since the beginning of

- 190 its operation. This information is very useful for estimating the current state of fatigue of the various structures. Wind turbines 1 and 5 are already instrumented. The following section describes the various instrumentation systems adopted, together with the presentation and analysis of preliminary results for wind turbine 1. Since the installation of these components is still being adjusted and the amount of data acquired is still limited, the results presented here are intended to demonstrate what is being measured, to certify the correct functioning of the systems and to demonstrate the capabilities of the most appropriate menitoring layout.
- 195 complete monitoring layout.

200

4.1 Tower Monitoring System: Accelerometers

In order to obtain the best possible characterization of the tower accelerations a commercial system based on 6 force-balance unidirectional accelerometers connected to a 24 bits acquisition system was deployed. As depicted in Figure 8 a), this involved the instrumentation of 3 sections of the tower along two orthogonal horizontal directions. These 3 sections coincide with the height of the technical platforms, in order to facilitate the installation and maintenance of the monitoring equipment. The sensors are connected by cables to a central acquisition system that continuously records acceleration time series with a sample rate of 20 Hz. This data is accessible from FEUP through an internet connection.



Figure 8. Sections instrumented with accelerometers: a) force balance sensors; b) MEM sensors; c) photos of the force balance sensors (connected to cables) and of the MEM based acquisition system (grey box with antenna).

- 205 Complementary, a MEM based system was also installed. This is a standalone system developed at FEUP that integrates a triaxial acceleration sensor (in this application just the two horizontal directions are being recorded with a sample rate of 62.5 Hz), a set of batteries that ensure 5 months of continuous operation, a memory card for data storage, high-precision clocks and a radio for data transmission (in the present application the data transmission is limited to state-of-health parameters to increase the system autonomy). Two of these devices were installed in the tower in the positions marked in Figure 8 b). One of the 210 project goals is the development and test of easy to deploy and cost effective systems for wind turbines testing and monitoring,
- so the evaluation of the performance of these devices designed and assembled in FEUP is very relevant.

Figure 9 shows two examples of spectra obtained from acceleration series recorded by the two alternative sensor under test, considering the wind turbine in production (figure on the right) and parked (figure on the left). It appears that the system designed at FEUP demonstrates a performance that is comparable to the more expensive and difficult to install commercial

215

system (KMI). These figures are in accordance with the results of the ambient vibration test presented above. Under nonoperating conditions, the peak pairs associated with the first two tower mode pairs clearly stand out. In operating conditions, additional peaks associated with the rotor rotation frequency appear. The peaks associated with the second pair of bending modes become much more diffuse, which makes their tracking over time quite challenging.



Pitch angle = 90° ; Rotor speed = 0.0 rpm; Wind speed = 2.9 m/sPitch angle = -1.7° ; Rotor speed = 11.1 rpm; Wind speed = 5.4 m/s Figure 9. Power spectra from force balance (KMI) and MEM sensors (1 Ω , 3 Ω and 6 Ω marked with dashed vertical lines).

220 Figure 10 shows the colormaps obtained from spectra of singular values calculated with the acceleration time series acquired

with the commercial system during January 2019, after their projection according to the FA and SS directions. As might be expected, variations in frequency content are observed over time due to varying operating conditions. It is also possible to visually track the time evolution of the natural frequencies associated with the first two pairs of tower modes.

The data collected by both systems is being processed with the algorithms presented in (Oliveira, Magalhães et al., 2018b).



225 Figure 10. Colour maps with singular value spectra for the FA and SS directions during January/2019.

4.2 Tower Monitoring System: Strains and Rotations

These monitoring components are essential for fatigue assessment of the tower and one important goal is the evaluation of two

230 alternatives for estimating static and dynamic bending moment diagrams along the tower: using strain and rotation measurements, combined with accelerometers.

The strains system is composed of six 2D rosette strain gages (measurement of the strain in two orthogonal directions) and 4 temperature sensors. In order to try to evaluate the static bending moment diagrams evolution along the tower, the six strain gauges are distributed in two sections: four sensors at 6.5m from the base of the tower (bottom section) and two sensors at

235 7.7m (top section) as shown in Figure 11. The four temperature sensors are located in the bottom section, close to the strain gauges. Measuring deformation in the direction perpendicular to the tower axis and temperatures is important to allow the evaluation of alternative procedures to minimize the influence of temperature on the measured longitudinal deformations.



Figure 11. Locations of the strain gages (\Diamond) and temperature sensors (\bigvee^{\downarrow}) and photograph of the position of the clinometers and strain gauges along the same vertical alignment (strain gauges A and E).

240 The installation of the clinometers aims to measure the rotation at the base of the tower and to alternatively estimate the extensions from the measurement of rotations in two close sections. The main advantage of estimating bending moments from rotations is that the installation of the clinometers is less intrusive than the installation of strain gauges, which involves removing of tower painting. The three clinometers were installed along the vertical alignment formed by strain gauges A and E. One of the clinometers was installed close to the foundation (near the base flange), while the two ones are positioned according the Figure 11.

The two monitoring components are connected to a National Instruments digitizer and processor (model cRio 9056 - http://www.ni.com), installed at the base of the tower. Data acquisition is ensured by a program developed in LabView for this specific application (sample rate of 100 Hz).

Figure 12 a) shows an example of the strains time series obtained for stop event of the rotor. Although the main purpose of

250 this monitoring system is to characterize the static component of the response, it is possible to characterize the dynamic component with good accuracy. With this data, it will be relevant to test and compare the various approaches for estimating the dynamic stresses in the tower from acceleration measurements (Maes, Iliopoulos et al., 2016).



Figure 12. Tower Monitoring System Strains and Rotations: a) Example of strain time series; b) Strain and rotations during nacelle yawing, SG – strains; CL - rotations (see sensor positions in Figure 11).

- 255 The records obtained from strain gauges are influenced by several factors, including the effect of temperature. Thus, the experimental determination of bending moments in the tower requires the acquired raw data to be pre-processed to obtain the real deformation. In the present application, as a first trial, the methodology presented in (Loraux, 2018) is being followed. In a general way, this methodology consists of the following steps: a) correction of the effect of temperature on strain gauges; b) signal correction based on the average value of the extensions recorded on diametrically opposed sensors; c) signal calibration
- according to (IEC 61400-13, 2015). For this last step, it is necessary to have a record of strain time series measured during a 360° nacelle rotation, with wind speeds lower than the generator cut-in wind speed. The eccentricity of the nacelle and rotor mass generates a sinusoidal signal in the sensors, being the mean value of this signal the zero baseline Figure 12 b). Applying the described method to the recorded series, in Figure 13 the temporal evolutions of the bending moments observed in the bottom instrumented section are presented, for the two main directions, considering two alternative turbine operation scenarios.
- 265 The experimental results are compared with numerical ones, obtained from a model developed on FAST and calibrated using the methodology described in (Pimenta, Branco et al., 2019). Please note this is just a qualitative comparison, the inflows in the experiment and numerical model are different, only the average wind speed and turbulence intensity are the same.



Rotor speed = 14.9 rpm; Wind speed = 13.0 m/s; TI = 14.6 %

Rotor speed = 13.0 rpm; Wind speed = 7.9 m/s; TI = 4.4 %

Figure 13. FA and SS bending moments in the bottom instrumented section considering two different operating situations and comparison with FAST numerical results (TI: turbulence intensity).

- 270 Figure 14 shows the average spectra of the six force-balance accelerometers (first row) longitudinal deformations recorded by sensors A, B, C and D (second row) and clinometer 3 (third row), considering the rotor parked (left) and in operation (right). These spectra show excellent agreement of results between the alternative monitoring components and demonstrate that it is possible to perform operational modal analysis from the data collected by all these systems.
- Comparing the spectra with those shown in Figure 9, it is clear that the peaks corresponding to the tower bending modes are more pronounced and clearer, so measuring strains can be very useful in distinguishing tower modes from the rotor modes observed in the tower.

Rotor speed = 0.0 rpm; Wind speed = 2.4 m/s; TI = 20.4%





Figure 14. Averaged power spectra: longitudinal strains A to D (first row) and rotation at clinometer 3 (second row) in non-operating condition (left column) and operating condition (right column).

4.3 Rotor Monitoring System: Accelerometers

- 280 The goal of this monitoring system is the characterization of the rotor under different operating conditions. The analysis of the results of the ambient vibration tests show the existence of several resonance frequencies that could not be attributed to the tower fundamental modes. These are certainly related to modes more dominated by the rotor. In addition, direct identification of rotor modes may be beneficial for automatically detecting blade changes, driven either by reduced stiffness due to damage or by additional masses due to ice formation. In this way, the same MEM based devices that were installed in the tower were 285
- also installed inside the blades, one in each blade, 10 m from the blade root, as shown in Figure 15 (sample rate of 62.5 Hz).



Figure 15. MEM based system installed inside one blade and direction of measurements (X approximately aligned with edgewise direction).

From the simultaneous recording of the acceleration time series on the blades it is possible to estimate the modal parameters of the rotor, in particular their modal configurations. However, as this is a preliminary step, and since the data available so far is limited, only examples of the time series and their spectra are show in Figure 16, considering the stopped rotor (left) and in

- 290 operation (right) are presented. Signals X, Y and Z are in accordance with the referential presented in Figure 15. Considering the figures obtained with the rotor parked, in addition to the various peaks corresponding to the main tower modes, peaks are also identified for various other resonant frequencies that are certainly associated with the rotor modes. Already when the rotor is in operation, the adopted sensors measure the gravity, being the registered accelerations dominated by the
- 295 rotor rotation frequency. Several other frequencies associated with vibration modes in flapwise (Z) and edgewise (X) directions can still be observed.



Pitch angle = 90° ; Rotor speed = 0.0 rpm; Wind speed = 5.5 m/s

Pitch angle = 0° ; Rotor speed = 10 rpm; Wind speed = 5.9 m/s

Figure 16. Example of acceleration time series, corresponding operation parameters and power spectra.

300 4.4 Rotor Monitoring System: Strains

305

The main goal of the blades strains monitoring is to collect data to estimate the fatigue condition of these elements, as well as to evaluate their structural performance from the evolution of the continuously estimated modal parameters. On the other hand, the joint analysis of the wind characteristics, the moments acting at the blades and the bending moments at the tower will also be relevant to understand the mechanism of transmission of loads from the rotor to the tower and to validate numerical modelling.

The solution adopted is based on a commercial system provided by HBM / FiberSensing called WindMeter (https://www.hbm.com) with a sample rate of 100 Hz. Each blade is instrumented with four fiber optic strain sensors and temperature sensors for compensation of the temperature effects. As shown in Figure 17, each set of sensor is connected to a central acquisition system installed on the hub, which in turn allows remote access to data via a 3G modem.



310 Figure 17. Strain measurement at the blades root: wiring and photo.

320

As an example, Figure 18 shows two strains time series their spectra, considering the rotor stopped (left) and in operation (right). Sensors *S*1 and *S*3 correspond to blade bending according to edgewise direction, while sensors *S*2 and *S*4 correspond to flapwise direction. The following results show that the acquired data, besides being fundamental to obtain the stress history for fatigue analyses, can also be used for operational modal analysis of the structure.

315 It should be noted that the deformations measured on the blades are not as sensitive to the tower bending modes as in the case of accelerations, since although tower movement produces blade movements, it does not lead to relevant bending levels. Thus, the spectra peaks shown in the spectra can only be motivated by the contribution of the blades modes.

By comparing the spectra of Figure 17 and Figure 18 for the parked situation, it is possible to identify several coincident peaks for the same frequencies. While in operation, the observed resonant frequencies depend on the rotor speed of the rotor, so the peaks do not coincide.



10

0

2

3

Frequency [Hz]

5

6

4

Figure 18. Example of detrended strain time series (static component was removed) and corresponding operation parameters (S1, S3 bending in the edgewise direction; S2, S4 bending in the flapwise direction) and power spectra.

 $10^{(}$

0

1

2

3

Frequency [Hz]

4

5

- 325 As noted with respect to measuring tower extensions, a similar methodology was also followed for processing the blade strains records. Note that the calibration step according to the standard (IEC 61400-13, 2015) is not yet fully tuned. However, the data acquired so far allowed the elaboration of Figure 19, which represents the evolution of the bending moments at blade root B (wind turbine 1) to the flapwise direction as a function of wind speed and considering different turbulence intensities. Firstly, the moment value increases as the wind speed increases. When the wind turbine's nominal wind speed (12 m/s) is reached, the
- 330 actuation of the pitch angle mechanism causes the momentum to decrease even though the wind speed continues to increase.



Figure 19. Wind turbine power curve and bending moments recorded at blade root B according to flapwise direction as a function of wind speed and considering different turbulence intensities (05-Fev to 17-Dec-2019: 20027 10 minutes times series).

335 5 Conclusions

This paper presented the quite extensive monitoring camping that is being conducted in Tocha wind farm, described the installation of the monitoring components that are already in operation and presented some preliminary results.

The preliminary analyses performed in the frequency domain show that operational modal analysis has the potential to extract useful information from both strain and acceleration measurements performed either in the tower or in the blades.

- 340 A deeper processing of the data that is being continuously collected by all the monitoring components will certainly contribute to better understand the in-operation dynamic behavior of these quite complex structures, to devise processing procedures for effective evaluation of their structure health and to calculate accumulated damage due to fatigue. This step will be instrumental in defining the most effective procedures for assessing structural performance and for estimating accumulated fatigue damage. The analysis of data simultaneously collected in several wind turbines will be very important for understanding the relation
- 345 between the observed fatigue wear and to devise techniques to extrapolate results from ones to the others.

References

Autodesk: Robot Structural Analysis Professional (Version 29.0.05650(x64)), 2016.
EWEA: Wind energy in Europe: Scenarios for 2030. Brussels, Belgium, 2017.
EWEA: Wind in power 2017 - Annual combined onshore and offshore wind energy statistics. Brussels, Belgium, 2018.

350 Google. (n.d.-a). [Google Maps location of Tocha Wind Farm, Tocha, Cantanhede, Coimbra, Portugal]. Retrieved March 21, 2018, from https://www.google.com/maps/@39.5170771,-9.4259083,7.5z.

Google. (n.d.-b). [Google Maps location of Tocha Wind Farm, Tocha, Cantanhede, Coimbra, Portugal]. Retrieved March 21, 2018, from https://www.google.com/maps/@40.3244121,-8.8220541,7848m/data=!3m1!1e3.

IEC 61400-13.: IEC 61400-13 Wind energy generation systems - Part 13: Measurement of Mechanical Loads: International Electrotechical Commission (IEC), 2015.

Jonkman, J., Butterfield, S., Musial, W., and Scott, G.: Definition of a 5-MW Reference Wind Turbine for Offshore System Development. National Renewable Energy Laboratory (NREL), 2009.

355

Loraux, C. and Brühwiler, E.: The use of long term monitoring data for the extension of the service duration of existing wind turbine support structures. Journal of Physics: Conference Series, 753(7), 1742-6596, 2016.

360 Loraux, C. T.: Long-term monitoring of existing wind turbine towers and fatigue performance of UHPFRC under compressive stresses. École Polytechnique Fédérale de Lausanne, 2018.

Maes, K., Iliopoulos, A., Weijtjens, W., Devriendt, C., and Lombaert, G.: Dynamic strain estimation for fatigue assessment of an offshore monopile wind turbine using filtering and modal expansion algorithms. Mechanical Systems and Signal Processing. 76, 2016.

- Magalhães, F. and Cunha, A.: Explaining Operational Modal Analysis with data from an arch bridge. Mechanical Systems and Signal Processing, 25(5), 1431-1450, 2011.
 Moutinho, C. and Cunha, A.: Contribution to new solutions of instrumentation of Civil structures for continuous dynamic monitoring, IX ECCOMAS Thematic Conference on Smart Structures and Materials (SMART 2019), Paris, France, 2019.
- Oliveira, G., Magalhães, F. Cunha, A. and Caetano, E.: Vibration based damage detection in a wind turbine using one year of data. Structural Control and Health Monitoring, 25, 11, 2018a.

Oliveira, G., Magalhães, F., Cunha, A., and Caetano, E.: Continuous dynamic monitoring of an onshore wind turbine, Engineering Structures, 164, 22-39, 2018b.

Pimenta, F., Branco, C.M., Teixeira, C.M., and Magalhães, F.: Calibration of onshore wind turbine numerical model using experimental data, 15th EAWE PhD Seminar on Wind Energy, Nantes, France, 2019.

- Sprague, M., Jonkman, J. M. and Jonkman, B.: FAST Modular Framework for Wind Turbine Simulation: New Algorithms and Numerical Examples. In: Proc. 33rd Wind Energy Symposium. Kissimmee, Florida, 2015.
 Weijtjens, W., Noppe, N., Verbelen, T., Iliopoulos, A., and Devriendt, C.: Offshore wind turbine foundation monitoring, extrapolating fatigue measurements from fleet leaders to the entire wind farm. Journal of Physics: Conference Series, 753(9), 1742-6596, 2016.
- 380 Weijtjens, W., Verbelen, T., Capello, E and Devriendt, C.: Vibration based structural health monitoring of the substructures of five offshore wind turbines. Procedia Engineering, 199, 2017.