

The following pages contain the updated manuscript with tracked changes (compared to the last version) as well as a reply to all of the reviewers. Below, the updated manuscript with tracked changes can be found.

Review of rolling contact fatigue life calculation for oscillating bearings and application-dependent recommendations for use

Oliver Menck¹ and Matthias Stammer¹

¹Fraunhofer Institute for Wind Energy Systems IWES, Am Schleusen graben 22, 21029 Hamburg, Germany

Correspondence: Oliver Menck (oliver.menck@iwes.fraunhofer.de)

Abstract. In contrast to the multitude of models in the literature for the calculation of rolling contact fatigue in rotating bearings, literature on oscillating bearings is sparse. This work summarizes the available literature on rolling contact fatigue in oscillating bearings. Publications which present various theoretical models are summarized and discussed. A number of errors and misunderstandings are highlighted, information gaps are filled, and common threads between publications are established.

5 Recommendations are given for using the various models for any oscillating bearing in any industrial application. The applicability of these approaches to pitch and yaw bearings of wind turbines is discussed in detail.

1 Introduction

While most bearings in industrial applications rotate, there are some notable ones which are required to oscillate. These include bearings in helicopter rotor blade hinges (Tawresey and Shugarts, W. W., Jr., 1964; Rumbarger and Jones, 1968), cardan joints (Breslau and Schlecht, 2020), offshore cranes (Wöll et al., 2018), and blade and yaw bearings in wind turbines, shown in Fig. 1. Blade bearings turn (“pitch”) the blade around its longitudinal axis to change the blade’s angle of attack. Their movements in modern wind turbines mostly consist of small (typically¹ $\varphi < 10^\circ$, often as small as $\varphi < 1^\circ$, cf. Stammer et al. (2020)) oscillations with the occasional 90° movement to bring the turbine to a halt. Similarly, yaw bearings rotate the turbine to face into the wind. Their movements are typically fewer and, depending on the site and the yaw system design, longer ($< 10^\circ$ during power production but potentially more while idling) ~~while they~~. [Yaw movements](#) do not tend to become as low ($\varphi < 1^\circ$) as pitch angles (Wenske, 2022).

Rolling contact fatigue is a possible failure mechanism of bearings. It is caused by the fact that, even under a constant external load, movement of the bearing (rotation or oscillation) causes movement of the rolling bodies (balls or rollers) relative to the bearing rings. If the rolling bodies transmit load to the raceway, their movement leads to stress cycles, because every location of the raceway changes from a loaded state while it is in contact with a rolling body to an unloaded one while it is not (cf. Fig. 6, left hand side, for a typical case in a rotating bearing). The resulting stress amplitudes can, over time, cause fatigue damage on the raceways, or, less frequently, the rolling bodies. The driving stress for rolling contact fatigue is typically considered to be shear stress. Fatigue can be initiated from shear stress below the surface of the raceway (subsurface fatigue)

¹See Fig. 3 for amplitude definition.

and from shear stress at its surface (surface fatigue) (Lundberg and Palmgren, 1947; Ioannides et al., 1999; Harris and Kotzalas, 2007; Zaretsky, 2013).

Rolling bearings under oscillatory movements are commonly associated with wear damage to the raceways and rolling bodies (Grebe, 2017; Stammler, 2020; Behnke and Schleich, 2022; FVA, 2022b; de La Presilla et al., 2023). Small oscillation amplitudes are generally seen to be a risk factor for wear, particularly in grease lubricated bearings (Behnke and Schleich, 2022; Stammler, 2020; Grebe, 2017; FVA, 2022b). However, wear can also be prevented by a number of measures (Schwack, 2020; Wandel et al., 2022) and it is definitely possible for rolling contact fatigue to occur without wear² even for oscillating amplitudes as low as $\theta = 1^\circ$ ($\varphi = 2^\circ$). Rolling contact fatigue, on the other hand, is always a possible failure mechanism even in a properly designed bearing (Sadeghi et al., 2009), except for very low loads (Ioannides et al., 1999), at which there is dispute about its occurrence (Zaretsky, 2010). In many cases, such as large oscillation amplitudes, or the use of oil lubrication, wear is unlikely to occur and thus, rolling contact fatigue becomes a more important focus. Moreover, depending on its severity, wear in itself doesn't necessarily cause a complete failure of the bearing but it can also accelerate rolling contact fatigue (FVA (2022a, b)(FVA, 2022a, b). Engineers should therefore consider both wear and rolling contact fatigue as a possible failure mechanism possible failure mechanisms. This paper reviews calculation approaches to determining the rolling contact fatigue life of oscillating bearings. There are a number of approaches for rolling contact fatigue life calculation in the literature, see Sadeghi et al. (2009) and Tallian (1992) for an overview, but they are mostly intended for rotating applications. While any of these could in principle be changed to be used in oscillating applications, this paper collates all approaches that have explicitly been developed for oscillating bearings in general, or that are concerned with specific bearings which oscillate, such as pitch bearings.

As part of the introduction, phenomena which are present in oscillating bearings but not in rotating ones are discussed in Sec. 1.1. An overview of calculation approaches is given in Section 2. It includes three different commonly used ISO-based factors (Harris, Rumbarger, and Houpert), all of which have been designed for oscillations with a constant amplitude, and a number of other approaches described in the literature. Section 3 gives an overview of experimental results and Section 4 then discusses when to apply these methods, with an example explaining their applicability to pitch and yaw bearings, which oscillate with a varying amplitude.

1.1 Operational conditions of oscillating bearings

Most operating conditions of oscillating bearings are similar to those of rotating bearings, and much has been written about these conditions. Similarities include the load distribution among the rolling elements, which tends to spread as a function of the radial and axial load (Harris and Kotzalas, 2007) and the bending moment, if present. Individual rolling elements experience point or line contacts, originally described by Hertz for balls (Hertz, 1882) and later described by other methods for rollers (Reusner, 1977; de Mul et al., 1986), resulting in contact pressures on inner and outer ring that tend to be different. The raceways experience cyclic loading, which can cause rolling contact fatigue, often assumed to be caused by shear stress in particular (Lundberg and Palmgren, 1947; Harris and Kotzalas, 2007). There In both oscillating and rotating bearings, there

²Discussed in Sec. 3 of this review. The references for which this statement applies use oil lubrication.



Figure 1. Wind turbine pitch bearing (green, also called blade bearing) and yaw bearing (blue). ©Fraunhofer IWES/Jens Meier

can be grease and oil lubrication present (Hamrock et al., 2004), raceway surface quality and lubrication contamination affects the bearing (Ioannides et al., 1999), and so on.

Since this review focuses on oscillating bearings, some differences between rotating and oscillating bearings are, however, worth pointing out. One main difference is simply the travel that a bearing performs when it oscillates as compared to when it rotates: For an oscillation as depicted in Fig. 3, an oscillation arc A is covered. This is typically smaller than the 360° covered during a rotation. Therefore the life of an oscillating bearing, if measured in oscillations, tends to be bigger than that of an otherwise identical bearing that rotates, measured in revolutions.

One commonly discussed difference is the fact that, for small oscillation angles, only a part of the raceway ~~may be loaded~~ is ever loaded while the remaining part is always unloaded. For the bearings depicted in Fig. 4, the bearing on the left side only sees cyclic loading on selected locations of its ring, whereas the bearing on the right side sees loading all over its ring, which is distributed unevenly. In Fig. 2, the blue oscillation pattern (“stochastic”) causes the entire ring to experience an uneven number of load cycles, depicted in the right of the Figure. The red pattern on the other hand leads only leads to stress cycles in selected locations, exactly like the left part of Fig. 4. All of the aforementioned cases are fundamentally different from a rotating bearing, in which for both inner and outer ring, every location of a ring experiences the same amount of stress cycles if the bearing is rotated for long enough.

Although the stress cycles are evenly distributed on each ring of a rotating bearing, the load is not. It is typically assumed to be constant with respect to one ring, the so-called stationary ring, while the other one rotates relative to it. If the load distribution is uneven, such as the load distribution shown in the top of Fig. 5, this causes the stationary ring to always experience its highest load in the same location. The rotating ring, on the other hand, will have all of its circumferential locations see stress cycles as shown in the bottom of Fig. 5, with only a time shift between the loading of each circumferential location of that rotating ring.

For an oscillating bearing, the stationary ring is loaded similarly (identical, if one ignores the fact that there is a discrete amount of rolling elements), but the rotating ring is loaded differently over time: All of its circumferential positions can experience a very different stress cycle history as shown in Fig. 5 for a small and large oscillation amplitude θ .

80 From a viewpoint of rolling contact fatigue, it is also noteworthy that the stress cycles experienced by the raceway are not identical in an oscillating and a rotating bearing. For a rotating bearing, the left of Fig. 6 shows the typical type of shear stress loading history as assumed in the literature (Lundberg and Palmgren, 1947; Harris and Kotzalas, 2007). The center figure shows that at reversal points of the oscillation, the amplitude of the shear stress can be lower than in a rotating bearing (blue case), and thereafter, the sign of the shear stress cycle flips (red case). For small oscillations, the right part of Fig. 6 shows that
85 the oscillation amplitude of a rotating bearing may even never be reached.

Aside from these effects that concern the stress cycle history and its distribution over the circumferential locations of inner and outer ring, lubrication is well known to behave differently in an oscillating bearing as compared to a rotating one, causing a time- and movement-dependent film thickness (Venner and Hagmeijer, 2008). As discussed above, this can cause wear if [the lubricant film thickness is](#) bad enough, but even if no wear occurs, different lubricant film thickness than in a rotating bearing
90 may be present.

2 Existing calculation approaches

There are a number of publications on the issue of rolling contact fatigue in oscillating bearings. Most of them are based on ISO (ISO, d, c, a, b) or closely related to the model used for ISO. These publications are summarized in Sec. 2.1. Several approaches that have little relation to ISO and its foundations have also been proposed, and are discussed in Sec. 2.2. Some of
95 the ISO-related methods are intended for constant oscillation amplitudes as depicted red in Fig. 2, where an oscillation with a constant amplitude about a position of 0° is shown³, while some other ISO-related methods and all non-ISO related methods are intended for arbitrary movement as depicted blue in Fig. 2.

2.1 ISO-related approaches

Fundamentally, rolling contact fatigue in oscillating applications is caused by a rolling element repeatedly rolling over locations
100 on a raceway, as is the case in rotating applications. For this reason, many researchers have sought to adapt the well-known ISO approach for rolling contact fatigue calculation to oscillating applications. All of these approaches are hence characterized by the fact that they are based on Lundberg and Palmgren (1947), who proposed that

$$\ln \frac{1}{S} \propto \frac{\tau_0^c N^e}{z_0^h} V, \quad (1)$$

³Rolling contact fatigue is driven by relative movement of one of the rings to the other, which means that the mean position of the oscillations in Fig. 2 only moves the position where load cycles occur on the raceway but has no effect on the life of the bearing. The critical difference between the blue and red lines is their relative movement, not their absolute position.




Figure 2. Load cycles resulting from oscillation and stochastic movement in a bearing with $Z = 15$ rolling elements.

where S is the survival probability, τ_0 is the maximum orthogonal shear stress and z_0 its depth under the raceway surface at which τ_0 occurs, N is the number of load cycles (rollovers), and V is the loaded volume (Lundberg and Palmgren, 1947, 1952; Harris and Kotzalas, 2007; Zaretsky, 2013).

Lundberg and Palmgren used Eq. 1 to derive their well-known life equation $L_{10,rev} = (C/P)^p$, with dynamic load rating C and dynamic equivalent load P , which remains the basis for ISO 281 (ISO, d) and ISO/TS 16281 (ISO, c) as well as countless other publications. They assumed the bearings to be rotating. $L_{10,rev}$ then gives the number of millions of revolutions at which 10% of bearings are expected to suffer the first visible raceway damage⁴, also called “basic rating life”. In principle, their derivation can be adapted for use in oscillating movement as well. This section discusses publications which either apply or derive such adaptations of the original Lundberg-Palmgren approach, or approaches very similar to it but also based on Eq. 1. Most of these approaches derive corrective factors a_{osc} that are intended to be applied to a life measured in revolutions and convert it into a life measured in oscillations, i.e.,

$$L_{10,osc} = a_{osc} L_{10,rev}, \tag{2}$$

where $L_{10,osc}$ is the life measured in oscillations and $L_{10,rev}$ is the life in revolutions. This equation applies to all so-called “oscillation factors” in this paper. For small oscillation amplitudes, a_{osc} typically becomes very large, with a_{osc} commonly (but not always) being in the range of 1...1000. All factors a in this paper are instances of a_{osc} as shown in Eq. 2.

There are two common definitions of an oscillation “amplitude”; this paper mainly uses θ as defined in Fig. 3. Some equations are also given in terms of the double amplitude φ if there are differences to the equation in terms of θ .

⁴Or rolling element damage as per ISO 281(ISO, d); strictly speaking this is not included in the derivation by Lundberg and Palmgren (1947) but ISO included it in the definition of life, presumably because it rarely occurs anyway.

2.1.1 Harris: Traveled distance

The Harris factor⁵ is given in various editions of *Rolling Bearing Analysis* by Harris (Harris, 2001; Harris and Kotzalas, 2007). It considers the effect whereby an oscillating bearing will, depending on the oscillation amplitude, experience a different number of stress cycles on the rings than a rotating bearing. The factor can be interpreted as a conversion of traveled distance
125 into an equivalent number of rotations. For the angle definition in Fig. 3, the total traveled arc A during one oscillation amounts to $A = 4\theta$ ($= 2\varphi$). The Harris factor is then simply

$$a_{\text{Harris}} = \frac{360^\circ}{A} = \frac{90^\circ}{\theta} \left(= \frac{180^\circ}{\varphi} \right). \quad (3)$$

Thus, taking an exemplary bearing that oscillates with an amplitude of $\theta = 10^\circ$ and that, if it were rotating, would have a life of $L_{10,\text{rev}} = 1$ million revolutions, and applying Eq. 2 and Eq. 3 gives a life of $L_{10,\text{osc}} = \frac{90^\circ}{10^\circ} L_{10,\text{rev}} = 9$ million oscillations
130 according to the Harris factor. This is because it will execute an arc of $A = 40^\circ$ per oscillation, which is considered as $1/9^{\text{th}}$ of a rotation by the Harris factor.

Several references (e.g., IEC (2019)) recommend the use of a so-called load revolution distribution (LRD) or load duration distribution (LDD) for rotating bearings. LRDs sum the number of revolutions at a given load. It is possible to use this approach for oscillating bearings, too, if oscillations are summed and equated to one revolution for every 360° of movement.
135 Doing so is in principle identical to using the Harris factor, if the Harris factor is used to sum up movement independently at each of the same load cases. For a constant rotational speed, LDDs are identical to LRDs; for varying speeds they are merely an approximation.

The Harris factor can be seen as a simplification that neglects various effects which may occur in oscillating bearings as
140 opposed to rolling ones. In particular, it does not take account of the fact that the load distribution on the moving ring over time is different in an oscillating bearing, a fact originally taken into account by Houpert (1999), nor that only part of the raceway may be loaded⁶, originally described by Rumbarger and Jones (1968). A combination and correction of some of the errors in the two aforementioned approaches has been proposed by Breslau and Schlecht (2020) as well as by Houpert and Menck (2021). These approaches are discussed in the following sections.

145 2.1.2 Rumbarger: Partially loaded volume

The Rumbarger effect⁷ was originally introduced by Rumbarger and Jones (1968) as early as 1968. This original publication, which has been described as “complex and impracticable” (Breslau and Schlecht, 2020), was then simplified in Rumbarger

⁵This approach has also been referred to as “Harris 1” in some publications (Schwack et al., 2016; Schmelter, 2011; FVA, 2021; Wöll et al., 2018) to distinguish it from the Rumbarger effect (cf. Sec. 2.1.2), which they falsely attribute to Harris, thus denoting it “Harris 2”.

⁶More generally: that there may be a difference in the number of stress cycles for different circumferential locations of the rings, as shown in Fig 2, right. However, Rumbarger only considered differences caused by the fact that some parts of the raceway are unloaded in his publications.

⁷This approach has also been referred to as “Harris 2” in some publications (Schwack et al., 2016; Schmelter, 2011; FVA, 2021; Wöll et al., 2018) due to Harris’s authorship of the NREL DG03 (Harris et al., 2009). Since the earliest publications of this approach in the literature are by Rumbarger, and since Rumbarger was a co-author of NREL DG03, he is credited with the idea here.




Figure 3. One oscillation covering arc $A = 4\theta (= 2\varphi)$ with oscillation amplitude θ (and double amplitude φ) as defined in this paper.

(2003) and NREL DG03 (Harris et al., 2009), but without a derivation of the simplified approach⁸. Each of these publications introduces an adjusted load rating⁹ C_{osc} for oscillating bearings, and using this in $L_{osc} = (C_{osc}/P)^p$ gives the life in oscillations. It is possible to introduce an oscillation factor¹⁰ a_{osc} that produces identical results to the adjusted load rating C_{osc} , cf. App. A or Wöll et al. (2018). In Appendix A of this paper, the authors include a derivation of the simplified approach and in Appendix B a discussion of inaccuracies and assumptions contained therein.

Aside from the effects also considered by Harris, the Rumbarger effect is based on the assumption that for small oscillation amplitudes, only a part of the raceway may ever be loaded. The loaded volume V of Eq. 1 and its load cycles N are then adjusted accordingly, depending on the given oscillation amplitude¹¹. Rumbarger does so by defining the angle θ_{crit} (φ_{crit}) as

$$\theta_{crit} = \frac{360^\circ}{Z(1 \pm \gamma)}, \left(\varphi_{crit} = \frac{720^\circ}{Z(1 \pm \gamma)}, \right) \quad (4)$$

where the minus (–) sign refers to the outer raceway and the plus (+) ~~one sign~~ to the inner raceway, and γ is a common auxiliary factor used in rolling bearing calculations related to the geometry of the bearing¹². θ_{crit} is the oscillation amplitude required to move a rolling element from its initial location on a raceway to that of the next rolling element. Figure 4 shows stressed volumes above and below the critical angle on an inner raceway. The Rumbarger factor as recommended by the authors

⁸Breslau and Schlecht (2020) give a more appropriate treatment of this effect by introducing the factor $a_{osc,2}$ with their Eq. 19, which does not contain the simplifications taken by Rumbarger in his simplified approach. This equation was rearranged (without simplifications, but to obtain a less cluttered equation) by Houpert and Menck (2021) into a corrective factor called $f_{\theta_{crit},i,o}$ in their Eq. 45, here used for the recommended approach. Although Rumbarger uses an adjusted load rating while the other authors use corrective factors, all of these approaches attempt to consider the same effect. The differences arise only because of simplifications in Rumbarger's derivation, cf. Appendices A and B.

⁹Called C_{osc} in Rumbarger and Jones (1968), C_{ao} and C_{ro} for axial and radial bearings in Rumbarger (2003), and $C_{a,osc}$ in Harris et al. (2009).

¹⁰Called a_{prt} in App. A and a_{osc_nHa2} in Wöll et al. (2018).

¹¹The Harris factor, cf. Eq. 3, does not consider that only part of the raceway is loaded for small oscillation angles. Since it merely adjusts the standard (rotation-based) calculation approach by the effect of the difference in traveled distance, it implicitly assumes the same loaded volume as in a rotating bearing.

¹²It is defined as $\gamma = \frac{D \cos \alpha}{d_m}$, where D refers to the rolling body (ball or roller) diameter; d_m gives the so-called pitch diameter, i.e., the mean of the inner and outer raceway diameters; and α is the contact angle, where $\alpha = 0^\circ$ is a purely radial bearing and $\alpha = 90^\circ$ is a purely axial one.

of this paper is given by¹³ (see Tab. A1 for e)

$$a_{\text{Rumbarger}} = \begin{cases} \left(\frac{\theta}{\theta_{\text{crit}}}\right)^{1-1/e} \cdot a_{\text{Harris}} & \text{for } \theta < \theta_{\text{crit}}, \\ a_{\text{Harris}} & \text{for } \theta \geq \theta_{\text{crit}}. \end{cases} \quad (5)$$

For $\theta < \theta_{\text{crit}}$, only part of the raceway volume is loaded during operation. For this case, Rumbarger (2003) and Harris et al. (2009) give a load rating that is derived in Appendix A. This derivation makes some simplifications, and Appendix B shows the errors that occur when using Rumbarger's derivation. If applied correctly, the factor (or load rating) should shorten the life of a bearing as compared to Harris¹⁴, though the simplified factor (or load rating) sometimes increases the life for no other reason than the simplifications made in its derivation. The form of Eq. 5 is thus based on Appendix A without any simplifications. Note that, since θ_{crit} differs between the inner and outer races, so does $a_{\text{Rumbarger}}$. Amplitude θ_{crit} of the outer raceway may be used if a more conservative estimate for the entire bearing is desired¹⁵.

For values of $\theta \geq \theta_{\text{crit}}$, the simplified approach published in Rumbarger (2003) and Harris et al. (2009) is identical to using the Harris factor. This, too, is merely an approximation: Strictly speaking, the life of an unevenly stressed volume (as illustrated in Fig. 4, right hand side) is not the same as that of an evenly stressed volume which occurs in a rotating bearing¹⁶ (identical to an oscillating bearing with $\theta = \theta_{\text{crit}}$) if the total movement of both bearings is the same. Appendix C proposes an extension of the Rumbarger factor for such situations, but also concludes that the difference in the factor as compared to a_{Harris} is almost negligible in most cases. The factor chosen for Eq. 5 thus follows the above-mentioned publications.

The Rumbarger effect does not consider the effects of an uneven load zone on the moving ring, which are covered by Houpert. Moreover, it assumes that no slippage of the rolling element set occurs, which would move load cycles to occur on different positions of the ring circumference. For a properly installed bearing, Rumbarger and Jones (1968) demonstrated that this assumption can hold true.

2.1.3 Houpert: Load zone effects on the moving ring

The Houpert effect was originally covered by Houpert (1999), with a small error in its derivation. This was corrected by Breslau and Schlecht (2020) as well as Houpert and Menck (2021)¹⁷. Aside from the effects also considered by Harris, the Houpert

¹³Eq. 5 is identical in terms of φ .

¹⁴In contrast to the Harris effect, with the Rumbarger effect two competing effects ultimately cause a reduction in life. The loaded volume is lower, which increases life; but the load cycles on that small volume which is loaded are higher, thereby decreasing life. The second effect is stronger and reduces the overall life of the bearing, cf. Eq. A3.

¹⁵Since the traveled distance of a rolling element contact in the rolling direction x is identical on the inner and outer raceways, but the outer raceway's circumference is longer than the inner raceway's circumference for contact angles $\alpha \neq 90^\circ$, the Rumbarger effect is relatively more detrimental to the outer race: It creates a larger deviation from the loaded volume of a rotating bearing than on the inner ring.

¹⁶This follows from Eq. 1, where the volume V has exponent 1 and the stress cycles N have exponent $e \neq 1$.

¹⁷The two approaches are not completely identical but very similar: Breslau and Schlecht (2020) employ a thorough calculation of the effect only for oscillation amplitudes $\theta > \theta_{\text{crit}}$, cf. Section 2.1.2. For a circumferentially loaded ring with oscillating motion, they thus introduce the load integrals called $J_{\theta_a, \psi}$ and J_{θ_a} in their Eqs. 32 and 33. Houpert and Menck (2021) derive an equivalent load called $Q_{\text{eq}}(\psi)$ in their Eq. 35. This term differs from that derived by Breslau and Schlecht (2020) because they (Breslau and Schlecht) use a calculation approach resembling that of Lundberg and Palmgren (1947) and ISO (d), whereas Houpert and Menck (2021) use an approach close to that used by Dominik (1984). The approach used by Dominik is very similar to that of




Figure 4. Rumbarger effect: stressed volume on the inner ring as a function of inner ring angle θ relative to $\theta_{\text{crit}} = \theta_{\text{crit},i}$, for $\theta < \theta_{\text{crit}}$ and $\theta > \theta_{\text{crit}}$. Yellow volume is stressed twice per oscillation cycle (cf. Fig. 3), red volume is stressed four times per oscillation cycle. Black volume is never stressed. Only stress cycles for the inner ring are shown.

effect considers that the stress cycle history of the moving ring will be different for an oscillating bearing than for a rotating one. This is illustrated in Fig. 5 for an exemplary element on the moving ring.

185 In the standard life calculation as pioneered by Lundberg and Palmgren (1947) or used in ISO 281 (ISO, d), the load zone is assumed to be constant relative to one ring (called the stationary ring, typically the outer ring). From the viewpoint of Houpert's considerations, movement of the other ring (rotating or oscillating, typically the inner ring) then does not change the load distribution of the stationary ring's raceway. This ring is loaded identically for rotating or oscillating operation. Thus, a_{Harris} gives the correct life of the stationary ring according to Houpert's derivation.

190 For the moving ring, however, the Houpert effect predicts a different value to a_{Harris} . Since Harris merely adjusts the standard (rotation-based) calculation approach by the effect of the difference in traveled distance, he implicitly assumes that the effect of the load zone is the same as that in a rotating bearing¹⁸. Thus, a_{Harris} implicitly assumes an element as depicted in blue in Fig. 5 moves through the entire load zone once for each 360° of movement¹⁹. However, in reality this only applies for oscillations where $\theta = i \cdot 180^\circ$ ($\varphi = i \cdot 360^\circ$), $i = 1, 2, 3, \dots$, because for these values of θ each element will move around the entire raceway $2 \cdot \theta = i \cdot 360$ times per oscillation ($\varphi = i \cdot 360$ times per oscillation). For very small oscillations $\theta \rightarrow 0^\circ$ ($\varphi \rightarrow 0^\circ$) on the other hand, the elements increasingly converge toward the stress cycle history seen in a stationary ring²⁰, see Fig. 5. The Houpert

Lundberg and Palmgren, but uses different sets of equations. These two approaches ultimately give almost identical results if similar empirical exponents (cf. Table A1) are used, but details differ, hence the derivation by Houpert and Menck (2021) includes a term called H that cancels out whereas that by Breslau and Schlecht (2020) does not.

¹⁸As does Rumbarger, who uses the same equivalent load for an oscillating ring as for a rotating one in Rumbarger and Jones (1968), and also in Rumbarger (2003), cf. App. A.

¹⁹ 360° of movement consisting, for example, of 9 oscillations with $\theta = 10^\circ$.

²⁰In Houpert's model the stress cycle history of an oscillating ring converges, for small oscillations, against that of a stationary ring in both a rotating and oscillating bearing. These two cases (a stationary ring in a rotating and oscillating bearing) can be considered identical here because Houpert's effect alone, unlike Rumbarger's, does not consider that there are a discrete number of rolling elements in the bearing for the circumferential distribution of load cycles. Rather, he assumes all circumferential locations to experience the same number of stress cycles (with differences in load cycle magnitude only), as is common in a rotating bearing, and integrates over a continuous load distribution around the circumference. This is standard practice for the life calculation of typical rotating bearings and as such also employed in ISO 281.

factor is generally at or in between the following extreme cases

$$a_{\text{Houpert}} = \begin{cases} a_{\text{Harris}} & \text{for } \theta = i \cdot 180 \text{ with } i = 1, 2, 3, \dots \\ & \text{or: purely axial load } (\varepsilon \rightarrow \infty) \\ a_{\text{Harris}} \text{ in a bearing with both rings} & \text{for } \theta \rightarrow 0. \\ \text{stationary relative to load}^{21} & \end{cases} \quad (6)$$

200 In between these extreme cases, detailed calculations have to be performed, curve fits of which can be found in Houpert and Menck (2021). They depend on a value ε , a measure of the load zone size²². If applied correctly, the Houpert factor will either be identical to a_{Harris} in the above given cases or shorten the life of the bearing in all other cases²³. The Houpert effect is most noticeable for narrow load zones (small ε) and small oscillation angles θ . Houpert and Menck (2021) find deviations which differ by up to 22% from those given by the Harris factor for very narrow load zones and small oscillation amplitudes using
205 ISO exponents (cf. Table A1) and larger deviations of up to 52% using exponents given by Dominik (1984). This is due to Dominik using a higher Weibull slope of $e = 1.5$. Houpert and Menck (2021) give curve fits to calculate the Houpert factor²⁴ for ball and roller bearings. If ISO/TS 16281 (ISO, c) is used for the life calculation, the extreme case of small theta ($\theta \rightarrow 0$) can be taken into account by assuming both rings are stationary relative to the load and using a_{Harris} .

210 Strictly speaking, the Houpert effect is not independent of the Rumbarger effect, but for its derivations in Breslau and Schlecht (2020) and Houpert and Menck (2021) it is assumed to be.

2.1.4 Other ISO-related approaches and further literature

The above three factors have been covered in a number of publications²⁵, and Breslau and Schlecht (2020) as well as Houpert and Menck (2021) present the most up-to-date models which include them. Besides the above given publications, there are a number of additional approaches and applications of the above methods. Since all of the above cases are intended for constant

²¹Both rings being stationary relative to load slightly reduces the life as compared to standard calculations (in which one ring is assumed to be rotating) because it increases the equivalent load of the ring which would otherwise be assumed to rotate. It does not affect the factor a_{Harris} .

²²Common formulae for ε in the literature tend to be based on small bearings where the rings can be assumed to be stiff. For bearings with large deflection of the rings, based on e.g., FE simulations, different formulae for ε must be used to approximate it, see Houpert and Menck (2021). For multi-row bearings, each row's ε must be determined independently. Either the life of each row is then calculated independently and combined into a total bearing life, or the lowest ε value is taken as a conservative measure.

²³It shortens the life in all other cases because, from a viewpoint of rolling contact fatigue, the even distribution of loads over time that is present on a rotating ring is the best case scenario for damage accumulation of a ring. Any oscillation that deviates from this loading causes increasingly more concentrated damage accumulation on selected locations of the ring. Concentrated loading (as present, for instance, on the stationary ring in a typical bearing in most industrial applications) causes a higher equivalent load, and thus a lower life, if all else is equal, than the loading of a ring that rotates relative to the load (Lundberg and Palmgren, 1947; ISO, c). Note that the Houpert effect is, however, expressed through a factor here, rather than by changing the equivalent load.

²⁴The reference calls the Houpert factor $a_{\text{osc}, \dots}$, and includes in it a corrective factor for the Rumbarger effect, denoted f_{θ_crit} . If only the Houpert factor is desired, $f_{\theta_crit} = 1$ can be used for the equations in the reference.

²⁵A comprehensive list including all publications with relation to the factors, to the best knowledge of the authors, includes: The factors are derived in Rumbarger and Jones (1968); Houpert (1999); Rumbarger (2003); Harris et al. (2009); Breslau and Schlecht (2020); Houpert and Menck (2021), and they are used or discussed in some form in Schmelter (2011); Schwack et al. (2016); Münzing (2017); Wöll et al. (2018); FVA (2021); Menck (2023); Hwang (2023).




Figure 5. Houpert effect: load history of an exemplary element as a function of movement relative to load zone. Small θ are similar to no movement, large θ are similar to rotation.

215 oscillation amplitudes, some alternative approaches have been developed which are also intended to be usable for stochastic movement, which leads to different load cycles²⁶ on the bearing rings as depicted in Fig. 2, blue.

Menck (2023) generalized the Lundberg-Palmgren method to a discrete model (“The Finite Segment Method”) that can be applied to arbitrary movement. The model applies Eq. 1 to segments of a bearing. The movement of the balls relative to the inner and outer rings for each discrete simulation point are analyzed for potential stress cycles on the respective rings. For each stress cycle N , the variables τ_0 , z_0 , and V in Eq. 1 are then directly evaluated and the corresponding damage according to

²⁶The term “load cycles” is used here synonymously with “rollovers”. Load cycles in Fig. 2 were determined by using the inner ring angle θ_i as depicted on the left-hand side of Fig. 2 (outer ring assumed stationary) to calculate the movement of the cage $\theta_c = 0.5 \cdot \theta_i \cdot (1 - \gamma)$. This was then used to obtain relative cage movement on the inner ring $\theta_{rel,i} = \theta_i - \theta_c$. A change in $\theta_{rel,i}$ is then considered a load cycle on the respective position where it occurred.

the Palmgren-Miner hypothesis is calculated. The individual survival probabilities of all segments can then be combined into raceway lives, which can be combined into a total bearing life. The model thus encompasses previous use cases and includes the Rumbarger and Houpert effect, but can also be used for arbitrary movement and load histories. Menck (2023) shows the model to produce effectively identical results to ISO 281 for simple use cases which are defined by assumptions identical to those of Lundberg and Palmgren (1947), and reproduces results of oscillating bearings from Houpert and Menck (2021), but also applies the model to a rotor blade bearing of a wind turbine.

Hai et al. (2012) propose a generalization of ISO 281 specifically for slewing bearings. They divide the bearing into several segments in a similar way to Menck (2023), but unlike Menck's, their segment width depends directly on the oscillation amplitude. They also make a number of simplifications not made by ISO 281 or Menck²⁷. Their model can be used for individual operating conditions with either rotation or a constant oscillation amplitude; however, several conditions with different amplitudes may also be combined using equivalent loads and equivalent oscillation amplitudes for the segments. They compare their results to an exemplary calculation of NREL DG03 and conclude that their somewhat similar results validate the method. The simplifications make it impossible to establish whether their method is actually more accurate than simply using the oscillation factors given above.

Schwack et al. (2016) do not present a new model but compare factors from Harris, Houpert, and Rumbarger. They also include an approach denoted "ISO", which is identical to that of Harris. Having published in 2016, the authors also use the erroneous model of Houpert (1999) that was later corrected (cf. Sec. 2.1.3). Moreover, their application of the Houpert factor is not recommended for double-row bearings with large structural deformation²⁸. Their evaluation of the Rumbarger factor²⁹ results in a longer life than using the Harris factor³⁰. As explained in Sec. 2.1.2, this increase only occurs because of simplifications in the derivations performed by Rumbarger but for no physical reason, since the effects considered should shorten the life, not prolong it. The relatively large deviations from a_{Harris} shown in Schwack et al. (2016) are therefore both due to inaccuracies in the factors that were used.

Wöll et al. (2018) present a "numerical approach" to calculate the life of a bearing subjected to arbitrary time series. Their model evaluates the life of the whole³¹ bearing at every discrete time step of the simulation and then calculates the inferred damage according to Palmgren-Miner for every time step, based on the movement that occurred. The model is shown to be

²⁷Because their approach is intended for slewing bearings, they assume the contact ellipse dimensions a and b as well as z_0 to be identical on the inner and outer rings; they approximate $z_0 \approx 0.5b$ and $\tau_0 \approx 0.25P_{\text{max}}$, which is only completely correct for roller bearings but not ball bearings; they assume the cage moves at half the speed of the rotating ring, which is only true if a purely axial contact of $\alpha = 90^\circ$ is present; and they assume the critical angle to be identical for the inner and outer rings, using $\theta_{\text{crit}} = 360^\circ/Z$ for both rings.

²⁸The publication in question uses a single ε value for a large four-point slewing bearing that is based on deformations in Finite Element (FE) simulations. The purpose of ε in Houpert's approach lies in its ability to describe the load zone of a race. Thus, each inner-outer raceway pair should get an ε value for a proper calculation, as each of them may have a different load zone. Moreover, determining ε based on deformations that occur in FE simulations can be misleading for large slewing bearings, since they tend to have a lot of structural deformation, but common equations given for ε are mostly based on assumptions of rigid races. Various suggestions for the derivation of ε , including ones for large slewing bearings, can be found in (Houpert and Menck, 2021).

²⁹Called "Harris 2" in the reference.

³⁰Called "Harris 1" in the reference.

³¹The fact that Wöll et al. use the *whole* bearing life is the critical difference to Menck's Finite Segment Method, cf. Menck (2023), Sec. 2.2.

identical to a bin count using the Harris factor, cf. Sec. 2.1.1, for simple sinusoidal movements³². For a stochastic time series, their numerical approach produces a shorter life than either Harris's³³, Rumbarger's³⁴, or Houpert's approaches applied to a bin count. Because Wöll et al. (2018) published in 2018, they still use the erroneous Houpert factor from 1999 rather than more recent results, cf. Sec. 2.1.3, hence they obtain a longer life with the Houpert factor even though there is no physical reason for such an increase. Furthermore, they compare a bin count using the approaches of Harris, Rumbarger, and Houpert and obtain results that are higher than those of the numerical approach with all three bin count approaches including Harris, and conclude that using these bin counts "overestimates the lifetime for non-sinusoidal loads and speeds". It is not possible to assess the accuracy of this statement because their model is based on the life of the whole bearing and thus also includes simplifications as pointed out by Sec. 2.2 of Menck (2023). They also produce a simple method to calculate an equivalent load for oscillating loads but it fails to take local effects into account as accurately as Menck (2023).

2.1.5 Further effects during oscillation

Further effects occur during oscillation which are not considered by any of the above approaches.

When a rolling element passes completely over a position on the raceway, the orthogonal shear stress below the surface changes from maximum ($+\tau_0$) to minimum ($-\tau_0$) (Lundberg and Palmgren, 1947; Harris and Kotzalas, 2007). This is the typical stress cycle assumed in all ISO-based approaches mentioned here; it is depicted in Fig. 6 on the left. This stress cycle history behaves different in oscillating bearings: For raceway positions close to the reversal points of the oscillation, the direction of the load cycles changes; this phenomenon is depicted in Fig. 6 (oscillation, red case). The shear stress of the volume close to the reversal points does not fully span from $+\tau_0$ to $-\tau_0$ but is stopped prematurely; this too is depicted in Fig. 6 (oscillation, blue case). Similarly, for oscillations with small amplitudes, the stress range does not extend to the maximum and minimum of a passing contact in rotation, see Fig. 6 (small oscillation). None of these effects is considered in the ISO-based approaches (all approaches covered in Sec. 2.1) named herein.

Lubricant film quality is well known to have a significant impact on rolling contact fatigue life (Ioannides et al., 1999; Harris and Kotzalas, 2007). The thickness of the lubricant film is affected by oscillation, and may even become so poor that wear rather than fatigue becomes the dominant damage mechanism. Numerous studies investigate wear phenomena in oscillating bearings; for a review, see de La Presilla et al. (2023). As far as the authors are aware, there are no simple models to estimate the thickness of the lubrication film as a function of the oscillation and thus determine its potential effects on rolling contact fatigue. Most bearings are grease-lubricated (Lugt, 2009), including most pitch and yaw bearings (Becker, 2011; Wenske, 2022). Grease consists of, among other things, thickener and base oil (Lugt, 2009). Film thickness estimation would likely become even more challenging with grease lubrication due to the effect of the thickener. Therefore, the effect of lubrication is

³²Even though they only show equivalence for sinusoidal movements, one can conclude that their numerical approach is equivalent to usage of the Harris factor for any type of movement if one evaluates the life and the corresponding movement of the bearing as shown in Sec. 2.1.6 with each time step used as a bin, and uses only the Harris factor.

³³Called "Harris 1" in the reference.

³⁴Called "Harris 2" in the reference.




Figure 6. Left: load cycle as assumed by all ISO-based approaches; other examples: further types of load cycles not considered in ISO.

275 mostly ignored in all models for rolling contact fatigue calculation in oscillating bearings of which the authors are aware. This statement also applies for the non-ISO based approaches discussed in Sec. 2.2.

2.1.6 Binning for oscillating bearings

Life calculations often need to be performed for operating conditions that vary over time. As argued in Sec. 2 of Menck (2023), the most accurate way to calculate the rolling contact fatigue life of a bearing under varying operating conditions according to the assumptions in Eq. 1 made by ISO-related approaches is to use the Finite Segment Method according to Menck (2023). This is because the Finite Segment Method considers local load changes rather than summing global, location-independent bearing damage over time. For most users, it will however be simpler to remain closer to existing approaches that are based on C and P and do not require a more detailed calculation approach with local damage calculation. Doing so for oscillating bearings necessitates the use of bins representing similar operating conditions in combination with oscillation factors (Harris, Houpert, or Rumbarger). This is the most commonly recommended approach, a version of which is also found e.g., in the NREL DG03 (Harris et al., 2009). Using bins is merely an approximation when compared to a proper application of Eq. 1 (cf. Menck (2023)). It is an approximation since the aforementioned factors have all been developed for constant oscillation amplitudes around the same mean position and they all assume there is a constant load acting on the bearing as it moves, along with a number of other assumptions made by Lundberg and Palmgren (1947), resulting in the life of a whole bearing, a process in which local information is lost.

To apply oscillation factors, movement such as depicted in the stochastic case of Fig. 2 must be translated into bins of oscillations. Typically, variable load is taken into account in fatigue calculations by using rainflow counting (ASTM, 2017) for classical fatigue of structural components. Rainflow counting is also used for the bearing movement (as opposed to the load) for the life calculation of pitch bearings in NREL DG03³⁵, Menck et al. (2020), and Keller and Guo (2022).³⁶ Performing a rainflow count will provide the bins required for further calculations.

³⁵Misspelled as “rainbow cycle” in the reference.

³⁶For damage mechanisms like wear, where the order of movement is important, Stammler et al. (2018) recommend range-pair counting. In fatigue calculations, rainflow counting is more useful because it can fully represent the effect of a large movement (or load cycle) that is interrupted by many small ones. However, this effect is only noticeable in rolling contact fatigue calculations if the Houpert effect is considered. Otherwise a range-pair count will produce a

The load acting on the bearing is irregular and must be simplified into a single equivalent load P_m for each bin of the cycle count. Ideally, to this end, the equivalent load P_i per time step i is determined and the equivalent load over the bin P_m is determined from all time steps $i = 1 \dots n$ in the bin as per

$$P_m = \left(\frac{N_1 P_1^p + N_2 P_2^p + \dots + N_n P_n^p}{N_1 + N_2 + \dots + N_n} \right)^{1/p} \quad (7)$$

300 The value $N_i = n_i \cdot \Delta t_i$ here represents the distance covered in the condition i (measured in degrees or revolutions), and can be calculated from the speed n_i and the time t_i in that condition³⁷. The exponent p is given in Table A1. The approach in Eq. 7 is not specific to oscillation and can similarly be found in various bearing manufacturer catalogs and basic machine element text books (Roloff et al., 1987; Decker, 1995; Haberhauer and Bodenstein, 2001; Liebherr-Components AG, 2017; Schaeffler Technologies AG & Co. KG, 2019).

305 If it is not possible to determine P_i for each time step, potentially due to the calculation being too costly, it is possible to apply Eq. 7 to the force and moment components ~~making up contributing to P~~ (including radial force F_r , axial force F_a , and bending moment M) ~~and to then determine $P_m = f(F_{r,m}, F_{a,m}, M_m)$ and then determine P_m~~ from a suitable function³⁸ $f(\cdot)$ based on their values $F_{r,m}, F_{a,m}, M_m$ for each bin (calculated as per Eq. 7, but using F_r, F_a, M instead of P).

Using the P_m -values of each bin, it is now possible to calculate the life of each bin $L_{rev} = (C/P_m)^p$. The life in oscillations L_{osc} according to Eq. 2, using the appropriate factor as determined on the basis of Sec. 4, can be determined too.

310 All of the bins $b = 1 \dots B$ obtained are then typically combined into one final life using the Palmgren-Miner hypothesis (cf. also Zaretsky (1997); Kenworthy et al. (2023)) according to

$$L = \frac{1}{\frac{\phi_1}{L_1} + \frac{\phi_2}{L_2} + \dots + \frac{\phi_B}{L_B}}, \quad (8)$$

where L_1, \dots, L_B denote the life in bin b . This may be either the life in oscillations, revolutions, or time. Typically, the life would be in oscillations if oscillation factors have been used but it may be converted to time or revolutions. L denotes the total, combined life of all operating conditions. The variable ϕ gives the proportion of oscillations, revolutions, or time performed in that bin. It is calculated according to

$$\phi_b = \frac{s_b}{s_1 + s_2 + \dots + s_B} \quad (9)$$

320 where variables $s_1, s_2, \dots, s_b, \dots, s_B$ are the oscillations, time, or revolutions that occurred while in that bin, but must have the same unit as the lives in Eq.8. It follows that $\phi_1 + \phi_2 + \dots + \phi_B = 1$.

It is worth noting that binning is solely used to reduce the number of data points from real-life data or a simulation. Using modern computers, if there is no hardware-specific necessity to reduce the number of data points, it is possible to use each very similar result to a rainflow count. This is because oscillation cycles of the moving ring in rolling contact fatigue are different from a load cycle: The load cycles are caused by the rolling elements rolling over the raceway and are thus very local phenomena that are seldom interrupted.

³⁷Strictly speaking, this equation only applies for a constant load direction, but it can be used as an approximation with some variations in the load direction, too, as proposed here. The same applies for Eq. 8. This increases the uncertainty surrounding the calculation result somewhat, which is explored in Sec. 4.4.

³⁸Functions $f(\cdot)$ for bearings with only radial and axial load components can be found in ISO 281 (ISO, d). Examples of a function $f(\cdot)$ for pitch bearings can be found in (Harris et al., 2009; Menck et al., 2020), where the latter publication is to be preferred.

single step taken from e.g., an aeroelastic wind turbine simulation or some other data set and treat it as a separate bin to which Eq. 8 is directly applied, rather than processing the steps into a reduced number of bins. From the perspective of a proper application of the Palmgren-Miner rule to a whole bearing, usage of each single step is the most accurate approach. It is thus both easier and less error-prone, as well as more accurate than binning beforehand. In order to account for oscillation effects, it would then be required to consider the larger oscillation cycle (amplitude) that a specific step is part of and adjust its life based on that, where the step will typically make up a fraction of the complete oscillation.

2.2 Non-ISO related approaches

A number of alternative approaches have been developed in recent years, particularly with a focus on blade bearings. Many of these approaches rely on S-N curves that can be determined without testing a complete bearing.

Lopez et al. (2019) propose a model for a blade bearing that uses the movement of the bearing as a basis and computes the multiaxial stress-state at the subsurface of the raceway. Loads are obtained from FE simulations using blade root loads from multibody simulations. They apply various multiaxial fatigue criteria and compare the results. They find that IPC control strategies significantly increase the damage inflicted on a bearing compared to CPC due to the increased movement. The lives calculated with the different fatigue criteria are also sometimes very different from each other.

Leupold et al. (2021) segment a bearing and use a reduced Finite Element model in a multibody simulation to determine the stress on each segment. Using bearing movement from time series they obtain the number and magnitude of stress cycles for each segment. Individual loads are combined using the Palmgren-Miner hypothesis. Unlike almost all literature on rolling contact fatigue, their model is based on Hertzian normal contact pressure rather than subsurface shear stress. However, they note that “fatigue criteria such as Fatemi–Socie (Fatemi and Socie, 1989) or Dang Van (Dang Van et al., 1989) could also be applied” in subsequent work. They obtain empirical values of the cycles to failure used for the Palmgren-Miner hypothesis from a test of a full-sized blade bearing³⁹ and an assumed slope of the S-N curve from the literature. Further, they note that “a large number of tests are necessary for reliable results”, but that “currently, not enough tests have been carried out to determine a reliable service life” with their model.

Hwang and Poll (2022) propose an approach that is then further detailed in Hwang (2023). The approach is based on one circumferential position of the inner bearing ring denoted “small stressed volume” (SSV). The stress-load-history of different layers below the race at the SSV is analyzed in detail based on the behavior of the inner ring and the load distribution of the bearing. Residual stresses are optionally included in the calculation. For all load cycles that occur, the Palmgren-Miner hypothesis is applied to layers at the SSV. The layer with the lowest survival probability is used to calculate the life of the bearing. To consider the effect of loaded volume, Hwang proposes a simplified method to estimate the loaded volume in the specimens on which his S-N curves are based, and the loaded volume in the bearing, and to correct the bearing life based on this estimation. The model is applied to rotating and oscillating bearings under constant operating conditions. Hwang (2023) further outlines a proposed application of his model to rotor blade bearings that is not carried out in detail.

³⁹Presumably a bearing of the same type as used for the calculation, though this is not specified in the reference.

355 Escalero et al. (2023) propose a method for the probabilistic prediction of rolling contact fatigue in multiple-row ball bearings
subject to arbitrary load and movement histories. They use a three-dimensionally discretized model of the raceway in which
each finite element's individual stress cycle history over time is analyzed using a rainflow count. They use orthogonal shear
stress as the governing parameter but note other criteria may be included in the future. The failure probability of the individual
elements is determined based on S-N curves obtained from rotating bending specimens and by applying scale factors because
360 of size differences between the specimen and the elements, and because of the conversion from normal to shear stress. All
individual element failure probabilities are combined using the Weibull weakest link principle (Weibull, 1939). The authors
demonstrate their method for a reference case in which a blade bearing was tested (cf. Sec. 3).

3 Experimental validation

Despite the large number of theoretical models discussed above, there are only a few published experimental results of fatigue
365 tests on oscillating bearings.

Tawresey and Shugarts, W. W., Jr. (1964) tested approximately 750 oil-lubricated bearings under oscillating conditions
closely duplicating those encountered in helicopter rotor blade hinges but failed to produce a logical explanation of their
results (Rumbarger and Jones, 1968). Rumbarger and Jones (1968) therefore reanalyzed 388 of these bearings comprising 13
test series of identically sized, caged needle-roller bearings and derived a life calculation approach based on the Lundberg-
370 Palmgren theory, cf. Sec. 2.1.2. They conclude that “the theory of Lundberg and Palmgren is [...] favorably compared with the
life tests” and derive an experimental load rating C that is shown to be within the bounds defined by the relevant standards at the
time (then ASA and AFBMA, today ANSI and ABMA) when adjusted for oscillating motion according to Sec. 2.1.2. Further,
they specifically conclude that “the life varied inversely to the fourth power of the radial load”, thus giving $p = 4$, which is
identical to the load-life exponent of Lundberg and Palmgren (1952) for the case of pure line contact, cf. also Table A1. For the
375 13 test series, they derive Weibull slopes ranging from $e = 1.13$ to 3.55 , with a mean value of $e = 2.04$. This is higher than the
value of Lundberg and Palmgren (1952) and ISO 281 ISO (d), cf. Table A1, but they also note that “the wide variation in the
values of the Weibull slope are well known”, since different bearing tests routinely produce different Weibull slopes, including
even the test data of Lundberg and Palmgren (1952) on which the values of ISO are based; and that the higher Weibull slope
may be a product of using more modern steels than those used by Lundberg and Palmgren (1952). Despite the tests going as low
380 as an amplitude of $\theta = 1^\circ$ ($\varphi = 2^\circ$), none of the bearings show evidence of wear⁴⁰, but the failed bearings presented “varying
degrees of flaking breakout or spalling which is characteristic of failure in rolling-contact bearings subjected to rotation”.

Halmos et al. (FVA, 2021) use oil-lubricated cylindrical roller bearings for fatigue tests. They obtain rolling contact fatigue
for oscillation amplitudes⁴¹ as low as $\theta = 1^\circ$ ($\varphi = 2^\circ$). The final number of fatigue results is too low to compare them against
theoretical calculations, but they conclude that “at least for selected amplitudes, the existing calculation approaches [referring
385 to ISO-based approaches] deliver conservative results compared to the experimentally determined lives”.

⁴⁰A common value to compare wear tests on different bearings is the $x/2b$ ratio (Schwack, 2020). Low values of $x/2b$ are often used to indicate wear
potential (de La Presilla et al., 2023). Using the data given in the reference, the authors determined this test to correspond to $x/2b \approx 5$.

⁴¹The given amplitude equals $x/2b = 1$.

Münzing (2017) tests seven ball screws with $\theta = \theta_{\text{crit}}$. The lubricant is an aviation grease type Aeroshell 33 MS. The test duration is equivalent to the L_{10} of the ball screws, which Muenzing determines based on the simplified version of the Rumbarger factor found in NREL DG03 (Harris et al., 2009), cf. Sec. 2.1.2, which he modifies⁴² to be equal to 1 for $\theta \geq 90^\circ$ ($\varphi \geq 180^\circ$). Five out of seven show initial damage on the raceways. As the standard DIN 631 for ball screws defines a minimum size for surface damage to be considered as fatigue damage and this size is not reached, they are assessed as having passed according to the standard.

Escalero et al. (2023) propose an approach discussed in Sec. 2.2. They compare their results to the test of a single blade bearing under axial load but obtain no correlation. The failure onset in the bearing could not be established exactly as failure already had progressed significantly once it was opened.

Hwang (2023) applies his model to rotating cylindrical roller bearings and angular contact ball bearings as well as four-point bearings. He compares his results to tests of 200 radial cylindrical roller bearings (NU 1006, 55 mm outer diameter) and several double-row four-point bearings of 2.4 m diameter. The model deviates from his experimental results by a factor of about 2 to 10, giving a lower estimate than observed in the tests.

4 Use of the approaches

This section contains recommendations for ~~when to use which~~ selection of a rolling contact fatigue life calculation approach. Section 4.1 contains a number of general recommendations, Sec. 4.2 and 4.3 discuss some simple illustrative examples, and Sec. 4.4 and 4.5 detail possible uses for a pitch and yaw bearing in a wind turbine.

4.1 Recommendations for use

A flowchart of when to use which ~~method~~ rolling contact fatigue life calculation approach, based on the underlying modeled physical principles, is given in Fig. 7. Theoretically, the conditions in the flowchart must hold all the time. Practically, it will be sufficient if they hold most of the time. Dashed arrows represent mathematical approximations, which are considered less accurate than exact calculations. For the ISO-related approaches, recommendations are given according to the underlying physical phenomena considered in the derivations as described in this paper. The recommendations herein may therefore deviate from those given by the respective authors. For the non-ISO related approaches, recommendations generally follow the respective authors since they rely on less widely acknowledged approaches and may therefore be subject to the more individual interpretation of the respective authors. Further comparisons between the approaches are given in Tab. 2.

⁴²The application of the Rumbarger factor in the reference takes place by changing the equivalent load P as done in other references (cf. Sec. 2.1.2) but his application, including his changes, are equivalent to those described here. The modification to $a_{\text{Rumbarger}} = 1$ for large amplitudes is presumably the result of a misunderstanding: Münzing claims the NREL DG03 to state that for oscillation amplitudes of $\theta > 90^\circ$ ($\varphi > 180^\circ$), the influence of the oscillatory movement can be neglected and the life of a continually rotating bearing can be used for an oscillating one. This is not stated in NREL DG03 though, rather, it implies that the life of a rotating bearing and that of an oscillating one are identical in the case of $\theta = 90^\circ$ ($\varphi = 180^\circ$) only, but not for amplitudes exceeding this value (cf. Harris et al. (2009): “The total stressed volume and number of stress repetitions per cycle are identical to a bearing in continuous rotation when $[\varphi] = 180^\circ$ ”).

Generally, the start of the flowchart is given by the “Start” box. If bins are used (cf. Sec. 2.1.6), the “Start bins” box can be used for an approximation. In this case, the condition $\theta \geq \theta_{\text{crit}}$ applies if all circumferential positions of the ring experience some stress cycles over all bins⁴³.

415 For general users seeking to apply a life calculation, ISO related approaches are preferred to non-ISO related ones due to their simplicity and the fact that there is much more empirical basis underlying them. In case of an invariant load direction and oscillation amplitude θ , various methods are shown in the figure. Among the ISO related ones, that by Menck can be considered to be most accurate, however, it is also complicated to apply. A less accurate (i.e., an approximated) but simpler method will be most useful for most readers. Among the approximated ISO related methods for an invariant load direction and θ , “Bins
420 with Palmgren-Miner” is the recommended approach due to its wide use in many areas. Among the non-ISO related methods, Table 2 gives an overview of advantages and disadvantages of each method. Since only users with very specific aims will refer to these methods, it is up to readers to take their own decision as to which of these methods, if any, to use.

None of the ISO-related approaches predicts huge deviations from a_{Harris} for regular operating conditions. For a rough estimate, if the desired life is well below that calculated with the Harris approach, it is very likely to pass with the other ISO-
425 related approaches, too. For a more precise calculation, narrow load zones or small oscillation angles below θ_{crit} will produce the largest deviations from the Harris factor.

For the Rumbarger effect, based on Sec. 2.1.2 and App. A, the flowchart recommends combining this effect with the Houpert effect for non purely-axial loads (i.e., radial and moment loads). This deviates from Rumbarger and Jones (1968), where the Rumbarger effect is used without consideration of the Houpert effect for radial bearings, and Harris et al. (2009), where the
430 Rumbarger effect is used without consideration of the Houpert effect for moment loads, but this recommendation is based on the fact that particularly for these cases which represent relatively small load zones ε , the Houpert effect is to be taken into account⁴⁴.

The flowchart considers the “numerical approach” of Wöll et al. (2018) as well as Hai et al. (2012) to be approximations. Although Wöll et al. use the approach for a series of stochastic movements and load directions, they also note “the numerical
435 approach lacks the capability of taking sophisticated distinctions into account, as [Rumbarger]⁴⁵ does with the critical angle distinction and Houpert does with comparing the oscillation amplitude to the load zone size”. The reason their method cannot consider these local effects is due to the global application of the Palmgren-Miner hypothesis, see Menck et al. (2022), Sec. 2.2. Menck’s Finite Segment Method can be seen as a more accurate (but more difficult to implement) version of Wöll’s numerical approach that considers local effects also seen with Houpert and Rumbarger. Wöll’s numerical approach is also effectively

⁴³Since the use of bins represents an approximation, there is no more precise wording than “some stress cycles” for this issue. See e.g. Fig. 2, blue, for an example for which $\theta \geq \theta_{\text{crit}}$ even though individual oscillation amplitudes may be below θ_{crit} . Note that the position of the rolling elements w.r.t. the rings is required for this assessment, not the position of the inner ring, θ_i . The position of the rolling elements w.r.t. a stationary outer ring is given by $\theta_c = 0.5 \cdot \theta_i \cdot (1 - \gamma)$; the position of the rolling elements w.r.t. a moving inner ring is then given by $\theta_i - \theta_c$.

⁴⁴This may seemingly contradict the conclusions in Sec. 3, which state that Rumbarger and Jones (1968) already find their results to be consistent with standards despite not considering the Houpert effect. For a radial load giving $\varepsilon = 0.5$ and small oscillation amplitudes, Houpert and Menck (2021) predict a life reduction of about 10% which would still put Rumbarger and Jones’ results within the range of the standards at the time. This statement therefore does not contradict Rumbarger and Jones’ conclusions.

⁴⁵Called “Harris 2” in the reference.




Figure 7. Flowchart to find the simplest applicable life calculation approach for a given oscillating bearing.

440 identical to a bin count, listed below it in the flowchart. Hai et al. (2012) is listed as an approximation due to the reasons set out in Sec. 2.1.

As noted in App. C, the Rumbarger effect actually applies even for oscillation amplitudes $\theta > \theta_{crit}$, but since its effect is so small at these amplitudes the effect at larger amplitudes is not considered in Fig. 7.

Some approaches are derived in different sources. The authors recommend using the following sources: The Harris factor is given in Sec. 2.1.1. The Houpert factor is best considered according to the model of Breslau and Schlecht (2020) or Houpert and Menck (2021). The latter reference includes curve fits for ease of use. Older references may be erroneous. The Rumbarger effect is best calculated according to Eq. 5 or Breslau and Schlecht (2020) or Houpert and Menck (2021), cf. also Sec. 2.1.2. Older references may be oversimplified. A combination of the Houpert factor and the Rumbarger factor is best performed according to Breslau and Schlecht (2020) and Houpert and Menck (2021). All other approaches in the flowchart are best performed according to the publications of their respective authors.

Table 1. Comparison of different life calculation approaches

Approach	Based on bearing tests or small specimen S-N curves	Considers partial load cycles (cf. Fig. 6)	Considers volume effect	Considers whole race volume	Stress criterion	Experimental validation
ISO-based	bearing	no	yes	yes	τ_0	ok but incomplete
Leupold et al.	bearing	yes	unclear	yes	normal stress P , pot. more	not available
Lopez et al.	S-N	yes	unclear	yes	various	not available
iKonPro	S-N	yes	yes	yes	τ_0 , pot. more	limited data
Hwang	S-N	no	partially	no (only SSV)	various	some deviations

4.2 Application to a cardan joint bearing

An exemplary cardan joint connects two shafts whose axes are inclined to each other. The shafts rotate, causing the cardan joint bearing to oscillate with a constant oscillation amplitude of $\theta = 5^\circ$. The exemplary bearing is a radial bearing with contact angle $\alpha = 0^\circ$. It contains $Z = 15$ balls with a diameter of $D = 10$ mm, and has a pitch diameter of $d_m = 60$ mm. The critical amplitude according to Eq. 4 is then $\theta_{crit,o} = 28.8^\circ$ and $\theta_{crit,i} = 20.6^\circ$ for the outer and inner raceways, respectively. The load zone is made up of a purely radial load that is constant with respect to the outer ring. Half the circumference is loaded, giving $\varepsilon = 0.5$, and inner and outer ring osculation are identical.

In the context of Fig. 7, both the load direction and θ are thus time invariant. There is no purely axial load, and $\theta \geq \theta_{crit}$ does not apply. A combination of the Houpert and Rumbarger factors can thus be used by multiplying them as shown in Houpert and Menck (2021), using the Rumbarger factor for the outer race to be conservative. Alternatively, the approach given by Breslau and Schlecht (2020), who discussed cardan joint bearings in their paper in more detail, may be used. Furthermore, the other approaches in the top right of Fig. 7 may also be used since they apply to general time-series based data and thus also apply to simpler data.

The Harris factor for this bearing is $a_{Harris} = 18$ according to Eq. 3. The Rumbarger factor according to Eq. 5 is $a_{Rumbarger} = 15.1$ if the outer ring is assumed to be conservative; it would be 15.6 for the inner ring. A combination of the Rumbarger and Houpert effect is calculated according to Houpert and Menck (2021) being⁴⁶ $a_{osc} = 14.2$. This final value is recommended here because it accounts for both relevant effects that occur in the bearing described above. It is smaller than the Harris factor alone, and also smaller than the Rumbarger factor alone, since the effects of both Rumbarger and Harris decrease life.

4.3 Application to a crane slewing bearing

An exemplary crane slewing bearing is located at the bottom of a crane which is exclusively used to perform oscillation amplitudes of $\theta = 90^\circ$ to unload a ship. It is an axial bearing with $\alpha = 90^\circ$. The critical amplitude according to Eq. 4 is

⁴⁶The Houpert factor was calculated using Eqs. 45, 46, 48 and 49 of Houpert and Menck (2021) using the bearing data stated in the above text. Variables $f_{\theta_{crit,i}}$ and $f_{\theta_{crit,o}}$ in the aforementioned equations account for the Rumbarger effect.

$\theta_{\text{crit}} = 8^\circ$ for both inner and outer rings. The load is mostly an axial load with only a slight tilting moment component. According to Fig. 7, the load direction is then invariant, and so is the oscillation amplitude θ . The load is (approximately) purely axial, and $\theta > \theta_{\text{crit}}$. Therefore, the Harris factor applies for this bearing. For the amplitude of $\theta = 90^\circ$, $a_{\text{Harris}} = 1$.

475 The Rumbarger factor according to Eq. 5 would be equal to a_{Harris} due to $\theta > \theta_{\text{crit}}$. The Houpert factor according to Eq. 6 is approximately $a_{\text{Houpert}} \approx a_{\text{Harris}}$ due to the mostly axial load giving a large $\varepsilon \gg 1$. This is why it is valid to simply use a_{Harris} for the given case.

If θ were time invariant, it would also be possible to use the Harris factor and combine different bins using the generalized mean in Eq. 7. Again, more complicated approaches in the top right of the flowchart would also apply.

480 4.4 Application to rotor blade bearings

A number of publications include rolling contact fatigue calculations for rotor blade bearings, some ISO-related⁴⁷, see Harris et al. (2009); Schwack et al. (2016); Menck et al. (2020); Keller and Guo (2022); Menck (2023); Rezaei et al. (2023), and some not, see Lopez et al. (2019); Leupold et al. (2021); Escalero et al. (2023); Hwang (2023). The non-ISO based methods are, as stated in Sec. 4, best applied according to the respective publications given above, though many of these publications are relatively short and likely not sufficient for an end user to actually copy their technique and apply to an actual bearing. 485 Moreover, according to Sec. 3, the experimental validation for these models is still lacking. Therefore this section will focus on ISO-based approaches, which remain the most common life calculation methods for rolling contact fatigue.

Rotor blade bearings typically experience pitch amplitudes as in the stochastic case depicted in Fig. 2: Their oscillation amplitude is irregular, as are the loads acting on the blade in five degrees of freedom. Moreover, the load direction changes due to the ~~M_x component of the bending moment caused by gravitational loads, though for bigger resulting moments, M_y is driving the direction of the resulting moment~~ blade weight bending moment as the blade rotates and the blade aerodynamic bending moment that varies with the turbine operating conditions (Menck et al., 2020). Therefore, according to Fig. 7, the Finite Segment Method (Menck, 2023) would be the most appropriate ISO-based method for an engineer to use. However, some simplified approaches exist, too. These include the methods by Wöll et al. (2018) and Hai et al. (2012), and the approach 495 most often chosen by users, a bin count. Using a bin count is likely the most user-friendly and well-known of the approaches. Section 2.1.6 details how to do a bin count and therefore represents the first step required for calculating the life of a pitch bearing, and this step is described in detail below.

At this point we assume bins to be present, where ideally no binning is performed but each time step of the simulation is used as an individual bin (cf. Sec. 2.1.6). Prior to the application of Eq. 8, the lives L_b of each bin must be calculated using 500 an approach which takes the oscillation into consideration. To this end it is useful to refer to Fig. 7. Although both the load direction and pitch angle θ are time invariant, they have to be considered to be approximately constant in order to use oscillation factors, hence the start at “Start bins”. The loads are not purely axial, but the oscillation of the bearing - over the entire operating

⁴⁷Among the ISO-related publications it is worth noting that NREL DG03 (Harris et al., 2009) is the most common guideline for blade bearing life calculation, and Schwack et al. (2016); Menck et al. (2020); Keller and Guo (2022); Rezaei et al. (2023) are all, at least in part, based on it; only Menck (2023) is not. The publications have not been included in Sec. 2.1 if they merely apply the DG03 but present no new methods or findings relevant to this review.

time of the turbine - is large enough to have rolling elements cover the entirety of the raceway at one point or another^{48,49}. That is to say there is no area that is never stressed, giving $\theta > \theta_{crit}$. The Houpert factor is therefore a useful factor to employ, whereas the Rumbarger factor is not, since each segment of the raceway will see rolling elements pass by fairly regularly.⁵⁰

Using ISO/TS 16281, there are two different equivalent loads: Q_{ei} for the inner ring and Q_{ee} for the outer ring. For each of these rings, users must decide whether the ring is rotating or stationary relative to the load. Since rotor blade bearings mostly perform small oscillations below approximately 20° of amplitude, an alternative to using the Houpert factor is to use the equivalent load of a stationary ring for both rings in combination with the Harris factor (cf. Sec. 2.1.3). This is equivalent to the “worst case” scenario of the Houpert factor and is almost identical to it at small oscillation amplitudes.

Figure 8 shows different approaches to calculate the life of a rotor blade bearing using data from aeroelastic simulations. Table 2 summarizes the approaches. The five approaches are ordered with increasing accuracy to the right of the figure, where “increasing accuracy” means that the Palmgren-Miner hypothesis is applied as accurately as possible. All of them are closely related to ISO and therefore to Eq. 1. The first three approaches (name containing “bins”) all pre-process the time series data into bins based on the bearing movement and load data acting in a given time step. The fourth approach (“stepwise”) uses each individual time step of the simulation as a separate bin. The fifth method (“Finite Segment Method”) does not use binning but directly calculates damage based on the number of rollovers occurring in segments of the ring. This is the most accurate method and can be used as a reference for the others. Results for the first four methods have been obtained using ISO/TS 16281 for the equivalent load. All results are displayed using the Harris factor, if applicable (that is, if bins were used in some form), assuming one ring to be rotating in ISO/TS 16281; and using a more accurate method for oscillation, which means that both rings have been calculated as stationary according to ISO/TS 16281 in combination with the Harris factor. The Finite Segment Method automatically includes effects of oscillation and cannot be used with the Harris factor.

The first three approaches shown in Fig. 8 involve pre-processing into bins. It can be seen that some of their results deviate more, some deviate less from the Finite Segment Method. These results are heavily dependent on details of the pre-processing used for the data and the results shown here are not representative for other potential types of pre-processing. The fact that the “coarse bins”-simulation using an oscillation correction is so close to the Finite Segment Method is thus likely accidental and not because this particular approach is particularly representative of a more correct method.

Comparing the life $L_{10,stepwise}$ of the stepwise calculation where one ring is assumed to be stationary and one is assumed to be rotating (“Harris factor/LRD”) to the results $L_{10,FSM}$ of the more accurate Finite Segment Method, one can see

⁴⁸Individual pitch cycles may cover only a small portion of the raceway, but this only causes deviations as large as those given by the Rumbarger factor if this behavior continues for the bulk duration of operation along the same mean position with the same amplitude, which is not the case in a typical pitch bearing.

⁴⁹The entirety of the raceway is covered by rolling elements if for the largest amplitude θ_{max} done by the bearing, $\theta_{max} \geq \theta_{crit}$ is true. Since all pitch bearings perform 90° movements (Burton et al., 2011) (corresponding to $\theta = 45^\circ$), this is achieved in virtually all pitch bearings: Due to the rolling element diameter being small compared to the pitch diameter (Wenske, 2022), pitch bearings commonly have close to $Z = 100$ and more rolling elements and small values of γ . This means that for a four-point bearing as used in Menck et al. (2020), $\theta_{crit,i} = 2.48^\circ$ and $\theta_{crit,o} = 2.42^\circ$, values which are easily exceeded by a pitch controller even without taking the 90° movement into account (Bossanyi et al., 2013; Bartschat et al., 2023).

⁵⁰Note that this recommendation is in contrast to the current version of NREL DG03, which uses the Rumbarger effect only (by modifying the load rating - equivalent to using a factor as discussed in Sec. 2.1.2).

Table 2. Different approaches to calculate the life of a rotor blade bearing

Denomination	Details
coarse bins	1 080 bins with the upper load level per bin used for P
fine bins	151 200 bins with the upper load level per bin used for P (Implementation of Menck et al. (2020))
fine bins, P_m	Identical to “fine bins” but using generalized mean loads P_m of each bin according to Eq. 7
stepwise	Creates one individual bin per simulation time step
Finite Segment Method	Sums damage from individual rollovers on individual locations of the rings (Implementation of Menck (2023))

530 that

$$L_{10,FSM} = 0.86 \cdot L_{10,stepwise}. \quad (10)$$

This is roughly in line with using the Houpert factor or assuming both rings to be stationary, which gives a result which is only slightly higher (cf. Fig. 8, stepwise, Oscillation correction). The result of the Finite Segment Method is slightly lower because it first sums local damage over the entire span of the simulation before determining the global bearing life. Therefore, 535 load concentrations on individual segments and bearing rings are considered more accurately than with the other methods⁵¹. For calculations performed with ISO-related approaches using binning of data in some form, where one ring is assumed to be stationary and one is assumed to be rotating⁵² it is therefore reasonable to expect a life which is 10 to 15% longer than that obtained with more advanced methods. Further deviations that are caused by binning of the data and other forms of pre-processing are impossible to predict and therefore a stepwise calculation is preferable.

⁵¹The result of the Finite Segment Method may thus also be influenced slightly by the Rumbarger effect, i.e., an uneven distribution of rollovers along the circumference, although the effect is much less than would be predicted by the Rumbarger factor if applied directly to the individual pitch cycles. It also captures potential load concentrations on individual raceways because the life of the raceways is determined from their individual segments, therefore including a load history for the raceways too, whereas with the other methods the raceway life is included in a bearing life which is then used for the Palmgren-Miner hypothesis, leading to a loss of information.

⁵²This is the standard assumption in virtually all typical rolling contact fatigue life calculations including ISO 281 (Lundberg and Palmgren, 1947; Harris and Kotzalas, 2007; ISO, a).




Figure 8. Comparison of the different approaches in Tab. 2 with Harris factor and additional effects for oscillation considered.

540 4.5 Application to yaw bearings

For yaw bearings, the oscillation behavior is highly site dependent. Any wind direction history can be calculated using the Finite Segment Method or the other approaches highlighted with thick borders in Fig. 7. For the design of a wind turbine, yawing movements are seldom simulated, apart from a few design load cases (Wenske, 2022). Rather, constant offsets from an optimal yawing position are simulated and assumed to be present for a certain amount of operating time. Yaw movement is then assumed to be distributed among these simulated cases. Since detailed time series will typically not be available, binning will often be necessary in order to calculate the life, though detailed time series would be preferable, if available.

Though the behavior is highly dependent on both the site of the turbine as well as the design of the yaw system, some general statements can be made. Firstly, even at sites with only one main wind direction, it is likely that this wind direction will vary by a few degrees. Secondly, the yaw misalignment that triggers a yaw movement is dependent on the yaw system design. Yaw misalignments of 3° to 8° are common, realistic values (Wenske, 2022). Finally, the design of large scale yaw bearings, like that of pitch bearings, usually includes a large number of rolling elements in excess of 50 or even 100 and more per row⁵³, giving small critical angles θ_{crit} . It is thus unlikely that any yaw bearing will be operated in a manner whereby during the entire operating history of the bearing, the loads are truly concentrated only on parts of the raceway, since that would require yaw movements to be consistently smaller than θ_{crit} despite fluctuations in the wind direction and possible slippage of the rolling element set. The Rumbarger effect is thus unlikely to be relevant for yaw bearings in the field.

Regarding the Houpert effect, the wind direction is important. Unlike for typical bearings, the rotating (oscillating) ring is the one that will always be loaded in one primary position since it is consistently moved toward the wind. The stationary ring, on the other hand, can experience very concentrated loads in one position (in the case of a site with only one main wind direction) or it can even experience loads spread evenly over its circumference (on sites with no clear main wind direction, where the wind can come from any direction). In the first case (one main wind direction only), similar to pitch bearings,

⁵³See footnote 49.

both rings experience a high concentration of loads in one spot. It is thus recommended that the Houpert effect is considered, ideally by using the equivalent load for a stationary ring, for the calculation of both Q_{ei} and Q_{ee} if ISO/TS 16281 is used. Otherwise, the Houpert effect can be taken into account by using the publications mentioned in Sec. 4.1. Assuming one main wind direction is the more conservative assumption and should be the approach to choose in case of doubt. Since yaw bearings, like pitch bearings, are strongly affected by a tilting moment, each of their raceways is commonly loaded around half of its circumference (Chen and Wen, 2012; Schwack et al., 2016; Menck et al., 2020; Graßmann et al., 2023), corresponding to a load zone parameter (cf. Sec. 2.1.3) of $\varepsilon = 0.4 \dots 0.6$. With this value of ε , a life which is around 10% shorter than that obtained with the Harris factor is to be expected for small oscillation amplitudes (Houpert and Menck, 2021). If the main wind direction is truly evenly spread over all compass directions, it is permissible to use the equivalent load of a ring that rotates relative to the load for the outer ring, approximately equivalent to simply using the Harris factor for the entire bearing⁵⁴.

5 Current challenges and critical future work

While there are a number of different approaches for the calculation of rolling contact fatigue in oscillating bearings, the validation of these models is lacking to a large extent. Among the ISO related approaches, some experimental results suggest that the predictions may be accurate, as discussed in this paper. One can also argue that the ISO related approaches, being based on the widely accepted standard ISO 281, are partially validated by the rotating bearings which were used to validate the standard in itself.

For regular operating conditions, the ISO related approaches do not differ by a huge margin. Validation of one approach therefore also increases the likelihood that another of the ISO related ones is accurate. Potential attempts to validate these bearings can focus on the different phenomena that are covered by the Houpert and the Rumbarger effect to validate them independently of each other, but as they are based on the same foundation, these validations (if successful) will have a positive effect on each other, too.

A number of publications have shown deviations of rotating bearing lives from the ISO standard (Harris and Kotzalas, 2007; Londhe et al., 2015). A validation of the ISO related models in this paper should therefore take into account that they are relative values. Any bearings used for oscillating tests should ideally also be used for rotating tests in otherwise identical or similar conditions, to ensure that potential deviations from the results shown in this review are not simply due to the bearings themselves lasting longer than suggested by the standard, but actually due to the relative factors given here being inaccurate.

⁵⁴In this example, the behavior of a typical bearing is flipped on its head. Typical bearings in most industrial applications experience concentrated loading on the stationary ring, since it is stationary with respect to the load. The rotating ring, on the other hand, sees loads all over its circumference (cf. Fig. 5, “rotation”: All elements on a rotating ring are loaded like the example one, only with a time shift.). In a yaw bearing in which the wind comes evenly from all directions eventually during the turbine lifespan (for example, 25% of operational time coming from north, 25% from south, 25% from south and 25% from west), the outer ring is loaded in all positions at some point and thus experiences similar damage accumulation over its circumference as a rotating ring in a typical bearing. This is a very theoretical example to illustrate potential influences of the Houpert effect, in most cases, it will be easier to simply assume concentrated loading as discussed above, which is the more conservative case.

All of the models - ISO related and non-ISO related alike - completely neglect the influence of lubrication. This is probably the grossest simplification and the biggest uncertainty underlying all models discussed in this review. Lubrication is a complicated topic that is often simplified. Even for regular bearings, over 90% of bearings are grease-lubricated (Lugt, 2009) but for the life calculation the grease behavior is mostly approximated using base oil properties even though grease is well known to behave differently (Lugt, 2012). For oscillating applications, due to the movement-dependent lubrication film (Venner and Hagmeijer, 2008), this issue becomes much more complex than for rotating bearings, hence why all models in this review simply neglect the topic completely.

While this review, and many publications before it (Harris et al., 2009; Schwack et al., 2016; Menck, 2023) applied ISO related methods to large slewing bearings, there have been publications suggesting (without evidence) that the ISO standard does not apply for pitch and yaw bearings (Potočnik et al., 2010; Lopez et al., 2019). Whether or not this is the case is another topic worth researching. The non-ISO related methods in this review present an alternative approach at life calculation for people who distrust the ISO standard, but the evidence proving their aptitude is, to date, lacking to a much greater extent than that of the ISO related models. While it is possible that large oscillating slewing bearings behave differently than suggested in this review, it is also an option to introduce corrective factors or change load rating and equivalent load in order to perform a standard calculation for large oscillating slewing bearings nonetheless.

6 Conclusions

This work has given an overview of the literature on rolling contact fatigue calculation for oscillating bearings. Many approaches are based on ISO, tend to be user friendly, and are often applied in the literature. Most of these approaches have been proposed and used in the literature without an explanation as to when they apply. The aim of this paper was to explain when which approach can be applied. It is worth noting that many older publications, particularly for the Rumbarger effect and the Houpert effect, include errors or simplifications and hence more recent publications, including this one, are to be preferred as a source. When applied correctly according to more recent literature and for standard operating cases, the deviations between Harris, Rumbarger, and Houpert as well as other ISO-based approaches are typically not huge. This also applies to the operating conditions of pitch and yaw bearings. The large deviations obtained with alternative approaches to the Harris factor that are seen in some publications are often due to errors or simplifications. All ISO-based approaches shorten the calculated life compared to the Harris factor (or are identical to it) if applied correctly. This is because all ISO-based approaches that deviate from Harris do so because they either incorporate the Houpert or Rumbarger effect, or both, and both of these effects cause either the same life or a reduction in life compared to the Harris factor if applied correctly. Currently published ISO-based calculation approaches that increase life compared to the Harris factor are erroneous, potentially due to being overly simplified. Some phenomena described in this paper that have not yet been analyzed in the literature could slightly increase lives even for ISO-based methods.

Aside from these commonly used factors, a number of alternative approaches have been discussed. These include some ISO-related ones and some approaches that deviate significantly from ISO. Many of these alternative approaches, including
620 ISO-related and non-ISO-related ones, have been designed particularly for rotor blade bearings.

The experimental validation of all models in the literature is relatively poor. Some experimental results from the ISO-based approaches compared well with the calculated life, suggesting that that the predictions of ISO-based methods may be relatively close to the actual life, while validations of the alternative approaches are mostly lacking.

This work may help engineers identify which approach to use for the rolling contact fatigue life calculation for a given
625 oscillating bearing. It has been written with a particular focus on wind turbine slewing bearings, but may also be used as a reference for any other oscillating bearings in other industrial sectors.

Data availability. Aeroelastic load time series and FE-simulated bearing loads for the rotor blade bearing calculations in this paper can be found under <https://doi.org/10.24406/fordatis/113> (Popko, 2019) and <https://doi.org/10.24406/fordatis/109> (Schleich and Menck, 2020). All other data is included in this paper.

630 Appendix A: Derivation of the Rumbarger factor

Lundberg and Palmgren (1947) state, using Eq. 1 and knowing that $N = uL$,

$$\ln \frac{1}{S} \propto \frac{\tau_0^c (uL)^e}{z_0^h} V, \quad (\text{A1})$$

where τ_0 is the maximum shear stress and z_0 its depth under the raceway, V is the loaded volume, and u gives the stress cycles per million oscillations or revolutions L . For a constant survival probability S , it follows that

$$635 L \propto \left(\frac{z_0^h}{\tau_0^c V} \right)^{1/e} u^{-1}. \quad (\text{A2})$$

Comparing two identical bearings under identical τ_0 and z_0 , one oscillating and one rotating, for $\theta < \theta_{\text{crit}}$, where $V_{\text{osc}}/V_{\text{rot}} = \theta/\theta_{\text{crit}}$ we obtain

$$a_{\text{prt}} = \frac{L_{\text{osc}}}{L_{\text{rot}}} = \frac{u_{\text{rot}}}{u_{\text{osc}}} \left(\frac{\theta}{\theta_{\text{crit}}} \right)^{-1/e}. \quad (\text{A3})$$

This is equivalent to Eq. 18 given by Breslau and Schlecht (2020). In their Eq. 19, using θ_{crit} from Eq. 4, they then go on to
640 derive⁵⁵

$$a_{\text{prt i,o}} = \frac{Z(1 \pm \gamma)}{4} \left[\frac{\theta Z(1 \pm \gamma)}{360^\circ} \right]^{-1/e} \quad (\text{A4})$$

with the minus (−) sign referring to the outer and the plus (+) sign to the inner raceway. Using a_{Harris} from Eq. 3, this can be rewritten as done by Houpert and Menck (2021)

$$a_{\text{prt i,o}} = \left(\frac{\theta}{\theta_{\text{crit i,o}}} \right)^{1-1/e} a_{\text{Harris}}. \quad (\text{A5})$$

⁵⁵Equations here are adjusted to use degrees rather than radians as done in the reference.

Table A1. Exponents c, e, h, p according to ISO

	c	e	h	p
Point contact (ball bearings)	31/3	10/9	7/3	3
Line contact (roller bearings)	31/3	9/8	7/3	4 or ⁵⁶ 10/3

645 Both Rumbarger and the NREL DG03 (co-authored by Rumbarger) use a different amplitude definition than in this paper, defined by $\varphi = 2\theta$. Equation A4 then becomes

$$a_{\text{prt i,o}} = \frac{Z(1 \pm \gamma)}{4} \left[\frac{\varphi Z(1 \pm \gamma)}{720^\circ} \right]^{-1/e} \quad (\text{A6})$$

$$= \underbrace{(1 \pm \gamma)^{1-1/e} 4^{-1+1/e}}_{f_{\text{Rum}}} Z^{1-1/e} \left[\frac{\varphi}{180^\circ} \right]^{-1/e}. \quad (\text{A7})$$

The factor f_{Rum} is introduced here to include the terms $(1 \pm \gamma)$ and $4^{-1+1/e}$, both of which Rumbarger assumes to be approx-
650 imately 1. Thus, Rumbarger obtains $f_{\text{Rum}} \approx 1$. In order to keep track of the error introduced by this assumption, f_{Rum} will be retained in the following equations.

Rumbarger does not adjust life by using a factor, but by changing the load rating. A factor can be converted to an equivalent load rating using

$$L_{10,\text{prt}} = a_{\text{prt}} \left(\frac{C}{P} \right)^p = \left(\frac{a_{\text{prt}}^{1/p} C}{P} \right)^p = \left(\frac{C_{\text{Rum}}}{P} \right)^p \quad (\text{A8})$$

655 with Eq. A7 used for the adjusted Rumbarger load rating

$$C_{\text{Rum}} = a_{\text{prt}}^{1/p} C = \left(f_{\text{Rum}} Z^{1-1/e} \left[\frac{\varphi}{180^\circ} \right]^{-1/e} \right)^{1/p} C. \quad (\text{A9})$$

Equation A9 is identical to the load ratings given in (Rumbarger, 2003) and (Harris et al., 2009) when assuming $f_{\text{Rum}} = 1$ and using the parameters given in Table A1.

The error can simply be corrected by using either Eq. A9 or Eq. A7 separately for each raceway (cf. Breslau and Schlecht
660 (2020)) and without assuming $f_{\text{Rum}} = 1$.

⁵⁶Exponent $p = 4$ follows from the given $c, e,$ and $h,$ and is consequently used by Rumbarger (2003) as well as Breslau and Schlecht (2020) in their derivations. Nonetheless, ISO 281 uses $p = 10/3$ in calculating $L = \left(\frac{C}{P} \right)^p$. This is explained in (Lundberg and Palmgren, 1952) and (ISO, a), which argue for the choice of $p = 10/3$ because in some load cases, line contact within roller bearings may turn into point contact. Thus: $p = 4$ for detailed calculations of rolling contact fatigue where line contact is sure to take place; and $p = 10/3$ for calculations by general users applying $(C/P)^p$.

Appendix B: Error of the Rumbarger factor for $\theta < \theta_{\text{crit}}$

By assuming $(1 \pm \gamma) \approx 1$, Rumbarger effectively neglects the difference between inner and outer races and obtains an equation which can be used for the entire bearing. The assumption $4^{-1+1/e} \approx 1$, on the other hand, is an unnecessary simplification that leads to errors, as will be seen in the following.

665 B1 Error on one raceway

The error of Rumbarger's assumptions for one single raceway can be easily calculated by comparing the life $L_{10,\text{prt}}$ from Eq. A8 that, correctly, assumes $f_{\text{Rum}} \neq 1$ to that which approximates $f_{\text{Rum}} = 1$ as done by Rumbarger.

$$\frac{L_{10,\text{prt}}(f_{\text{Rum}} = 1)}{L_{10,\text{prt}}(f_{\text{Rum}} \neq 1)} = \frac{1}{f_{\text{Rum}}} \quad (\text{B1})$$

670 Values of $1/f_{\text{Rum}}$ for point and line contact as well as different values of γ are depicted in Fig. B1. One can see that C_{Rum} consistently overestimates the actual life, up to 23% for $\gamma = 0.35$ on a roller bearing's outer ring. The error is dominated by Rumbarger's neglect of the factor $4^{-1+1/e}$, which is 0.87 for point contact and 0.86 for line contact. Simply assuming $\gamma = 0$ thus causes an error of roughly 15% to 17%. Further differences are caused by neglecting $(1 \pm \gamma)^{1-1/e}$, which appears reasonable for very large bearings ($\gamma \rightarrow 0$) but less so for smaller ones ($\gamma \gg 0$).




Figure B1. $\frac{L_{10,\text{prt}}(f_{\text{Rum}}=1)}{L_{10,\text{prt}}(f_{\text{Rum}} \neq 1)}$ for inner and outer ring with point and line contact.

B2 Error for the entire bearing

675 For the entire bearing, the matter is more complex. Adjusted lives $L_{\text{prt } i} = a_{\text{prt } i} L_i$ of the inner ring and $L_{\text{prt } o} = a_{\text{prt } o} L_o$ of the outer one can be combined via

$$L_{\text{prt}} = \left(L_{\text{prt } i}^{-e} + L_{\text{prt } o}^{-e} \right)^{-1/e}. \quad (\text{B2})$$

For an axial bearing with $\gamma = 0$ giving $a_{\text{prt } i} = a_{\text{prt } o}$ and $L_i = L_o$ this can be simplified into

$$L_{\text{prt}} = 2^{-1/e} a_{\text{prt } i} L_i. \quad (\text{B3})$$

680 The relative difference between assuming $f_{\text{Rum}} = 1$ and $f_{\text{Rum}} \neq 1$ is then again given by $L_{\text{prt}}(f_{\text{Rum}} = 1)/L_{\text{prt}}(f_{\text{Rum}} \neq 1) = 1/f_{\text{Rum}}$, thus giving the same deviations as Fig. B1 for $\gamma = 0$. If $\gamma \neq 0$, the errors will deviate depending on the specific bearing design.

Appendix C: Extension of the Rumbarger effect for unevenly loaded volume with $\theta > \theta_{\text{crit}}$

For the operational scenario shown in Fig. 4 on the right hand side, the volume may be separated into volumes ψ_1 and ψ_2 each
 685 experiencing one or two stress cycles per half oscillation, with $\psi_1 + \psi_2 = 360^\circ/Z$. The corresponding oscillation amplitudes are given by $\theta_{\psi_1} + \theta_{\psi_2} = \theta_{\text{crit}}$, where $\theta_{\psi_2} = \theta - \theta_{\text{crit}}$. Equation A4 may then be used separately for each of the individual volumes to obtain $L_{\psi_1} = a_{\text{prt},\psi_1} L$ and the overlapping volume ψ_2 experiencing twice as many cycles, giving $L_{\psi_2} = \frac{1}{2} a_{\text{prt},\psi_2} L$. These can be combined via

$$L_{\psi_1+\psi_2} = \left(L_{\psi_1}^{-e} + L_{\psi_2}^{-e} \right)^{-1/e} \quad (\text{C1})$$

$$690 \quad = \underbrace{\left(a_{\text{prt},\psi_1}^{-e} + \left(\frac{1}{2} a_{\text{prt},\psi_2} \right)^{-e} \right)^{-1/e}}_{a_{\text{prt},\psi_1+\psi_2}} L. \quad (\text{C2})$$

This allows for the analysis of the Rumbarger effect for oscillations $\theta > \theta_{\text{crit}}$ with overlapping volumes. Fig. C1 shows an exemplary calculation of $a_{\text{prt},\psi_1+\psi_2}$ for a 7220 type bearing normalized to the Harris factor. The result of $a_{\text{prt},\psi_1+\psi_2}$ can be seen to be almost identical to a_{Harris} .




Figure C1. $a_{\text{prt},\alpha+\beta}/a_{\text{Harris}}$ for the inner ring of a 7220 type bearing for $\theta > \theta_{\text{crit}}$.

Author contributions. OM: Conceptualization, Investigation, Writing - original draft preparation, Data curation, Software, Visualization;
 695 MS: Investigation, Writing - review & editing, Supervision

Competing interests. The authors declare that they have no conflict of interest.

Acknowledgements. This research has been supported by the German Federal Ministry for Economic Affairs and Climate Action, project HAPT2, grant reference number 03EE2033A.

References

- 700 FVA-Nr. 824 I Schwenkbewegungen, final report, FVA-Heft Nr. 1465, 2021.
FVA-Nr. 540 II Stillstehende fettgeschmierte Wälzlager, final report, FVA-Heft Nr. 1268, 2022a.
FVA-Nr. 540 III Stillstehende fettgeschmierte Wälzlager, final report, FVA-Heft Nr. 1494, 2022b.
- ASTM: ASTM E1049-85(2017): Standard Practices for Cycle Counting in Fatigue Analysis, <https://doi.org/10.1520/E1049-85R17>, 2017.
- 705 Bartschat, A., Behnke, K., and Stammler, M.: The effect of site-specific wind conditions and individual pitch control on wear of blade bearings, <https://doi.org/10.5194/wes-2023-51>, 2023.
- Becker, D.: Hoch belastete Großwälzlagerungen in Windenergieanlagen, Dissertation, Clausthal University of Technology, 2011.
- Behnke, K. and Schleich, F.: Exploring Limiting Factors of Wear in Pitch Bearings of Wind Turbines with Real Scale Tests, <https://doi.org/10.5194/wes-2022-96>, 2022.
- Bossanyi, E. A., Fleming, P. A., and Wright, A. D.: Validation of Individual Pitch Control by Field Tests on Two- and Three-Bladed Wind
710 Turbines, *IEEE Transactions on Control Systems Technology*, 21, 1067–1078, <https://doi.org/10.1109/tcst.2013.2258345>, 2013.
- Breslau, G. and Schlecht, B.: A Fatigue Life Model for Roller Bearings in Oscillatory Applications, *Bearing World Journal*, pp. 65–80, <https://d-nb.info/1233208187/34#page=65>, 2020.
- Burton, T., Jenkins, N., Sharpe, D., and Bossanyi, E.: *Wind energy handbook*, Wiley, Chichester, West Sussex, second edition edn., 2011.
- Chen, G. and Wen, J.: Load Performance of Large-Scale Rolling Bearings With Supporting Structure in Wind Turbines, *Journal of Tribology*,
715 134, <https://doi.org/10.1115/1.4007349>, 2012.
- Dang Van, K., Griveau, B., and Message, O.: On a new multiaxial fatigue limit criterion: Theory and application, *Biaxial and multiaxial fatigue*, pp. 479–496, 1989.
- de La Presilla, R., Wandel, S., Stammler, M., Grebe, M., Poll, G., and Glavatskih, S.: Oscillating rolling element bearings: A review of tribotesting and analysis approaches, *Tribology International*, 188, 108 805, <https://doi.org/10.1016/j.triboint.2023.108805>, 2023.
- 720 de Mul, J. M., Kalker, J. J., and Fredriksson, B.: The Contact Between Arbitrarily Curved Bodies of Finite Dimensions, *Journal of Tribology*, 108, 140–148, <https://doi.org/10.1115/1.3261134>, 1986.
- Decker, K.-H.: *Maschinenelemente, Das Fachwissen der Technik*, Hanser, München, 12., überarb.u. erw. Aufl. edn., 1995.
- Dominik, W. K.: Rating and Life Formulas for Tapered Roller Bearings, in: *SAE Technical Paper Series*, SAE Technical Paper Series, SAE International 400 Commonwealth Drive, Warrendale, PA, United States, <https://doi.org/10.4271/841121>, 1984.
- 725 Escalero, M., Olave, M., Behnke, K., and Muñoz-Calvente, M.: iKonPro®: A software for the probabilistic prediction of rolling contact fatigue, in publication, 2023.
- Fatemi, A. and Socie, D.: Multiaxial fatigue: damage mechanisms and life predictions, *Advances in fatigue science and technology*, pp. 877–890, 1989.
- Graßmann, M., Schleich, F., and Stammler, M.: Validation of a finite-element model of a wind turbine blade bearing, *Finite Elements in
730 Analysis and Design*, 221, 103 957, <https://doi.org/10.1016/j.finel.2023.103957>, 2023.
- Grebe, M.: False-Brinelling und Stillstandsmarkierungen bei Wälzlagern: Schäden bei Vibrationsbelastung oder kleinen Schwenkwinkeln, vol. 703. *TAE of Kontakt & Studium*, expert verlag, Renningen, <https://doi.org/3351>, 2017.
- Haberhauer, H. and Bodenstern, F.: *Maschinenelemente: Gestaltung, Berechnung, Anwendung: mit 108 Tabellen*, Springer-Lehrbuch, Springer, Berlin and Heidelberg, 11., vollst. überarb. Aufl. edn., 2001.

- 735 Hai, G. X., Diao, H. X., Jing, H. R., Hua, W., and Jie, C.: A Rolling Contact Fatigue Reliability Evaluation Method and its Application to a Slewing Bearing, *Journal of Tribology*, 134, <https://doi.org/10.1115/1.4005770>, 2012.
- Hamrock, B. J., Schmid, S. R., and Jacobson, B. O.: Fundamentals of fluid film lubrication, vol. 169 of *Mechanical engineering*, Dekker, New York, NY, 2. ed. edn., <http://www.loc.gov/catdir/enhancements/fy0647/2004555403-d.html>, 2004.
- Harris, T., Rumbarger, J. H., and Butterfield, C. P.: Wind Turbine Design Guideline DG03: Yaw and Pitch Rolling Bearing Life, 740 <https://doi.org/10.2172/969722>, 2009.
- Harris, T. A.: Rolling Bearing Analysis, 4th Edition, John Wiley & Sons, Inc., 2001.
- Harris, T. A. and Kotzalas, M. N.: Rolling Bearing Analysis, 5th Edition, Taylor & Francis, Boca Raton, 2007.
- Hertz, H. R.: Über die Berührung fester elastischer Körper und über die Härte, *Verhandlungen des Vereins zur Beförderung des Gewerbefleißes*, pp. 449–463, 1882.
- 745 Houpert, L.: Bearing Life Calculation in Oscillatory Applications©, *Tribology Transactions*, 42, 136–143, <https://doi.org/10.1080/10402009908982200>, 1999.
- Houpert, L. and Menck, O.: Bearing life calculations in rotating and oscillating applications, *Journal of Tribology*, pp. 1–31, <https://doi.org/10.1115/1.4052962>, 2021.
- Hwang, J.-I.: Damage accumulation based fatigue life prediction of rolling bearings, Dissertation, Gottfried Wilhelm Leibniz University 750 Hannover, Hanover, 2023.
- Hwang, J.-I. and Poll, G.: A new approach for the prediction of fatigue life in rolling bearings based on damage accumulation theory considering residual stresses, *Frontiers in Manufacturing Technology*, 2, <https://doi.org/10.3389/fmtec.2022.1010759>, 2022.
- IEC: Wind turbines - Part 1: Design requirements, 2019.
- Ioannides, E., Bergling, E., and Gabelli, A.: An Analytical Formulation for the Life of Rolling Bearings, *Acta Polytechnica Scandinavica*, 755 *Mechanical Engineering Series*, 1999.
- ISO: ISO/TR 1281-1:2008 + Cor. 1:2009: Rolling bearings — Explanatory notes on ISO 281 — Part 1: Basic dynamic load rating and basic rating life , a.
- ISO: ISO/TR 1281-2:2008(E) - Rolling bearings — Explanatory notes on ISO 281 — Part 2: Modified rating life calculation, based on a systems approach to fatigue stresses, b.
- 760 ISO: ISO/TS 16281:2008 + Cor. 1:2009: Rolling bearings – Methods for calculating the modified reference rating life for universally loaded bearings , c.
- ISO: ISO 281:2007: Rolling bearings – Dynamic load ratings and rating life, d.
- Keller, J. and Guo, Y.: Rating of a Pitch Bearing for a 1.5-Megawatt Wind Turbine, <https://doi.org/10.2172/1902646>, 2022.
- Kenworthy, J., Hart, E., Stirling, J., Stock, A., Keller, J., Guo, Y., Brasseur, J., and Evans, R.: Wind turbine main bearing rating lives as 765 determined by IEC 61400–1 and ISO 281: A critical review and exploratory case study, *Wind Energy*, <https://doi.org/10.1002/we.2883>, 2023.
- Leupold, S., Schelenz, R., and Jacobs, G.: Method to determine the local load cycles of a blade bearing using flexible multi-body simulation, *Forschung im Ingenieurwesen*, 85, 211–218, <https://doi.org/10.1007/s10010-021-00457-y>, 2021.
- Liebherr-Components AG: Product Catalogue Slewing Bearings, 2017.
- 770 Londhe, N. D., Arakere, N. K., and Haftka, R. T.: Reevaluation of Rolling Element Bearing Load-Life Equation Based on Fatigue Endurance Data, *Tribology Transactions*, 58, 815–828, <https://doi.org/10.1080/10402004.2015.1021943>, 2015.

- Lopez, A., Zurutuza, A., Olave, M., Portugal, I., Muñiz-Calvente, M., and Fernandez-Canteli, A.: Pitch bearing lifetime prediction considering the effect of pitch control strategy, *Journal of Physics: Conference Series*, 1222, 012017, <https://doi.org/10.1088/1742-6596/1222/1/012017>, 2019.
- 775 Lugt, P. M.: A Review on Grease Lubrication in Rolling Bearings, *Tribology Transactions*, 52, 470–480, <https://doi.org/10.1080/10402000802687940>, 2009.
- Lugt, P. M.: *Grease lubrication in rolling bearings*, John Wiley & Sons, 2012.
- Lundberg, G. and Palmgren, A.: *Dynamic Capacity of Rolling Bearings: Proceedings of the Royal Swedish Academy of Engineering Sciences*, 196, Generalstabens Litografiska Anstalts Förlag, Stockholm, 1947.
- 780 Lundberg, G. and Palmgren, A.: *Dynamic Capacity of Roller Bearings: Proceedings of the Royal Swedish Academy of Engineering Sciences*, 210, Generalstabens Litografiska Anstalts Förlag, Stockholm, 1952.
- Menck, O.: The Finite Segment Method—A Numerical Rolling Contact Fatigue Life Model for Bearings Subjected to Stochastic Operating Conditions, *Journal of Tribology*, 145, <https://doi.org/10.1115/1.4055916>, 2023.
- Menck, O., Stammler, M., and Schleich, F.: Fatigue lifetime calculation of wind turbine blade bearings considering blade-dependent load distribution, *Wind Energy Science*, 5, 1743–1754, <https://doi.org/10.5194/wes-5-1743-2020>, 2020.
- 785 Menck, O., Behnke, K., Stammler, M., Bartschat, A., Schleich, F., and Graßmann, M.: Measurements and modeling of friction torque of wind turbine blade bearings, *Journal of Physics: Conference Series*, 2265, 022087, <https://doi.org/10.1088/1742-6596/2265/2/022087>, 2022.
- Münzing, T.: *Auslegung von Kugelgewindetrieben bei oszillierenden Bewegungen und dynamischer Belastung*, Dissertation, Universität Stuttgart, Stuttgart, <https://doi.org/10.18419/opus-9601>, 2017.
- 790 Potočník, R., Göncz, P., Flašker, J., and Glodež, S.: Fatigue life of double row slewing ball bearing with irregular geometry, *Procedia Engineering*, 2, 1877–1886, <https://doi.org/10.1016/j.proeng.2010.03.202>, 2010.
- Reusner, H.: *Druckflächenbelastung und Oberflächenverschiebung im Wälzkontakt von Rotationskörpern*, 1977.
- Rezaei, A., Guo, Y., Keller, J., and Nejad, A. R.: Effects of wind field characteristics on pitch bearing reliability: a case study of 5 MW reference wind turbine at onshore and offshore sites, *Forschung im Ingenieurwesen*, 87, 321–338, <https://doi.org/10.1007/s10010-023-00654-x>, 2023.
- 795 Roloff, H., Matek, W., and Wittel, H.: *Maschinenelemente: Normung, Berechnung, Gestaltung*, Viewegs Fachbücher der Technik, Vieweg, Braunschweig, 11., durchges. Aufl. edn., 1987.
- Rumbarger, J. H.: Simplification of Dynamic Capacity and Fatigue Life Estimations for Oscillating Rolling Bearings, *Journal of Tribology*, 125, 868–870, <https://doi.org/10.1115/1.1576424>, 2003.
- 800 Rumbarger, J. H. and Jones, A. B.: Dynamic Capacity of Oscillating Rolling Element Bearings, *Journal of Lubrication Technology*, 90, 130–138, <https://doi.org/10.1115/1.3601528>, 1968.
- Sadeghi, F., Jalalahmadi, B., Slack, T. S., Raje, N., and Arakere, N. K.: A Review of Rolling Contact Fatigue, *Journal of Tribology*, 131, <https://doi.org/10.1115/1.3209132>, 2009.
- Schaeffler Technologies AG & Co. KG: *Rolling bearings, Catalogue (HR 1): order number 029679141-0000*, 2019.
- 805 Schmelter, R.: *Über die Lebensdauerberechnung oszillierender Wälzlager*, https://www.imw.tu-clausthal.de/fileadmin/Forschung/InstMitt/2011/_1.Artikel_8_35_rs_Beruecksichtigung_oszillatorischer_Rotation_bei_der_Auslegung_von_Waelzlagern_.pdf, 2011.
- Schwack, F.: *Untersuchungen zum Betriebsverhalten oszillierender Wälzlager am Beispiel von Rotorblattlagern in Windenergieanlagen*, Dissertation, Leibniz University Hannover, <https://doi.org/10.15488/9756>, 2020.

- Schwack, F., Stammler, M., Poll, G., and Reuter, A.: Comparison of Life Calculations for Oscillating Bearings Considering Individual Pitch Control in Wind Turbines, *Journal of Physics: Conference Series*, 753, 112 013, <https://doi.org/10.1088/1742-6596/753/11/112013>, 2016.
- 810 Stammler, M.: Endurance test strategies for pitch bearings of wind turbines, Dissertation, Leibniz University Hannover, <https://doi.org/10.15488/10080>, 2020.
- Stammler, M., Reuter, A., and Poll, G.: Cycle counting of roller bearing oscillations – case study of wind turbine individual pitching system, *Renewable Energy Focus*, 25, 40–47, <https://doi.org/10.1016/j.ref.2018.02.004>, 2018.
- 815 Stammler, M., Thomas, P., Reuter, A., Schwack, F., and Poll, G.: Effect of load reduction mechanisms on loads and blade bearing movements of wind turbines, *Wind Energy*, 23, 274–290, <https://doi.org/10.1002/we.2428>, 2020.
- Tallian, T. E.: Simplified Contact Fatigue Life Prediction Model—Part I: Review of Published Models, *Journal of Tribology*, 114, 207–213, <https://doi.org/10.1115/1.2920875>, 1992.
- Tawressey, J. S. and Shugarts, W. W., Jr.: An Experimental Investigation of the Fatigue Life and Limit Load Characteristics of Needle Roller Bearings Under Oscillating Load Conditions, <https://apps.dtic.mil/sti/citations/AD0437467>, 1964.
- 820 Venner, C. H. and Hagmeijer, R.: Film thickness variations in elasto-hydrodynamically lubricated circular contacts induced by oscillatory entrainment speed conditions, *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 222, 533–547, <https://doi.org/10.1243/13506501JET306>, 2008.
- Wandel, S., Bader, N., Schwack, F., Glodowski, J., Lehnhardt, B., and Poll, G.: Starvation and relubrication mechanisms in grease lubricated oscillating bearings, *Tribology International*, 165, 107 276, <https://doi.org/10.1016/j.triboint.2021.107276>, 2022.
- 825 Weibull, W.: A statistical theory of the strength of materials, *Ingeniörsvetenskapsakademiens handlingar*, 1939.
- Wenske, J., ed.: Wind turbine system design: Volume 1, nacelles, drive trains and verification, vol. 142A of *IET energy engineering series*, The Institution of Engineering and Technology, London and Stevenage, <https://doi.org/10.1049/PBPO142F>, 2022.
- Wöll, L., Jacobs, G., and Kramer, A.: Lifetime Calculation of Irregularly Oscillating Bearings in Offshore Winches, *Modeling, Identification and Control: A Norwegian Research Bulletin*, 39, 61–72, <https://doi.org/10.4173/mic.2018.2.2>, 2018.
- 830 Zaretsky, E. V.: A Palmgren Revisited—A Basis for Bearing Life Prediction: NASA Technical Memorandum 107440, <https://ntrs.nasa.gov/citations/19970025228>, 1997.
- Zaretsky, E. V.: In search of a fatigue limit: A critique of ISO Standard 281: 2007, *Tribology & lubrication technology*, 66, 2010.
- Zaretsky, E. V.: Rolling bearing life prediction, theory, and application: NASA/TP—2013-215305, <https://ntrs.nasa.gov/citations/20160013905>, 2013.
- 835

This document contains replies to all reviewers in blue. Original review comments are black.

Edward Hart

I am very grateful that the authors took the time to address all of my comments thoroughly. I believe the paper is now ready for publication.

Thank you for your comment. We are glad to be in agreement.

Jonathan Keller

In this paper, the authors summarize the literature pertaining to rolling contact fatigue life calculations for oscillating bearings – including many clarifications and filling of gaps. This reviewer’s experience is that the variety of these methods is quite confusing, so having a succinct review of them – especially with a few examples is helpful. The revised paper includes many changes – large and small – that improve the paper’s clarity and presentation quality. Having said that, I still recommend further polishing or clarifications as described below.

Line 14: I believe it would be clearer to say “...and, depending on the site and the yaw system design, larger ($< 10^\circ$ during power production but potentially more while idling) (Wenske, 2022).” I do not believe the phrase at the end beginning with “while they” is needed – unless the point is to specifically state that they are very rarely ever small. If so, it could remain, but I would recommend making it a separate sentence.

The point of the phrase starting with “while they” was indeed to point out that they are rarely ever very small (this might have implications on wear or fatigue mechanisms noted in the paper). Moved into a separate sentence.

Line 35: I believe the reference to FVA should be within parenthesis “...fatigue (FVA 2022 a,b).”

Added parenthesis.

Line 36: Minor grammar change recommended “...both wear and rolling contact fatigue as possible failure mechanisms.”

Changed as suggested.

Line 55: The sentence “There can be grease and oil lubrication present (Hamrock et al., 2004), raceway surface quality and lubrication contamination affects the bearing (Ioannides et al., 1999), and so on” is a bit garbled and still needs some polishing. I’m not sure I understand it to be honest.

The sentence is part of a paragraph that points out commonalities between oscillating and rotating bearings, the intention of this sentence is simply to state that both kinds can be oil- or grease-lubricated and that raceway surface quality and lubrication contamination effects affect both bearings in a similar manner.

Changed to:

In both oscillating and rotating bearings, there can be grease and oil lubrication present (Hamrock et al., 2004), raceway surface quality and lubrication contamination affects the bearing (Ioannides et al., 1999), and so on.

Line 62: I was a bit confused by the wording here. I believe a clearer way to state this is “...only a part of the raceway is ever loaded while the remaining part is always unloaded.” This at least is the concept that I see illustrated in Figure 2 (right).

Changed as suggested.

Line 68: I don’t believe the phrase “...if the bearing is rotated for long enough” is needed. That is, even for a single revolution (at a constant load) every location on the rotating ring experiences the same number of stress cycles, right? I also believe this sentence is really referring only to the rotating ring, instead of “both inner and outer ring”. I may just be plain confused here.

Due to the discrete number of rolling elements in a bearing, for one rotation, not all locations see the same number of stress cycles - Imagine a pure axial bearing (contact angle 90 deg) where the balls move at half the speed of the rotating ring. Rotating the bearing by 360 deg will cause ball movement of 180 deg. If the bearing had, for example, three balls (a didactic example), it is possible to draw on a sheet of paper the ball movements on each ball and one can see that some locations see one load cycle and others two.

Furthermore, the sentence applies to both inner and outer ring because balls are rolling relative to inner and outer ring. The number of load cycles can be different *between* inner and outer ring, but it is identical within all locations of one ring (if one considers load cycles at 0 load as load cycles, too, which is common practice), if the bearing has been turned for long enough.

So the sentence is, in our opinion, correct as written and should remain that way.

Line 85: I'm not sure I understand the sentence "As discussed above, this can cause wear if bad enough, but even if no wear occurs, different lubricant film thickness than in a rotating bearing may be present." Specifically, what "this" and "if bad enough" means. I think it means "if the lubricant film thickness is insufficient for hydrodynamic lubrication".

Changed to "As discussed above, this can cause wear if the lubricant film thickness is bad enough,". We are skeptical about adding the reference to hydrodynamic lubrication because grease lubricated oscillating bearings likely never develop proper hydrodynamic lubrication yet they do not necessarily experience wear. The lubricant film thickness at which the lubricant film is bad enough for wear to occur is not perfectly clear.

Line 158: I think it'd be clearer to say "...sign refers to the outer raceway and the plus (+) sign..."

Changed as suggested.

Line 302: The forces F_a and F_r and moment M are not defined in the paper. In this context, I think the sentence is easily revised without them to "...it is possible to apply Eq. 7 to the force and moment components contributing to P (including applied radial force, axial force, and bending moment) and then determine P_m from a suitable function³⁸ based on their values." I believe this still retains the meaning of the original and is simpler. And/or the sentence could be retained and these forces and moments added to Figure 1 and/or Figure 5.

Changed as suggested.

Line 396 and 400: Since "which approach" is a bit vague at this point in the paper, I recommend a minor grammar change to "...recommendations for selection of a rolling contact fatigue life calculation approach."

Changed as suggested.

Line 486: Similar to Line 302, the moment components M_x and M_y are not defined anywhere. I believe the sentence can be rewritten to "...load direction changes due to the blade weight bending moment as the blade rotates and the blade aerodynamic bending moment that varies with the turbine operating conditions (Menck et al. 2020)." I believe this still retains the meaning of the original and is simpler. And/or the sentence could be retained and these forces and moments added to Figure 1 and/or Figure 5.

Changed as suggested.

Line 524: The "FSM" in the variable name shouldn't be italicized.

Corrected.

Thank you for your comments and corrections.

Yi Guo

The authors have addressed my comments in a satisfactory manner. But there are substantial changes (mainly editorial) that might requires some editorial help from either the journal or author themselves. Experimental validation is still missing and I hope to see that in future publications.

Thank you for your comment. We believe editorial changes will be performed in the process of creating the final paper.