

1 **Effect of scour on the fatigue life of offshore wind turbines and**
2 **its prevention through passive structural control**

3

4 Yu Cao¹, Ningyu Wu², Jigang Yang², Chao Chen^{1,3*}, Ronghua Zhu^{3,4*}, Xugang Hua¹,

5

6 ¹Key Laboratory for Bridge and Wind Engineering of Hunan Province, College of Civil
7 Engineering, Hunan University, Changsha, China

8 ²Hebei Construction Investment Offshore Wind Power Co., Ltd., Tangshan, China

9 ³Yangjiang Offshore Wind Laboratory, Yangjiang, China

10 ⁴Ocean College, Zhejiang University, Hangzhou, China

11

12

13

14

15

*Corresponding author: steinchen@hnu.edu.cn, zhu.richard@zju.edu.cn

16 **Abstract**

17 Offshore wind turbine (OWT) support structures are exposed to the risk of fatigue
18 damage and scour, and this risk can be effectively mitigated by installing structural
19 control devices such as tuned mass dampers (TMDs). However, time-varying scour al-
20 tering OWTs' dynamic characteristics has an impact on the TMD design and fatigue
21 life, which was rarely studied before. In this paper, a simplified modal model is used to
22 investigate the influence of scour and a TMD on the fatigue life evaluation of a 5 MW
23 OWT's support structure, and a traditional method and a newly developed optimization
24 technique are both presented to obtain TMD parameters. This optimization technique
25 aims at finding optimal parameters of the TMD which maximizes the fatigue life of a
26 hotspot at the mudline, and effect of time-varying scour can be considered. This study
27 assumes the TMD operates in the FA direction, and the vibration in the SS direction is
28 uncontrolled. Results show that scour can decrease the fatigue life by about 24.1%, and
29 the TMD can effectively suppress vibration and increase the fatigue life. When the
30 scour depth reaches 1.3 times the pile diameter, the TMD with a mass ratio of 1% can
31 increase the fatigue life of OWT's support structure by about 64.6%. Further, it is found
32 that the fatigue life can be extended by 25% with the TMD optimized by the proposed
33 optimization technique, compared to that with the traditionally optimized TMD which
34 does not take the change of dynamic characteristics into account.

35 **Keywords:** scour, offshore wind turbine, structural control, modal analysis, fatigue life.

36

37 **1 Introduction**

38 With the continuous development of large-size fixed-bottom OWTs, local scour
39 and scour protection of pile foundation have become a common issue (L. Wang et al.,
40 2020; X. Wang et al., 2019; F. Zhang et al., 2022). Scour have a significant impact on
41 dynamic characteristics, vibration magnitudes, and thus fatigue life of OWTs under
42 wind and wave loads. On the one hand, the action of currents and waves causes local
43 scour pits around pile foundations, which reduces the burial depth of pile foundations.
44 This phenomenon usually causes a reduction in natural frequencies of OWTs and
45 changes in other dynamic characteristics, possibly leading to resonance, large ampli-
46 tude stress cycles and fatigue damage when one of natural frequencies is close to the
47 rotational frequency of the blades (Sørensen and Ibsen, 2013). On the other hand,

48 current scour protection measures cannot completely avoid scour and have their own
49 shortcomings. For example, armouring protection has the disadvantages that the pro-
50 jectile cannot be accurately cast in complex sea conditions and is easy to be washed
51 away (G. Wang et al., 2023; F. Zhang et al., 2023). Flow-altering protection has the
52 disadvantages of high cost and changing the dynamic characteristics of the foundation
53 (Tang et al., 2023). As offshore structures, wind turbines are vulnerable to corrosion
54 from seawater, which makes the fatigue problem worse (Amirafshari et al., 2021). Thus,
55 the scour-induced changes in dynamic characteristics and risk in resonance inevitably
56 induce a further increase in fatigue damage and deserve in-depth research (Mayall et
57 al., 2018).

58 Many researchers have studied the effect of scour on fatigue damage accumulation
59 in OWTs. For instance, Tempel et al. (2006) investigated the frequency and fatigue of
60 piles under different scour depths and concluded that scour has a little effect on the
61 natural frequencies but a great effect on fatigue damage. Zhang et al. (2021) found that
62 scour depth has a significant influence on monopile impedance. Rezaei et al. (2018)
63 showed that scour leads to an increase in the maximum bending moment of the mono-
64 pile and a shortening of the fatigue life. To mitigate the fatigue damage in OWTs, in-
65 stalling structural control devices is an effective way. It was demonstrated that TMDs
66 have a positive effect on reducing vibration amplitudes of wind turbine systems (Lack-
67 ner and Rotea, 2011a; Dinh and Basu, 2015; Lu et al., 2023; Aydin et al., 2023). Dai et
68 al. (2021) conducted a shaker experiment using a scaled wind turbine model and
69 showed that the installed TMD can suppress the vibration of the structure more effec-
70 tively considering soil-structure interaction (SSI).

71 In the previously mentioned studies, researchers have individually investigated the
72 effect of scour on structural vibration and fatigue, and the structural control by TMDs
73 for OWTs. However, in practice, the effect of scour combining structural control via
74 TMDs could have a significant impact on OWTs' fatigue life. Moreover, whether con-
75 sidering scour could influence the design of TMDs, and TMDs with different parame-
76 ters can also have an impact on fatigue damage accumulation.

77 The purpose of this study is to explore the effect of scour on the fatigue life of
78 wind turbine structures and the control effect of TMD on the fatigue life of wind turbine
79 structures under scour conditions. The authors use a 5 MW single-pile wind turbine as
80 a case study to carry out related research. In this study, ABAQUS is used to establish a


81 detailed SSI model with different scour depths. A finite element model considering
82 wind loads and TMD was established in MATLAB, and the scour effect is considered
83 by establishing a relationship with the ABAQUS model by means of the equivalent
84 stiffness matrix. And the finite element model is simplified to a modal model for fast
85 prediction of fatigue life. The TMD operates in the FA direction and does not work in
86 the SS direction. This study investigates the effect of different scour depths on the per-
87 formance of the TMD and the fatigue life of a 5 MW OWT's support structure including
88 a tower and a monopile foundation, and the optimization of the TMD's parameters con-
89 sidering time-varying scour depths to maximum fatigue life is also presented. This
90 study provides some knowledge of the effects of the time varying scour and the TMD
91 on the fatigue life of wind turbines, as well as a new TMD design method targeting at
92 enhancing fatigue resistance. The rest of the paper is organized as follows: Section 2
93 introduces the numerical models used in the research. Section 3 introduces the tradi-
94 tional TMD design method and the newly developed parameter optimization method.
95 Section 4 describes the load cases for the fatigue analysis, the analysis results of this
96 study and the TMD parameter optimization results. Section 5 concludes the study.

97 **2 Model description**

98 **2.1 Finite element model and implementation of tuned mass damper**

99 An FE model of a monopile-supported OWT installed with a TMD is established
100 in MATLAB. This model contains a flexible tower, a rotor-nacelle assembly (RNA),
101 and an external TMD, considering the foundation flexibility. The model is based on the
102 widely used NREL 5MW reference OWT, and its detailed properties are shown in Ta-
103 ble 1. Three-dimensional beam elements are used to create the FE model and the theo-
104 retical basis is the standard Euler-Bernoulli beam theory. The wind turbine tower is
105 divided into 18 beam elements, and the monopile between the mudline and the mean
106 sea level (MSL) are divided into 4 beam elements. A convergence test by comparing
107 the first natural frequencies shows that 22 beam elements are sufficient. Each element
108 node has 6 degrees of freedom (DOFs) corresponding to the translational and rotational
109 motions in different directions. The mass matrix and stiffness matrix in the equation of
110 motion of the OWT structure can be obtained given the material properties. The damp-
111 ing matrix is applied by means of Rayleigh damping, and the combined damping ratio
112 of soil damping and structural damping is assumed to be 1% (Chen and Duffour, 2018).
113 The Rayleigh mass and stiffness coefficients α_1 and α_2 are defined by $\alpha_1 = \alpha_2 =$

114 $\frac{\zeta_c}{\frac{1}{2\omega} + \frac{\omega}{2}}$. ω is the natural frequency of the first fore-aft mode, and ζ_c is the combined
 115 damping ratio. The RNA is represented by a lumped mass at the tower top.



116

117 Fig. 1. Schematic of NREL 5MW wind turbine and scour effect

118 The TMD is mounted on the top of the tower, and the effect of the TMD is consid-
 119 ered by adding its mass, damping, and stiffness terms at relevant positions in the local
 120 mass, damping, and stiffness matrices of the beam element representing the tower top.

121 The equation of motion of the OWT main structure is:

$$\begin{aligned} \mathbf{M}_s \ddot{\mathbf{U}}_s + \mathbf{C}_s \dot{\mathbf{U}}_s + \mathbf{K}_s \mathbf{U}_s + \mathbf{C}_T (\dot{\mathbf{U}}_s - \dot{\mathbf{U}}_T) + \mathbf{K}_T (\mathbf{U}_s - \mathbf{U}_T) \\ = \mathbf{F}_{\text{wind}} + \mathbf{F}_{\text{wave}}, \end{aligned} \quad (1)$$

122 where \mathbf{M}_s , \mathbf{C}_s , \mathbf{K}_s are the mass, damping and stiffness matrices of the main structure.

123 \mathbf{C}_T , \mathbf{K}_T are matrices with same dimensions containing c_T , k_T , $\mathbf{C}_T = \begin{bmatrix} 0 & \cdots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \cdots & c_T \end{bmatrix}$, $\mathbf{K}_T =$

124 $\begin{bmatrix} 0 & \cdots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \cdots & k_T \end{bmatrix}$. \mathbf{U}_s is the displacement vector of the main structure, $\mathbf{U}_s = \begin{bmatrix} u_{s-1} \\ \vdots \\ u_{s-top} \end{bmatrix}$.

125 \mathbf{U}_T is the displacement vector containing u_T , $\mathbf{U}_T = \begin{bmatrix} 0 \\ \vdots \\ u_T \end{bmatrix}$. \mathbf{F}_{wind} , \mathbf{F}_{wave} are the aerody-
 126 namic and wave load vectors. The equation of motion for the TMD can be represented
 127 by

$$m_T \ddot{u}_T + c_T (\dot{u}_T - \dot{u}_{s-top}) + k_T (u_T - u_{s-top}) = 0, \quad (2)$$


128 where m_T , c_T , k_T are the mass, damping and stiffness of the TMD, u_T , u_{s-top} are the
 129 displacement of the TMD and the displacement of the top node. The modelling of SSI
 130 is realized by an equivalent stiffness matrix, which will be introduced in detail subse-
 131 quently in Section 2.3.

132 Table 1. Basic properties of the NREL 5MW reference OWT (J. Jonkman et al.,
 133 2009; Rezaei, 2017)

Number of blade	3
Rotor diameter	126 m
Tower length	80 m
Tower diameter	3.87–6.00 m
Tower thickness	28–38 mm
Pile length	75 m
Pile penetration depth	45 m
Pile diameter	6 m
Pile thickness	80 mm
Hub height from MSL	92.4 m
Turbine mass	350000 kg
Blade mass	17740 kg
Rated wind speed	12.1 m/s

134 Wind loads were calculated using modified unsteady blade element momentum
 135 (BEM) theory (Branlard, 2017; B. J. Jonkman and Buhl, 2006) with Prandtl and Glauert
 136 corrections. Ignoring the iterative loop (Chen, Duffour, Fromme, et al., 2021) in the
 137 steady-state BEM code, the instantaneous aerodynamic forces were calculated for each
 138 time step within the time integration. The turbulent wind field was generated using the
 139 Kaimal spectrum according to the wind field parameters of IEC 61400-3 (2019) as-
 140 suming moderate turbulence intensity. It should be noted that the aerodynamic loads

141 from the rotor applied at the tower top were calculated using an aerodynamic force
 142 linearization technique previously developed by authors (Chen, Duffour, Fromme, et
 143 al., 2021; Chen et al., 2020). This technique divides the aerodynamic loads into two
 144 parts. The first part is the quasi-steady aerodynamic force calculated by BEM theory,
 145 which does not consider the influence of tower top motion. The second part considers
 146 the effect of aerodynamic damping by introducing an additional aerodynamic damping
 147 matrix. The adoption of this technique is to enable the development of the simplified
 148 modal model for rapid fatigue calculation, which will be introduced in detail in Sub-
 149 section 2.4. To represent the influence of controller in the OWT, a standard relationship
 150 (J. Jonkman et al., 2009) between the mean wind speed, rotor rotation speed and blade
 151 pitch angles, which represents the OWT's normal operational conditions, are adopted
 152 throughout the wind loading calculation.



153

154

Fig. 2 Schematic of wind turbine load application

155

Wave loads were calculated using the Morison equation, which includes viscous
 156 drag and inertial forces:

$$\mathbf{F}_{\text{wave}} = \frac{1}{2} \rho_w D_{\text{pile}} C_d |\dot{\mathbf{u}}_w| \dot{\mathbf{u}}_w + \frac{\pi}{4} \rho_w D_{\text{pile}}^2 C_m \ddot{\mathbf{u}}_w, \quad (3)$$

157 where $\dot{\mathbf{u}}_w$ and $\ddot{\mathbf{u}}_w$ are the velocity and acceleration of water particles, C_d is the drag
 158 coefficient, D_{pile} is the diameter of the monopile between the mean sea level and the
 159 mudline, C_m is the inertia coefficient and ρ_w is the density of water. C_d and C_m were
 160 chosen as 1 and 2 respectively as the recommended values in Shirzadeh et al (2013).
 161 The wave profiles were obtained through the superposition of wave components, com-
 162 bining linear wave theory and JONSWAP spectra (Klaus et al., 1973). The application
 163 of wind and wave loads is shown in Fig. 2.

164 2.2 Scour modelling in ABAQUS


165 Using solid elements to model pile-soil interaction (S. Dai et al., 2021; Fard et al.,
 166 2022; Ma and Chen, 2021; Zdravković et al., 2015) is usually considered to be more
 167 accurate than the p-y curve method (Liang et al., 2018; Song and Achmus, 2023) and
 168 the equivalent embedding method (Shahmohammadi and Shabakhty, 2020; Bergua et
 169 al., 2022). The solid element method can also reduce the influence of empirical formula
 170 on the results. Therefore, the solid element method is used to establish the wind turbine
 171 scour model. The wind turbine scour model established in ABAQUS contains soil, pile
 172 foundation, tower, and the RNA is replaced by a concentrated mass located at the top
 173 of the tower. The diameter of the soil body is selected as 20 times of the pile diameter,
 174 the soil under the pile foundation is selected as 2.5 times of the pile diameter, and the
 175 total height of the soil body is 60 m. The soil body is made of homogeneous dense
 176 sandy soil, and the piles and tower are made of steel. The material parameters of the
 177 soil body, pile and tower are shown in Table 2 below:

178 Table 2. Soil, pile and tower material parameters

Type	Weight γ (kN/m ³)	modulus of elasticity E_S (MPa)	Poisson's ratio ν	Internal friction angle φ (°)	Expansion angle ψ (°)	Cohesion c (kPa)
Soil	19	80	0.3	35	23	0.1
Pile	78.5	215	0.25	-	-	-
Tower	85	215	0.25	-	-	-

179 The Mohr-Coulomb model is used for the soil, and the pile, tower, and nacelle are
 180 assumed to be elastic as they are much stiffer than the soil and do not deform plastically
 181 for the normal operational conditions. The pile and tower are connected by a binding
 182 relationship. The normal contact between the pile and soil adopts the hard contact, and
 183 the tangential contact adopts the friction penalty function. The relative sliding friction

184 factor at the interface, μ is equal to $\tan(0.75 \varphi)$, where φ is the internal friction angle.
185 The pile-soil contact is in the form of frictional contact, where mutual contact pairs are
186 established between the pile and the soil, including the contacts between the pile bottom
187 surface and the soil, between the outside surface of the pile and the soil, and the inside
188 surface of the pile and the soil core. The frictional contact between pile bottom surface
189 and soil is omitted due to the small area of the contact surface. These frictional contacts
190 all adopt the face-to-face contact, and the contact discretization method adopts the face-
191 to-face discretization method, considering the large stiffness of the main surface and
192 small stiffness of the slave surface. The perimeter of the soil body is translationally
193 constrained, and the bottom surface of the soil adopts a fixed constraint. The eight-node
194 linear brick element (C3D8R) is used to model the pile and soil, and the mesh division
195 is realized by arranging seeds as shown in Fig. 2. The whole model is set up by adopting
196 the modelling method of “element birth and death”, which realizes the operation of
197 initial soil stress balance and sets up contacts and other related steps by killing and
198 activating relevant elements.



199

200 Fig. 3. Pile-soil interaction modelled by ABAQUS


201 The scour conditions can be represented by a deep conical pit around the pile under
202 the long-term action of the waves and currents. According to the specification of Det
203 Norske Veritas (DNV) (2014b), the radius of the pit surface formed by scour, R , can
204 be related to the depth of the scour pit by

$$R = \frac{D}{2} + \frac{S}{\tan\varphi}, \quad (4)$$

205 where D is the diameter of the pile, S is the scour depth, and φ is the angle of internal
 206 friction of the soil.

207 2.3 Equivalent stiffness matrix method

208 It is necessary to consider the effect of scour in the FE model in MATLAB. An
 209 equivalent stiffness matrix method is adopted in the FE model to consider the flexibility
 210 induced by SSI. The 6 DOFs of node at the mudline are assumed to be constrained by
 211 a series of coupled springs, and the stiffnesses of the coupled springs form a 6×6 stiff-
 212 ness matrix. For one specific stiffness term used in the FE model, for instance the one
 213 relevant to the lateral displacement in the fore-aft (FA) direction, the value of the stiff-
 214 ness term can be found from the relationship between the reaction force at the mudline
 215 and the pile top displacement (Jung et al., 2015). The equivalent stiffness schematic of
 216 the pile-soil interaction in the FA direction for the OWT is shown in Fig. 4.



217

218 Fig. 4. Equivalent stiffness schematic of pile-soil interaction in the FA direction

219 According to the principle of virtual displacement and with the DOFs in the other
 220 directions constrained, a unit displacement or rotation was first applied in one direction,
 221 and then the reaction force in that direction can be known. The equivalent stiffness in
 222 that direction can be subsequently calculated by the relationship between the displace-
 223 ment and reaction force. Using the same approach, the stiffness terms corresponding to
 224 the remaining five DOFs were calculated. The stiffness terms in all the six DOFs to-
 225 gether form all the diagonal terms of the soil stiffness matrix. With the diagonal terms
 226 known, the off-diagonal stiffness terms can be found by applying a unit displacement
 227 in one direction and looking at the reaction force in the other concerned direction, with
 228 the other four DOFs constrained. Using the same principle, the off-diagonal terms can
 229 also be found from the relationship between the displacements and reaction forces,

230 which ultimately results in a 6×6 stiffness matrix (Bergua et al., 2021; Pedersen and
 231 Askheim, 2021):

$$\mathbf{F}_{\text{soil}} = \begin{Bmatrix} F_x(t) \\ F_y(t) \\ F_z(t) \\ M_x(t) \\ M_y(t) \\ M_z(t) \end{Bmatrix} = \begin{bmatrix} k_{xx} & 0 & 0 & 0 & k_{x\theta y} & 0 \\ 0 & k_{yy} & 0 & k_{y\theta x} & 0 & 0 \\ 0 & 0 & k_{zz} & 0 & 0 & 0 \\ 0 & k_{\theta xy} & 0 & k_{\theta x\theta x} & 0 & 0 \\ k_{\theta yx} & 0 & 0 & 0 & k_{\theta y\theta y} & 0 \\ 0 & 0 & 0 & 0 & 0 & k_{\theta z\theta z} \end{bmatrix} \begin{Bmatrix} u_x(t) \\ u_y(t) \\ u_z(t) \\ \theta_x(t) \\ \theta_y(t) \\ \theta_z(t) \end{Bmatrix} \quad (5)$$

$$= \mathbf{K}_{\text{soil}} \mathbf{u}_{\text{soil}},$$

232 where \mathbf{K}_{soil} is the equivalent soil stiffness matrix, \mathbf{u}_{soil} is the displacement vector, and
 233 \mathbf{F}_{soil} is the reaction force vector. **The equivalent soil stiffness matrix ignores the nonlin-**
 234 **earity in the force-displacement relationship. This approach is suitable for fatigue anal-**
 235 **ysis, as in normal operation conditions the deformation of the soil around the monopile**
 236 **is relatively small and the nonlinearity in soil stiffness is very weak.** The 6×6 soil stiff-
 237 ness matrix obtained from ABAQUS is imported to the FE model in MATLAB. This
 238 modelling method possesses the advantages of the increase in accuracy brought by the
 239 scour model in ABAQUS with solid elements, and the fast calculation speed and con-
 240 venience in applying wind and wave loads brought by the usage of the FE model in
 241 MATLAB.

242 2.4 Rapid fatigue evaluation method

243 The established FE model in MATLAB can generate dynamic responses of the
 244 OWT, considering wind and wave loads and scour effect. However, a comprehensive
 245 fatigue life prediction in time domain needs to consider a large number of environmen-
 246 tal states and load cases, so simulation efficiency is very important. Moreover, the TMD
 247 design optimization requires much more dynamic response time series. The FE model
 248 is not fast enough in this case. Therefore, a simplified modal model is developed from
 249 the FE model in MATLAB following the method develop in Ref. (C .Chen et al., 2021).
 250 The total aerodynamic forces from the rotor applied on the tower top node are linearized
 251 to the sum of a term corresponding to the forces for an assumed rigid tower, plus a term
 252 proportional to the tower top linear and angular velocities. The hydrodynamic forces
 253 are linearized by ignoring the relatively small monopile vibrations. The details for force
 254 linearization can be found in the authors' previous studies (Chen, Duffour, Fromme, et
 255 al., 2021). Since the dynamic responses of the OWT are mainly dominated by the first

256 two bending vibration modes, the FE model is reduced into a 4-DOF simplified modal
 257 model by considering only the first two bending modes in the FA and side-side (SS)
 258 directions respectively. The development of the simplified 4-DOF modal model is
 259 briefly introduced as follows. Denoting the mass matrix and stiffness matrix of the
 260 OWT as \mathbf{M} and \mathbf{K} including the TMD and the lumped soil stiffness matrix, the un-
 261 damped vibration mode matrix $\mathbf{\Psi}$ can be obtained directly through eigen analysis. Ac-
 262 cording to relationship $\mathbf{u} = \mathbf{\Psi}\alpha$ and multiplying the transpose of the undamped vibra-
 263 tion matrix $\mathbf{\Psi}^T$ with the equation of motion, the following equation is obtained:

$$\mathbf{\Psi}^T \mathbf{M} \mathbf{\Psi} \ddot{\alpha} + \mathbf{\Psi}^T \mathbf{C} \mathbf{\Psi} \dot{\alpha} + \mathbf{\Psi}^T \mathbf{K} \mathbf{\Psi} \alpha = \mathbf{\Psi}^T \mathbf{F}. \quad (6)$$

264 Then rewrite the above equation as

$$\bar{\mathbf{M}} \ddot{\alpha} + \bar{\mathbf{C}} \dot{\alpha} + \bar{\mathbf{K}} \alpha = \bar{\mathbf{F}}, \quad (7)$$

265 where α is the general coordinate vector, $\bar{\mathbf{M}}$ is the modal mass matrix, $\bar{\mathbf{C}}$ is the modal
 266 damping matrix, $\bar{\mathbf{K}}$ is the modal stiffness matrix, $\bar{\mathbf{F}}$ the modal load matrix. Truncating
 267 Eq. (6) by only considering the first two bending modes, the FE model is reduced to a
 268 4-DOF modal model, which can be used for a rapid fatigue analysis. The dynamic re-
 269 sponses of the OWT can be obtained by modal superposition after solving the general
 270 coordinate vector by time integration. In the 4-DOF simplified modal model, the cross-
 271 section stress at any height can be calculated from the calculated node displacements.
 272 According to the dynamic stress extraction method provided by Pelayo et al. (Pelayo et
 273 al., 2015), the cross-section stress $\sigma_z(t)$ at any moment at a given location can be ob-
 274 tained by:

$$\sigma_z(t) = -E(\mathbf{N}^{e''}(z)\mathbf{u}_x^e(t)x + \mathbf{N}^{e''}(z)\mathbf{u}_y^e(t)y), \quad (8)$$

275 where \mathbf{u}^e is the nodal displacement vector at the cross section, E is the material elastic
 276 modulus, and \mathbf{N}^e is the elemental shape function vector of FE model, x and y are the
 277 positions within the section at the height z of the tower. After cyclic counting the stress
 278 time series using the rainfall counting method, the fatigue damage at the hotspot can be
 279 evaluated by utilizing the Palmgren-Miner rule based on the S-N fatigue calculation
 280 method. The S-N curve for steel under water can be obtained by the following equation
 281 considering the thickness effect in DNV (2014a):

$$\log N = \log \bar{a} - m \cdot \log \left[\Delta \sigma \left(\frac{t}{t_{\text{ref}}} \right)^k \right], \quad (9)$$

282 where N is the number of cycles to failure, $\Delta \sigma$ is the stress range. $\Delta \sigma$ is calculated from
 283 the nominal stress $\Delta \sigma_{\text{nominal}}$ by the equation $\Delta \sigma = \text{SCF} \cdot \Delta \sigma_{\text{nominal}}$, SCF is the stress
 284 concentration factor. m is the negative inverse slope of the S-N curve, and $\log \bar{a}$ is the
 285 intercept between the $\log N$ axis and the S-N curve, t_{ref} is the reference thickness for
 286 welded joints, t is the thickness at which cracks may grow. **And $t = t_{\text{ref}}$ is used for**
 287 **thickness less than t_{ref} . When t is larger than t_{ref} , t is the actual thickness of the pile.** k
 288 is the thickness exponent of fatigue strength. For pile joints, $t_{\text{ref}} = 25\text{mm}$. According
 289 to the DNV code, a bilinear S-N curve is usually used for offshore structures subjected
 290 mainly to typical wind and wave loads, using the Class E structural detail S-N curve
 291 shown in Table 3.

292 Table 3 Class E structural detail S-N curves

$N \leq 10^6$		$N \geq 10^6$		k	t (mm)	SCF
m_1	$\log \bar{a}_1$	m_2	$\log \bar{a}_2$			
3.0	11.610	5.0	15.350	0.2	80	1.13

293 For variable amplitude stresses, the fatigue damage index is calculated using the
 294 Palmgren-Miner summation rule:

$$D_k = \sum_{i=1}^{N_c} \frac{n_i}{N_i}, \quad (10)$$


295 where N_c is the total number of bins, n_i is the number of cycles in i^{th} stress bin, N_i is
 296 the number of cycles to failure for the i^{th} stress range, and D_k is the total fatigue dam-
 297 age index. **The “rainflow” function in MATLAB is adopted for rainflow counting.**
 298 **When a stress time history is given, this function can automatically obtain the i^{th} stress**
 299 **range and the corresponding cycle number n_i , and N_c is the total number of stress**
 300 **ranges.** Fatigue failure occurs at the hotspot when the fatigue damage index reaches
 301 unit 1.

302 3 Damper design and optimisation method

303 Installing damping devices can efficiently reduce the vibration amplitudes of
 304 OWTs so that their service life can be greatly prolonged. Using TMDs as passive

305 control devices is most widely used to control the vibration of OWT support structures.
 306 Usually, most of TMDs are designed according to the dynamic characteristics of the
 307 OWTs determined in the preliminary design stage, without considering the changes in
 308 dynamic properties possibly caused by scour and soil degradation. However, in the real
 309 environment, scour can cause the dynamic characteristics of OWTs to change, which
 310 perhaps makes installed dampers become less effective or even completely ineffective.
 311 Therefore, it is a great significance to consider the change in dynamic properties caused
 312 by scour on the TMD design. The following two subsections first introduce the tradi-
 313 tional TMD design method considering constant dynamic characteristic in the initial
 314 state, and then an optimal parameter searching method for the design of TMDs is pre-
 315 sented considering the effect of scour and fatigue life evaluation.

316 3.1 TMD design in initial state



317

318 Fig. 5. Schematic diagram of TMD arrangement in the tower tube

319 As the dominant vibration mode of the OWT structure in operation is the first
 320 bending mode, the largest vibration amplitude occurs at the tower top and installing the
 321 TMD at the tower top is most effective. Therefore, the TMD is installed inside the steel
 322 tube at the tower top to mainly control the vibration in the FA direction, as shown in
 323 Fig. 5. **And the TMD can be aligned with the FA direction by rotating the damper.**
 324 Accordingly, the initial design of the TMD is mainly carried out based on the dynamic
 325 properties for the first-order mode. The initial design is conduct based on the assump-
 326 tion that the monopile foundation is not scoured.

327 Numerous studies have shown that a TMD can effectively suppress the vibration
328 of a main structure when the mass ratio of the TMDs to the main structure is 1%-2%
329 (Lackner and Rotea, 2011b; R. Zhang et al., 2019). After determining the mass ratio of
330 the TMD to the OWT structure, according to the classic TMD optimization theory
331 proposed by Den Hartog (1957), the optimal frequency ratio of the TMD to the OWT
332 structure is

$$\alpha_{\text{opt}} = \frac{1}{1 + \mu}. \quad (11)$$

333 The optimal damping ratio for the TMD can be calculated by

$$\xi_{\text{opt}} = \sqrt{\frac{3\mu}{8(1 + \mu)}}, \quad (12)$$


334 where μ is the mass ratio of the TMD to the OWT structure, α_{opt} is the optimal fre-
335 quency ratio of the TMD to the OWT structure and ξ_{opt} is the optimal damping ratio
336 of the TMD.

337 Considering that excessive mass will lead to increased construction costs and dif-
338 ficulties and changes in the inherent characteristics of the original structure, the mass
339 ratio of the TMD system to the main structure is first selected to be 1%. Moreover,
340 previous studies have found that TLCD with a mass ratio of 1% and TMD with a mass
341 ratio of 2% can effectively suppress vibration (Colwell and Basu, 2009; Lackner and
342 Rotea, 2011b; R. Zhang et al., 2019). According to Den Hartog's optimization theory
343 for the initial TMD design, it can be determined that the optimal frequency ratio of the
344 TMD to the main structure is 0.99, and the optimal damping ratio of the TMD is 0.061.
345 When the OWT support structure is not scoured, the first-order modal mass of the struc-
346 ture is 440350 kg, and the first-order modal frequency is 0.265 Hz. Therefore, accord-
347 ing to the initial design parameters, the mass, stiffness coefficient and damping coeffi-
348 cient of the TMD system are 4403.5 kg, 11,952 N/m and 885 Ns/m respectively.

349 3.2 Fatigue-based damper optimisation technique

350 After scour occurs around the monopile foundation, the burial depth of the mono-
351 pile and natural frequencies of the OWT gradually change. The vibration mitigation
352 effect of the TMD designed based on the dynamic parameters in the initial state can be

353 reduced, which may lead to the increase of fatigue damage of the OWT support struc-
 354 ture. Therefore, when designing the TMD, considering the influence of the time-vary-
 355 ing scour can enhance the performance of the TMD and thus result in a longer fatigue
 356 life of the support structure.



357

358

Fig. 6. Flowchart of TMD fatigue-life-based optimization technique

359

360

361

362

363

364

365

366

367

368

369

370

371

Here a fatigue-life-based optimization technique (FOT) to find optimal parameters of the TMD is developed in MATLAB as shown in Fig. 8. In this technique, the frequency ratio, mass ratio and damping ratio of the TMD are set as the optimal parameters to search, and the fatigue life is the optimization objective. When considering the time-varying scour process, the time-varying scour depth curve is first divided into a number of scour depths with an increment of 0.1d. For each scour depth, the fatigue damage is calculated respectively and then the total fatigue damage in a particular duration can be summarised. When the scour pit becomes deeper, the fatigue damage accumulates and finally reaches unit 1 which denotes the end of fatigue life. The simplified 4-DOF modal model incorporating scour modelling is used to generate the stress time series. The optimization problem is formed so that the optimal parameters of the TMD correspond to the longest fatigue life of the OWT support structure. The GlobalSearch function in MATLAB was used to solve the optimization problem. In the TMD optimization

372 process, the mass ratio of TMD is first set to 1%, and only the parameter frequency
 373 ratio and damping ratio are optimized. Subsequently, in order to understand the optimi-
 374 zation effect of TMD when the value of TMD mass ratio is not fixed, a mass ratio
 375 optimization interval is given, so the mass ratio becomes a variable within the optimi-
 376 zation interval.

377 4 Results

378 4.1 Environmental states and load cases

379 In this study, fatigue analyses are performed under 22 environmental states pro-
 380 vided by Tempel (2006), taking into account both operational and parked conditions.
 381 These 22 environmental states are shown in Table 4. **In operating conditions, the wind**
 382 **turbine bears the aerodynamic load of the rotating rotor and the wind load of the tower,**
 383 **and the wind load on the rotor is calculated using the BEM theory. In parked conditions,**
 384 **the wind turbine mainly bears the aerodynamic load on the tower, and the aerodynamic**
 385 **damping is very small. The aerodynamic loading on the blades is calculated by directly**
 386 **looking at the aerodynamic loading coefficient table given the local attack angles.** The
 387 wind and wave loads are assumed to be always in the same direction to simplify the
 388 analysis. When the mean wind speeds are above the cut-in wind speed and below the
 389 cut-out wind speed, a 95% wind turbine availability is assumed following the setting
 390 in Ref (Velarde et al., 2020), meaning that the OWT does not produce power for 5%
 391 when the mean wind speeds are in the operating range. For a particular set of mean
 392 wind speed, wave period and wave height, six different random seed numbers are used
 393 to generate different wind fields and wave profiles to reduce the influence of random-
 394 ness. To obtain the stress time histories at the mudline, a 700s simulation for each ran-
 395 dom seed was conducted and the response in the first 100 seconds was deducted to
 396 eliminate the effect of initial transient vibration. (Capaldo and Mella, 2023; Stieng and
 397 Muskulus, 2020).

398 Table 4. Environmental states, adopted from Tempel (van der Tempel, 2006).

State	V _w (m/s)	T _z (s)	H _s (m)	P _{State} (%)	State	V _w (m/s)	T _z (s)	H _s (m)	P _{State} (%)
1	4	3	0.5	3.95	12	14	5	2	3.26
2	4	4	0.5	3.21	13	16	4	2	1.79
3	6	3	0.5	11.17	14	16	5	2.5	3.1
4	6	4	0.5	7.22	15	18	5	2.5	1.74

5	8	3	0.5	11.45	16	18	5	3	0.8
6	8	4	1	8.68	17	20	5	2.5	0.43
7	10	3	0.5	5.31	18	20	5	3	1.14
8	10	4	1	11.33	19	22	5	3	0.4
9	12	4	1	5.86	20	22	6	4	0.29
10	12	4	1.5	6	21	24	5	3.5	0.15
11	14	4	1.5	4.48	22	24	6	4	0.1

399 In Table 4, V_w is the wind speed, T_z is the zero-crossing wave period, H_s is the
400 wave height, and P_{state} is the probability of environmental state. To investigate the ef-
401 fect of scour and installation of the TMD on the fatigue damage accumulation, six load
402 cases (LCs) are selected as shown in Table 5. LC 1 is used as the reference case, and
403 other cases are distinguished by different scour and TMD settings. For LC 4 to LC 6,
404 the initial design of the TMD with the mass ratio of 1% is used.

405

Table 5. Load case definition

LC number	TMD condition	Scour condition	LC number	TMD condition	Scour condition
LC 1	No	No Scour	LC 4	Enable	No Scour
LC 2	No	Time-varying	LC 5	Enable	Time-varying
LC 3	No	Maximum	LC 6	Enable	Maximum

406 When considering the time-varying scour depth, for a particular time t , the time-
407 varying scour depth S can be predicted by the equation provided by Nakagawa et al.
408 (1976):


$$S = \left(\frac{t}{t_1}\right)^{0.22} D, \quad (13)$$

409 where D is the diameter of the monopile, t_1 is the reference time and can be calculated
410 by

$$t_1 = 29.2 \cdot \frac{D}{\sqrt{2} \cdot u} \cdot \left(\frac{\sqrt{\Delta \cdot g \cdot d_{50}}}{\sqrt{2} \cdot u - u_c}\right)^3 \cdot \left(\frac{D}{d_{50}}\right)^{1.9}. \quad (14)$$

411 u is the tidal velocity and taken as 0.5 m/s, u_c is the critical shear velocity and taken as
412 0.37 m/s, g is the acceleration of gravity and taken as 9.8 m/s², d_{50} is grain size of sea
413 sand and taken as 0.2 mm. The parameter $\Delta = \frac{\rho_s}{\rho_w} - 1$, where ρ_s is density of sand and
414 taken as 2.65 g/cm³, ρ_w is density of water and taken as 1 g/cm³. Rudolph et al.

415 (Rudolph et al., 2016) provided the sea state and measured the scour depth for the North
 416 Sea where the monopile N7 is located. The measured scour depth was fitted well for
 417 the first five years based on the time-varying scour depth prediction equation shown in
 418 Eq. (13). Therefore, the data from the North Sea site can represent a typical ocean en-
 419 vironment with time-varying scour and is used for the correlation analysis in this study.



420


421 Fig. 7. Time-varying scour depth curve for pile N7 in the North Sea

422 When conducting analysis with the time-varying scour, an increment of scour
 423 depth equal to $0.1D$ is used. At one particular scour depth, the fatigue damage is calcu-
 424 lated and then the total fatigue damage during a longer period with a changing scour
 425 depth can be obtained by damage accumulation. According to the specification of DNV,
 426 the maximum depth of a local scour pit formed around a pile foundation is 1.3 times
 427 the diameter of the pile. Therefore, it is assumed that the local scour pit has a maximum
 428 scour depth of $1.3D$ at which the scour process achieves equilibrium.

429 4.2 Scour influence on natural frequencies

430 The scour of the soil around the monopile has an important effect on the natural
 431 frequencies of the OWT. For different scour depths, the first natural frequencies ob-
 432 tained the by the models in ABAQUS and MATLAB are compared in Fig. 8. It shows
 433 the increase in the scour depth leads to a decrease in the first natural frequency of the
 434 OWT. The first natural frequency is 0.265 Hz when no scour occurs, and the natural
 435 frequency is reduced to 0.248 Hz when the depth of the scour pit reaches the maximum
 436 depth. The first natural frequency is reduced by 6.42% due to the maximum scour depth.
 437 It shows that the natural frequency nearly monotonically decreases with the increase of
 438 the scour depth. The installation of TMD also influences the natural frequency of the
 439 OWT main structure. The TMD with a mass ratio of 1% makes the first natural


440 frequency of the OWT main structure reduces to 0.251 Hz when no scour occurs, mean-
441 ing that the natural frequency is reduced by 5.28%.



442

443 Fig. 8. Relationship between wind turbine natural frequency and scour depth

444 In the TMD design process, the feasible displacement should be considered. The
445 smaller the mass ratio of TMD is, the larger the feasible displacement is required. The
446 22nd environmental state corresponds to the greatest vibration responses of the wind
447 turbine tower top due to large wind speed variations and lower aerodynamic damping,
448 and the stroke of the TMD could be the largest. As shown in the Fig. 9, the relative
449 displacement between the TMD and the tower top is much less than the inner diameter
450 of the wind turbine tower top in the 22nd environmental state. It shows that the stroke
451 of the TMD is sufficient when the mass ratio of TMD is 1%.




452

453 Fig. 9 Displacement of tower top and TMD under the 22nd environmental state

454 4.3 Dynamic response analysis


455 When the OWT in the operating state is under the 9th environmental state which
456 corresponds to the rated wind speed of 12 m/s, a comparison for the tower top displacements
457 is made for LC 1, LC 3, LC 4 and LC 6, as shown in Fig. 10. These displacements

458 are obtained from the FE model in MATLAB described in Subsection 2.1. By compar-
 459 ing the displacements from 300 seconds to 420 seconds for LC 1 and LC 4, it can be
 460 found that the displacement amplitudes of the tower top decreases when the TMD is
 461 installed. It is known that the aerodynamic damping is large when the OWT is operating
 462 under the rated wind speed, so it is normal that the vibration mitigation effect of the
 463 TMD is less significant in this case.



464

465 Fig. 10. Dynamic response of wind turbine under wind-wave coupled loads for four
 466 operating conditions



467


468 Fig. 11 The displacement response of wind turbine tower under the parked condition
 469 with 3 m/s wind speed

470 The effect of the TMD is more prominent for parked conditions with less aerody-
 471 namic damping. As shown in the Fig. 11, the vibration mitigation effect of the TMD is
 472 more significant under the parked condition with 3 m/s wind speed. Moreover, by com-
 473 paring the displacement responses for LC 1 and LC 3, it can be found that the average
 474 of the displacement at the tower top increases when the scour depth reaches 1.3D. This
 475 is because scour makes the OWT support structure become more flexible.

476 4.4 Fatigue calculation results

477 In Subsection 2.4, it is mentioned that in the process of fatigue life analysis, the 4-
 478 DOF simplified modal model is used to greatly save the calculation time. The accuracy
 479 test of the 4-DOF modal model in generating dynamic responses is first present in this
 480 subsection. Under the turbulent wind field with a turbulence intensity of 11.9% and an
 481 average wind speed of 12 m/s, the FE model and the 4-DOF simplified modal model
 482 are used to calculate the stress responses at the mudline for 10 minutes.


483 As shown in Fig. 12, the stress responses from these two models are very close,
 484 confirming good accuracy of the 4-DOF modal model. The fatigue damage caused by
 485 the FE model in 10 min is 2.108×10^{-7} , and the fatigue damage caused by the 4-DOF
 486 model in 10 min is 2.1×10^{-7} , with an error of 0.05%. Moreover, the calculation time
 487 of the 4-DOF simplified modal model is only about 1/55 of that of the FE model, which
 488 shows that the 4-DOF simplified modal model is adequate to replace the FE model
 489 when conducting fatigue life prediction.



490 Fig. 12. Comparison of stresses at the mudline from the FE model and the 4-DOF
 491 model in time domain (a) and frequency domain (b)

492 The 4-DOF simplified modal model is used to conduct fatigue life prediction for
493 the OWT support structure under LC 1 to LC 6. A 10 min simulation for each random
494 seed of six different random seed numbers conducted to obtain the stress time histo-
495 ries at the mudline. The location of the hotspot used to evaluate fatigue damage is se-
496 lected at the point where the maximum stress is reached, and this point is in the support
497 structure cross section at the mudline. Although the location in the monopile where the
498 moment reaches its maximum value can be below the mudline, the location at the mud-
499 line is picked for simplicity. Further, as the SSI is modelled in the FE model by an
500 equivalent soil stiffness matrix, it is unstraightforward to obtain the internal forces at
501 the cross sections below the mudline. Given the stress time series at the selected hotspot,
502 the corresponding fatigue damage is calculated. Then the fatigue damage for the set of
503 mean wind speed, wave period and wave height in 10 min is obtained by averaging the
504 fatigue damage for all the six random seeds. For all the 22 environment states, the 10
505 min fatigue damage are calculated, and the fatigue life is predicted according to
506 Palmgren-Miner sum rule by combing these calculated fatigue damage and the occur-
507 rence probabilities of the environmental states.

508 For different scour depths, the fatigue life of the OWT considering both operating
509 and parked conditions is predicted with or without TMD installation, and the results are
510 shown in Fig. 13. It is shown that an increase in scour depth leads to a decrease in
511 fatigue life, and an increasing fatigue life reduction rate can be observed when the scour
512 depth increases. When no scour occurs and the TMD is not installed on the OWT, the
513 OWT's fatigue life is 59.3 years, and the fatigue life drops to 45.0 years when consid-
514 ering the maximum scour depth of 1.3 D. There exist some uncertainties in the fatigue
515 life prediction process due to the generation of random wind field and wave profile. It
516 should be noted that the predicted fatigue life is much longer than the normally adopted
517 OWTs' design fatigue life of 25-30 years. This can be explained by the following rea-
518 sons. First, the maximum moment of the OWT support structure is not at the cross
519 section at the mudline where the selected hotspot is located. Second, the complex wind
520 and wave directionality during the OWT's lifetime is simplified, which would influence
521 the fatigue calculation result. Third, many other operation conditions such as starting
522 up, shutting down phases are not considered in this study, which can also have an im-
523 pact on the fatigue damage accumulation. Moreover, the installation of the TMD greatly
524 extends about 51.8% of the OWT support structure's fatigue life.



525

526

Fig. 13. Fatigue life of wind turbine with different scour depths

527

528

529

530

531

532

533

534

535

536


537

538

539

The fatigue life prediction results of the OWT were obtained for all the six LCs, as shown in Fig. 14. The fatigue life from the reference case LC 1, 59.3 years, is regarded as the reference fatigue life. It shows that the fatigue life decreases by 14.3 years, or about 24.1%, when the scour depth is set as the maximum value of 1.3D without applying the TMD, compared to the reference fatigue life. When considering the time-varying scour, the fatigue life decreases by about 22.1% from the reference value. When comparing the results for LC 1 and LC 4, it shows the installation of the TMD results in a significant increase in the fatigue life of the OWT, with an increase in fatigue life of about 30.7 years, which is about 51.8%. In LCs with the TMD installed, the fatigue life in LC 6 decreases by about 17.7% when the scour depth reaches 1.3 D, compared to the result in LC 4. But the fatigue life in LC 6 is still 1.25 times of the reference fatigue life, which indicates that the imposition of TMD can effectively increase the fatigue life of the OWT by reducing vibration amplitudes.

540



541

Fig. 14. Fatigue life of the wind turbine under six operating conditions

542 **4.5 Fatigue calculation with optimized TMD**

543 To compare the optimization effect and speed up the optimal parameter search
 544 process, the mass ratio of TMD is first kept as 1%. Before the optimization, the param-
 545 eter ranges of the frequency ratio and damping ratio need to be defined. The optimal
 546 frequency of the TMD is usually close to the resonance frequency of the main structure,
 547 so the range of the frequency ratio was chosen to be from 0.8 to 1.1 for optimization.
 548 As the optimal damping ratio could vary in a relatively larger range, the range of the
 549 damping ratio for optimization is chosen to be from 1% to 30%. The optimization of
 550 the TMD is also conducted with the mass ratio not fixed. A range of the mass ratio from
 551 0.001 to 0.1 is used to optimize the TMD so that the influence of the mass ratio can be
 552 evaluated.

553 Table 6. Optimization of TMD parameters

Optimization method	Mass ratio range	Time-varying scour	Optimal mass ratio	Optimal frequency ratio	Optimal damping ratio	Fatigue life (Year)
Initial (LC 5)	0.01	Use	0.01	0.99	0.061	74.6
FOT	0.01	Use	0.01	0.94	0.050	93.2
FOT	0.001-0.1	Use	0.097	0.92	0.150	133.2

554 The optimal parameters obtained by FOT as well as the predicted fatigue life are
 555 listed in Table 6. The fatigue life for LC 5 and the parameters of the initially designed
 556 TMD are also shown in Table 6 for comparison. It shows that when the mass ratio is
 557 fixed at 1%, the optimal frequency ratio is 0.94, the optimal damping ratio is 5%, and
 558 the final fatigue life is 93.2 years. Compared to the fatigue life with initially optimized
 559 TMD using the traditional method without considering scour, the fatigue life is in-
 560 creased by 18.6 years or about 25%. It indicates that the parameter search in the opti-
 561 mization process is correct and it is better to use the TMD parameter search method to
 562 design the TMD after obtaining the time-varying scour curve. When the mass ratio
 563 range is taken from 0.1% to 10%, the optimal mass ratio of the TMD is 9.7%, the fre-
 564 quency ratio is 0.92, the damping ratio is 15%, and the final fatigue life is 133.2 years.
 565 In this case, the fatigue life of the OWT is significantly increased mainly due to the
 566 large mass ratio. However, in practice, it might be uneconomic to implement a TMD
 567 with such a large mass ratio.

568 5 Conclusions

569 This study establishes a rapid numerical model which can consider the effect of
570 scour and installation of a TMD, and the TMD operates only in the FA direction. The
571 model is simplified by using concentrated mass instead of RNA and ignores the non-
572 linearity of the equivalent stiffness matrix. The established model is used to investigate
573 the influence of scour and the installed passive structural control device on the OWT's
574 natural frequencies and fatigue life through 22 environmental states. An optimization
575 technique is also developed to find optimal parameters of the TMD considering time-
576 varying scour. Moreover, it shows that the vibration amplitude of the OWT can be ef-
577 fectively reduced by the TMD. On the one hand, results show that the TMD reduces
578 the vibration amplitude of the tower top. On the other hand, when the scour depth
579 reaches 1.3D, the wind turbine support structure becomes more flexible, with the dis-
580 placement of the tower top increased without TMD.

581 In addition, the fatigue calculation results show that installation of the TMD sig-
582 nificantly extends the fatigue life of the OWT, but scour can cause a reduced perfor-
583 mance of the TMD. It is found that when the initially designed TMD does consider
584 scour and the scour-induced natural frequency reduction during the OWT's lifetime, its
585 performance is not as good as the TMD optimized by the developed FOT in terms of
586 fatigue life enhancement. Given a mass ratio of 1%, the fatigue life can be extended by
587 25% with the TMD optimized by FOT. This is because FOT can consider the effect of
588 time-varying scour. This study only performs the analysis with scour, but other factors
589 such as soil degradation can also alter the dynamic characteristics of OWTs and thus
590 have some influence on structural control devices' performance and fatigue life evalu-
591 ation. Additionally, during OWTs' lifetime, the properties of installed TMDs can also
592 change, making the evaluation of TMDs' performance and OWTs' fatigue life more
593 complicated. These factors are worthwhile investigating in the future.

594 6 Competing interests

595 The contact author has declared that none of the authors has any competing inter-
596 ests.

597 7 Acknowledgements

598 The financial supports from the National Natural Science Foundation of China (No.
599 52108280), Yangjiang Offshore Wind Laboratory (No. YJOWP-OF-2022A10),

600 the National Science Fund for Distinguished Young Scholars (No. 52025082) are
601 greatly appreciated.

602

603

604

605

606

607

608 **References**

- 609 Amirafshari, P., Brennan, F. and Kolios, A. (2021). A fracture mechanics framework
610 for optimising design and inspection of offshore wind turbine support structures
611 against fatigue failure. *Wind Energy Sci.*, 6(3), 677–699.
612 <https://doi.org/10.5194/wes-6-677-2021>
- 613 Aydin, E., Öztürk, B., Kebeli, Y. E. and Gültepe, G. (2023). An Experimental Study on
614 the Effects of Different Pendulum Damper Designs on Structural Behavior. In
615 G. P. Cimellaro (Ed.), *Seismic Isolation, Energy Dissipation and Active Vibration
616 Control of Structures* (Vol. 309, pp. 240–253). Cham: Springer Interna-
617 tional Publishing. https://doi.org/10.1007/978-3-031-21187-4_18
- 618 Bergua, R., Robertson, A., Jonkman, J. and Platt, A. (2021). Specification Document
619 for OC6 Phase II: Verification of an Advanced Soil-Structure Interaction Model
620 for Offshore Wind Turbines (NREL/TP--5000-79938; p. NREL/TP--5000-
621 79938).
- 622 Bergua, R., Robertson, A., Jonkman, J., Platt, A., Page, A., Qvist, J., Amet, E., Cai, Z.,
623 Han, H., Beardsell, A., et al. (2022). OC6 Phase II: Integration and verification
624 of a new soil–structure interaction model for offshore wind design. *Wind En-
625 ergy*, 25, 793–810.
- 626 Branlard, E. (2017). *Wind Turbine Aerodynamics and Vorticity-Based Methods: Fun-
627 damentals and Recent Applications* (Vol. 7). Cham: Springer International Pub-
628 lishing.
- 629 Capaldo, M. and Mella, P. (2023). Damping analysis of floating offshore wind turbines
630 (FOWTs): a new control strategy reducing the platform vibrations. *Wind En-
631 ergy Sci.*, 8(8), 1319–1339. <https://doi.org/10.5194/wes-8-1319-2023>
- 632 Chen, C. and Duffour, P. (2018). Modelling damping sources in monopile-supported
633 offshore wind turbines. *Wind Energy*, 21(11), 1121–1140.
634 <https://doi.org/10.1002/we.2218>
- 635 Chen, C., Duffour, P., Dai, K., Wang, Y. and Fromme, P. (2021). Identification of aer-
636 odynamic damping matrix for operating wind turbines. *Mech. Syst. Signal Pro-
637 cess.*, 154, 107568. <https://doi.org/10.1016/j.ymssp.2020.107568>
- 638 Chen, C., Duffour, P. and Fromme, P. (2020). Modelling wind turbine tower-rotor in-
639 teraction through an aerodynamic damping matrix. *J. Sound Vib.*, 489, 115667.
640 <https://doi.org/10.1016/j.jsv.2020.115667>
- 641 Chen, C., Duffour, P., Fromme, P. and Hua, X. (2021). Numerically efficient fatigue
642 life prediction of offshore wind turbines using aerodynamic decoupling. *Renew.
643 Energy*, 178, 1421–1434. <https://doi.org/10.1016/j.renene.2021.06.115>
- 644 Colwell, S. and Basu, B. (2009). Tuned liquid column dampers in offshore wind tur-
645 bines for structural control. *Eng. Struct.*, 31(2), 358–368.
646 <https://doi.org/10.1016/j.engstruct.2008.09.001>
- 647 Dai, K., Huang, H., Lu, Y., Meng, J., Mao, Z. and Camara, A. (2021). Effects of soil–
648 structure interaction on the design of tuned mass damper to control the seismic
649 response of wind turbine towers with gravity base. *Wind Energy*, 24(4), 323–
650 344. <https://doi.org/10.1002/we.2576>

- 651 Dai, S., Han, B., Wang, B., Luo, J. and He, B. (2021). Influence of soil scour on lateral
652 behavior of large-diameter offshore wind-turbine monopile and corresponding
653 scour monitoring method. *Ocean Eng.*, 239, 109809.
654 <https://doi.org/10.1016/j.oceaneng.2021.109809>
- 655 Den Hartog, J. P. (1957). *Mechanical Vibrations*. Fourth Edition. *Aeronaut. J.*, 61(554),
656 139–139.
- 657 Dinh, V.-N. and Basu, B. (2015). Passive control of floating offshore wind turbine nacelle
658 and spar vibrations by multiple tuned mass dampers. *Struct. Control Health*
659 *Monit.*, 22(1), 152–176. <https://doi.org/10.1002/stc.1666>
- 660 DNVGL-RP-0005. (2014a). RP-C203: Fatigue design of offshore steel structures.
- 661 DNV-OS-J101. (2014b). Design of Offshore Wind Turbine Structures.
- 662 Fard, M. M., Erken, A., Erkmen, B. and Ansal, A. (2022). Analysis of Offshore Wind
663 Turbine by considering Soil-Pile-Structure Interaction: Effects of Foundation
664 and Sea-Wave Properties. *J. Earthq. Eng.*, 26(14), 7222–7244.
665 <https://doi.org/10.1080/13632469.2021.1961936>
- 666 IEC 61400-3-1. (2019). Wind energy generation systems Part 3-1: Design requirements
667 for fixed offshore wind turbines.
- 668 Jonkman, B. J. and Buhl, M. L. (2006). *TurbSim User's Guide*. Tech. Rep., 500, 39797.
- 669 Jonkman, J., Butterfield, S., Musial, W. and Scott, G. (2009). Definition of a 5-MW
670 Reference Wind Turbine for Offshore System Development (NREL/TP-500-
671 38060, 947422; p. NREL/TP-500-38060, 947422).
- 672 Jung, S., Kim, S.-R., Patil, A. and Hung, L. C. (2015). Effect of monopile foundation
673 modeling on the structural response of a 5-MW offshore wind turbine tower.
674 *Ocean Eng.*, 109, 479–488.
- 675 Klaus, H., Dirk, J. O. and Peter, M. (1973). Measurements of wind-wave growth and
676 swell decay during the joint North Sea wave project (JONSWAP).
- 677 Lackner, M. A. and Rotea, M. A. (2011a). Passive structural control of offshore wind
678 turbines. *Wind Energy*, 14(3), 373–388. <https://doi.org/10.1002/we.426>
- 679 Lackner, M. A. and Rotea, M. A. (2011b). Structural control of floating wind turbines.
680 *Mechatronics*, 21(4), 704–719. <https://doi.org/10.1016/j.mechatronics.2010.11.007>
- 682 Liang, F., Chen, H. and Jia, Y. (2018). Quasi-static p-y hysteresis loop for cyclic lateral
683 response of pile foundations in offshore platforms. *Ocean Eng.*, 148, 62–74.
684 <https://doi.org/10.1016/j.oceaneng.2017.11.024>
- 685 Lu, D., Wang, W. and Li, X. (2023). Experimental study of structural vibration control
686 of 10-MW jacket offshore wind turbines using tuned mass damper under wind
687 and wave loads. *Ocean Eng.*, 288, 116015.
688 <https://doi.org/10.1016/j.oceaneng.2023.116015>
- 689 Ma, H. and Chen, C. (2021). Scour protection assessment of monopile foundation de-
690 sign for offshore wind turbines. *Ocean Eng.*, 231, 109083.
691 <https://doi.org/10.1016/j.oceaneng.2021.109083>

- 692 Mayall, R. O., McAdam, R. A., Byrne, B. W., Burd, H. J., Sheil, B. B., Cassie, P. and
693 Whitehouse, R. J. S. (2018). Experimental modelling of the effects of scour on
694 offshore wind turbine monopile foundations. In A. McNamara, S. Divall, R.
695 Goodey, N. Taylor, S. Stallebrass, and J. Panchal (Eds.), PHYSICAL MODEL-
696 LING IN GEOTECHNICS, VOL 1 (pp. 725–730). Int Soc Soil Mech & Ge-
697 otechn Engr, Tech Comm 104 Phys Modelling Geotechn; Active Dynam;
698 Tekscan.
- 699 Nakagawa, H. and Suzuki, K. (1976). Local Scour Around Bridge Pier in Tidal Current.
700 Coast. Eng. Jpn., 19(1), 89–100.
701 <https://doi.org/10.1080/05785634.1976.11924219>
- 702 Pedersen, D. M. and Askheim, H. (2021). Implementation of seismic soil-structure in-
703 teraction in OpenFAST and application to a 10MW offshore wind turbine on
704 jacket structure. Norwegian University.
- 705 Pelayo, F., Skafte, A., Aenlle, M. L. and Brincker, R. (2015). Modal Analysis Based
706 Stress Estimation for Structural Elements Subjected to Operational Dynamic
707 Loadings. Exp. Mech., 55(9), 1791–1802. <https://doi.org/10.1007/s11340-015-0073-6>
708
- 709 Rezaei, R. (2017). Fatigue Sensitivity of Monopile-supported Offshore Wind Turbines.
710 University College London.
- 711 Rezaei, R., Duffour, P. and Fromme, P. (2018). Scour influence on the fatigue life of
712 operational monopile-supported offshore wind turbines. Wind Energy, 21(9),
713 683–696. <https://doi.org/10.1002/we.2187>
- 714 Rudolph, D., Bos, K. J., Luijendijk, A. P. and Rietema, K. (2016). Scour around off-
715 shore structures-analysis of field measurements.
- 716 Shahmohammadi, A. and Shabakhty, N. (2020). Pile Apparent Fixity Length Estima-
717 tion for the Jacket-type Offshore Wind Turbines under Lateral Loads Applica-
718 ble to Fatigue Analysis. Int. J. Coast. Offshore Eng., 3(4), 25–33.
719 <https://doi.org/10.29252/ijcoe.3.4.25>
- 720 Shirzadeh, R., Devriendt, C., Bidakhvidi, M. A. and Guillaume, P. (2013). Experi-
721 mental and computational damping estimation of an offshore wind turbine on a
722 monopile foundation. J. Wind Eng. Ind. Aerodyn., 120, 96–106.
723 <https://doi.org/10.1016/j.jweia.2013.07.004>
- 724 Song, J. and Achmus, M. (2023). Cyclic overlay model of p – y curves for laterally
725 loaded monopiles in cohesionless soil. Wind Energy Sci., 8(3), 327–339.
726 <https://doi.org/10.5194/wes-8-327-2023>
- 727 Sørensen, P. H. S. and Ibsen, L. B. (2013). Assessment of foundation design for off-
728 shore monopiles unprotected against scour. Ocean Eng., 63, 17–25.
- 729 Stieng, L. E. S. and Muskulus, M. (2020). Reliability-based design optimization of off-
730 shore wind turbine support structures using analytical sensitivities and factor-
731 ized uncertainty modeling. Wind Energy Sci., 5(1), 171–198.
732 <https://doi.org/10.5194/wes-5-171-2020>
- 733 Tang, Z., Melville, B., Shamseldin, A., Guan, D., Singhal, N. and Yao, Z. (2023). Ex-
734 perimental study of collar protection for local scour reduction around offshore
735 wind turbine monopile foundations. Coast. Eng., 183, 104324.
736 <https://doi.org/10.1016/j.coastaleng.2023.104324>

- 737 van der Tempel, J. (2006). Design of support structures for offshore wind turbines.
738 Technische Universiteit Delft.
- 739 Velarde, J., Kramhøft, C., Sørensen, J. D. and Zorzi, G. (2020). Fatigue reliability of
740 large monopiles for offshore wind turbines. *Int. J. Fatigue*, 134, 105487.
741 <https://doi.org/10.1016/j.ijfatigue.2020.105487>
- 742 Wang, G., Xu, S., Zhang, Q. and Zhang, J. (2023). An experimental study of the local
743 scour protection methods around the monopile foundation of offshore wind tur-
744 bines. *Ocean Eng.*, 273, 113957.
745 <https://doi.org/10.1016/j.oceaneng.2023.113957>
- 746 Wang, L., Zhou, W., Guo, Z. and Rui, S. (2020). Frequency change and accumulated
747 inclination of offshore wind turbine jacket structure with piles in sand under
748 cyclic loadings. *Ocean Eng.*, 217, 108045.
749 <https://doi.org/10.1016/j.oceaneng.2020.108045>
- 750 Wang, X., Zeng, X., Li, X. and Li, J. (2019). Investigation on offshore wind turbine
751 with an innovative hybrid monopile foundation: An experimental based study.
752 *Renew. Energy*, 132, 129–141. <https://doi.org/10.1016/j.renene.2018.07.127>
- 753 Zdravković, L., Taborda, D., Potts, D., Jardine, R., Sideri, M., Schroeder, F., Byrne, B.,
754 McAdam, R., Burd, H., Houlsby, G., et al. (2015). Numerical modelling of large
755 diameter piles under lateral loading for offshore wind applications. *Front. Off-
756 shore Geotech. III*, 759–764.
- 757 Zhang, F., Chen, X., Feng, T., Wang, Y., Liu, X. and Liu, X. (2022). Experimental
758 study of grouting protection against local scouring of monopile foundations for
759 offshore wind turbines. *Ocean Eng.*, 258, 111798.
760 <https://doi.org/10.1016/j.oceaneng.2022.111798>
- 761 Zhang, F., Chen, X., Yan, J. and Gao, X. (2023). Countermeasures for local scour
762 around offshore wind turbine monopile foundations: A review. *Appl. Ocean
763 Res.*, 141, 103764. <https://doi.org/10.1016/j.apor.2023.103764>
- 764 Zhang, H., Liang, F. and Zheng, H. (2021). Dynamic impedance of monopiles for off-
765 shore wind turbines considering scour-hole dimensions. *Appl. Ocean Res.*, 107,
766 102493. <https://doi.org/10.1016/j.apor.2020.102493>
- 767 Zhang, R., Zhao, Z. and Dai, K. (2019). Seismic response mitigation of a wind turbine
768 tower using a tuned parallel inerter mass system. *Eng. Struct.*, 180, 29–39.
769 <https://doi.org/10.1016/j.engstruct.2018.11.020>
- 770
- 771