# **Comparison of wind-farm control strategies under realistic offshore wind conditions: turbine quantities of interest**

Joeri A. Frederik<sup>1</sup>, Eric Simley<sup>1</sup>, Kenneth A. Brown<sup>2</sup>, Gopal R. Yalla<sup>2</sup>, Lawrence C. Cheung<sup>2</sup>, and Paul A. Fleming<sup>1</sup>

<sup>1</sup>National Wind Technology Center, National Renewable Energy Laboratory, Golden, CO 80401, USA <sup>2</sup>Wind Energy Technologies Department, Sandia National Laboratories, Albuquerque, NM 87123, USA

Correspondence: Joeri A. Frederik (joeri.frederik@nrel.gov)

**Abstract.** Wind farm flow control is a strategy to increase the efficiency, and therefore lower the levelized cost of energy, of a wind farm. This is done by using turbine settings such as the yaw angle, blade pitch angles, or generator torque to manipulate the flow behind the turbine affecting downstream turbines in the farm. Two inherently different wind farm flow control methods have been identified in literature: wake steering and wake mixing. This paper focuses on comparing the

- 5 turbine quantities of interest between these methods for a simple two-turbine wind farm setup, while a companion article (Brown et al., 2025) focuses on the wake quantities of interest for a single wind turbine setup. Both papers use the same set of wind farm simulations based on high-fidelity large-eddy simulations coupled with OpenFAST turbine models. First, precursor simulations are executed in order to match wind conditions measured with lidars in an offshore wind farm off the US east coast. These measurements indicate general wind conditions that exhibit substantially higher vertical wind shear and veer than
- 10 any of the LES studies performed with wind farm flow control strategies currently available in literature. The precursors are used to evaluate the effectiveness of the control methods. In the LES simulations, the wind veer leads to highly skewed wakes, which has considerable influence on the power uplift of wind farm flow control strategies. In addition to a baseline controller, four different control strategies, each of which uses either pitch or yaw control, are implemented on the upstream turbine of a simple two-turbine wind farm. Assuming the wind direction is known and constant over time, the simulations show that wake
- 15 steering is generally the superior wind farm flow control strategy considering both wind farm power production and turbine damage equivalent loads when substantial wind veer is present. This result is consistent over different wind speeds and wind directions. On the other hand, for similar wind conditions with lower veer, wake mixing was found to yield the highest power production, although at the expense of generally higher loads. This leads us to conclude that the effect of wind veer, which was so far not usually considered, can not be neglected when determining the optimal wind farm flow control strategy.

# 20 1 Introduction

Dozens to hundreds of wind turbines are commonly placed closely together in so-called wind farms. While this decreases installation and maintenance costs and increases power capacity for the available installation area, it also comes at a price. As turbines extract energy from the wind, they create a wake in which the wind speed is lower and the turbulence is higher. When

turbines are installed close together in wind farms, some form of interaction between turbines and their wakes is inevitable.

25 A downstream turbine located partially or fully in the wake of another turbine subsequently produces lower power while experiencing higher loads.

Field studies have shown that the average loss of power on these waked turbines is in the range of 20–40 % with respect to their upstream counterparts (Nygaard, 2014; El-Asha et al., 2017). For low-turbulence wind conditions, this loss can be even higher. As a result, finding the optimal control settings for a wind farm is not necessarily the same as finding the optimal control settings for a wind farm is not necessarily the same as finding the optimal control settings for a wind farm turbines operate at a suboptimal setpoint for

the benefit of downstream turbines – this premise is exploited in the field of wind farm flow control (WFFC) research.

30

A wind turbine has a limited number of actuators that can be controlled to influence its performance and the characteristics of its wake. Wind turbine control publications focus on one or multiple of the following three actuation methods: blade pitch, generator torque, and nacelle yaw. All of these affect the axial induction factor, i.e., how much of the available kinetic energy

- 35 is extracted from the wind, and subsequently, the behavior of the wake. When the blade pitch or the generator torque is moved away from the optimal power coefficient,  $C_{P,max}$ , that turbine's power production drops. However, as the turbine extracts less energy from the wind, the kinetic energy in the wake increases, potentially leaving more energy to be extracted by downstream turbines. This method is commonly referred to as *axial induction control*, as it changes the induction factor, i.e., the ratio of the wind velocity reduction in the wake. Similarly, yawing the nacelle at an offset with the wind direction also lowers the power
- 40 extraction. Simultaneously, this yaw offset introduces a lateral force on the flow of the wind, thus deflecting the wake away from its usual path. This strategy is known as *wake steering*.

When a fixed yaw offset or derating level is prescribed for given wind conditions, this can be thought of as static or steadystate control strategies. Such strategies aim to find control setpoints that are constant over time, assuming the wind conditions do not change. Much of the early WFFC research focuses on controllers that fall into this categorization. For example, given

- a certain wind speed and direction and a predefined wind farm layout, Marden et al. (2012) and Ciri et al. (2017) used optimization algorithms to find the optimal induction factor for each turbine in the farm. While static induction control initially showed some potential, additional studies in higher-fidelity models (Annoni et al., 2016), scaled experiments (Campagnolo et al., 2016), and full-scale experiments (van der Hoek et al., 2019; Bossanyi and Ruisi, 2021) found limited to nonexistent gains. Steady-state wake steering, on the other hand, has shown potential to improve wind farm annual energy production in full-scale wind farms (Fleming et al., 2019; Howland et al., 2019a; Fleming et al., 2020; Doekemeijer et al., 2021) and has
  - since been incorporated in commercial WFFC products (Martinez and Coussy, 2024; Bachant et al., 2024).

More recently, interest has increased in time-varying or dynamic WFFC strategies. Unlike static strategies, these methods not only allow, but even depend on time-varying control signals under constant wind conditions. A similar distinction between axial induction and wake steering strategies can be made here. Dynamic induction control (DIC), in this paper referred to as

55 the *pulse* strategy, changes the induction factor of a turbine at a specific frequency to vary the wake width, which has been shown to enhance mixing in the wake of the turbine. This mixing promotes interaction between the slower wind in the wake of the turbine and the faster, freestream flow around it. As a result, the average velocity in the wake increases, and downstream turbines can improve their energy capture. In dynamic wake steering, a similar strategy is applied, but it uses the yaw angle as the time-varying actuator instead of the induction factor. Research on this strategy is more sparse than on its induction

60

equivalent (Meyers et al., 2022), and it is found to be less effective than static yaw (Munters and Meyers, 2018b; Howland et al., 2020). We therefore dismiss dynamic wake steering for now and focus on different variants of DIC.

The easiest way to achieve induction variations is by controlling the pitch actuators. This strategy was first implemented in wind tunnel experiments executed in Frederik et al. (2020c), showing its effectiveness in a scaled, controlled environment. Alternatively, a combination of pitch and torque control could be used (Yılmaz and Meyers, 2018). Time variations come in

infinitely many different shapes, but ever since Munters and Meyers (2018a) showed that simple sinusoidal signals are very effective in DIC applications, most research has focused on sinusoidal variations. Munters and Meyers (2018a) suggested normalizing the frequency, f, used for these sinusoidal variations using the freestream wind speed,  $U_{\infty}$ , and the turbine rotor diameter, D, to attain a specific Strouhal number, St, defined as

$$St = \frac{fD}{U_{\infty}},\tag{1}$$

- and reported an optimum of St = 0.25. Although later publications found slightly different optima (Yılmaz and Meyers, 2018; Frederik et al., 2020c; Coquelet et al., 2022; Wang et al., 2020), the optimum is always found to be in the range 0.2–0.4. Differences in optima might be attributed to variations in wind conditions, spacing, actuator implementation, and/or turbine characteristics. Power uplifts in the range of 2.3–6.3 % are found in these simulation studies for simple two- or three-turbine wind farms with full wake overlap and low turbulence intensities ( $\leq 6$ %). However, studies into turbine (damage equivalent)
- 75 loads show that the variations in induction, and subsequently rotor thrust, substantially increase the loads experienced by the excited turbine's tower and blades (Frederik et al., 2020c; Wang et al., 2020; Frederik and van Wingerden, 2022).

To mitigate these large thrust variations while retaining the potential power uplift, a variation to DIC was proposed in Frederik et al. (2020b). In this publication, the induction was varied over each blade of a turbine individually instead of over the entire rotor plane. When combined with the Coleman – or multiblade coordinate – transformation (Batchelor and Gill,

- 80 1962), dynamic variations in the rotor plane tilt (vertical) and yaw (horizontal) moments can be accomplished. Fleming et al. (2015) first proposed to apply static offsets in the tilt and yaw moments with the purpose of steering the wake without using a yaw or tilt angle offset. However, the static application of a multiblade coordinate-transformed offset proved to be ineffective and was subsequently disregarded.
- Nevertheless, when the tilt and yaw moments are varied at the same frequency and with a 90-degree phase offset, a moment that rotates over the rotor disk over time is created, resulting in a helical wake structure. This method is therefore called the *helix approach*, where the wake can rotate in either the clockwise or counterclockwise direction, depending on whether the tilt moment has a 90-degree phase lead or lag with respect to the yaw moment. Frederik et al. (2020b) showed that the counterclockwise helix enhances wake mixing substantially more than the clockwise helix and found energy uplifts that even exceeded DIC. Comparing these results to Fleming et al. (2015) once more underlines how dynamic control signals can
- 90 outperform static signals, in this case the multiblade coordinate-transformed blade moments, in terms of wind farm power production.

The helix approach has since attracted more research: Frederik and van Wingerden (2022), Van Vondelen et al. (2023), and Taschner et al. (2023) simulated turbine loads when the helix approach was implemented, finding that the biggest load impact was made on the controlled, upstream turbine. The helix approach was found to impact mostly blade flapwise (or out-of-plane)

- 95 moments and tower top moments as well as the pitch bearings due to increased pitching activity. Comparing the helix approach to DIC, Frederik and van Wingerden (2022) found substantially lower tower loads at the expense of the blades and pitch bearings. Taschner et al. (2024) studied the potential benefit of the helix approach compared to wake steering for different wind turbine layouts, demonstrating that the helix could be preferable over wake steering in near-full wake overlap scenarios with turbine spacing of up to 6 rotor diameters. Brown et al. (2022), Korb et al. (2023), and Cheung et al. (2024) investigated
- 100 the flow characteristics underlying this method, finding that the helix increases turbulent entrainment, wake deflection, and wake mixing. Coquelet et al. (2024) investigated why the counterclockwise helix is more effective than its clockwise rotating counterpart, and concludes that it is likely due to the wake swirl created by blade rotation. In Van der Hoek et al. (2024) and Mühle et al. (2024), the helix approach was implemented on model turbines in a wind tunnel. The outcomes of these experiments generally agreed with results from simulation studies: The counterclockwise helix outperforms the clockwise
- 105 variant, and the obtained power uplift exceeds the gains obtained with DIC in similar wind tunnel experiments (Frederik et al., 2020c; Van der Hoek et al., 2022). Finally, Van Den Berg et al. (2022) investigated the implementation of the helix approach on a floating offshore wind turbine and found that the combination of pitch actuation and platform motion might further enhance the wake mixing effect.

The same multiblade coordinate-transformed tilt and yaw moments can also be applied separately (Frederik et al., 2020a;
Cheung et al., 2024), or at higher harmonics (Huang et al., 2023). These approaches have not yet been investigated to the same degree as the helix approach, but initial results are promising and show that perhaps strategies based on individual pitch control (IPC) other than the helix approach should be considered in future research.

Because the dynamic pitch methods work on the premise that they actively increase the mixing between the slower flow in the wake and the faster flow around the wake, we will reference the totality of these strategies as active wake mixing

- 115 (AWM) strategies. In this paper, the validity of these relatively novel AWM strategies is further investigated by comparing them, in terms of both power uplift and structural loads, to the more established wake steering strategy. We implement the helix approach, an IPC approach where only the yaw moment is varied, DIC (or, the pulse strategy), and wake steering on a wind turbine, and examine the effect they have the turbine, on the wake, and on a potential downstream turbine. For this purpose, high-fidelity flow simulations are set up to resemble data acquired from lidar measurements in a real offshore wind
- 120 farm off the east coast of the United States. We investigate the effect that wind properties such as speed, direction, turbulence intensity, and veer have on the effectiveness of WFFC strategies. Apart from wind turbine and wind farm power production, we also review the damage equivalent load (DEL) of multiple critical turbine components. The results of these simulations contribute to our understanding of the potential of AWM as a WFFC strategy depending on wind speed, turbulence intensity, atmospheric stability, and wind farm layout.
- 125 This paper is a companion to Brown et al. (2025). Where this paper mainly focuses on the turbine-level behavior of the different control strategies, Brown et al. (2025) dives deeper into the fluid dynamics behind the results. On multiple occasions,

we will summarize results from and reference Brown et al. (2025) for the reader's convenience. However, for a complete understanding of the effect AWM has on both turbine and flow, the reader is advised to study both papers.

# 2 Methodology

130 As mentioned in Sect. 1, the objective of this paper is to compare different AWM strategies to the more established wake steering control approach. To assess the effectiveness in terms of wind farm power and turbine structural loads of these strategies, high-fidelity simulations of the turbine-flow interaction are executed. In this section, we discuss the simulation environment in detail as well as the control strategies that are implemented. First, we review the simplified wind farm setup used in this study.

### 2.1 Wind farm setup

150

- 135 As discussed previously, applying WFFC only makes sense if there is some sort of interaction between turbines through their wakes. Without interaction, the optimal WFFC strategy in terms of power production would always be to have each turbine operate at its individual optimum. However, wind farm layouts are not standardized but depend on the topology of the farm, and wind directions vary over time. As a result, the potential of WFFC varies substantially between different wind farms, and it is not possible to assess one specific case and then extrapolate the results for different farms. We therefore choose to
- 140 study a simplified wind farm case with only two interacting turbines. The internal distance between the two turbines is set to be 5D in the streamwise direction, assuming perfect alignment with the average wind direction, unless stated otherwise. Note that this means that we ignore the possible benefit of controlling turbines downstream. Studies have shown that applying yaw control (Howland et al., 2019b) or AWM (van Vondelen et al., 2023) on downstream turbines could have the potential to further increase power capture. However, including this interaction in our study would substantially increase the number of
- 145 simulations. Due to the relatively large number of different wind conditions that are to be studied, the scope of this paper is limited to a single controlled turbine.

Apart from these two-turbine simulations, we also execute simulations with a single turbine to study the wake of the turbine. By sampling flow data in the wake, we are able to estimate the potential power uplift of a downstream turbine at any given location. We call this a virtual turbine and determine its power by using the rotor-averaged wind speed,  $\bar{U}_r(t)$ , as a function of wind speed data points  $u_{i,j,k}(t)$ , where i, j, k are the grid points in the x-, y- and z-directions, respectively, and virtual hub location  $\mathbf{x} = [x_h, y_h, z_h]$ .

The set of points within the rotor-swept area, C, is first defined as

$$C(y_h, z_h) = \left\{ (j, k) \mid (y_j - y_h)^2 + (z_k - z_h)^2 \le (D/2)^2 \right\},\tag{2}$$

where the subscript h in  $y_h$  and  $z_h$  denotes the index of the location of the hub of this virtual turbine in the lateral and wallnormal (vertical) directions, respectively. Note that the location  $x_h$  of the turbine in the streamwise direction does not affect C, as we assume the virtual turbine is yawed perpendicular to the average wind direction. The rotor-averaged wind speed at streamwise location  $x_h$  is then defined as

$$\bar{U}_r(t, \mathbf{x}) = \frac{\sum_n \sum_m u_{\mathbf{h}, j, k}(t)}{|C(y_{\mathbf{h}}, z_{\mathbf{h}})|} \qquad \forall \quad (m, n) \in C(y_h, z_h),$$
(3)

where  $|C(y_h, z_h)|$  is the size of set  $C(y_h, z_h)$ . Finally, the power of the virtual turbine,  $P_v(t, \mathbf{x})$ , is computed as

160 
$$P_v(t,\mathbf{x}) = \frac{1}{2}\rho A_r C_P \left(\bar{U}_r(t,\mathbf{x})\right)^3,$$
 (4)

where the power coefficient,  $C_P$ , is assumed to be a function of the wind speed as provided by a lookup table of the chosen turbine model (see Sect. 2.2.2). In Sect. 3, we evaluate how well the power of a virtual turbine corresponds to simulations with an actual downstream turbine model.

#### 2.2 Simulation environment

The simulations conducted for this paper have been executed in AMR-Wind (Lawrence Berkeley National Laboratory et al., 165 2024), an incompressible flow solver for wind turbine and wind farm simulations that is part of the ExaWind ecosystem. AMR-Wind is actively being developed by Lawrence Berkeley National Laboratory, National Renewable Energy Laboratory (NREL), and Sandia National Laboratories, and executes large-eddy simulations (LES) of atmospheric boundary layer flows. For more information on AMR-Wind, see, e.g., Brazell et al. (2021) and Min et al. (2024).

#### 2.2.1 Flow conditions 170

The wind flow conditions of the simulations used in this paper are based on measurements from a floating-lidar campaign at a proposed wind farm site in the New York Bight (Mason, 2022). Wind measurements were collected over a period of 1.6 years, with the lidars sampling at heights between 20 and 200 m. All data used to set up these simulations are publicly available (DNV, 2023).

- 175 The effectiveness of different WFFC strategies can depend heavily on the wind conditions. Therefore, the lidar data are divided over three wind speed (WS) and turbulence intensity (TI) bins: low ( $6 \text{ m s}^{-1} < \text{WS} \le 7 \text{ m s}^{-1}$ ), medium ( $8.5 \text{ m s}^{-1} < 10^{-1}$ )  $WS \le 9.5 \text{ m s}^{-1}$ ) and high  $(11 \text{ m s}^{-1} \le WS \le 12 \text{ m s}^{-1})$  WS cases, and low  $(TI \le 5\%)$ , medium  $(5\% \le TI \le 10\%)$ , and high (TI > 10%) TI cases, see Brown et al. (2025) details. This results in a total of nine cases that could be investigated. Both the low- and medium-WS cases are in the below-rated regime of the modeled turbine, while the high-WS cases are in the 180 above-rated regime (see Sect. 2.2.2).

185

Note that WFFC is generally considered to be most effective at low TI. Turbulence provides mixing between the slower flow in the wake with the faster freestream flow, thus inducing natural wake recovery. As WFFC reduces wake losses, lower natural losses imply lower potential for improvement by implementing WFFC. Furthermore, above-rated conditions are less favorable for the implementation of WFFC, as upstream turbines are already operating at lower-than-maximal power and thrust coefficients. Subsequently, the relative wake deficit – and therefore the potential gain for WFFC – is lower than in below-rated conditions. As a consequence, we focus most of our attention in this paper on the low- and medium-WS, low-TI cases. Nevertheless, we also study the high-WS, low-TI, and medium-WS, medium-TI cases, to demonstrate their effects on WFFC strategies. More details on the setup of these simulations can be found in the companion paper Brown et al. (2025).

In addition to the simulation cases based on lidar measurements, one more simulation case is added to study the direct effect

190 of veer and shear on the effectiveness of WFFC. This case is set up to be comparable to the main medium-WS, low-TI case, but with negligible veer and shear. There is some evidence in literature (Bodini et al., 2017; Churchfield and Sirnivas, 2018) that LES overestimates the amount of wake skewing induced by wind veer, which is discussed in more detail in Sect. 3.3.2. This case is therefore included to account for that possibility. Furthermore, it serves to show the direct effect of both TI (by comparing to the medium-TI case) and wake skewing (by comparing to the low-TI case) on the effectiveness of WFFC strategies. The numerical domain of simulation for all cases is summarized in Table 1, and Table 2 shows relevant quantities that define the air flow through the domain in all of the simulation cases.

It should be noted that although not all simulations have the same cell size in the outer regions of the domain, the cell size in the region of interest, i.e., around and behind the turbines, is the same for all simulations. For practical reasons, not all simulation settings are uniform throughout the different precursors. These reasons include ensuring the desired wind conditions over the simulation time and reducing computation time. More details on these choices can be found in the companion paper (Brown et al., 2025).

200

Table 1.	An overview	of the most re	elevant AMR	-Wind LES	settings used	in the different	t wind	condition of	cases reviewed	in this paper.
----------	-------------	----------------	-------------	-----------	---------------	------------------	--------	--------------	----------------	----------------

Case	Simulation length	Domain size	Cell size (outer region)	Cell size (wake)	Air density
Low WS, low TI	1000 s	$6.72\times2.0\times0.96\mathrm{km}$	$5 \times 5 \times 5 \mathrm{m}$	$2.5\times2.5\times2.5\mathrm{m}$	$1.2456{ m kg}{ m m}^{-3}$
Medium WS, low TI	1200 s	$4.56\times2.0\times0.96\mathrm{km}$	$5 \times 5 \times 5 \mathrm{m}$	$2.5\times2.5\times2.5\mathrm{m}$	$1.2456{ m kg}{ m m}^{-3}$
Medium WS, low TI, low veer	1200 s	$5.12\times5.12\times1.28\mathrm{km}$	$10\times10\times10\mathrm{m}$	$2.5\times2.5\times2.5\mathrm{m}$	$1.225{ m kg}{ m m}^{-3}$
Medium WS, medium TI	1000 s	$7.2\times4.0\times1.44\rm{km}$	$10\times10\times10\mathrm{m}$	$2.5\times2.5\times2.5\mathrm{m}$	$1.2456{ m kg}{ m m}^{-3}$
High WS, low TI	1000 s	$6.72\times2.0\times0.96\mathrm{km}$	$5 \times 5 \times 5 \mathrm{m}$	$2.5\times2.5\times2.5\mathrm{m}$	$1.2456{ m kg}{ m m}^{-3}$

**Table 2.** Wind conditions for different precursors, including WS, TI, and veer levels. The veer is expressed in terms of degrees of wind direction change over the rotor disk (height of 30 m to 270 m). The shear is expressed as the power exponent that best fits the vertical wind speed profile and, in brackets, as the wind speed difference over the rotor disk in meters per second.

Case name	Acronym	Hub height wind speed	Hub height TI	Veer	Shear
Low WS, low TI	LSLT	$6.48{ m m~s^{-1}}$	2.85 %	$8.77^{\circ}$	$0.139 (1.75 \mathrm{m \ s^{-1}})$
Medium WS, low TI	MSLT	$9.00 \mathrm{m  s^{-1}}$	2.36 %	$11.86^{\circ}$	$0.177 (3.03 \mathrm{m \ s^{-1}})$
Medium WS, low TI, low veer	MSLT-LV	$8.97 \mathrm{m  s^{-1}}$	3.36 %	$1.99^{\circ}$	$0.080 (1.56 \mathrm{m  s^{-1}})$
Medium WS, medium TI	MSMT	$8.98{ m m~s^{-1}}$	7.00 %	$1.32^{\circ}$	$0.070 (1.30 \mathrm{m \ s^{-1}})$
High WS, low TI	HSLT	$11.47{ m m~s^{-1}}$	2.84 %	$7.18^{\circ}$	$0.163 (3.60 \mathrm{m  s^{-1}})$

### 2.2.2 Turbine model

simulations are run with a constant time step of  $5 \cdot 10^{-3}$  s.

The AMR-Wind flow solver described above is coupled with the well-known OpenFAST wind turbine simulation tool (National Renewable Energy Laboratory, 2024b). OpenFAST couples computational models for aerodynamics, electrical system dynamics, structural dynamics, and controls to simulate the wind turbine response in the time domain. The OpenFAST turbine

205

Because this study focuses specifically on offshore wind conditions, the 15 MW monopiled offshore reference wind turbine model developed in IEA Wind Task 37 is used (Gaertner et al., 2020). This turbine is henceforth referenced to as the IEA 15 MW turbine, and has a hub height of 150 m, a rotor diameter of 240 m, and a rated wind speed of  $10.59 \text{ ms}^{-1}$ .

210

215

The structural dynamics of the turbine are calculated using the ElastoDyn solver. All blade, tower, generator, and drivetrain degrees of freedom are activated, while the turbine is not allowed to yaw away from its setpoint.

Although BeamDyn is the preferred module to calculate the structural loads on the blades, this also substantially increases the computational load of the simulations. As this study comprises a large number of highly expensive LES simulations, we chose to use the simpler ElastoDyn solver instead. This should be taken into consideration when evaluating the blade loads presented in Section 3.

#### 2.3 Turbine control

In this paper, we investigate five different WFFC strategies. Before elaborating on these strategies, it is relevant to discuss how a standard wind turbine controller works. In below-rated wind conditions a turbine controller typically aims to maximize  $C_P$ , so it operates using constant blade pitch angles and a nacelle yaw angle that is aligned with the wind direction. The generator torque is then controlled to regulate the blade tip-speed ratio,  $\lambda$ , toward its optimum for maximal power extraction,  $C_P^{\text{opt}}$ . This strategy can be called greedy control from the perspective of individual wind turbines. As the IEA 15 MW turbine has a rated wind speed of 10.59 ms<sup>-1</sup>, all simulation cases apart from the HSLT case fall within the below-rated regime.

In above-rated conditions, maximal power production is no longer the control objective. In this regime, a typical wind turbine controller actuates the blade pitch angles to keep the rotor speed constant while producing rated power. As a result, the controller is pitching the blades to counteract changes in wind speed. The HSLT simulation case is the only one with above-rated conditions considered in this paper.

225

In this paper, the control strategy aimed at maximizing the power yield of individual turbines in below-rated conditions, and producing constant rated power in above-rated conditions, is the first approach implemented. It is used as the baseline strategy to which we compare the different WFFC strategies. Furthermore, all downstream turbines implemented in this paper are also controlled using this baseline controller.

The four WFFC strategies investigated in this paper are summarized in Table 3. Three of these strategies are AWM strategies: DIC, from here on out referred to as the pulse strategy, which uses collective pitching, and the helix and side-to-side strategy, using IPC. These AWM strategies are compared to wake steering, which uses a time-invariant yaw angle offset.

Table 3. Overview of WFFC strategies and how they are applied on the upstream wind turbine.

Control strategy	Actuation Desired effect on the wake				
Baseline	None	Establish baseline wake deficit for comparison to the different WFFC strategies			
Helix	Individual blade pitch variations	Dynamically steering the wake horizontally and vertically			
Pulse	Collective blade pitch variations	Dynamically varying the rotor thrust to modulate wake depth			
Side-to-side	Individual blade pitch variations	Dynamically steering the wake horizontally			
Wake steering	Nacelle yaw offset	Statically steering the wake horizontally			

To implement the different control strategies on the IEA 15 MW turbine, NREL's reference open-source controller (ROSCO v2.8.0; National Renewable Energy Laboratory (2024a)) is used. ROSCO was developed to offer the scientific community a baseline wind turbine reference controller with industry-standard functionality (Abbas et al., 2022).

For the work executed in this paper, AWM functionality had to be added to ROSCO. This functionality was included in ROSCO version 2.8.0, and uses the Coleman transformation (Batchelor and Gill, 1962) to set the parameters for different wake mixing strategies. The pitch angles  $\theta_i$ ,  $i \in 1, 2, 3$  are defined as the outcome of the inverse Coleman transformation:

$$240 \quad \begin{bmatrix} \theta_1(t) \\ \theta_2(t) \\ \theta_3(t) \end{bmatrix} = \begin{bmatrix} \cos(n\psi_1(t)) & \sin(n\psi_1(t)) \\ \cos(n\psi_2(t)) & \sin(n\psi_2(t)) \\ \cos(n\psi_3(t)) & \sin(n\psi_3(t)) \end{bmatrix} \begin{bmatrix} M_{\text{tilt}}(t) \\ M_{\text{yaw}}(t) \end{bmatrix},$$
(5)

where n is the Coleman transformation harmonic number, and  $\psi_i(t)$ ,  $i \in 1, 2, 3$  is the azimuth position of blade i at time t. In ROSCO, the user is able to define  $M_{\text{tilt}}$  and  $M_{\text{yaw}}$  individually as a constant or sinusoidal signal:

$$M = A\cos(2\pi f_e t + \phi) = A\cos(\omega_e t + \phi),\tag{6}$$

245

with amplitude A, frequency  $f_e$ , and offset angle  $\phi$  user inputs, and  $\omega_e = 2\pi f_e$ . For the AWM strategies investigated in this paper, the required settings are summarized in Table 4. Note that, equivalent to the Coleman transform method, the AWM strategies can also be defined by using the normal mode method (Cheung et al., 2024). For completeness, these settings are shown in Table 4 as well.

To limit the number of simulations to be executed, the amplitude and frequency of the AWM strategies is not optimized for all wind conditions. Instead, a Strouhal frequency of St = 0.3 and a pitch amplitude of  $A = 4^{\circ}$  is used in all simulations. This frequency was found to be optimal in the MSLT case, and from literature (Frederik et al., 2020c; Van der Hoek et al., 2024) we know that the gradient is low around the optimum. The pitch amplitude of A = 4 is relatively large, but is chosen to represent the case in which maximizing power production is prioritized over minimizing loads. Decreasing the amplitude has a close-to-linear effect on power production and DEL, see, e.g., Van Vondelen et al. (2023).

As the azimuth angle is a function of rotor speed  $\omega_r$ ,

255 
$$\psi_i(t) = \omega_r t + \frac{2\pi}{3}(i-1),$$
 (7)

Table 4. Control settings for AWM as implemented in ROSCO. St is the Strouhal number, set at 0.3 in this paper, and D = 240 m is the turbine rotor diameter.

		settings	Co	leman	method	Normal mode method		
Control strategy	$\mathbf{A}_{tilt}$	$\mathbf{A}_{yaw}$	$\mathbf{f}_{\mathbf{e}}$	n	$\phi_{ m tilt}$	$\phi_{ m yaw}$	n	$\phi_{ m clock}$
Pulse	4	n/a	$St \cdot U_{\infty}/D$	0	0°	n/a	0	90°
Helix	4	4	$St \cdot U_{\infty}/D$	1	0°	90°	-1	90°
Side-to-side	0	4	$St \cdot U_{\infty}/D$	1	n/a	$0^{\circ}$	+1, -1	90°

the individual pitch angles  $\theta_i$  for each blade *i* are a product of two sinusoidal signals, which, using simple rules of trigonometry, can be simplified to:

$$\begin{aligned}
\theta_{i}^{\text{pulse}} &= A\sin(\omega_{e}t), \\
\theta_{i}^{\text{helix}} &= A\sin\left((\omega_{r}+\omega_{e})t + \frac{2\pi}{3}(i-1)\right), \\
\theta_{i}^{\text{side-to-side}} &= A\sin\left(\omega_{r}t + \frac{2\pi}{3}(i-1)\right)\sin(\omega_{e}t).
\end{aligned}$$
(8)

Note that the rated rotor rotational frequency  $f_r = 7.56$  rpm = 0.126 Hz is on the order of magnitude of 10 times faster than the standard excitation frequency  $f_e = St \cdot U_{\infty}/D = 1.25 \cdot 10^{-3} \cdot U_{\infty}$ . As a result, the pitch frequency of the pulse strategy is about 10 times slower than that of the helix and side-to-side strategies. This is visualized in Fig. 1, which shows the pitch signals of one blade for all control strategies.



Figure 1. A visualization of typical pitch actuation for a single blade when different AWM strategies are applied, as defined in Eq. (8). This example comes from a simulation with a wind speed  $U_{\infty} = 9.0 \text{ m s}^{-1}$ , with an amplitude of  $A = 4^{\circ}$  and a Strouhal number of St = 0.3, resulting in an excitation frequency  $f_e = 1.13 \cdot 10^{-2}$  Hz and an excitation period of  $T_e = 88.9$  s. The average rotor speed over these simulations is  $f_r = 6.6$  rpm = 0.11 Hz.

Finally, for the wake steering case, no active control is implemented. For this strategy, the turbine runs using the same control settings as the baseline case, with the exception of a constant yaw misalignment defined with respect to the mean wind

265 direction. Note that, for simplicity, we assume that the wind direction is constant over time and known a priori in all control cases. Subsequently, the yaw angle is constant over the entire simulation and based on the average wind direction. The positive yawing direction is defined as counterclockwise when seen from above.

Equivalently to the AWM pitch amplitude, in the simplified case of a constant wind direction with full wake overlap, a larger yaw angle offset generally results in higher powers at the expense of higher loads. Therefore, to match the large pitch amplitudes used in AWM, we have also chosen to implement a relatively large yaw angle offset. In field experiments, a yaw angle offset of up to 20° is commonly considered acceptable to manage structural loads (Fleming et al., 2019; Doekemeijer

et al., 2021; Simley et al., 2021). We have subsequently chosen to implement a yaw angle offset of  $\pm 20^{\circ}$  in all WS simulations.

# 2.4 Load calculations

A common argument that is regularly made against WFFC strategies, specifically AWM, is that the benefits in terms of power increase do not outweigh the drawback of higher structural turbine fatigue loads. To address these valid concerns, we will not only study wind farm power uplift in this paper but also investigate the effect on fatigue loads. Specifically, we look at a quantity called damage equivalent load (DEL).

The DEL of a component is calculated using rainflow counting to obtain the amplitudes and frequencies of different load cycles within load bins k. To correct for mean loads, the Goodman correction (see, e.g., Sutherland and Mandell (2004)) is applied to obtain stress signals L based on the ultimate stresses of the materials. The DEL is then computed as

$$\text{DEL} = \left(\frac{1}{T}\sum_{k} n_k \left(L_k\right)^m\right)^{\frac{1}{m}},\tag{9}$$

where T is the number of 1 Hz cycles over the simulation,  $n_k$  is the number of cycles of amplitude L in load bin k, and m is the Wöhler exponent in question. All material properties used in these calculations are shown in Table 5. Note that when a component consists of multiple different materials, the lower ultimate load is used here to obtain a worst-case DEL.

Table 5. Material properties of all the components considered in the load studies executed in this publication.

Component	Ultimate stress	Wöhler exponent
Blade	1047 MPa	10
Tower	450 MPa	4
Yaw bearing	113 MPa	4
Low-speed shaft	814 MPa	4

285

280

In turbine load calculations, orthogonal signals – such as the blade root flapwise and edgewise bending moments – are typically studied individually. However, in reality, these orthogonal projections form a single moment that has both a magnitude and a direction. Therefore, in Thedin et al. (2024), a method is used that combines these orthogonal loads over a 180° rose with  $10^\circ$  steps. The DEL is then calculated for each of the 18 directional bins, and the highest DEL is taken as the critical DEL. The loads of the components described in Table 5 are determined by using the blade root flapwise and edgewise moments, the

290 tower base fore-aft and side-side moments, the yaw bearing pitch and roll moments, and the low-speed shaft nonrotating yaw and tilt bending moments at the shaft tip, respectively.

# **3** Results

300

In this section, we discuss the results from the simulations executed based on the methodology described in Sect. 2. Unless stated otherwise, the simulations consist of a two-turbine wind farm, with 5*D* streamwise spacing and 0*D* lateral spacing, i.e., the downstream turbine is experiencing full wake overlap in baseline operation.

### 3.1 Upstream turbine behavior

First, we consider the behavior of the upstream turbine, on which the different control strategies introduced in Sect. 2.3 are implemented. Some relevant turbine signals are plotted in Fig. 2. As known from literature, the most significant power drop is observed for the wake steering case. However, it is also expected to yield the most significant uplift on downstream turbines. When the pulse is implemented, the variations in thrust also lead to power fluctuations, as would be expected. Note that these power fluctuations are not present for the IPC-based AWM strategies, as these are designed to keep the rotor-averaged induction constant.



**Figure 2.** The generator power and rotor speed, torque, and thrust for all five control cases described in Table 3. The active wake control strategies each have an amplitude of  $4^{\circ}$ , while the wake steering yaw offset is  $+20^{\circ}$ .

The average power production of the turbine for all control strategies is shown in Table 6. The power loss of the AWM strategies is well within single digit percentages; the helix strategy has the highest power loss, and the side-to-side strategy has the lowest power loss.

# 305

**Table 6.** The average power production over the last eight excitation periods ( $\approx 707$  s) of the single turbine LES simulation, for all five control strategies. The relative loss is given compared to the baseline case.

Control strategy	Average power	Relative loss
Baseline	9.12 MW	n/a
Helix	8.83 MW	-3.22%
Pulse	8.91 MW	-2.27 %
Side-to-side	9.05 MW	-0.76 %
Wake steering	7.87 MW	-15.9 %

#### 3.2 Single-turbine wake analysis

Next, we study the wake behind a single turbine. In Sect. 3.2.1, we investigate the effect the wind veer has on wake skewing in baseline control operation, and in Sect. 3.2.2, the effect of the different control strategies on the wind speed in the wake is examined.

#### 310 3.2.1 Wind veer analysis

As shown in Table 2, the low-TI cases all exhibit substantial wind veer. Specifically, case MSLT has very high veer: 11.86° over the D = 240 m rotor disk. As a result, we expect the wake to be skewed, possibly affecting the downstream wake loss. To estimate the level of wake skewing, the average wake profile is fitted to a Gaussian curve defined as

$$f(x) = U_{\infty} - U_d \cdot e^{-\frac{(r-\mu)^2}{2\sigma^2}},$$
(10)

315 where  $U_d$  is a measure of the wake deficit, r is the lateral distance from the hub center,  $\mu$  is the lateral wake center position, and variance  $\sigma^2$  is a measure for the wake width. Using simple nonlinear least squares optimization to find all the above-mentioned parameters, we can extract the wake center  $\mu$  at different elevations. The result is shown in Fig. 3 for the MSLT case, at 5D behind a turbine operating with the baseline controller.

Considering Fig. 3, the wake skew at 5D is substantial, but in line with what could be expected based on the veer (solid

320 blue line). Apart from the exact skewing of the wake, other factors might affect the power production of a downstream turbine. First, the shape of the wake is not circular or even very elliptical. Instead, the wake width stays relatively consistent over the y-axis while only the wake center shifts. As a result, the wake would not affect a downstream turbine as much as would be the case in unveered conditions, and subsequently, the potential gain of using WFFC is also expected to be lower. Second, the



Figure 3. Average wake skewing at 5D downstream of a turbine operating using baseline control on the MSLT simulation. The average is taken over the last 500 s of the simulation. In the top figure, the velocity profile over a cross section of the flow is shown. The solid line shows the expected skew, assuming veer is 1:1 correlated to skew. The dotted line shows the estimated wake center based on the Gaussian fits. The white dotted circle represents the location of the upstream rotor disk. The bottom figure shows the average wind speeds and the corresponding fit and resulting wake center at hub height (y/D = 0.625).



Figure 4. Average wake skewing at 5D downstream of a turbine operating using baseline control on the LSLT (a) and HSLT (b) simulations. The average is taken over the last 500 s of the simulation. In the top figure, the velocity profile over a cross section of the flow is shown. The solid line shows the expected skew, assuming veer is 1:1 correlated to skew. The dotted line shows the estimated wake center based on the Gaussian fits. The white dotted circle represents the location of the upstream rotor disk. The bottom figure shows the average wind speeds and the corresponding fit and resulting wake center at hub height (y/D = 0.625).

aforementioned wake center does not align with the wind direction but instead veers slightly to the right looking downstream.

325 At hub height, this offset is 0.12D (28.7 m), equivalent to a wind direction offset of  $1.4^{\circ}$ . Both effects could possibly favor wake steering over AWM as a WFFC strategy, as both make it easier to steer the deepest part of the wake away from downstream turbines.

Figure 4 similarly shows the wake skewing at 5D downstream for the low- and high-WS simulations. In these cases, the veer, and subsequently the wake skew, is slightly less prominent than in the MSLT case. The correspondence between the

- 330 veer and the wake skew is still close to a 1:1 ratio. To see if this is realistic, we compare the wakes to similar cases found in literature. In Churchfield and Sirnivas (2018), the effects of wake skew were studied using a different LES code called SOWFA (Churchfield and Lee, 2012). This study investigated the actual-to-expected skew angle ratio, i.e., the ratio between skew and veer, as a function of downstream location, and shows a ratio close to 1 at 2D downstream, going down to 0.8 at 10D. This is very similar to the LSLT case, as shown in Fig. 5a. The MSLT and HSLT cases have slightly higher relative skewing, which is
- 335 likely to influence the performance of downstream turbines. Churchfield and Sirnivas (2018) showed that a turbine located 9D downstream of a different turbine in a skewed wake produces 30% more power than in a nonskewed wake, and experiences generally higher DELs.

Bodini et al. (2017) studied the structure of wakes using lidar wind measurements in a land-based wind farm. This study showed that, at the measured downstream distance of 8.5D (680 m), the wake skewing was substantially lower than a 1:1

- 340 relationship with wind veer (see the solid lines in Fig. 5b). The values at 8.5*D* downstream for the simulation cases from this paper are shown by the dots. In comparison, the simulation cases presented here, as well as those in Churchfield and Sirnivas (2018), have wake skewing that is much closer to the wind veer conditions. Furthermore, in the field measurements, the relationship effect of veer on wake skewing decreases as veer increases, whereas this is not observed in any of the LES cases.
- Churchfield and Sirnivas (2018) showed the effect that wake skewing has on downstream turbine behavior, and Bodini et al. (2017) showed that the wake skew in our simulation cases is substantially higher than that observed in field experiments. Therefore, the results in this paper might overestimate the effect of wind veer on WFFC. However, these field experiments were conducted onshore, whereas the wind measurements used to generate these simulations were taken offshore. It is therefore also plausible that the wake skewing effect is bigger offshore than it is onshore due to a lack of ground effects to disturb the flow.

### 350 **3.2.2** Energy in the wake

In this section, we study the level of wake recovery realized by the different control strategies, and the effect it could have on wind farm power production. Figure 6 shows the rotor-averaged wind speed for a downstream turbine location, assuming alignment with the wind direction, as a function of downstream distance. Note that this figure shows that the streamwise plane at hub height does not give an accurate estimate of the rotor-averaged wind speed for all cases. There is a clear discrepancy with

355 the more accurate cross sections that is likely explained by the significant wake skew present in these cases. Furthermore, this figure clearly shows that wake steering results in the highest velocity uplift in the wake. However, this strategy also accounts for the largest upstream power loss.



**Figure 5.** The wake skewing obtained in the simulations assessed here are compared to results found in literature. Figure 5a shows the actual-to-expected wake skew ratio based on the veer present for the three different wind speeds. Figure 5b shows the skew-to-veer ratio at 8.5*D* downstream (dotted line in Figure 5a) and compares it to the fits found for onshore lidar wake measurements performed in Bodini et al. (2017) and LES simulations from Churchfield and Sirnivas (2018). The wake skewing in our simulations is determined by taking the difference between the time-averaged flow wake center at the bottom and top of the rotor plane.



**Figure 6.** The rotor-averaged velocity as a function of downstream distance for the MSLT simulation, assuming alignment with the upstream turbine. The solid lines show the estimated average velocity for all five control strategies when only the streamwise hub height data are taken into account. The dotted line uses cross-sectional planes that capture the entire rotor plane and should therefore be considered more accurate. The relative wind speed in the bottom graph uses the cross-sectional data only.



Figure 7. The estimated power gains with respect to baseline for a combined two-turbine wind farm when different control strategies are implemented for the MSLT simulation. The power of the downstream turbine is given as a function of its position with respect to the upstream turbine and is based on the rotor-averaged downstream velocities in the cross-sectional planes. The + in each figure shows the location of a downstream turbine that would experience the highest percentage power uplift based on the estimated downstream power.

360

To get the full picture in terms of wind farm power, the power loss at the upstream turbine should also be taken into account. This is shown in Fig. 7, where the *combined* power production of a two-turbine wind farm is estimated for any position of the downstream turbine, based on the rotor-averaged velocity obtained from the cross-sectional planes. This figure shows that for specific locations of the downstream turbine, wake steering and the pulse have the highest predicted power uplift, 7.7% and 9.0%, respectively. Both these optima are at 4D downstream and have a slight offset -0.4D to the right for the pulse, 0.3Dto the left for wake steering. The helix and side-to-side strategies both have a maximum predicted uplift of 2.4 %, where the side-to-side optimum lies slightly farther downstream.

- 365 Note that the width of this uplift region is essentially different for wake steering and wake mixing. For the former, there is a narrow band of turbine locations with high uplift, but outside of this band, wake steering results in substantial power losses. For the latter, the gradient of the uplift with respect to lateral offset is much smaller. This difference has two causes. First of all, the power loss of the upstream turbine, as shown in Figure 2, is substantially higher for WS than for AWM. Subsequently, the combined two-turbine power drops much quicker when the wake interaction decreases, as the downstream machine gains less
- while the upstream machine loses the same. Secondly, WS directs the wake away from a specific location. This is very effective 370 if the downstream turbine is positioned at this location, but could work counterproductive if it is not. If the downstream turbine is located in the negative y direction in Figure 7, it would experience increased wake overlap and lose power compared to the baseline case. This could be an argument for applying wake mixing in real-world wind farms, as the wind direction is rarely known exactly, and varies over time. This is also argued in Taschner et al. (2024). This study shows that, in the case of close to
- 375 full wake overlap, the helix strategy provides power gains that are more robust to wind direction changes.

Finally, Fig. 7 shows that the IPC-based control strategies (helix and side-to-side) are not nearly as effective as the other two strategies. This is likely related to the skewed shape of the wake: As the wake is not cylindrical, these strategies might not be as successful in creating the helical structures that enable wake mixing in lower-veer conditions. Note that Brown et al. (2025) comes to the same conclusion by investigating the mean and turbulent entrainment in the wake of the turbines. This result is further discussed in the next section.

3.3 Two-turbine results

380

385

In this section, we discuss the results from simulations run with two turbines. The second turbine is located 5D downstream of the first turbine with, unless stated otherwise, no lateral offset. First, we discuss the results in the medium-WS, low-TI (MSLT) case, followed by a comparison with the low-veer MSLT-LV and medium turbulence MSMT cases. Finally, we discuss the results from the low- and high-WS cases.

3.3.1 Effect of wind farm layout

In this section, we discuss the results from the medium-WS, low-TI (MSLT) case, as defined in Table 2, focusing our attention on the turbine power and DEL of four relevant components through the method described in Sect. 2.4. We study the effect of wind farm layout on the turbine performance by varying the location of the downstream turbine.

- For a two-turbine wind farm, with the second turbine aligned with the first 5D downstream and running with a baseline controller, the power and critical DELs are plotted in Fig. 8. Looking at the top row, representing the upstream turbine, we see the same power losses as observed in Sect. 3.2 on the *y*-axis, with wake steering resulting in the biggest and side-to-side resulting in the smallest power loss. On the *y*-axes, we see the effect on DEL. What stands out is that wake steering has very minimal effect on the DELs compared to the wake mixing strategies. The blades and tower are most impacted by the pulse strategy while the internal components (yaw bearing and low-speed shaft) are more impacted by the AWM strategies using
- IPC. The helix and side-to-side strategy generally lead to similar DELs, except for the yaw bearing moments. This can be explained by the lack of rotor tilt moment excitation in the side-to-side method, which subsequently does not excite the yaw bearing pitch moment as the helix strategy does.

The second row shows the results for the downstream turbine. The only strategy that has any substantial impact on the blades 400 is the pulse, although the impact is still significantly lower than the impact on the upstream blades. The downstream tower is most affected by the side-to-side strategy. A possible explanation for this is the increased turbulent entrainment at the left and right side of the wake documented in the companion paper (Brown et al., 2025). Wake steering, on the other hand, reduces the tower DEL of the downstream turbine by a factor of 2. The effect of different control strategies on the internal components is much smaller but again shows that wake steering can lower downstream turbine DELs.

405 Comparing rows 1 and 2, it should be noted that although some of the turbine 1 DELs increase significantly when AWM is applied, all but the blade loads are still comparable or lower than the loads of the waked second turbine. In other words, although the loads increase, they are still close to the loads of a normally operated waked turbine.



**Figure 8.** DELs plotted on the *x*-axis versus generator power on the *y*-axis for the different control strategies in the medium-WS, low-TI (MSLT) case. The first row shows the results for the upstream turbine, the second row shows the results for the downstream turbine, and the third row sums the results of both turbines. The different columns represent the DEL for different turbine components, as labeled at the top.

Finally, the third row shows the sum of results from the first two rows. Note that these results are not weighted in any way, and the DELs should therefore not be considered equivalent to the likelihood of damage to any of the two turbines in the wind
farm. Clearly, the ideal control strategy would live in the upper-left corner of the plots in this row, as this would represent the highest power capture while the turbines experience the lowest DELs. Wake steering can actually be found closest to this upper-left corner in all the plots, indicating that, in these conditions, wake steering is the superior control strategy.

Next, we study the impact of different wind directions on the effectiveness of the WFFC strategies. In these simulations, the downstream turbines are no longer aligned with the wind direction but are instead offset by -0.5D (120 m) in either direction. This corresponds to a wind direction change of 5.72°. Note that the yaw angle offset of the upstream turbine is adjusted such

that the wake is steered away from the downstream turbine, i.e., for an offset of 0.5D, the yaw angle is  $-20^{\circ}$  instead of  $20^{\circ}$ .

Figure 9 shows the time-averaged flow fields when the downstream turbine is offset by -0.5D. It demonstrates how, on average, all the wake mixing strategies manage to create a narrower wake, thus increasing the wind speed experienced by the downstream turbine while losing minimal power at the upstream turbine. However, comparatively, the pulse method appears to be the most effective, substantially narrowing the wake from 2.5D onward. As expected, though, wake steering is the most

420

415



Figure 9. Average flow field at hub height for the two-turbine wind farm when different control strategies are applied. The second turbine is offset by -0.5D or 120 m at 5D downstream, equivalent to a wind direction change of  $5.72^{\circ}$  compared to the aligned case.

effective control strategy when there is a lateral offset in turbine locations, as the bottom plot in Fig. 9 shows that the wake is steered almost completely away from the downstream turbine. As a result, the power uplift is also greatest for wake steering, as shown in Fig. 10.

The power and DELs on turbine 1 are equivalent to those shown in Fig. 8, as the upstream turbine operates in the same conditions regardless of the downstream turbine's location. On the downstream turbine, however, the loads are generally lower than in the aligned case – note that the scales of Figs. 8 and 10 are not identical. As the turbine is now experiencing more less-turbulent freestream flow, the DEL on all components is also reduced substantially. Compared to baseline control, wake steering now has a slightly adverse effect on the yaw bearing and low-speed shaft DELs, whereas in the aligned case it reduced these loads.

430 In terms of power production, wake steering is, as expected, clearly the best choice in this scenario, increasing overall power production by 7.8%. The wake mixing strategies score substantially worse, with 0.9%, 3.3%, and 2.0% power uplift for helix, pulse, and side-to-side strategies, respectively. Note that in these conditions, the side-to-side strategy performs better than the helix, even though it requires lower pitch actuation and subsequently also has generally lower DELs. This shows that



Figure 10. DELs plotted on the x-axis versus generator power on the y-axis for the different control strategies in the medium-WS, low-TI (MSLT) case, with a lateral turbine offset of -0.5D and 0.5D. The first row shows the results for the upstream turbine, the second row shows the results for the downstream turbine, and the third row sums the results for both turbines. The different columns represent the DEL for different turbine components, as labeled at the top.

the additional pitch actuation that is intended to excite the wake in the vertical direction is clearly not effective and perhaps even counterproductive in these high-veer, high-shear wind conditions.

Comparing these results to the estimated power gains from Fig. 7, we find that these estimates are close but not exact. The estimated uplift for the helix is very close to the uplift found in the two-turbine simulation, but the side-to-side strategy performs slightly better than predicted. For the pulse, Fig. 7 predicted a 5 % power uplift, whereas only a 3.3 % uplift is achieved. The opposite is true for wake steering, which performs substantially better than the 4 % power uplift estimated based on the flow field.

440 field

Finally, Fig. 10 also shows the power and DELs for a lateral offset of the downstream turbine of +0.5D. The first row of this figure is still equivalent to the cases with a different lateral offset, but the second row is remarkably different from the -0.5D offset case. Due to the shape of the wake, shown in Fig. 3, the wake loss at 0.5D lateral offset is substantially higher than at -0.5D. As a result, wake mixing strategies, specifically the pulse, are able to create more power uplift at the downstream

turbine at the same cost for the upstream turbine. This is also visible in Fig. 7, where the negative offset direction clearly shows a higher power uplift than the positive offset direction.

Overall, all strategies still lead to a power uplift compared to the baseline: The helix and side-to-side strategies both increase power by 1.4 %, the pulse strategy increases power by 10.8 %, and wake steering increases power by 11.0 %. Note that although the power uplift for the IPC-based AWM strategies is limited, they correspond well with the expected uplift predicted in Fig. 7.

450 The pulse strategy, on the other hand, significantly outperforms the expected power uplift obtained from the single-turbine simulations, although they did predict this downstream turbine location to be the "sweet spot" in terms of power uplift.

Investigating the horizontal axes of Fig. 10, we see that wake steering has the lowest DELs for all signals except for the downstream turbine low-speed shaft. The DELs of the AWM strategies are in line with what we have seen at different lateral offsets. Overall, wake steering should still be considered the best strategy in terms of combined power and loads.

### 455 3.3.2 Effect of veer and turbulence

In this section, we study the results obtained in the cases with low wind veer, as defined in Table 2. First, we consider the results in the MSLT-LV case, which is similar to the conditions discussed in the previous section but with substantially lower wind veer and shear. Subsequently, the wakes in these conditions are more circular, resulting in higher downstream wake losses. The ensuing power and DEL results are shown in Fig. 11.

- 460 If we compare the first row, i.e., the first turbine, with the results in Fig. 8, we observe very similar behavior between the two cases. The overall power is slightly higher in the low-veer case, which makes sense, as the rotor is more uniformly aligned with the wind in this case. The DELs, too, are similar to the high-veer case, with the pulse strategy mostly increasing the tower DEL, and the helix and side-to-side strategies increasing the DELs of the yaw bearing and low-speed shaft.
- The second row of Fig. 11 shows some significant differences with the high-veer case. First and foremost, the power gained at the second turbine when AWM is applied on the upstream turbine is substantially higher here. This likely has to do with the fact that we now have full wake overlap at the downstream turbine, whereas in the previous case, the veered wind already naturally created some recovery at the downstream turbine location (see Fig. 3). Note that the absolute power production of the downstream turbines for all control cases is still lower than in the MSLT case, but as the baseline power is now lower, the relative power uplift is bigger. Wake steering is still increasing downstream power the most, but the pulse and helix now have a
- 470 similar uplift. In terms of loads, the differences with the MSLT case are smaller. Most notably, the tower DEL is not decreased as significantly with wake steering as was the case in Fig. 8. This is likely caused by the fact that the downstream rotor now experiences partial wake overlap, whereas in the MSLT case, the wake was steered away from the downstream turbine more successfully.

Finally, the bottom row of Fig. 11 displays the sum of the results from the first two rows. Whereas in the MSLT case, this
showed wake steering as a clear winner, the picture is a lot more ambiguous in low-veer conditions. Overall, wake steering
still performs best in terms of DELs, but is now surpassed in terms of power production by all AWM strategies. The pulse and
helix strategies are on par in terms of power production, with, again, the pulse having higher blade and tower loads and the
helix a bigger impact on the yaw bearing and low-speed shaft. In these conditions, picking the most preferable WFFC strategy

therefore depends on how much priority is given to increasing wind farm power and whether increasing the DEL on certain 480 specific components might be more acceptable than on others.



**Figure 11.** DELs plotted on the *x*-axis versus generator power on the *y*-axis for the different control strategies in the medium-WS, low-TI, low-veer (MSLT-LV) case. The first row shows the results for the upstream turbine, the second row shows the results for the downstream turbine, and the third row sums the results for both turbines. The different columns represent the DEL for different turbine components, as labeled at the top.

Next, we study the turbine behavior in the medium-WS, medium-TI (MSMT) case. This case has higher turbulence than any of the other cases studied in this paper, which is expected to have a number of effects on turbine performance. Turbulence induces natural wake mixing, resulting in lower power deficits at waked downstream turbines. This also affects the potential of WFFC, as a lower power deficit means the achievable uplift at the downstream turbine is lower as well. Additionally, variations in wind speed and direction inherent to turbulence are known to result in higher DELs.

485

The results of these simulations are shown in Fig. 12. The first important observation taken from these plots is that the DELs are, contradictory to literature, lower than in the low-TI case. This is most likely explained by the lower wind veer and shear in the medium-TI simulations. The higher TI causes variations in the moments experienced by the turbine, but at a relatively slow time scale. In the low-TI case, however, the wind veer and shear cause variations at the faster, once-per-rotation (1P)

490 frequency, resulting in generally higher DELs. Compared to Fig. 11, the relative change in DELs for all WFFC signals is very similar between the low- and medium-TI cases.

A second observation from Fig. 12 is that the relative power uplift achieved by the different WFFC strategies matches the low-TI, low-veer case much better than the low-TI, high-veer case. Similar to this case, the pulse and helix strategies are on par as the strategies with the highest uplift, while wake steering results in lower DELs at the expense of lower power production.

495 The relative power uplift compared to the baseline case is, as expected, generally lower than in the low-TI cases. However, for the helix strategy, the power uplift in the MSMT case, 5.2 %, is higher than in the MSLT case (3.6 %). Wake steering and the pulse strategy, on the other hand, only generate half (3.7 %) and two-thirds (5.4 %) of the relative power uplift, respectively, compared to the MSLT case, while the side-to-side method remains about equally effective with a 2.9 % power uplift. This result clearly shows that the effect of veer on WFFC effectiveness is substantial, and should be considered when determining the optimal WFFC strategy.



**Figure 12.** DELs plotted on the *x*-axis versus generator power on the *y*-axis for the different control strategies in the medium-WS, medium-TI (MSMT) case. The first row shows the results for the upstream turbine, the second row shows the results for the downstream turbine, and the third row sums the results for both turbines. The different columns represent the DEL for different turbine components, as labeled at the top.

## 3.3.3 Effect of wind speed

505

Next, we study the results from the low-WS, low-TI (LSLT) case. This case is similar to the MSLT case in a lot of ways. Like this previously discussed case, it features below-rated wind speed and high wind veer. Subsequently, the results from this case resemble the MSLT results to a high degree. This is shown in Fig. 13, showing again the power and DELs for the two-turbine wind farm in these conditions. The most notable difference to the MSLT case is the fact that the pulse strategy loses some of its ability to increase wind farm power. The DEL results look very similar to the MSLT case, with the most significant difference being that all control strategies now lead to a general decrease in tower DELs. Subsequently, wake steering is also the preferred WFFC strategy in these simulations, generally reducing overall DELs while resulting in the highest power uplift.



Figure 13. DELs plotted on the x-axis versus generator power on the y-axis for the different control strategies in the low-WS, low-TI (LSLT) case. The first row shows the results for the upstream turbine, the second row shows the results for the downstream turbine, and the third row sums the results for both turbines. The different columns represent the DEL for different turbine components, as labeled at the top.

510

Finally, we examine the results from the high-WS, low-TI (HSLT) case. As discussed in Sect. 2.2.1, the wind speed is above rated in this simulation case. This makes this case significantly different from the previous cases. First, applying WFFC on the upstream turbine no longer leads to a loss in turbine power. Therefore, the uplift at the downstream turbine comes without the cost of power loss at the upstream machine. Second, in the below-rated cases, the baseline pitch angle was constant at zero. In

above-rated conditions, the pitch angle is regulated by the baseline controller to regulate the turbine power to the rated value. The AWM pitch signal is then superimposed on this baseline pitch control signal.

515

The pulse strategy, in which all blades are pitched collectively, leads to an undesired interaction between the baseline controller and the AWM signal. The fluctuations sent by the active wake controller interfere with the objective of the baseline controller to regulate the power at rated value. As a result, the baseline controller counteracts the AWM signal in order to keep power constant. This leads to a controller that does not demonstrate the desired variations in thrust that make the pulse a successful WFFC strategy. To circumvent this issue, the baseline pitch controller is turned off in the above-rated pulse case.

520 Instead, the baseline controller pitch signal for the pulse simulation is set to be constant at the average angle obtained from the baseline simulation. The AWM signal is now again superimposed on top of this baseline controller signal. Note that this does not lead to behavior that can realistically be expected from an above-rated turbine, and the results from the pulse simulation should therefore be taken with this in mind. However, for completeness, these results are still included in our analysis.



Figure 14. DELs plotted on the x-axis versus generator power on the y-axis for the different control strategies in the high-WS, low-TI (HSLT) case. The first row shows the results for the upstream turbine, the second row shows the results for the downstream turbine, and the third row sums the results for both turbines. The different columns represent the DEL for different turbine components, as labeled at the top. Note that the increased power in the pulse simulation for the first turbine is caused by adjustments made to the controller.

Fig. 14 shows the results for the above-rated conditions. As explained, the power of the first turbine is not truly relevant here. The DELs are affected more significantly in these higher wind speeds, and the baseline DELs are already higher than for any 525 WFFC case in the lower wind speed simulations. Overall, the trend is similar to the below-rated simulations, but with wake steering leading to the lowest (if any) increase in DELs. The DELs of the downstream turbine are affected less by the WFFC strategy implemented, with only the tower moments increasing significantly for the pulse case. In these above-rated conditions, wake steering is the most effective strategy in terms of power maximization, surpassing the pulse despite the artificial power 530 uplift the latter sees at the upstream turbine.

The results for all aligned two-turbine simulations investigated in this study are summarized in Table 7 for power and Table 8 for DELs. The power results show that each WFFC strategy investigated in this paper is able to increase wind farm power production in every wind condition studied. Wake steering is generally the most effective strategy in veered wind conditions, followed closely by the pulse strategy. The helix strategy specifically shows a direct relationship between skewedness of the wake and loss of power uplift.

535

Table 7. The power uplift of each WFFC strategy relative to the baseline controller implementation, in each of the wind condition cases studied. Note that the pulse case at HSLT (marked with a \*) should be considered academically relevant only, not practically, as the baseline controller was deactivated for the above-rated conditions, resulting in very large power and thrust variations on the upstream turbine.

Case		Helix			Pulse			Side-to-side			g	
Turbine	T1	T2	Total	T1	T2	Total	T1	T2	Total	T1	T2	Total
LSLT	-3.90%	+35.64%	+5.31 %	-4.21 %	+49.36%	+8.27%	-1.44%	+29.96%	+3.66~%	-13.96%	+91.81 %	+10.68 %
MSLT	-3.18%	+23.09%	+3.62 %	-2.18%	+34.66%	+7.34 %	-1.11 %	+16.03%	+3.32%	-13.08%	+67.93%	+7.33 %
MSLT-LV	-4.17%	+48.38%	+9.47 %	-4.58%	+50.35%	+6.82 %	-3.19%	+27.31%	+3.14 %	-11.43%	+55.31 %	+2.42 %
MSMT	-2.10%	+29.20%	+5.21 %	-2.98%	+33.02%	+5.43 %	-1.26%	+16.79%	+2.95 %	-13.67%	+60.80%	+3.73 %
HSLT	+0.00%	+13.08%	+4.86 %	+1.83 %*	+19.72%*	+8.49 %*	+0.00%	+7.97 %	+2.97 %	+0.00%	+23.72%	+8.83 %

In terms of DELs, the results for all simulations with respect to baseline control is summarized in Table 8. We see here that at lower wind speeds, the impact of using WFFC on DELs of the upstream turbine is generally smaller than at higher wind speeds. Furthermore, the impact of a veered wake on the relative DEL change is generally small. Overall, we can conclude that wake steering performs substantially better than the AWM strategies in terms of DELs, with loads generally decreasing or only increasing by a small amount.

540

#### 4 **Conclusions and discussion**

545

In this paper (and its companion paper, Brown et al. (2025)), we have investigated and compared the performance of four different WFFC strategies that are currently considered in literature as viable options to increase wind farm power. Highfidelity flow simulations were set up in AMR-Wind to replicate average wind speeds, turbulence intensities, and wind veer and shear obtained from lidar measurements in a proposed offshore wind farm site. These datasets exhibited significant wind veer in low-turbulence conditions, which showed to have significant effects on the performance of different WFFC strategies.

**Table 8.** The relative effect on DEL of each WFFC strategy relative to the baseline controller implementation, in each of the wind condition cases studied. All loads are relative to the baseline case for that turbine, where it should be noted that the DELs for the downstream baseline case are generally higher than for the upstream turbine to start with. Note also that the pulse case at HSLT (marked with a \*) should be considered academically relevant only, not practically, as the baseline controller was deactivated for the above-rated conditions, resulting in very large power and thrust variations on the upstream turbine.

		He	lix	Pul	Pulse		Side-to-side		teering
DEL	Case	T1	Т2	T1	T2	T1	Т2	T1	Т2
	LSLT	+8.85%	-0.32%	+6.02%	+1.44%	+6.78%	+0.51%	-0.81%	-0.20 %
Diada na sé	DELCaseT1T2T1T2T1T2T1T2HeirLSLT+8.85 %-0.32 %+6.02 %+1.44 %+6.78 %+0.51 %Hae rootMSLT+23.47 %+0.36 %+31.30 %+4.52 %+18.53 %+0.75 %MSLT-LV+19.02 %-0.21 %+38.85 %+4.53 %+18.30 %-0.68 %MSMT+22.97 %+2.61 %+35.77 %+7.09 %+20.84 %+0.75 %HSLT+44.79 %+3.55 %+65.90 %*+7.27 %*+30.85 %+1.45 %MSLT+43.75 %-14.51 %+438.19 %-7.55 %+3.02 %+31.59 %MSLT+22.41 %-18.10 %+410.77 %+14.56 %+20.68 %+9.50 %MSLT+26.41 %+6.00 %+136.95 %*+41.22 %*-0.39 %-4.83 %MSLT+26.41 %+6.00 %+136.95 %*+41.22 %*-0.39 %-4.83 %MSLT+329.10 %+0.47 %+36.36 %-5.61 %+43.61 %+0.28 %MSLT+321.45 %+15.15 %+36.63 %11.74 %+67.96 %+13.65 %MSLT+329.30 %-2.30 %+48.39 %+0.36 %+127.90 %-5.38 %MSLT+381.03 %+5.62 %+48.85 %+5.20 %+141.46 %+3.76 %MSLT+322.83 %-14.13 %-0.53 %-16.05 %+302.95 %-33.55 %MSLT+326.59 %-5.35 %+4.09 %-20.23 %+309.90 %-14.19 %MSLT+326.59 %-5.3	-3.94%	-0.73%						
blade root	MSLT-LV	+19.02%	-0.21%	+38.85%	PulseSide-to-sideWake steeringT2T1T2T1T2 $+1.44\%$ $+6.78\%$ $+0.51\%$ $-0.81\%$ $-0.20\%$ $+4.52\%$ $+18.53\%$ $+0.75\%$ $-3.94\%$ $-0.73\%$ $+4.53\%$ $+18.30\%$ $-0.68\%$ $-2.57\%$ $-3.49\%$ $+7.09\%$ $+20.84\%$ $+0.75\%$ $-2.21\%$ $-0.25\%$ $+7.27\%$ $+30.85\%$ $+1.45\%$ $-1.03\%$ $-0.57\%$ $-27.82\%$ $+19.76\%$ $-51.38\%$ $-59.54\%$ $-34.80\%$ $-7.55\%$ $+3.02\%$ $+31.59\%$ $-3.94\%$ $-55.50\%$ $-6.93\%$ $+1.44\%$ $-4.82\%$ $-10.36\%$ $-27.87\%$ $* +41.22\%$ $-0.39\%$ $-4.83\%$ $+9.97\%$ $-9.12\%$ $-5.61\%$ $+43.61\%$ $+0.28\%$ $-11.54\%$ $-6.68\%$ $11.74\%$ $+67.96\%$ $+13.65\%$ $-5.62\%$ $-5.06\%$ $+0.36\%$ $+127.90\%$ $-5.38\%$ $-7.20\%$ $-2.95\%$ $+7.31\%$ $+88.55\%$ $+10.07\%$ $-9.37\%$ $-4.86\%$ $-20.23\%$ $+309.90\%$ $-14.19\%$ $+0.31\%$ $-25.91\%$ $-2.88\%$ $+307.27\%$ $+8.37\%$ $-3.15\%$ $-1.33\%$ $-5.67\%$ $+243.80\%$ $+7.67\%$ $-5.40\%$ $-12.65\%$ $+6.43\%$ $+361.03\%$ $+9.42\%$ $+3.37\%$ $+15.45\%$				
	MSMT	MSMT         +22.97 %         +2.61 %         +35.77 %         +7.09 %         +20.84 %         +0.75 %           HSLT         +44.79 %         +3.55 %         +65.90 %*         +7.27 %*         +30.85 %         +1.45 %           LSLT         -23.71 %         -34.00 %         +0.42 %         -27.82 %         +19.76 %         -51.38		+0.75%	-2.21%	-0.25%			
	HSLT	+44.79%	+3.55%	+65.90%*	$+7.27\%^{*}$	+30.85%	+1.45%	-1.03%	-0.57%
	LSLT	-23.71%	-34.00%	+0.42%	-27.82%	+19.76%	-51.38%	-59.54%	-34.80%
Towor boss	MSLT	+43.75%	-14.51%	+438.19%	-7.55%	+3.02%	+31.59%	-3.94%	-55.50%
Tower base	MSLT-LV	+28.47%	-18.10%	+410.77%	+14.56~%	+20.68%	+9.50%	-10.64%	-8.08%
	MSMT	+16.39%	+18.80%	+202.60%	-6.93%	+1.44%	-4.82%	-10.36%	-27.87%
	HSLT	+26.41%	+6.00%	+136.95%*	$+41.22\%^{*}$	-0.39%	-4.83%	+9.97%	-9.12%
	LSLT	+329.10%	+0.47%	+36.36%	-5.61%	+43.61%	+0.28%	-11.54%	-6.68%
Vow booring	MSLT	+321.45%	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	-5.06%					
raw bearing	MSLT-LV	+329.30%	-2.30%	+48.39%	+0.36~%	+127.90%	-5.38%	-7.20%	-2.95%
	MSMT	+245.98%	+6.53%	+34.55%	+7.31%	+88.55%	+10.07%	-9.37%	-4.86%
	HSLT	+381.03%	+5.62%	+48.85%*	+5.20%*	+141.46%	+3.76%	-5.17%	+5.07%
	LSLT	+322.83%	-14.13%	-0.53%	-16.05%	+302.95%	-33.55%	-3.06%	-19.89%
Low speed sheft	MSLT	+326.59%	-5.35%	+4.09%	-20.23%	+309.90%	-14.19%	+0.31%	-25.91%
Low-speed shart	MSLT-LV	+300.77%	+11.67%	-0.13%	-2.88%	+307.27%	+8.37%	-3.15%	-1.33%
	MSMT	+248.26%	+9.16%	+8.20%	-5.67%	+243.80%	+7.67%	-5.40%	-12.65%
	HSLT	+373.20%	+19.98%	+5.67%*	$+6.43\%^{*}$	+361.03%	+9.42%	+3.37%	+15.45%

First, the skewing of the wakes seen in this study were compared to results from literature. This comparison found that the skewing is in line with results from simulations using a different LES code. However, comparing our results with data from onshore lidar measurements shows that these real-world wakes are skewed substantially less relative to the wind veer. It is possible that this is caused by a difference between onshore and offshore conditions, but also that it is a undesired side-effect of how the simulations are set up. More research is therefore needed to conclude which one of these hypotheses holds true.

Regardless of wind speed, the simulations presented in this paper showed that when the wakes are highly skewed due to wake veer, wake steering is generally superior to the different wake mixing strategies investigated. The pulse strategy, where all blades are dynamically pitched collectively, showed similar effectiveness in terms of power uplift, but at the cost

550

555 of substantially higher DELs. The wake mixing strategies using individual pitch control – the counterclockwise helix and the side-to-side strategy – still achieved a power uplift, but less significant than the former two strategies.

The study further shows that, regardless of wind conditions, the pulse strategy leads to the most significant increase in DELs on the upstream turbine blades and tower. The yaw bearings and low-speed shaft of the upstream turbine, on the other hand, are more affected by the helix and side-to-side strategies. Comparatively, wake steering has minimal effect on the upstream turbine

560 loads, and in some cases even decreases them. Equivalently, the downstream turbine is affected much less by the control action implemented on the upstream turbine, with generally smaller changes in structural DELs regardless of the control strategy

585

implemented.
Additionally, we have executed simulations in otherwise similar wind conditions, but with lower veer and shear. These simulations showed markedly different results in terms of wind farm power uplift, with the pulse and helix wake mixing
strategies now being more effective than wake steering. In terms of DELs, the results were similar to the high-veer case. Simulations at higher turbulence intensity showed similar results. This is more in line with previous studies, which were also executed under low-veer conditions. These results highlight the importance of wind veer, which has so far not been given much attention in WFFC simulation research, on the effectiveness of different WFFC strategies. The results presented here demonstrate that veer, or more accurately, the wake skewing caused by veer, is a much more important variable to consider
than the wind speed or turbulence intensity when choosing the optimal WFFC strategy. High-wind-veer conditions generally

570 than the wind speed or turbulence intensity when choosing the optimal WFFC strategy. High-wind-veer conditions generally increase the effectiveness of wake steering while reducing the power uplift achieved with wake mixing strategies that use individual pitch control.

The results presented in this paper raise the question whether wake steering should always be preferred over wake mixing in low-turbulence conditions. The authors stress caution in making such claims. Most of the wakes seen in this study are highly skewed, and it is questionable whether a real-life wake would skew to the same degree. Furthermore, wake steering has another possible downside that is not captured in this study. In real wind farms, the wind direction is constantly changing, and the exact wind direction is not always known instantly or accurately at each turbine. As a result, wake steering sometimes results in a power loss in case of near-perfect alignment, as the wake can be accidentally steered toward a downstream turbine instead of away from it. Furthermore, yaw actuators are not able to respond to changes in wind conditions as quickly as pitch actuators. The effects of time-varying or uncertain wind conditions are not captured in the simulations presented here.

To conclude, this study shows that wind veer plays a major role on how effective different WFFC strategies are and should therefore always be considered as a variable when choosing the optimal strategy. Both wake mixing and wake steering strategies can achieve substantial power uplifts in all wind conditions. However, wake steering has shown to be the most reliable tool to achieve wind farm power uplift regardless of wind conditions, at minimal to no cost on the turbine DELs. Nonetheless, to conclusively say that wake steering outperforms wake mixing in realistic wind conditions, additional research is necessary.

Future studies should focus on time-varying wind conditions as well as wake skewing analysis and comparison with field measurements. Furthermore, this paper's scope is limited to a simple two-turbine wind farm, and can not be extrapolated directly to larger farms. Studies on larger wind farm layouts, potentially with WFFC applied to downstream turbines, is needed to validate whether the results presented here still hold. Finally, lidar measurements on the wake of a full-scale turbine operating

590 using different control strategies would be the next step in studying the effects of the control strategies on the wake and therefore on possible downstream turbines.

*Author contributions.* The NREL team (JF, ES, PF) was responsible for the running the majority of the simulations presented in this paper, for executing the analysis, and for writing the paper. Sandia National Laboratories (KB, LC, GY) developed the precursor simulations, and assisted in running simulations and analysis.

595 Competing interests. At least one of the (co-)authors is a member of the editorial board of Wind Energy Science.

Acknowledgements. This work was authored in part by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy, LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by U.S. Department of Energy Office of Energy Efficiency and Renewable Energy Wind Energy Technologies Office. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government. The U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or

600

article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes. A portion of this research was performed using computational resources sponsored by the U.S. Department of Energy's Office of Energy Efficiency and Renewable Energy and located at the National Renewable Energy Laboratory.

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of

605

Sandia, LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

# References

625

640

- Abbas, N. J., Zalkind, D. S., Pao, L., and Wright, A.: A reference open-source controller for fixed and floating offshore wind turbines, Wind Energy Science, 7, 53–73, 2022.
- 610 Annoni, J., Gebraad, P. M., Scholbrock, A. K., Fleming, P. A., and Wingerden, J.-W. v.: Analysis of axial-induction-based wind plant control using an engineering and a high-order wind plant model, Wind Energy, 19, 1135–1150, 2016.
  - Bachant, P., Ireland, P., Burrows, B., Qiao, C., Duncan, J., Zheng, D., and Dua, M.: Development and validation of a hybrid data-driven model-based wake steering controller and its application at a utility-scale wind plant, Wind Energy Science Discussions, 2024, 1–36, 2024.
- Batchelor, G. and Gill, A.: Analysis of the stability of axisymmetric jets, Journal of fluid mechanics, 14, 529–551, 1962.
   Bodini, N., Zardi, D., and Lundquist, J. K.: Three-dimensional structure of wind turbine wakes as measured by scanning lidar, Atmospheric Measurement Techniques, 10, 2881–2896, 2017.
  - Bossanyi, E. and Ruisi, R.: Axial induction controller field test at Sedini wind farm, Wind Energy Science, 6, 389-408, 2021.
- Brazell, M., Ananthan, S., Vijayakumar, G., Cheung, L., Sprague, M., Team, E. E. C. P., Team, H. F. M. P., et al.: Amr-wind: adaptive
   mesh-refinement for atmospheric-boundary-layer wind energy simulations, in: APS Division of Fluid Dynamics Meeting Abstracts, pp. T29–007, 2021.
  - Brown, K., Houck, D., Maniaci, D., Westergaard, C., and Kelley, C.: Accelerated wind-turbine wake recovery through actuation of the tip-vortex instability, AIAA Journal, 60, 3298–3310, 2022.
  - Brown, K., Yalla, G., Cheung, L., deVelder, N., Houck, D., Frederik, J., Simley, E., and Fleming, P.: Comparison of wind farm control strategies under a range of realistic wind conditions: wake quantities of interest, Wind Energy Science, 2025.
- Campagnolo, F., Petrović, V., Bottasso, C. L., and Croce, A.: Wind tunnel testing of wake control strategies, in: 2016 American Control Conference (ACC), pp. 513–518, 2016.

- 630 Churchfield, M. and Lee, S.: NWTC design codes-SOWFA, Tech. rep., National Renewable Energy Laboratory (NREL), 15013 Denver West Parkway, Golden, CO. http://wind.nrel.gov/designcodes/simulators/SOWFA, 2012.
  - Churchfield, M. J. and Sirnivas, S.: On the effects of wind turbine wake skew caused by wind veer, in: 2018 wind energy symposium, p. 0755, 2018.
  - Ciri, U., Rotea, M. A., and Leonardi, S.: Model-free control of wind farms: A comparative study between individual and coordinated

extremum seeking, Renewable energy, 113, 1033–1045, 2017.

- Coquelet, M., Moens, M., Bricteux, L., Crismer, J.-B., and Chatelain, P.: Performance assessment of wake mitigation strategies, in: Journal of Physics: Conference Series, vol. 2265, p. 032078, IOP Publishing, 2022.
- Coquelet, M., Gutknecht, J., Van Wingerden, J., Duponcheel, M., and Chatelain, P.: Dynamic individual pitch control for wake mitigation: Why does the helix handedness in the wake matter?, in: Journal of Physics: Conference Series, vol. 2767, p. 092084, IOP Publishing, 2024.
- DNV: NYSERDA Floating LiDAR Buoy Data, https://oswbuoysny.resourcepanorama.dnv.com/download/ f67d14ad-07ab-4652-16d2-08d71f257da1, accesssed: 2023-09-30, 2023.

Cheung, L. C., Brown, K. A., Houck, D. R., and Develder, N. B.: Fluid-dynamic mechanisms underlying wind turbine wake control with Strouhal-timed actuation, Energies, 17, 865, 2024.

Doekemeijer, B. M., Kern, S., Maturu, S., Kanev, S., Salbert, B., Schreiber, J., Campagnolo, F., Bottasso, C. L., Schuler, S., Wilts, F., et al.: Field experiment for open-loop yaw-based wake steering at a commercial onshore wind farm in Italy, Wind Energy Science, 6, 159–176,

645

660

2021.

El-Asha, S., Zhan, L., and Iungo, G. V.: Quantification of power losses due to wind turbine wake interactions through SCADA, meteorological and wind LiDAR data, Wind Energy, 20, 1823–1839, 2017.

Fleming, P., Gebraad, P. M., Lee, S., van Wingerden, J.-W., Johnson, K., Churchfield, M., Michalakes, J., Spalart, P., and Moriarty, P.: Simulation comparison of wake mitigation control strategies for a two-turbine case, Wind Energy, 18, 2135–2143, 2015.

650 Fleming, P., King, J., Dykes, K., Simley, E., Roadman, J., Scholbrock, A., Murphy, P., Lundquist, J. K., Moriarty, P., Fleming, K., et al.: Initial results from a field campaign of wake steering applied at a commercial wind farm–Part 1, Wind Energy Science, 4, 273–285, 2019.

Fleming, P., King, J., Simley, E., Roadman, J., Scholbrock, A., Murphy, P., Lundquist, J. K., Moriarty, P., Fleming, K., van Dam, J., et al.: Continued results from a field campaign of wake steering applied at a commercial wind farm: Part 2, Wind Energy Science Discussions, 2020, 1–24, 2020.

- 655 Frederik, J., Doekemeijer, B., Mulders, S., and van Wingerden, J.-W.: On wind farm wake mixing strategies using dynamic individual pitch control, in: Journal of Physics: Conference Series, vol. 1618, p. 022050, IOP Publishing, 2020a.
  - Frederik, J. A. and van Wingerden, J.-W.: On the load impact of dynamic wind farm wake mixing strategies, Renewable Energy, 194, 582–595, 2022.

- Frederik, J. A., Weber, R., Cacciola, S., Campagnolo, F., Croce, A., Bottasso, C., and van Wingerden, J.-W.: Periodic dynamic induction control of wind farms: proving the potential in simulations and wind tunnel experiments, Wind Energy Science, 5, 245–257, 2020c.
  - Gaertner, E., Rinker, J., Sethuraman, L., Zahle, F., Anderson, B., Barter, G. E., Abbas, N. J., Meng, F., Bortolotti, P., Skrzypinski, W., et al.: IEA wind TCP task 37: definition of the IEA 15-megawatt offshore reference wind turbine, Tech. rep., National Renewable Energy
- 665 Laboratory (NREL), Golden, CO (United States), 2020.
  - Howland, M. F., Lele, S. K., and Dabiri, J. O.: Wind farm power optimization through wake steering, Proceedings of the National Academy of Sciences, 116, 14495–14500, 2019a.

Howland, M. F., Lele, S. K., and Dabiri, J. O.: Wind farm power optimization through wake steering, Proceedings of the National Academy of Sciences, 116, 14 495–14 500, 2019b.

- 670 Howland, M. F., Ghate, A. S., Lele, S. K., and Dabiri, J. O.: Optimal closed-loop wake steering–Part 1: Conventionally neutral atmospheric boundary layer conditions, Wind Energy Science, 5, 1315–1338, 2020.
  - Huang, L., Mulders, S. P., Taschner, E., and van Wingerden, J.-W.: Enhancing Wake Mixing in Wind Farms by Multi-Sine Signals in the Helix Approach, in: 2023 American Control Conference (ACC), pp. 824–830, IEEE, 2023.

Korb, H., Asmuth, H., and Ivanell, S.: The characteristics of helically deflected wind turbine wakes, Journal of Fluid Mechanics, 965, A2, 2023.

675 2023

- Lawrence Berkeley National Laboratory, National Renewable Energy Laboratory, and Sandia National Laboratories: AMR-Wind v2.0.0, https://github.com/Exawind/amr-wind, 2024.
- Marden, J., Ruben, S., and Pao, L.: Surveying game theoretic approaches for wind farm optimization, in: 50th AIAA aerospace sciences meeting including the new horizons forum and aerospace exposition, p. 1154, 2012.

Frederik, J. A., Doekemeijer, B. M., Mulders, S. P., and van Wingerden, J.-W.: The helix approach: Using dynamic individual pitch control to enhance wake mixing in wind farms, Wind Energy, 23, 1739–1751, 2020b.

680 Martinez, J. J. P. and Coussy, J.: Wake steering experiments in onshore and offshore wind farms, in: Journal of Physics: Conference Series, vol. 2767, p. 092090, IOP Publishing, 2024.

Mason, J.: Energy Assessment Report, Tech. Rep. 10124962, DNV, 2022.

- Meyers, J., Bottasso, C., Dykes, K., Fleming, P., Gebraad, P., Giebel, G., Göçmen, T., and Van Wingerden, J.-W.: Wind farm flow control: prospects and challenges, Wind Energy Science Discussions, 2022, 1–56, 2022.
- 685 Min, M., Brazell, M., Tomboulides, A., Churchfield, M., Fischer, P., and Sprague, M.: Towards exascale for wind energy simulations, The International Journal of High Performance Computing Applications, 38, 337–355, 2024.
  - Mühle, F. V., Heckmeier, F. M., Campagnolo, F., and Breitsamter, C.: Wind tunnel investigations of an individual pitch control strategy for wind farm power optimization, Wind Energy Science, 9, 1251–1271, 2024.
- Munters, W. and Meyers, J.: Towards practical dynamic induction control of wind farms: analysis of optimally controlled wind-farm boundary layers and sinusoidal induction control of first-row turbines, Wind Energy Science, 3, 409–425, 2018a.
  - Munters, W. and Meyers, J.: Dynamic strategies for yaw and induction control of wind farms based on large-eddy simulation and optimization, Energies, 11, 177, 2018b.

National Renewable Energy Laboratory: ROSCO v2.8.0, https://github.com/NREL/ROSCO, 2024a.

National Renewable Energy Laboratory: OpenFAST v3.5.0, https://github.com/OpenFAST/openfast, 2024b.

- 695 Nygaard, N. G.: Wakes in very large wind farms and the effect of neighbouring wind farms, in: Journal of Physics: Conference Series, vol. 524, p. 012162, IOP Publishing, 2014.
  - Simley, E., Fleming, P., Girard, N., Alloin, L., Godefroy, E., and Duc, T.: Results from a wake-steering experiment at a commercial wind plant: investigating the wind speed dependence of wake-steering performance, Wind Energy Science, 6, 1427–1453, 2021.
  - Sutherland, H. J. and Mandell, J. F.: Effect of mean stress on the damage of wind turbine blades, J. Sol. Energy Eng., 126, 1041–1049, 2004.
- 700 Taschner, E., Van Vondelen, A., Verzijlbergh, R., and Van Wingerden, J.: On the performance of the helix wind farm control approach in the conventionally neutral atmospheric boundary layer, Journal of Physics: Conference Series, 2505, 012 006, 2023.
  - Taschner, E., Becker, M., Verzijlbergh, R., and Van Wingerden, J.: Comparison of helix and wake steering control for varying turbine spacing and wind direction, in: Journal of Physics: Conference Series, vol. 2767, p. 032023, IOP Publishing, 2024.

Thedin, R., Barter, G., Jonkman, J., Mudafort, R., Bay, C. J., Shaler, K., and Kreeft, J.: Load assessment of a wind farm considering negative
 and positive yaw misalignment for wake steering, Wind Energy Science Discussions, 2024, 1–26, 2024.

- Van Den Berg, D., De Tavernier, D., and van Wingerden, J.-W.: Using the helix mixing approach on floating offshore wind turbines, in: Journal of Physics: Conference Series, vol. 2265, p. 042011, IOP Publishing, 2022.
- van der Hoek, D., Kanev, S., Allin, J., Bieniek, D., and Mittelmeier, N.: Effects of axial induction control on wind farm energy production-A field test, Renewable Energy, 140, 994–1003, 2019.
- 710 Van der Hoek, D., Frederik, J., Huang, M., Scarano, F., Simao Ferreira, C., and van Wingerden, J.-W.: Experimental analysis of the effect of dynamic induction control on a wind turbine wake, Wind Energy Science, 7, 1305–1320, 2022.
  - Van der Hoek, D., den Abbeele, B. V., Simao Ferreira, C., and van Wingerden, J.-W.: Maximizing wind farm power output with the helix approach: Experimental validation and wake analysis using tomographic particle image velocimetry, Wind Energy, 27, 463–482, 2024.
- Van Vondelen, A. A., Navalkar, S. T., Kerssemakers, D. R., and Van Wingerden, J.-W.: Enhanced wake mixing in wind farms using the Helix
  approach: A loads sensitivity study, in: 2023 American Control Conference (ACC), pp. 831–836, IEEE, 2023.
- van Vondelen, A. A., Ottenheym, J., Pamososuryo, A. K., Navalkar, S. T., and van Wingerden, J.-W.: Phase synchronization for helix enhanced wake mixing in downstream wind turbines, IFAC-PapersOnLine, 56, 8426–8431, 2023.

Wang, C., Campagnolo, F., Sharma, A., and Bottasso, C.: Effects of dynamic induction control on power and loads, by LES-ALM simulations and wind tunnel experiments, in: Journal of Physics: Conference Series, vol. 1618, p. 022036, IOP Publishing, 2020.

720 Yılmaz, A. E. and Meyers, J.: Optimal dynamic induction control of a pair of inline wind turbines, Physics of Fluids, 30, 2018.