

Coriolis Recovery of Wind Farm Wakes

Ronald B. Smith¹ and Brian J. Gribben²

¹Department of Earth and Planetary Sciences, Yale University, New Haven, CT 06520, USA

²Frazer-Nash Consultancy Ltd., Bristol, BS1 4BA, UK

5 *Correspondence to:* Brian J. Gribben (b.gribben@fnc.co.uk)

Abstract. Two mechanisms cause wind speed recovery in the wake of a wind farm: momentum mixing and the Coriolis force.

To study these mechanisms, we use a steady linearized two-layer Fast Fourier Transform (FFT) model so that both analytical expressions and full flow fields can be derived. The model ~~parametrizes the vertical momentum mixing as Rayleigh friction; represents the complex vertical mixing processes by a simple Rayleigh friction. Rayleigh friction decays the wind disturbance at a rate proportional to its local value.~~ Pressure gradient forces are computed using a two-part vertical wave number formulation in the upper layer.

10 The Coriolis force recovery occurs by deflecting flow leftward (in the northern hemisphere). The Coriolis force, acting on this crossflow, re-accelerates the flow in the downwind direction.

The relative importance of Rayleigh versus Coriolis wake recovery depends on their two coefficients: C and f respectively,

15 each with units of inverse time. When the coefficient ratio is large, i.e. $\frac{C}{f} \gg 1$, Rayleigh friction restores the wake before Coriolis can act. Farm size and atmospheric static stability are also important to wake recovery. The wakes of small and medium size farms will quickly approach geostrophic balance. Once balance is established, the ratio of farm size " a " to the Rossby Radius of Deformation (RRD) determines the amount of Coriolis recovery. For a small farm in a stable atmosphere ($a < \text{RRD}$), Coriolis acts by adjusting the pressure field to obtain geostrophic balance rather than accelerating the wind. When 20 this occurs, only momentum mixing can restore the "inner" wake. For large farms in less stable conditions ($a > \text{RRD}$), the Coriolis Force significantly contributes to wake recovery. In this case, the leftward deflected flow creates "edge jets" on either side of the wake. Including the Coriolis force when modelling wind farm wakes is demonstrated to be increasingly important for larger wind farms or farm clusters.

1 Introduction

25 We investigate the role of the Coriolis force on wind farm wake recovery. Wake recovery has a large literature, but mostly focused on the role of turbulence in restoring the flow by mixing momentum from the ambient airstream back into the wake, both laterally and vertically. See reviews by Stevens and Meneveau (2017), Archer et al. (2018), Porté-Agel et al. (2020), Pryor et al. (2020), and Fischereit et al. (2021).

Formatted: Font: 10 pt

Formatted: Font: 10 pt

30 Another potential recovery mechanism is the generation of gravity waves (Smith 2010, 2022, 2024; Allaerts and Meyers 2017, 2019; Devesse et al. 2022, Khan et al. 2024). Our current interpretation of this previous work is that the pressure gradients from gravity waves act mostly locally with little impact on the far field wake recovery.

35 The literature on a Coriolis force recovery mechanism is now growing. In Dörenkämper et al. (2015) a large eddy simulation (LES) of a large offshore wind farm indicates a slight turning to the left in the wake which is attributed to increased friction by the wind turbines and thus a decreasing importance of Coriolis force. Abkar and Porté-Agel (2016) also used an LES method to simulate flow in an offshore wind farm, with a primary conclusion that the wind veer, due to Coriolis forcing, has a material effect on wake structure and evolution. Qian et al. (2022) carried out an LES simulation for a single wake, and noted a rightwards shift in the wake which is attributed to Coriolis. Van der Laan and Sørensen (2017) used a Reynolds-Averaged

40 Navier-Stokes (RANS) numerical model to see how two medium-size wind farms influence each other. Their model includes the role of wind veering with height in the regional boundary layer as well as local farm-induced pressure and Coriolis forces. They found that the wake slightly turned to the right under the influence of the entrained veered momentum. Earlier work from van der Laan et al. (2015), also using a RANS model, noted that the expected left turn when the flow is decelerated (at the turbine) is not visible, and the right turn as it is accelerated (in the wake recovery zone) dominates because there is more

45 time and a greater length scale for the deflection to take effect. Gadde and Stevens (2019) used an large eddy simulation (LES) model with veering wind and confirmed the rightward turning. Nygaard and Newcombe (2018) found evidence of it in Doppler radar data. In Nouri et al. (2020) an LES analysis concludes that Coriolis forcing is a major contributor to clockwise/anticlockwise asymmetry in the effectiveness of wake steering. Engleberger et al. (2020) use an LES analysis to investigate the interaction of veer in the boundary layer profile with turbine rotation direction, concluding that there is a

50 significant impact on the wake. Narasimhan et al. (2024) developed a quasi-analytic model of wakes in a veering boundary layer. These papers have not examined inertial wave generation and geostrophic adjustment. A broader look at Coriolis effects was given in Maas (2023). That paper used a full physics LES model to compare a 13 km and 90 km long wind farm of infinite width and found significant differences, also observing turning to the left within the farm and turning to the right in the wake. A similar full-physics approach was used by Heck and Howland (2025) to look at Coriolis effects on individual turbine wakes.

55 This literature represents progress made in understanding the role of Coriolis in wake structure and evolution. None of these previous analyses have specifically focussed on examined the role of static stability and geostrophic adjustment in the wake, rather having a primary focus on the effect of wind veer, or observing the effect of including Coriolis in the simulation without examining related mechanisms. In the present work, the role of veer is purposefully set aside such that the role in wake recovery that Coriolis takes via static stability and geostrophic adjustment can be the focus. As will be seen, this separation is

60 afforded by the modelling approach adopted here. Of the related work found in the literature, the study by Heck and Howland (2025) is perhaps closest to the current subject matter: using LES simulations, conclusions are drawn on the interaction of lateral pressure gradient and Coriolis force and how the wake deflection may therefore be limited. This is broadly in line with the analysis in the current work, although attribution of causation differs, and there is no mention of geostrophic adjustment.

lateral slope of the inversion or Rossby Radius as will be presented here, and their explanation focuses on wake deflection
65 rather than recovery.

In Section 2, we review the classical idea of geostrophic adjustment in a stratified fluid on a rotating planet that provides a foundation for this paper. In Section 3, we formulate a linearized steady-state two-layer problem with turbine drag applied to the lower layer. In Section 4, we find an idealized but instructive 1-D flow field solution for damped inertial waves. In Section
70 5 we find more useful 3-D solutions using Fourier Transforms. Using these solutions, we analyse the global competition between Coriolis (via geostrophic adjustment) and Rayleigh forces (i.e. vertical mixing) to recover the wake. In Section 6, we display wake solutions from Fast Fourier Transform (FFT) calculations. In Section 7, we describe the forces on air parcels passing though the wind farm. In Section 8, we explain how the wake approaches geostrophic balance in a stable atmosphere. In Section 9, we discuss wind power applications of the new theory.

75 2 Geostrophic Adjustment

The concept of geostrophic balance and the process of geostrophic adjustment are important in atmospheric and ocean dynamics (Rossby 1938, Blumen 1972, Lewis 1996, Chagnon and Bannon 2005, Mak 2011). We review these ideas here as a foundation for our wake recovery analysis. In the classical shallow layer adjustment problem, a band of air is suddenly put into motion with no surface tilt or pressure gradient. The Coriolis force pushes the band to the right (in the northern
80 hemisphere). This rightward shift does two things. First, it generates a Coriolis force that slows the band and second, it piles up air to the right and evacuates the left side creating a cross-flow pressure gradient. Together, these two processes restore geostrophic balance after an elapsed time of about $T = 1/f$ where f is the Coriolis parameter. In mid-latitudes $f \approx 0.0001 \text{ s}^{-2}$ so T is about 3 hours. A key aspect of geostrophic adjustment is the role of the Rossby Radius of Deformation (RRD). When the band of accelerated wind is wider than the RRD, the geostrophic adjustment occurs mainly by altering the
85 wind speed. However, when the band width is less than the RRD, the adjustment occurs by creating a balancing pressure gradient rather than recovering the wind speed.

Formatted: Superscript

The steady wind farm problem considered here is similar to Rossby's classic problem but instead of a temporal evolution, an upwind balanced flow is locally slowed by wind farm drag and eventually returns to geostrophic balance downwind. Thus, the
90 adjustment occurs in space, not in time. Like Rossby, we adopt a two-layer formulation with a uniform lower layer and stratification aloft. Our analysis of geostrophic adjustment in the wind farm context includes frictional dissipation as well as gravity wave and inertial wave generation. The related problem of a secondary circulation caused by frictional retardation was discussed by Eliassen (1952) and Egger (2003).

95 As may be appreciated from the references noted in this section, the present work uses foundations of established literature from mountain and dynamic meteorology. These sources are relevant and useful as the perturbations of the atmospheric boundary layer due to orography and due to wind farms have much in common.

3 Turbine Layer Formulation

3.1 Governing equations

100 The airflow in the lower “turbine layer” can be analysed using these linearized steady perturbation momentum equations.

$$U \frac{\partial u}{\partial x} + V \frac{\partial u}{\partial y} = F_x - \left(\frac{1}{\rho}\right) \frac{\partial p}{\partial x} - Cu + K \nabla^2 u + fv \quad (1a)$$

$$U \frac{\partial v}{\partial x} + V \frac{\partial v}{\partial y} = F_y - \left(\frac{1}{\rho}\right) \frac{\partial p}{\partial y} - Cv + K \nabla^2 v - fu \quad (1b)$$

105 where $F_x(x, y)$, $F_y(x, y)$ are the two components of the turbine drag with units of acceleration. The second term on the right is the pressure gradient force (PGF). Symbols C and K are the coefficients of Rayleigh friction and lateral momentum diffusivity. This formulation is consistent with that used in previous work (Smith 2010), and here also includes the lateral momentum diffusion term and Coriolis term as has been used by other authors (e.g. Allaerts and Meyers 2019). The derivation of these equations, the depth-averaging approach, and the linearization procedure are well established in the literature so further detail is omitted here. The components of undisturbed, depth averaged wind speed in the horizontal x, y plane are represented by U, V respectively. The corresponding perturbation wind speeds and pressure are $u(x, y), v(x, y)$ and $p(x, y)$. The air density ρ here is a constant. The formulation used allows for different wind speeds and directions in the lower, turbine layer and in the upper layer, however in this work we assume the same wind speed and direction in both layers. In this work, we are chiefly concerned by the competition between the Coriolis terms (fv, fu) and the Rayleigh friction terms (Cu, Cv) in Eq. (1) to recover the wake. The Coriolis force is explained more fully in Section 3.2. As will be discussed in Section 8, the action of Coriolis recovery is impeded when geostrophic balance is reached. Momentum restoration in the wake through the action of turbulent vertical mixing is represented in the Rayleigh term, which is discussed in Section 3.3.

3.2 Coriolis force

120 The Coriolis force in Eq. (1) is a deflecting force acting on objects moving horizontally on our rotating planet. This force is proportional to the Coriolis parameter f where

$$f = 2\Omega \sin(\phi) \quad (2)$$

Here ϕ is latitude and the rotation rate of the earth is $\Omega \approx 7.29 \times 10^{-5}$ radians per second. The signs of the f terms in Eq. 125 (1) ensure that the Coriolis force acts perpendicularly to the velocity vector. We assume the background flow $\vec{U} = (U, V)$ and pressure field $P(x, y)$ are in geostrophic balance

$$\frac{\nabla P}{\rho} = -f \vec{k} \times \vec{U} \quad (3)$$

130 where \vec{k} is the unit vector in the vertical direction. Any velocity perturbation $\vec{u} = (u, v)$ will cause a perturbation Coriolis force. There may also be a modified pressure field $p(x, y)$. If the slowed perturbation wind reaches a new state of geostrophic balance, the cross wind components of Eq. (1) would reduce to:

$$\frac{\nabla p}{\rho} = -f \vec{k} \times \vec{u} \quad (4)$$

135

In this paper a mid-latitude value of $f = 0.0001 \text{ s}^{-1}$ is employed, the only exception being for the case described in Section 9.2.

Formatted: Indent: Left: 0 cm, First line: 0 cm

Formatted: Font: (Default) +Body (Times New Roman)

3.3 Momentum mixing and Rayleigh Friction

The vertical mixing process is difficult to model in a simplified model context such as this. The eddies causing the vertical 140 transport of momentum may be ambient or “wake-generated” and may be sensitive to buoyancy effects in the boundary layer. Vertical mixing may be suppressed in a stable boundary layer or enhanced in an unstable one. The boundary layer stability in turn is influenced by surface heat flux and any warming aloft caused by broad tropospheric descent or cumulus convection (Barstad 2016). In this paper, we represent the complex vertical mixing processes by a simple Rayleigh friction. Rayleigh friction decays the wind disturbance at a rate proportional to its local value. The *ad hoc* nature of the Rayleigh friction 145 approach makes it difficult to estimate values of the coefficient C . Using a skin friction method, Smith (2010) chose $C=0.0001 \text{ s}^{-1}$, noting that here we combine the upper and lower Rayleigh coefficients as $C = C_T + C_B$. Gribben and Adams (2023) used estimates for C_B and C_T in a manner that is sensitive to surface layer stability via the surface layer friction velocity u_* as follows. C_B can be estimated as (Smith 2007):

$$C_B = 2(u_*)^2/(HU) \quad (5)$$

where H is the atmospheric boundary layer (ABL) height. By then assuming that the upper and lower friction forces are approximately equal in magnitude, C_T can be estimated as (Smith 2007):

155

$$C_T = C_B U / (U_g - U) \quad (6)$$

where U_g is the geostrophic wind speed. ~~Alternatively, the observed length of wakes could be used to "reverse engineer" a value for C . Gribben (2024) used a time series of wind atlas data (for a central position in the North Sea) to estimate a time series of Rayleigh friction coefficient values. The wind atlas data directly provided values for u_* and H , and also a range of values for wind speed at different heights which allowed U and U_g to be estimated. Then applying Eqs. (5) and (6) allowed the Rayleigh friction coefficients to be estimated for each thirty-minute time interval over a year. In that study, a value of $C = 0.0001 \text{ s}^{-1}$ represents the upper limit to the lowest decile of C values over a year, thus representing a low turbulence/high stability case that remains realistic. Most of the results in this study use this value, as it allows the impact of Coriolis forcing to be demonstrated and not dominated by friction effects, while remaining a realistic condition. Where other values for C are used, these are clearly indicated.~~

165

3.4 Wake Recovery Integrals

We can learn about the Coriolis and Rayleigh contributions to wake recovery from the governing equation (1) by integrating over the whole domain (see Smith 2022). The x-momentum Eq. (1a) gives, for westerly flow ($V=0$)

170

$$0 = \iint F_X \, dx \, dy - C \iint u(x, y) \, dx \, dy + f \iint v(x, y) \, dx \, dy \quad (7)$$

Note that the other terms in Eq. (1a) integrate to zero if the disturbance velocity and pressure decay at infinity. ~~We define the global Fractional Coriolis Recovery (FCR) and Fractional Rayleigh Recovery (FRR) as the fraction of the wake recovery due to Coriolis or Rayleigh forces respectively.~~

175

$$FCR = f \iint v(x, y) \, dx \, dy / \iint F_X \, dx \, dy \quad (8a)$$

and

$$FRR = -C \iint u(x, y) \, dx \, dy / \iint F_X \, dx \, dy \quad (8b)$$

180

From Eq. (7) we have

$$FCR + FRR = 1 \quad (9)$$

so together, the Coriolis and Rayleigh forces balance the net upstream turbine drag from the farm.

Another useful diagnostic is the Coriolis contribution to wake recovery along a streamline.¹⁸⁵ For this purpose, we temporarily neglect the action of PGF, Rayleigh friction and diffusivity.¹⁸⁶ Integrating Eq. (1a) downstream of the wind farm for westerly flow ($V = 0$) gives the net Coriolis Recovery (CR) in units of ms^{-1}

$$CR(x, y) = f\Delta(x, y) \quad (10)$$

where $\Delta(x, y)$ ¹⁸⁷ is the lateral displacement of a fluid parcel, given by

$$\Delta(x, y) = U^{-1} \int_{-\infty}^x v(x, y) dx \quad (11)$$

Physically, every increment of lateral displacement creates a downstream Coriolis acceleration, helping to restore the wake. Thus, Δ is a measure of the Coriolis Recovery. For example, if turbine drag slows the wind by 1 ms^{-1} , it can be recovered by Coriolis force alone (i.e. $CR = 1 \text{ ms}^{-1}$) with a $\Delta = \frac{CR}{f} = 10 \text{ km}$ lateral displacement in the case $f = 0.0001 \text{ s}^{-1}$.

4.1 Idealized 1-D solution with no pressure field

A simple one-dimensional solution to Eq.¹⁸⁸ (1) might arise from a westerly flow across a thin row of turbines with $F_y = V = K = 0$ with $p(x) = 0$. Then using delta function forcing

$$F_x(x) = B\delta(x) \quad (12)$$

gives $u(x) = v(x) = 0$ upwind and

$$u(x) = \left(\frac{B}{U}\right) \exp\left(-\frac{Cx}{U}\right) \cos\left(\frac{fx}{U}\right) \quad (13a)$$

$$v(x) = -\left(\frac{B}{U}\right) \exp\left(-\frac{Cx}{U}\right) \sin\left(\frac{fx}{U}\right) \quad (13b)$$

downwind. The factor B (with units m^2s^{-2})¹⁸⁹ is the integrated turbine drag across the farm. Solution Eq. (13) is a standing inertial wave with a restoring Coriolis force and damping by Rayleigh friction.¹⁹⁰ In the case $f = 0$, $v(x) = 0$ the speed deficit Eq. (13a) decays according to the Rayleigh decay length $L_{RAY} = U/C$. For example, with $U = 10 \text{ ms}^{-1}$ and $C = 0.0001 \text{ s}^{-1}$,

215 $L_{RAY} = 100$ km. With $f = 0.0001 \text{ s}^{-1}$, wake recovery is somewhat faster due to the Coriolis force contribution, reaching $\frac{u(x)}{u(0)} = e^{-1}$ at $x = 72$ km, a 28% shortening of the wake. This formulation is useful in understanding the infinitely wide wind farm cases investigated numerically by Maas (2023). [In that study, a case is shown where there appears to be an underdamped harmonic response in the wake recovery, i.e. the wake recovery response resembles that described by Eq. \(13a\). We will see in Section 8 that this case does not allow a cross-stream pressure gradient to form or geostrophic adjustment to occur.](#)

220 **4.2—Global Recovery**

The global Fractional Coriolis and Rayleigh Recoveries are found by substituting Eq. (13) into Eq. (8a,b) giving

$$FCR = \frac{1}{1 + \frac{f}{C}^2} \quad \text{and} \quad FRR = \frac{1}{1 + \frac{f}{C}^2} \quad (14a,b)$$

225 satisfying Eq. (9). For example, if $C = f$, then $FCR = 1/2$ and half the wake recovery is caused by the Coriolis force. A more general derivation of Eq. (14) will be seen in Section 5.

[4.3 Lateral deflection](#)

Formatted: Font: Not Bold

Formatted: Heading 1

230 Another way to diagnose the Coriolis Recovery is to compute the lateral parcel displacement by putting Eq. (13b) into Eq. (11) giving

$$\Delta(x) = -\left(\frac{B}{U}\right) \left[\frac{f - \left(c \sin\left(\frac{fx}{U}\right) + f \cos\left(\frac{fx}{U}\right)\right) \exp\left(-\frac{Cx}{U}\right)}{c^2 + f^2} \right] \quad (15)$$

235 This lateral displacement oscillates but eventually decays to

$$\Delta(x \rightarrow \infty) = -\left(\frac{B}{U}\right) \frac{f}{c^2 + f^2} \quad (16)$$

According to Eq. (16), increasing Rayleigh friction (C) reduces the final lateral displacement by damping the inertial wave
240 before it completes its natural oscillation. Using Eq. (10), this gives an FCR in agreement with Eq. (14).

These special solutions, Eqns. (13-16), are helpful in understanding the competition between Coriolis and Rayleigh forces and
241 the role of lateral streamline deflection, but they miss key aspects of wake dynamics. Missing are the roles of finite farm
width, the disturbed pressure field and the tendency for the wake to approach geostrophic balance. To include these essential
245 aspects, we solve Eq. (1), including the pressure field, using double Fourier transforms (Smith 2010).

5 Fourier Solution Methods

5.1 Turbine Layer

In Fourier space, the governing equations, Eqn. (1), become (with air density ρ hidden in p)
250

$$ikU\hat{u} + ilV\hat{u} = \hat{F}_x - ik\hat{p} - C\hat{u} - K(k^2 + l^2)\hat{u} + f\hat{v} \quad (17a)$$

$$ikU\hat{v} + ilV\hat{v} = \hat{F}_y - il\hat{p} - C\hat{v} - K(k^2 + l^2)\hat{v} - f\hat{u} \quad (17b)$$

where k and l are the wavenumber vector components. These equations are shortened by defining the complex acceleration-
255 friction-diffusion operator

$$D(k, l) = ikU + ilV + C + K(k^2 + l^2) \quad (18)$$

so Eq. (17) becomes

$$D\hat{u} = \hat{F}_x - ik\hat{p} + f\hat{v} \quad \text{and} \quad D\hat{v} = \hat{F}_y - il\hat{p} - f\hat{u} \quad (19a,b)$$

260

We solve these two simultaneous equations for $\hat{u}(k, l)$ and $\hat{v}(k, l)$ by substituting and grouping terms to obtain

$$\hat{u}(k, l) = [\hat{F}_x - ik\hat{p} + \frac{f}{D}(\hat{F}_y - il\hat{p})] / \left[D + \frac{f^2}{D} \right] \quad (20a)$$

$$\hat{v}(k, l) = [\hat{F}_y - il\hat{p} - \frac{f}{D}(\hat{F}_x - ik\hat{p})] / \left[D + \frac{f^2}{D} \right] \quad (20b)$$

265

The inertial waves described by Eq. (13) can be seen in the Fourier space representation Eq. (19, 20). If there is no dissipation
(i.e. $C = K = 0$), the operator D becomes $D = i\sigma = i(Uk + Vk)$ where σ is the intrinsic frequency (i.e. the frequency seen by

an air parcel). The inertial waves occur when $\sigma = \pm f$. Note that the square bracket in the denominator of Eq. (20) vanishes in this case. This singularity indicates a “free mode” where a widespread disturbance can exist with just local forcing.

270 **5.2 Pressure forces and the upper layer**

To complete the analysis, we include the hydrostatic pressure field generated by density anomalies aloft. The pressure anomalies are created by vertical displacement $\eta(x, y)$ of the inversion layer according to

$$\hat{p}(k, l) = (g' + \frac{IN^2}{m})\hat{\eta} = \Phi\hat{\eta} \quad (21)$$

275

where g' and N^2 are stability parameters for the inversion and free troposphere respectively (Smith, 2010). The reduced gravity g' term is a representation of a step-change in potential temperature at the inversion. The buoyancy frequency term N represents a continuous stable stratification in the troposphere. The quantity $m(k, l)$ in Eq. (21) is the vertical wavenumber for inertial gravity waves

280

$$m(k, l) = \frac{\pm N(k^2 + l^2)^{1/2}}{(\sigma^2 - f^2)^{1/2}} \quad (22)$$

285 Including the Coriolis force in lower layer Eq. (1) and upper layer Eq. (22) makes the model consistent. Note that we have chosen to include the Coriolis parameter in this vertical wavenumber formulation. This is an essential feature as we are including the Coriolis term in the turbine layer formulation too. Noting the sign ambiguity in Eq. (22), we break the wavenumber spectrum into two parts. When $\sigma^2 > f^2$, we have inertial gravity waves and choose the sign from the radiation condition: $sgn(m) = sgn(\sigma)$. The phase lines tilt upwind with height. When $f^2 > \sigma^2$, m is imaginary, the disturbance is evanescent and we chose the decaying (i.e. positive imaginary) root. This two-part approach is well established in the literature, see for example see Smith 1979, 1982, Sutherland 2010, Nappo 2012.

290

To couple the disturbance in the lower and upper layers, we compute the vertical displacement $\eta(x, y)$ of the inversion at $z = H$. We do this with the continuity condition in the lower layer

$$w(z = H) = U \frac{\partial \eta}{\partial x} + V \frac{\partial \eta}{\partial y} = -H \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} \right) \quad (23)$$

295

which in Fourier space is

$$\sigma\hat{\eta}(k, l) = -H(k\hat{u} + l\hat{v}) \quad (24)$$

It is important to note that the wave disturbance aloft and the disturbance in the lower turbine layer each influence the other.
 300 Thus, Eq. (24) must be solved simultaneously with Eqs. (20, 21). Doing this, the vertical displacement of the inversion becomes

$$\hat{\eta}(k, l) = \frac{-H[k(D\hat{F}_x + f\hat{F}_y) + l(D\hat{F}_y - f\hat{F}_x)]}{\sigma(D^2 + f^2) - iD H(k^2 + l^2)\Phi} \quad (25)$$

When $f = 0$, Eq. (25) reduces to

$$\hat{\eta}(k, l) = \frac{-H(k\hat{F}_x + l\hat{F}_y)}{\sigma D - iH(k^2 + l^2)\Phi} \quad (26)$$

which agrees with Eq. (4) in Smith (2010). The turbine layer velocity perturbations $\hat{u}(k, l)$ and $\hat{v}(k, l)$ are found by substituting Eqs. (21, 22, 25) into Eq. (20) so

$$\hat{u}(k, l) = \frac{D\hat{F}_x + f\hat{F}_y - i\Phi(Dk + fl)\hat{\eta}}{(D^2 + f^2)} \quad (27a)$$

$$\hat{v}(k, l) = \frac{D\hat{F}_y - f\hat{F}_x - i\Phi(Dl - fk)\hat{\eta}}{(D^2 + f^2)} \quad (27b)$$

where $D(k, l)$ is given by Eq. (18). Using the inverse Fast Fourier Transform (FFT), the fields $u(x, y)$, $v(x, y)$ and $\eta(x, y)$ are found. Eqs. (27, 28) capture a wide variety of fluid dynamical processes such as upstream blockage and deflection, vortex
 315 stretching, inertial waves, shallow water waves, vertically propagating gravity waves, frictional dissipation, lateral momentum diffusion and geostrophic adjustment. One disadvantage of the FFT solution is that the solutions are assumed to be periodic and thus can wrap from the exit to the entrance region if the Rayleigh friction or domain size are insufficient.

5.3 Global Wake Recovery

The Fourier solutions (see Eq. 25, 27) can be used to find the global Fractional Coriolis Recovery (FCR, see Eq. (8a)) using
 320 the property of Fourier transforms that the area integral of any function $G(x, y)$ is given by its Fourier Transform $\hat{G}(k, l)$
 evaluated at $k = l = 0$. That is, for any function $G(x, y)$

Formatted: Space Before: 0 pt, After: 0 pt

$$\iint G(x, y) dx dy = \hat{G}(k = 0, l = 0) \quad (28)$$

325 except for a possible normalizing coefficient. Using Eq. (18)

$$D(k \rightarrow 0, l \rightarrow 0) = ikU + ilV + C + K(k^2 + l^2) \rightarrow C \quad (29)$$

so that Eqs. (27, 28) gives (assuming a westerly flow and no lateral turbine forcing)

330

$$\hat{u}(k = 0, l = 0) = \frac{C \bar{F}_X(k=0, l=0)}{(C^2 + f^2)} \quad (30a)$$

$$\hat{v}(k = 0, l = 0) = \frac{-f \bar{F}_X(k=0, l=0)}{(C^2 + f^2)} \quad (30b)$$

335 The global Fractional Coriolis Recovery is then

$$FCR = \frac{-f v(k=0, l=0)}{\bar{F}_X(k=0, l=0)} = \frac{f^2}{(C^2 + f^2)} = \frac{1}{1 + (\frac{C}{f})^2} \quad (31)$$

and the Fractional Rayleigh Recovery is

340

$$FRR = \frac{C u(k=0, l=0)}{\bar{F}_X(k=0, l=0)} = \frac{C^2}{(C^2 + f^2)} = \frac{1}{1 + (\frac{f}{C})^2} \quad (32)$$

both in perfect agreement with Eq. (14). Thus, we learn that global FCR and FRR are not altered by finite fwarm width, stratification effects or lateral dispersion effects. However, the reader should be alert to the fact that these global measures of 345 recovery do not provide information on wake recovery at a specific location so are of limited use on their own for practical wake studies.

5.4 Diagnostic Fields

The impact of the Coriolis force and Rayleigh friction on the wake recovery can be seen using three diagnostic fields. The scalar wind speed deficit field Deficit is (Smith 2022)

350

$$\text{Deficit}(x, y) = -\frac{\vec{U} \cdot \vec{u}}{|\vec{U}|} = -(Uu + Vv)/(U^2 + V^2)^{1/2} \quad (33a)$$

355 This definition of [Deficit the deficit field](#) is simpler if we use natural coordinates (x', y') aligned with and perpendicular to the ambient wind direction and the corresponding perturbation wind components (u', v') so that

$$\text{Deficit}(x', y') = -u'(x', y')$$

(33b)

360 The scalar cross wind speed is

$$\text{Crosswind}(x, y) = \frac{(\vec{U} \times \vec{u}) \cdot \vec{k}}{|\vec{u}|} = (Uv - Vu)/(U^2 + V^2)^{1/2} \quad (34a)$$

or

$$\text{Crosswind}(x', y') = v'(x', y') \quad (34b)$$

365 where- \vec{k} is the unit vector in the vertical direction. Only two processes create a Crosswind, assuming that the turbine drag opposes the ambient wind. The high pressure region upwind of the farm will deflect air left and right giving a pair of Crosswind regions of opposite sign. If the turbine drag slows the air, the excess Coriolis force will deflect air leftward in the wake. The Crosswind is an important diagnostic of the Coriolis force impact, see Eqs. (10, 11).

370 The vertical displacement of the inversion $\eta(x, y)$ in Eq. (24) is also a useful diagnostic as it provides information on the divergence in the turbine layer and the forcing of gravity waves aloft that imprint a pressure field on the lower layer, see Eqs. (21, 25). An interesting property of these three diagnostics is their left-right symmetry across the wake. Cross-wake symmetry is judged relative to the centerline; a line parallel to the ambient flow passing through the farm center. This symmetry can be determined from the solutions Eqs. (25, 27) in Fourier space as even/odd functions have even/odd Fourier Transforms. The 375 result of such a symmetry analysis is shown in Table 1 and can be seen in Figures 1-3. The Rigid Lid case is described in the Appendix.

Table 1 Cross Wake Symmetry for a Symmetric Wind Farm

Diagnostic	$f = 0$	$f \neq 0$	$f \neq 0$ Rigid Lid
Vertical Displacement	symmetric	non-symmetric	non-symmetric
Deficit, Def	symmetric	symmetric	symmetric
Crosswind	anti-symmetric	non-symmetric	anti-symmetric

6 Fast Fourier Transform (FFT) Wake Computations

Analysis of the wake structure requires specification of the turbine forces acting on the lower layer. Here we use

385

$$\vec{F}(x, y) = -A \frac{\vec{U}}{|\vec{U}|} \exp\left(-\frac{x^p + y^p}{2a^p}\right) \quad (35)$$

where A is the drag in acceleration units at the farm center. When exponent $p = 2$, Eq. (35) gives a smooth circular Gaussian force field but we use $p = 20 \gg 1$ so Eq. (35) gives a sharp-edged square wind farm with dimensions $2a$ by $2a$.

390 A “reference” wind deficit profile Def_{REF} is found for westerly wind ($V = 0$) by integrating Eq. (1a) and Eq. (35) using the turbine drag force alone (i.e. $p(x, y) = f = C = K = 0$). This procedure gives

395

$$\begin{aligned} \text{Def}_{\text{REF}}(y') &\approx D_0 \quad \text{for } |y'| \leq a \\ \text{Def}_{\text{REF}}(y') &\approx 0 \quad \text{for } |y'| > a \end{aligned} \quad (36)$$

where $D_0 = \frac{2Aa}{|\vec{U}|}$ and y' is the distance from the centerline. If a wake deficit of $D_0 = 1 \text{ ms}^{-1}$ is desired with a wind speed of $U = 10 \text{ ms}^{-1}$ and farm half-width $a = 20 \text{ km}$, we choose $A = 0.00025 \text{ ms}^{-2}$. The area integrated force from Eq. (35) is then

400

$$\iint |\vec{F}| dx dy = 4Aa^2. \quad (37)$$

As F and A are expressed in acceleration units, the total farm drag in Newtons is written $4\rho Ha^2 A = 192 \times 10^6 \text{ N}$ using values from Table 2. Using Eqs. (25, 27, 35) we computed wind farm diagnostic fields for three cases (see Figs. 1-5) using the parameters in Tables 2 and 3. Our domain has 800-1024 by 800-1024 grid points with a grid spacing of 1000 m. The calculation is quick due to the efficiency of the FFT algorithm. The cases have been selected to allow a direct comparison of Coriolis force effect and stability effect. Case a has typical stability ($g' = 0.1$) and no Coriolis force, Case b is the same with a realistic, mid-latitude Coriolis force, and Case c has the same realistic Coriolis force but an excessive value of $g' = 10$. Although this is a high value for g' , high influence of stability can also be due to tropospheric stability N , as discussed in Smith 2024. In this way, the excessive g' value is not representative of reality and serves a purpose here to illuminate stability’s role.

Formatted: Font: 10 pt
 Formatted: Font: 10 pt

Table 2 Model Parameters


Parameter	Symbol	Units	Value
Wind speed	$ U $	ms^{-1}	10
Farm Half Width	a	km	20
Farm Drag	A	ms^{-2}	0.00025
Turbine Layer Depth	H	m	400
Inversion strength	g'	ms^{-2}	0.1 or 10.0
Troposphere Stability	N	s^{-1}	0.01
Lateral Diffusivity	K	m^2s^{-1}	200
Rayleigh coefficient	C	s^{-1}	0.0001
Coriolis parameter	f	s^{-1}	0 or 0.0001

Table 3 Three Cases

Case #	Coriolis Parameter, f	Reduced Gravity, g'	Conditions	f/C	$FS = a/RRD$	Figures
a	0	0.1	No Coriolis, typical stability	0	0	1a-5a
b	0.0001	0.1	Coriolis, typical stability	1	0.32	1b-5b
c	0.0001	10	Coriolis, strong stability	1	3.2	1c-5c

In Fig. 1 we show the wake deficit (see Eq. (33)) for the three cases in Table 3. All three patterns are symmetric across the centerline (see Table 1). Cases b and c have small regions of negative deficit (i.e. wind speed above ambient) to the left and right of the wake. The reason for these “edge jets” is discussed in Section 8.

420 In these cases, the wake is long and the wake recovery is slow, due to purposefully selecting a low value for Rayleigh friction coefficient as described in Section 3.3. Figure 2 shows the corresponding Crosswind patterns (see Eq. (34)). In Case a we see the left and right upstream cross flow caused by the gravity wave pressure field. In Case b, the pattern is asymmetric as the Coriolis force deflects air leftward. In Case c, with strong stratification, the Coriolis deflection on the centerline is suppressed by the quick establishment of geostrophic balance (Section 8).



Formatted Table





Figure 1

Wind speed deficit contour plots for three cases (see Table 3). Fields come from full FFT calculations of flow in the lower turbine layer. The wind direction is east to west (left to right). Dashed square marks the wind farm. See Table 1 for symmetries and Table 2 for common parameter values. These are zoomed in views, with the full domain extent being far greater than shown.

Figure 3 shows the vertical displacement of the inversion (see Eq. (25)). In Case a, we see the upwind lifting of the inversion that causes high pressure there. In Case b, note the important asymmetry across the wake, with lifting on the left and sinking on the right. This lateral gradient creates a cross wake PGF (Section 8). In Case c, the cross wake inversion tilt is still present. The magnitude of vertical displacement is small now but the cross wake PGF is still strong. This PGF keeps the flow in geostrophic balance.



Formatted Table





Figure 2

Similar to Figure 1 but for Crosswind, for Cases a,b,c in

Table 3.



Formatted Table




Figure 3

Similar to Figure 1 but for inversion layer vertical displacement, for Cases a,b,c in Table 3. Part (c) has an amplified scale.

7 Forces on the centreline

← Formatted: Space Before: 12 pt

440 To understand the wake recovery more fully, we consider the forces acting on the air along the flow centerline. We substitute the computed $u(x, y)$ and $v(x, y)$ along the centerline into the RHS of Eq. (1) to find the perturbation forces there. We neglect the small effect of lateral momentum diffusion. In Figure 4, we show the streamwise forces acting on the air along the centerline. For Case a with $f = 0$ (Fig. 4a) air approaching the farm first feels a retarding pressure gradient force (PGF). Soon after, the large turbine drag force begins to act (see Eq. (35)). Near the farm center, the PGF quickly turns positive and helps 445 to keep the air moving against the strong turbine drag. By this position, the wind speed deficit has become large and the Rayleigh friction is working hard to restore the wind speed. Rayleigh friction remains active far downwind. Case b with

Coriolis force acting (Fig. 4b) is similar but the Coriolis provides a significant positive force helping the wake to recover. In Case c, f is still non-zero but there is no Coriolis recovery as there is no cross wind (Fig 2c).

450




Figure 4

Downstream force components at the centerline, for three cases (see Table 3).

The cross-wake forces acting on the centerline are shown in Fig 5. In the Case a with $f=0$, there are no cross-wake forces. In Case b (Fig. 5b) the slowed wake flow creates a leftward perturbation Coriolis force. Further downstream (say $x = 150$ km), the lateral PGF puts the flow back into geostrophic balance (see Eq. (3)). For Case c, (Fig. 5c) geostrophic balance develops

455 immediately.




Figure 5

Cross stream force components at the centerline, for three cases (see Table 3).

8 Geostrophic Balance in the Wake

Formatted: Space Before: 12 pt

8.1 Geostrophic Adjustment

One of the most striking aspects of the FFT solutions is the quick adjustment to cross-wake geostrophic balance (See Eq. (4)) in the wake (Fig 5b, c). We estimate the downwind distance needed to achieve geostrophic balance adjustment distance (X_G)

465 as follows, using order of magnitude arguments. From Eq. (1b), slowed wake air will develop a leftward velocity $v(x) \sim -fux/U$ and from Eq. (11), a growing leftward displacement $\Delta(x) \sim -fux^2/U^2$. Here, the perturbation wind x-component $u = -\text{DeficitDef}$ from Eq. (33) and x is the distance downwind of the farm center, and we neglect the Rayleigh friction.

This leftward deflection distorts the inversion height $\eta(y) \sim H(\frac{\Delta}{a})$ (from Eq. (23)) and produces a lateral pressure gradient

$\frac{dp}{dy} \sim g' \frac{d\eta}{dy} \sim g'(\frac{\eta}{a})$ (from Eq. (21), keeping only the inversion stability g'). The PGF continues to grow until geostrophic

470 balance is reached $fu = -\frac{dp}{dy} \sim \frac{g' H f u x^2}{U^2 a^2}$ or

$$\frac{X_G}{a} \approx Fr \quad (38)$$

where the Froude number $Fr = U/\sqrt{g'H}$ and a is the farm width. The Froude number also characterizes the shallow water

475 waves in the solution and whether the flow is sub- or super-critical (Smith 2010). Surprisingly, this distance X_G depends only on the wind speed, static stability and farm width. The Coriolis parameter f cancels out of the estimate because the rate of deflection and the deflection needed for balance are both proportional to f . The strength of the wake deficit also cancels out.

If the inversion stability $g' = 0$, the tropospheric stability N plays a similar role (see Eq. (21)), but is more difficult to quantify (Smith 2024). Under typical atmospheric stability conditions (Table 4), X_G is only about two farm widths downstream even if

480 f is very small. According to Eq. (38), with an infinitely wide farm, geostrophic balance could never occur (see Section 4).

8.2 Geostrophic Balance

Formatted: Space Before: 24 pt, After: 12 pt

Once established, geostrophic balance requires that the perturbation cross-wake PGF and Coriolis forces cancel, see Eq. (4).

Again neglecting the tropospheric stability N , we can write the cross-wake PGF as the product of reduced gravity g' and the

485 lateral inversion tilt.

$$-g' \frac{d\eta(y)}{dy} + f \cdot \text{DeficitDef}(y) = 0$$

(39)

490 Assuming that the inversion displacement $\eta(y)$ vanishes at infinity, integrating Eq. (39) requires that the net wake deficit vanish once geostrophic balance is established, i.e.

$$\int_{-\infty}^{\infty} \text{DeficitDef}(y) dy = 0 \quad (40)$$

495

Combining Eq. (39) with the continuity equation, Eq. (23)

$$\eta(y) = -H \frac{d\Delta}{dy} \quad (41)$$

500 -and the Coriolis recovery formula Eqs. (10, 11)

$$\text{DefDeficit}(y) = \text{DefDeficit}_{REF}(y) - f\Delta(y) \quad (42)$$

505 gives a second order differential equation

$$g'H \frac{d^2\Delta}{dy^2} - f^2\Delta(y) = -f \cdot \text{DeficitDef}_{REF}(y) \quad (43)$$

510 for the lateral streamline deflection- $\Delta(y)$ profile. The quantity Deficit_{REF} is the initial wake deficit profile just behind the farm caused by turbine drag. A “box-car” wake Eq. (35) of width $2a$ has a constant Deficit_{REF} inside the wake ($|y| < a$) and zero deficit outside the wake.-Requiring smoothness at the wake edges ($y = \pm a$) and decay at infinity, the solutions to Eq. (43) in the outer and inner wake are

$$\Delta(y) = A_1 \exp(-\alpha|y|) \quad \text{for } |y| > a \quad (44a)$$

$$\Delta(y) = A_2(\exp(\alpha y) + \exp(-\alpha y)) + B \quad \text{for } |y| < a \quad (44b)$$

where the coefficients are

$$A_1 = \left(\frac{1}{2}\right) (\exp(\overline{FS}) - \exp(-\overline{FS}))B$$

520

$$A_2 = -\left(\frac{1}{2}\right) \exp(-\bar{FS}) B$$

$$B = \left(\frac{1}{f}\right) Def_{REF@}$$

525 10) gives Fractional Coriolis Recovery

$$FCR = 1 - \exp(-\bar{FS}) \quad (45)$$

530 valid for $N = C = 0$. Other wake variables can be computed from Eq. (44). The speed deficit profile comes from Eq. (42) and the vertical displacement of the inversion from Eq. (41). On the left side of the wake (looking downwind) the inversion is lifted while on the right side it is depressed.


Formatted: Font: 7 pt

Formatted: Font: 7 pt

535 The sensitivity of the lateral deflection profile $\Delta(y)$ to \bar{FS} is shown in Figure 6. With large \bar{FS} , the lateral deflection (and thus the Coriolis Recovery) acts primarily within the inner wake. Note however that the $\Delta(y)$ extends into the outer wake where the air was not slowed by the farm. The result is a narrow strip of air moving faster than ambient. We call this strip the “edge jet”. Its magnitude is $f\Delta(y = a)$ from Eq. (44). When $\bar{FS} < 1$, the lateral deflection is small and widespread. The “outer wake” air is pushed/pulled leftward by the “inner wake” air. The impact of geostrophic adjustment in this case is not to recover the inner wake but to accelerate the outer wake slightly above ambient. The net wake deficit is zero, see Eq. (40).

Figure 6

Sensitivity of cross-wake deflection, to achieve geostrophic balance, to non-dimensional farm size. The reference wake is 40km wide. For smaller \bar{FS} , the deflection is smaller but more widespread. The area under each curve is the same.



540

8.3 Comparison of geostrophic theory with the full FFT model

545 While we argue that geostrophic adjustment plays an important role in wake recovery, the real world and the FFT model includes other processes such as pressure gradients from vertically propagating gravity waves, shallow water waves and Rayleigh friction. Here we compare the Δ Deficit and Δ Vertical Δ Displacement profiles from geostrophic theory Eq. (44) with a full FFT model run at $x = 75$ km downwind of the farm center (Fig 7). We use our “standard” model run with $f = C = 0.0001 \text{ s}^{-1}$, $g' = 0.1 \text{ ms}^{-2}$, $N = 0.01 \text{ s}^{-1}$ and $\bar{FS} = 0.316$ (Tables 2, 3). The position $x = 75$ km is chosen from Figure 5 as a
550 point with geostrophic balance and still a strong wake deficit. The agreement in Figs 7 is good and improves if we increase f/C .




Figure 7. Comparison of geostrophic theory (Eq. 44) and FFT solutions, (a) for wake deficit and (b) for vertical displacement of the inversion layer. Deficit profiles show a local minimum on the centreline ($y = 0$) and edge jets near $y = \pm a$. Vertical displacement profiles show extrema of about 10 meters near the wake edges and a strong tilt across the inner wake. This tilt causes the PGF that balances the remaining wake deficit.

555

To further compare geostrophic theory with the FFT model, we chose the maximum FCR on the centerline as a measure of Coriolis recovery, see Eq. (45). This quantity is plotted in Figure 8 against the two non-dimensional control parameters f/C and \bar{FS} . For small f/C , Rayleigh friction generally dominates as it recovers the wake before Coriolis can act. For larger f/C , maximum FCR is sensitive to farm size \bar{FS} . With small \bar{FS} , the stratification quickly establishes geostrophic balance and 560 FCR is small. With large \bar{FS} , the Fractional Coriolis Recovery (FCR) is more significant. This sensitivity to \bar{FS} is captured in Eq. (45). The Global FCR is always greater than centreline FCR.


The geostrophic theory developed in this section explains how the interaction of the inversion layer displacement, pressure field and Coriolis term affects the behaviour in the wake. The comparisons with the full FFT solution show a qualitative match.

565 The match in Figure 7 is only approximate because the FFT solutions include Rayleigh friction, incomplete geostrophic adjustment and tropospheric stability while the Geostrophic curve does not. The geostrophic theory is not here recommended as a replacement for running the full FFT model, but rather as a useful aid to interpreting the role of geostrophic adjustment.

Figure 8

Sensitivity of maximum Fractional Coriolis

Recovery on the wake centreline to the ratio f/C and to farm size \bar{FS} . A global threshold (i.e. not only in the wake) is provided by Eq. (31), and Eq. (45) provides an estimate of wake centreline FCR in the absence of Rayleigh friction.



570

9. Applications

In this section we consider how the current analyses in this paper apply to the real world.

← Formatted: Space Before: 12 pt

9.1 Non-dimensional farm size and Froude Number

Three non-dimensional parameters control most of the results in this paper: C/f , Fr and \bar{FS} . Of these, C/f is the most

575 difficult to estimate due to the uncertainty in the Rayleigh coefficient C . In Table 4 we use a selection of atmospheric characteristics and wind farm sizes to estimate the range of the other two parameters: Fr and \bar{FS} . We fix $f = 0.0001 \text{ s}^{-1}$ corresponding to a latitude of about 45 degrees. We neglect the contribution from the continuous stratification above the boundary layer (N), which serves to strengthen the effect of the inversion. The small and large wind farm areas used are for Horns Rev 1, and for Hornsea 1 and Hornsea 2 combined, respectively. The wind farm radius is derived by simply considering
580 these areas as circles with radius a . The values selected for $\Delta\theta$ are supported by radiosonde data analysis from Barstad 2015 which was broadly replicated in a study by Gribben et al. 2023 although not included in that publication. The large and small values for [the depth of the atmospheric boundary layer](#) H are derived in the same way, although the typical H value comes from Rodaway et al. 2024.

585 [Even for the Large \$\bar{FS}\$ case, we can see from Table 4 that \$\bar{FS} \leq 1\$ therefore the wake recovery by Coriolis force will always be reduced by geostrophic balance, see Eq. \(45\). In the small \$\bar{FS} = 0.01\$ case, the rigid lid limit \(Appendix 1\) applies and geostrophic balance will prevent the Coriolis force from contributing to wake recovery.](#)

Table 4 Ranges of non-dimensional length scale \bar{FS} . Note that Froude number values assume $U = 10 \text{ ms}^{-1}$

Parameter	Symbol	Units	Value for Small \bar{FS}	Value for Large \bar{FS}	Value for Typical \bar{FS}
Wind Farm Area		km^2	19	869	100
Wind Farm Radius	a	km	2.46	16.63	5.64
Inversion strength	$\Delta\theta$	K	5	0.5	1.5
Reduced gravity	g'	ms^{-2}	0.1721	0.01721	0.05163
Layer depth	H	m	2000	300	500
Coriolis parameter	f	s^{-1}	0.0001	0.0001	0.0001
Rossby Radius of Deformation	RRD	m	185.5	22.7	50.8
Non-dimensional farm size	\bar{FS}	none	0.01	0.73	0.11
Froude number	Fr	none	0.54	4.40	1.97

Even for the Large \bar{FS} case, we can see from Table 4 that $\bar{FS} < 1$ therefore the wake recovery by Coriolis force will always be reduced by geostrophic balance, see Eq. (45). In the small $\bar{FS} = 0.01$ case, the rigid lid limit (Appendix 1) applies and geostrophic balance will prevent the Coriolis force from contributing to wake recovery.

The Froude number ranges from $Fr = 0.54$ to $Fr = 4.40$ in Table 4. These values imply that geostrophic balance will be commonly achieved quickly behind wind farms, see Eq. (38).

The methods of this paper might also be applied to natural wakes caused by mountains, islands or irregular coast lines. Wakes from mountainous islands such as St Vincent in the Caribbean (Smith *et al.* 1997) and Hawaii (Smith and Grubisic, 1993) sometimes extend to 200 km. These natural wakes may be important for offshore wind farm siting.

9.2 When will Coriolis force be important?

← Formatted: Space Before: 24 pt, After: 12 pt

As the magnitude of the Coriolis force on earth is generally small, it is fair to ask whether it can be important for wake recovery.

Furthermore, if the Rayleigh force (i.e. momentum mixing) is large, it will dominate recovery before Coriolis can act (Section 4). We also know from Section 8 that in a stable atmosphere Coriolis recovery is often reduced by geostrophic adjustment, especially for small farms. After some exploration of parameter space, we suggest that the most likely scenario for Coriolis

impact (on inner wake recovery) is relatively low wind (while still being above wind turbine cut-in wind speed of course), wide farm and weak stability in addition to small C/f .


615

A baseline test case to see Coriolis impact is constructed based on a square wind farm (half-width $a = 20$ km) with a uniform momentum sink, with a strength which on its own would result in a deficit of $D_{\text{eff,REF}} = 1 \text{ ms}^{-1}$ (see Eq. (35)).—Note that the area of this notional wind farm is approaching double that of the 'Large' case in Table 3 in order to represent future very large clusters. Atmospheric stability values are $g' = 0$ and $N = 0.01 \text{ s}^{-1}$.—A second case was constructed with a four times greater wind farm half-width (80 km), having the same length and reference deficit. Each case was run with and without Coriolis forcing, with other conditions selected to emphasise the Coriolis effect while remaining realistic: $C = 0.00005 \text{ s}^{-1}$, $f = 0.000124 \text{ s}^{-1}$, freestream wind speed = 7 ms^{-1} . The deficit profiles for each of the resulting runs, at 50 km downwind from the wind farm, are shown in Figure 9. The deficit profile is symmetric, see Table 1, so only half the profile is shown.

620 625 The impact of the Coriolis force on the inner wake deficit is evident by comparing the solid lines ($f = 0.000124 \text{ s}^{-1}$) with the dotted lines ($f = 0$) in Figure 9, especially for the wider case.—Figure 9 also shows acceleration of the outer wake and symmetric edge jets. This large impact provides motivation for including the Coriolis force in operational wake models.

Figure 9

Deficit profiles at a distance 50 km downwind from the wind farm edge. FFT calculations are shown with ($f = 0.000124 \text{ s}^{-1}$) and without Coriolis force modelling ($f = 0$). In each case the wind farm length is 40 km, with results for wind farm widths of 40 km and 160 km shown.



10 Conclusions

We examined wake recovery from the Coriolis and Rayleigh forces using a steady linearized two-layer model.⁶³⁵ This model allows us to obtain analytical expressions and do numerical wake computations including several interacting fluid dynamical processes.

In this complex problem, the simplest behaviour is the exponential recovery of the wake speed deficit by momentum mixing, parametrized as Rayleigh friction. This type of wake recovery gives an e-folding length scale of $L_{RAY} = U/C$ where U is the ambient wind speed and C is the Rayleigh coefficient. For example, if $U = 10 \text{ ms}^{-1}$ and $C = 0.0001 \text{ s}^{-1}$, the e-folding length for⁶⁴⁰ the wake is $L_C \approx 100 \text{ km}$. When Coriolis force is added, it accelerates the wake recovery and shortens the wake by introducing a damped inertial wave.

An interesting measure of the Coriolis force impact is the global Fractional Coriolis Recovery (FCR) and its complement the Fractional Rayleigh Recovery (FRR). When the ratio C/f is decreased, the Coriolis force does more of the wake recovery and⁶⁴⁵ Rayleigh friction does less. The expressions for global FCR and FRR derived in the idealized 1-D model continue to hold in the complex 3-D model including stratification and pressure disturbances. However, these global measures do not tell us all that we need about local wake structures.

The key finding in the paper is the strong tendency for the wake to approach geostrophic balance.⁶⁵⁰ This balance occurs through a mutual adjustment of the wake deficit and the cross-wake pressure gradient. When the Coriolis force deflects wake air leftward (in the northern hemisphere) two changes to the wake occur: a reacceleration of wake air and a distortion of the pressure field. Together, these changes bring the wake air into [geostrophic](#) balance. [Geostrophic adjustment occurs quickly, controlled by the atmospheric stability. Typically, this is within two or three farm widths.](#)

The nature of the balanced wake depends on the non-dimensional farm size $\bar{FS} = a/RRD$ where a is the half-width of the farm and the Rossby Radius of Deformation (RRD) is a measure of atmospheric stability. A geostrophic wake theory (Section 8.2) explains this dependence well.⁶⁵⁵ When $\bar{FS} > 1$, the Coriolis Recovery (CR) is effective at accelerating air in the “inner” wake.⁶⁶⁰ By pushing/pulling the adjacent “outer” wake [air](#) leftward, it also creates narrow “edge jets” to the left and right of the wake. In the opposite case of $\bar{FS} < 1$, the CR in the inner wake is weak as most of the geostrophic adjustment occurs via the PGF rather than flow acceleration. In this case, the wake speed can only be recovered by Rayleigh friction. At the same time however, a weak widespread Coriolis acceleration occurs over the outer wake.⁶⁶⁵ [The model suggests that this far-reaching Coriolis acceleration might benefit off-axis downwind farms.](#)

665 **If our results are correct, future** wake models should include the Coriolis force and outer wake acceleration, especially in cases with large farms, small wake mixing, weak atmospheric stability and high latitude.

Code Availability: The MATLAB code used in this paper is available from the first author.

Data Availability: There are no experimental data in this paper. The data for plots and tables come from MATLAB code.

670 **Competing Interests:** The authors have declared that there are no competing interests.

675 **Author Contributions:** BG proposed the project and asked RBS for help in properly applying Coriolis in the upper layer's vertical wave number. The revised solution for the wind farm layer was a joint effort. RBS led on all subsequent theoretical analyses, with BG confirming derivations and computations. Both authors developed software implementations independently as a cross-check.

680 **Acknowledgements:** We thank Nicolai Gayle Nygaard for insightful comments. We regret the recent passing of Dries Allaerts from the Delft University of Technology who worked to promote a deeper understanding of this subject and offered generous support to the authors' work with memorably knowledgeable and constructive review and discussions.

Appendix 1 : The limit of strong stratification

685 As argued in Section 8, strong atmospheric stratification weakens or eliminates Coriolis wake recovery leaving only Rayleigh frictional recovery. This conclusion can be demonstrated by considering the limit of $g' \rightarrow \infty$ making the inversion act like a rigid lid and making the turbine layer flow non-divergent (Smith 2024). This non-divergent limit is not really that extreme and in fact is well satisfied by the two real cases in Table 4 with small $\overline{FS} = 0.01$ and 0.11 .

690 -To investigate the strong stratification limit, we take $g' \rightarrow \infty$ in Eqs. (25,27) giving new expressions for the velocity field in Fourier space

$$\hat{u}(k, l) = \frac{l^2 \hat{F}_X - kl \hat{F}_Y}{D(k^2 + l^2)} \quad (\text{A1a})$$

$$\hat{v}(k, l) = \frac{-kl \hat{F}_X + k^2 \hat{F}_Y}{D(k^2 + l^2)} \quad (\text{A1b})$$

695 These simple expressions satisfy the non-divergent condition in Fourier space

$$\widehat{D}\widehat{v} = ik\widehat{u} + il\widehat{v} = 0 \quad (\text{A2})$$

700 The Coriolis parameter f cancels out in this derivation and does not appear in Eq. (A1), demonstrating the lack of Coriolis force influence on the perturbation velocity field. However, taking the same $g' \rightarrow \infty$ limit, the pressure field Eqs. (21, 25) becomes.

$$\hat{p}(k, l) = \frac{(k\hat{F}_x + l\hat{F}_y)}{i(k^2 + l^2)} + \frac{f(k\hat{F}_y - l\hat{F}_x)}{iD(k^2 + l^2)} \quad (\text{A3})$$

705 in which f still appears. The first term in Eq. (A3) is the dipole-like pressure field that decelerates and splits the airstream near the farm (Smith 2024). It is symmetric across the centreline and anti-symmetric along the flow direction with high/low pressure on the windward/leeward side of the farm. It is a local pressure response to the turbine drag. Note that this term includes no flow parameters (i.e. no U, V, C, K, f, g', H). The second term in Eq. (A3) describes the pressure field in the wake. It is proportional to f and is anti-symmetric across the centerline. It geostrophically balances the wake deficit until Rayleigh friction restores the wake. For example, with $F_y = V = 0$, the north-south Coriolis force from (A1a) $-f\hat{u}(k, l) = -f^2\hat{F}_x/(D(k^2 + l^2))$ is equal and opposite to the north-south pressure gradient force from the wake term in Eq. (A3) $-il\hat{p}(k, l) = f^2\hat{F}_x/(D(k^2 + l^2))$. As these two expressions in Fourier space are equal and opposite, Eq. (4) is satisfied everywhere in the wake, except for vestiges of the local turbine drag term. Note that we have taken the rigid lid limit with $g' \rightarrow \infty$ but we probably could have done it with tropospheric stability $N^2 \rightarrow \infty$ too (Smith (2024)).

715

References

Abkar, M. and Porté-Agel, F.: Influence of the Coriolis force on the structure and evolution of wind turbine wakes, *Phys. Rev. Fluids*, 1, 1–14, <https://doi.org/10.1103/physrevfluids.1.063701>, 2016.

720 Allaerts, D. and Meyers J.: Boundary-layer development and gravity waves in conventionally neutral wind farms. *J. Fluid Mech.*, 814, 95–130, doi:10.1017/jfm.2017.11, 2017.

Allaerts, D. and Meyers, J.: Sensitivity and feedback of wind-farm-induced gravity waves, *J. Fluid Mech.*, 862, 990–1028, <https://doi.org/10.1017/jfm.2018.969>, 2019.

725 Archer, C. L., Vasel-Be-Hagh, A., Yan, C., Wu, S., Pan, Y., Brodie, J. F., and Maguire, A. E.: Review and evaluation of wake loss models for wind energy applications, *Appl. Energ.*, 226, 1187–1207, <https://doi.org/10.1016/j.apenergy.2018.05.085>, 2018.

Barstad, I: Offshore validation of a 3 km ERA-Interim downscaling—WRF model's performance on static stability, *Wind Energy*, 19, 515–526, <https://doi.org/10.1002/we.1848>, 2015.

Blumen, W.: Geostrophic adjustment, *Rev. Geophys.*, 10(2), 485–528, <https://doi.org/10.1029/RG010i002p00485>, 1972.

730 Chagnon, J. M., and P. R. Bannon: Wave Response during Hydrostatic and Geostrophic Adjustment. Part I: Transient Dynamics, *J. Atmos. Sci.*, 62, 1311–1329, <https://doi.org/10.1175/JAS3283.1>, 2005.

Devesse, K., Lanzilao, L., Jamaer, S., van Lipzig, N., and Meyers, J.: Including realistic upper atmospheres in a wind-farm gravity-wave model, *Wind Energ. Sci.*, 7, 1367–1382, <https://doi.org/10.5194/wes-7-1367-2022>, 2022.

735 [Dörenkämper, M., Witha, B., Steinfeld, G., Heinemann, D., and Kühn, M.: The impact of stable atmospheric boundary layers on wind-turbine wakes within offshore wind farms, *J. Wind Eng. Ind. Aerodyn.*, 144, 146–153, doi:10.1016/j.jweia.2014.12.011](https://doi.org/10.1016/j.jweia.2014.12.011), 2015b.

Egger, J.: Gravity wave drag and global angular momentum: geostrophic adjustment processes, *Tellus A*, 55(5), 419–422, <https://doi.org/10.3402/tellusa.v55i5.12105>, 2003

Eliassen, A.: Slow thermally or frictionally controlled meridional circulations in a circular vortex. *Astrophys. Norv.*, 5, 19–60., 1951.

740 [Englberger, A., Dörnbrack, A., and Lundquist, J. K.: Does the rotational direction of a wind turbine impact the wake in a stably stratified atmospheric boundary layer?, *Wind Energ. Sci.*, 5, 1359–1374, https://doi.org/10.5194/wes-5-1359-2020](https://doi.org/10.5194/wes-5-1359-2020), 2020.

Fischereit, J., Brown, R., Larsén, X. G., Badger, J., and Hawkes, G.: Review of Mesoscale Wind-Farm Parametrizations and Their Applications, *Bound.-Lay. Meteorol.*, 182, 175–224, <https://doi.org/10.1007/s10546-021-00652-y>, 2021.

745 Gadde, S. N. and Stevens, R.J.A.M.: Effect of Coriolis force on a wind farm wake, *Wake Conference 2019, Journal of Physics: Conference Series*, 1256, 012-026, <https://dx.doi.org/10.1088/1742-6596/1256/1/012026>, 2019.

Gribben, B.J., and Adams, N.: Modelling Farm-to-Farm Wake Losses in Offshore Wind, With Sensitivity to Atmospheric Stability, *Wind Europe Technology Workshop*, Lyons, <https://windeurope.org/tech2023/programme/posters/PO089/>, June 2023.

750 Gribben, B.J.; Broad, A.T.; Cocks, J. and Hawkes, G.S.: Increasing Yield From Offshore Wind Farms via Thermal Boundary Layer-Sensitive Control, *KBR Journal 2023*, https://www.kbr.com/sites/default/files/documents/2023-10/TechnicalJournal2023_2016_Increasing_Yield_Offshore_Wind_Farms_Thermal_Boundary_Layer-Sensitive_Control_0.pdf, 2023.

755 [Gribben, B.J.: Gravity Waves and Long-Range Wakes Impacts for Very Large Clusters Offshore, Wind Europe Technology Workshop, Dublin](https://windeurope.org/tech2024/programme/posters/PO114/), <https://windeurope.org/tech2024/programme/posters/PO114/>, June 2024.

[Heck, S.H., and Howland, M.F.: Coriolis effects on wind turbine wakes across neutral atmospheric boundary layer regimes, *J. Fluid Mech.*, 1008, A7, doi:10.1017/jfm.2025.35](https://doi.org/10.1017/jfm.2025.35), 2025.

760 Khan, M.A., Watson, S.J., Allaerts, D.J.N., and Churchfield, M.: Recommendations on setup in simulating atmospheric gravity waves under conventionally neutral boundary layer conditions. The Science of Making Torque from Wind (TORQUE 2024), Journal of Physics: Conference Series 2767 092042, <https://doi.org/10.1088/1742-6596/2767/9/092042>, 2024.

Lewis, J. M.: C.-G. Rossby: Geostrophic Adjustment as an Outgrowth of Modeling the Gulf Stream. Bull. Amer. Meteor. Soc., 77(11), 2711–2728, [https://doi.org/10.1175/1520-0477\(1996\)077<2711:CGRGAA>2.0.CO;2](https://doi.org/10.1175/1520-0477(1996)077<2711:CGRGAA>2.0.CO;2), 1996.

765 Maas, O.: From gigawatt to multi-gigawatt wind farms: wake effects, energy budgets and inertial gravity waves investigated by large-eddy simulations, Wind Energ. Sci., 8, 535–556, <https://doi.org/10.5194/wes-8-535-2023>, 2023.

Mak, M: Atmospheric Dynamics, Cambridge University Press, Chapter 7 “Dynamic Adjustment”, <https://doi.org/10.1017/CBO9780511762031> , 2011.

Nappo, C. J.: An introduction to atmospheric gravity waves, Academic Press, 400pp, ISBN 9780123852243, 2012.

770 Narasimhan, G., Gayme, D.F., and Meneveau, C.: Analytical Wake Modeling in Atmospheric Boundary Layers: Accounting for Wind Veer and Thermal Stratification, The Science of Making Torque from Wind (TORQUE 2024) Journal of Physics: Conference Series 2767 092018, <https://doi.org/10.1088/1742-6596/2767/9/092018>, 2024.

Nouri, R., Vasel-Be-Hagh, A., and Archer, C. L.: The Coriolis force and the direction of rotation of the blades significantly affect the wake of wind turbines, Appl. Energy, 277, 115511, <https://doi.org/10.1016/j.apenergy.2020.115511>, 2020.

775 Nygaard, N. G. and Newcombe, A.C.: Wake behind an offshore wind farm observed with dual-Doppler radars, The Science of Making Torque from Wind (TORQUE 2018)–2018 Journal of Physics: Conference Series 1037 072008, <https://doi.org/10.1088/1742-6596/1037/7/072008>, 2018. Porté-Agel, F., Bastankhah, M., and Shamsoddin, S.: Wind-Turbine and Wind-Farm Flows: A Review, Bound.-Lay. Meteorol., 174, 1–59, <https://doi.org/10.1007/s10546-019-00473-0>, 2020.

Pryor, S. C., Shepherd, T. J., Volker, P. J. H., Hahmann, A. N., and Barthelmie, R. J.: “Wind Theft” from Onshore Wind Turbine Arrays: Sensitivity to Wind Farm Parameterization and Resolution, J. Appl. Meteorol. Clim., 59, 153–174, <https://doi.org/10.1175/JAMC-D-19-0235.1>, 2020.

780 Qian, G.-W., Song, Y.-P., and Ishihara, T.: A control-oriented large eddy simulation of wind turbine wake considering effects of Coriolis force and time-varying wind conditions, Energy, 239, 121876, <https://doi.org/10.1016/j.energy.2021.121876>, 2022.

Formatted: Font: Not Italic

Formatted: Font: Not Bold

785 Rodaway, C., Gunn, K., Williams, S., Sebastiani, A., Simon, E., Courtney, M., Thorsen, G.R., Clausen, E., Turrini, M., Wouters, D., Liu, Y., Gottschall, J., Dörrenkämper, M., Patschke, E., Hung, L.-Y., and Adams, N: OWA GloBE: Achieving Industry Consensus on the Global Blockage Effect in Offshore Wind, Wind Europe Technology Workshop, Dublin, June 2024.

Rossby, C.-G.: On the mutual adjustment of pressure and velocity distributions in certain simple current systems, II. J. Mar. Res, 5 , 239–263, 1938.

790 Smith R.B.: The influence of the earth's rotation on mountain wave drag, J. Atmos. Sci., 36, 177-180, [https://doi.org/10.1175/1520-0469\(1979\)036<0177:TIOTER>2.0.CO;2](https://doi.org/10.1175/1520-0469(1979)036<0177:TIOTER>2.0.CO;2) , 1997.

Smith R.B.: Synoptic observations and theory of orographically disturbed wind and surface pressure. *J. Atmos. Sci.*, 39, 60–70, [https://doi.org/10.1175/1520-0469\(1982\)039<0060:SOATOO>2.0.CO;2](https://doi.org/10.1175/1520-0469(1982)039<0060:SOATOO>2.0.CO;2) , 1982.

795 Smith, R. B., Gleason, A.C., Gluhosky, P.A. and Grubišić, V.: The wake of St. Vincent, *J. Atmos. Sci.*, 54, 606–623, [https://doi.org/10.1175/1520-0469\(1997\)054<0606:TWOSV>2.0.CO;2](https://doi.org/10.1175/1520-0469(1997)054<0606:TWOSV>2.0.CO;2) , 1997.

Smith, R. B., and Grubišić, V: Aerial Observations of Hawaii's Wake. *J. Atmos. Sci.*, 50, 3728–3750, [https://doi.org/10.1175/1520-0469\(1993\)050<3728:AOOHW>2.0.CO;2](https://doi.org/10.1175/1520-0469(1993)050<3728:AOOHW>2.0.CO;2) , 1993.

Smith, R. B.: Interacting Mountain Waves and Boundary Layers, *J. Atmos. Sci.*, 64, 594–607, <https://doi.org/10.1175/JAS3836.1> , 2007.

800 Smith, R. B.: Gravity Wave Effects on Wind Farm Efficiency, *Wind Energy*, 13, 449–458, <https://doi.org/10.1002/we.366>, 2010.

Smith, R. B.: A Linear Theory of Wind Farm Efficiency and Interaction. *J. Atmos. Sci.*, 79, 2001–2010, <https://doi.org/10.1175/JAS-D-22-0009.1> , 2022.

Smith, R. B.: The Wind Farm Pressure Field, *Wind Energ. Sci.*, 9, 253–261, <https://doi.org/10.5194/wes-9-253-2024>, 2024.

805 Stevens, R. J. A. M. and Meneveau, C.: Flow structure and turbulence in wind farms, *Annu. Rev. Fluid Mech.*, 49, 311–339, <https://doi.org/10.1146/annurev-fluid-010816-060206>, 2017.

Sutherland, B. R.: Internal Gravity Waves, 394pp, Cambridge University Press, 2010.

van der Laan, M. P., Hansen, K.S., Sørensen, N. N., and Réthoré P-E.: Predicting wind farm wake interaction with RANS: an investigation of the Coriolis force, *Wake Conference 2015*, *Journal of Physics: Conference Series* 625 012026, <https://doi.org/10.1088/1742-6596/625/1/012026>, 2015.

810 van der Laan, M. P. and Sørensen, N. N.: Why the Coriolis force turns a wind farm wake clockwise in the Northern Hemisphere, *Wind Energ. Sci.*, 2, 285–294, <https://doi.org/10.5194/wes-2-285-2017>, 2017.