

Investigating Grease Behaviour in Tilted Double-Row Tapered Roller Bearing Installed in Wind Turbine by Developing a Full Scale Multi-Phase CFD Model

Muhammad Ishaq Khan, Lorenzo Maccioni, and Franco Concli

Faculty of Engineering, Free University of Bozen-Bolzano, 39100 Bolzano, Italy.

Correspondence: Lorenzo Maccioni (lorenzo.maccioni@unibz.it)

Abstract. Lubrication plays a critical role in the effective performance of Tapered Roller Bearings (TRBs) used as main-bearing main bearings in wind turbines. Several experimental and CFD-based studies have investigated lubrication behaviour in single-row TRBs. However, grease-lubricated double-row TRBs have not yet been studied extensively, particularly in large-size large-size bearings. Therefore, this paper aims to investigate in detail the grease behaviour in a tilted double-row TRB installed in a direct-drive wind turbine by developing a novel, full-scale, three-dimensional, full-scale, multiphase CFD model. This model was implemented in the open-source environment OpenFOAM®, using a transient, incompressible solver. The grease was modeled as a, and multiphase solver based on the Volume of Fluid (VoF) model, where air and grease were treated as the two immiscible phases. Grease was modelled as a homogeneous non-Newtonian fluid using the Herschel-Bulkley formulation, with its rheological parameters determined by performing a best-fit analysis on experimentally obtained data. The simulated operating conditions included three grease filling ratios—45 %, 35 %, and 21 % of total volume of bearing lubricating chamber—at a rated rotational speed i.e. of 17.5 rpm, with a bearing tilt of 5° towards the Main-Frame Side (MFS) w.r.t the relative to vertical axis. The results highlight the grease flow characteristics including grease distribution, fluxes, and pressure fields within the bearing after one complete rotation of cage at the stated operating conditions. They emphasize that the lubricant behavior inside the bearing is strongly affected by the combined influence of bearing tilt and gravitational forces. The model captures grease distribution and fluxes across the bearing, identifying potential zones of lubricant starvation, and demonstrates how tilt affects grease flow between the two rows under varying fill conditions. Additionally, the model evaluates seal pressure, providing insights into the risk of grease leakage. The outcomes of this study have practical implications for optimizing relubrication strategies and improving maintenance planning for large wind turbine bearings.

1 Introduction

The generation of electricity from conventional energy sources, such as fossil fuels, has significantly contributed to the rise in global temperatures, resulting in global warming and increasingly severe environmental conditions (Ren et al., 2024). According to UN Climate Change 2022 Report, Earth has witnessed the highest levels of green house gases (GHG) emissions over the past decade (Intergovernmental Panel on Climate Change, 2022). Consequently, the transition to renewable energy

sources is imperative to ensure the sustainable development of the planet. Among various renewable energy sources, wind energy has emerged as one of the most penetrated and abundant sources of clean energy (Kaymaz et al., 2021). Therefore, The wind turbine main bearing is a critical component that transfers radial loads, axial forces, and bending moments from the rotor to the nacelle structure. It operates under complex dynamic loading and harsh environmental conditions, including low rotational speeds, high torque and variable temperatures. The reliability of the efficient and reliable operation of wind turbine is critical for ensuring the sustainability of renewable energy systems (Terwey and Mendelin, 2025).

Bearings are essential machine elements that play significant role in enabling efficient rotation in any mechanical system. They can carry radial and axial loads during operation (Hong and Tong, 2016). Tapered Roller Bearing (TRB) is one of the most widely used types of bearings in main bearing is essential to the overall availability and performance of wind turbines, automotive transmissions, and heavy machineries, due to its turbines, as its failure can result in extended downtime and costly repairs (Keller et al., 2016). According to Hart et al. (2019), main bearing failure rates can reach up to 30%, highlighting the importance of robust bearing design and lubrication strategies.

Tapered Roller Bearings (TRBs) are widely used in heavy-load applications—including wind turbines and automotive transmissions—due to their ability to support combined radial and axial loads (Tong and Hong, 2014). In particular, double-row Tapered Roller Bearing (TRB) is used to carry higher radial and axial loads as compared to single-row TRB. It supports loads in multiple directions (Bercea et al., 2003). Wind turbines are subjected to substantial loads due to their large and tall structures, as well as the variability in wind speed. Therefore loads (radial, axial, and bending), the absence of slip under ideal kinematic conditions, and high radial strength provided by line contact between rollers and raceways (Tong and Hong, 2014; Liu, 1976). In large wind turbines, double-row TRB are most commonly used as main bearing in wind turbines to support these high loads and provide better mechanical integrity. TRBs are employed as main bearings because they offer high load-carrying capacity and require less axial space than alternative configurations (Hart et al., 2020).

Effective lubrication is one of the key factors a key factor in maximizing the service life of bearing and ultimately any mechanical system (Khonsari and Booser, 2017). Lubricant distribution inside bearing makes it possible to minimize heat generation and also rapidly dissipates the heat generated (Mang and Dresel, 2007). Thus, keeping the bearing temperature in operating range reducing the losses due to friction known as load dependent power losses (P_{LB}). However, lubrication also contributes to the power losses that are due to and reliability of bearings (Khonsari and Booser, 2017). Proper lubricant distribution within the bearing assembly minimizes friction and wear between contacting surfaces, while also promoting heat dissipation from heavily loaded regions (Mang and Dresel, 2007). These effects contribute to a reduction in load-dependent power losses (P_{LB}), thereby improving overall system efficiency. In wind turbine main bearings, lubrication plays an even more critical role due to complex operating conditions. Therefore, effective lubrication is essential to prevent metal-to-metal contact and reduce the risk of premature main bearing failure (Hart et al., 2020). However, while lubrication improves bearing performance, it also introduces load independent power losses (P_{LB_o}), which result from viscous (drag) and inertial (churning) effects during its due to the lubricant's interaction with rolling elements (Niemann and Winter, 2002). These losses are called load independent power losses (P_{LB_o}). Therefore, lubrication strategies must balance wear protection and thermal control with energy efficiency considerations.

Eco-friendly and sustainable developments aim to develop efficient systems (Zhang, 2013). The advancement in computer technology paved the way to achieve the stated objective. Computational Fluid Dynamics (CFD) is one of the tools to study and optimize the lubrication behaviour and its key aspects inside bearing (Versteeg, 2007). Several CFD studies have been performed focusing lubrication. Experimental and numerical investigations have been extensively conducted to explore lubrication phenomena in rolling element bearings (Maccioni and Concli, 2020; Sadeghi et al., 2024). Wu et al. (2016) conducted an experimental study to investigate oil flow behavior and thermal characteristics in a jet-lubricated 7210 ball bearing with a bore diameter of 50 mm. A transparent test rig combined with high-speed imaging was employed to visualize oil supply patterns, flow fields, and temperature distributions. The results revealed that oil flow behavior is strongly influenced by the injection angle, nozzle position, and bearing rotational speed. Thermal analysis further indicated that insufficient lubrication can lead to elevated bearing temperatures, thereby increasing the risk of wear and failure. Wen and Oshima (2014) and Santhosh et al. (2017) performed numerical simulations, validated by experimental observations, to investigate the influence of cage design—specifically iron and plastic cages—on lubricant splash patterns in bearings from the last decade (Maccioni and Concli, 2020). CFD tool was used to estimate drag coefficient of roller in cylindrical rolling bearing exploiting single phase model by Marchesse et al. (2019), and Gao et al. (2022b). A multiphase solver was used to simulate single sector of oil-lubricated cylindrical roller bearing for estimation of (P_{LB_o}) by Concli et al. (2020) and Feldermann et al. (2017). Deng et al. (2022) combined CFD and non-linear dynamic models to analyze the oil-air flow and temperature in ball bearings. Chen et al. (2023) performed CFD simulation of single sector to study oil-air flows in ball bearings. Raju et al. (2013) simulated two different oil inlet positions in needle roller bearing to the optimum position for oil inlet. Multiphase simulations was performed by Crouchez-Pillot and Morvan (2014) capturing the behaviour of two immiscible fluids i.e., oil and air inside bearing. They used Volume of Fluid (VoF) model for their study. This model was used Hu et al. (2014) and developed transient model to simulate oil-gas phases in angular contact ball bearing. Gas flows in roller bearing were simulated under varying speed and cage structure by Sun et al. (2014). Transparent housings were utilized to facilitate macroscopic visualization of oil flow behavior under various operating conditions.

Several CFD studies have been applied to TRBs. Liebrecht et al. (2015, 2017) performed study to find the influence of oil quantity on total friction in TRB with vertical axis of rotation. Gonda et al. (2018, 2019) studied TRB having horizontal axis of rotation to calculate resistant torque under varying speed, oil levels, and temperature. Oil flows in 32312-A TRB were simulated by Maccioni et al. (2022b) studying the aeration impact on oil behaviour inside bearing. A numerical model was validated against experimental study by Maccioni et al. (2022a). P_{LB_o} were investigated by Maccioni et al. (2023b) in TRB by numerical and experimental study. Few studies have also been reported applying CFD. Russell et al. (2021) developed a novel test rig to investigate the frictional characteristics between the ball and cage in a deep groove ball bearing for four different cage types: a snap-on polymeric cage, a low-profile polymeric cage, a stamped steel cage, and a machined brass cage. The measured friction torque provided insights into the oil-air mixture dynamics within the cage pockets. The results also indicated that the coefficient of friction increased with rotational speed and decreased with applied load. Aamer et al. (2022) developed a test rig incorporating a transparent cage in a ball bearing to double-row TRBs. Li et al. (2022) studied double-row TRB during loss of lubrication process via CFD. Zhu et al. (2022) the effect of different rib structure on oil fluxes by using CFD tool. investigate the effect of cage position relative to the ball. It was observed that as the cage moved closer to the ball,

greater air entrainment occurred within the cage, and striated fluid layers formed over the ball surface. These phenomena were further supported by CFD analysis using a multiphase lubrication model.

Experimental studies have been conducted to study lubrication phenomenon in rolling bearings. Wu et al. (2016) performed experimental study for predicting oil flow behaviour and thermal characteristics in jet-lubricated ball bearings employing high speed imaging technique. Wen and Oshima (2014) and Santhosh et al. (2017) used transparent surfaces and macroscopically observed the affect of cage designs on oil splashing behaviour and patterns in ball bearings. Russell et al. (2021) developed a novel test rig to study the frictional characteristics for different cage designs in deep groove ball bearings. Aamer et al. (2022) extended the work of Russell et al. (2021) by modifying the test rig for optical visualization and also performed CFD analysis for predicting oil distribution. Arya et al. (2023) investigated oil starvation in a horizontally mounted angular contact ball bearing. A counter-rotating angular contact test rig (CRACR) equipped with transparent cages was developed to visualize oil distribution using high-speed imaging. The results showed that oil starvation within the bearing cage is influenced by several factors, including raceway motion, ball submersion level, lubricant properties, and cage pocket geometry. These experimental observations were further validated through CFD analysis using a two-phase lubrication model.

Experimental investigations have also been carried out on TRBs. Electrical Impedance Spectroscopy (EIS) technique was used to estimate lubricant film thickness (Manjunath et al. (2024) employed Electrical Impedance Spectroscopy (EIS) technique to estimate lubricant film thickness (Manjunath et al., 2024). Maccioni et al. (2022a) developed a test rig to analyze the lubricant behaviour in TRB using a TRB (SKF 81208TN). The results revealed a transition from boundary lubrication to mixed lubrication, and subsequently to elastohydrodynamic lubrication (EHL), as the rotational speed increased. To investigate lubrication dynamics in TRB (32312-A), Maccioni et al. (2022a) utilized Particle Image Velocimetry (PIV) technique. In this study, it was found by developing a custom test rig incorporating a sapphire outer ring to enhance optical accessibility. The PIV technique enabled the visualization of lubricant velocity patterns in the region between the cage and the outer ring—an area critical for understanding the pumping effect. The study also reported that bubble formation in oil increases with the rotational speed of bearing. within the lubricant increased with rising rotational speed, indicating the presence of aeration phenomena. To further explore this behavior, a new solver was developed and implemented in OpenFOAM® to account for aeration effects, and the CFD results showed good agreement with the experimental findings. In another study, Maccioni et al. (2023a) employing PIV method captured velocity fields in different regions in fully flooded oil lubricated TRB. Hoeprich (2005) studied grease behaviour in TRB experimentally. Gao et al. (2022a) experimentally studied conducted both experimental and numerical investigations to analyze lubricant fluxes in a fully flooded oil lubricated TRB (32312-A). PIV was employed to capture experimental velocity fields, while the numerical simulations were carried out using OpenFOAM®. The results revealed significant squeezing effects caused by high-pressure gradients near the edges of the rollers. Additionally, the tangential velocity of the lubricant was observed to be higher than that of the cage, highlighting the complex flow interactions within the bearing assembly.

P_{LB_o} have been investigated through both experimental and numerical approaches. Concli et al. (2020) and Feldermann et al. (2017) employed a multiphase CFD solver to simulate a single sector of an oil-lubricated cylindrical roller bearing to estimate P_{LB_o} . Marchesse et al. (2019) and Gao et al. (2022b) estimated the drag coefficient of rollers in cylindrical roller bearing using simplified, single-phase CFD models. Similarly, Hu et al. (2014) applied CFD techniques to evaluate drag losses in oil

jet-lubricated ball bearings. In the context of TRBs, Maccioni et al. (2023b) conducted a combined numerical and experimental study on a TRB (32208), providing a detailed breakdown of the contributions of individual bearing components to the overall P_{LB} .

Hoeprich (2005) conducted an experimental investigation on grease behavior in tapered roller bearings (TRBs) using nine different grease formulations (different combinations of thickeners and oil viscosities) at rotational speeds of 1800 and 3600 rpm. Grease film thickness was measured using an infrared (IR) technique, and bearing temperatures were recorded to assess thermal performance. The results indicated that higher-viscosity greases contributed to more thermally stable operating conditions, as evidenced by reduced temperature rise. In another experimental study, Gao et al. (2022a) examined the thermal characteristics of a railway double-row TRB by varying the rotational speed under varying rotational speeds. It was shown that the difference in temperature narrows down between found that the temperature difference between the inner and outer rings with the increase in rotational speed, diminished as the rotational speed increased, suggesting improved thermal equilibrium. Complementing these experimental studies, Li et al. (2022) and Zhu et al. (2022) employed CFD simulations to analyze the thermal and lubrication behavior of double-row TRBs during lubrication loss scenarios and investigated the influence of rib structures on oil flow dynamics.

Based on the study performed by Ishaq Khan et al. (2025), it is witnessed was found that most experimental and numerical studies have been limited to oil-lubricated single-row TRB. Furthermore, the TRBs that were studied had an Outside Diameter (OD) less than 300 mm. No comprehensive study has been reported for grease-lubricated double-row TRB at such a large scale. It is also worth mentioning that the simulation models developed in the above studies employed a symmetry-based approach—simulating only a single sector and extrapolating the results to represent the entire bearing—except for the work by Concli et al. (2020). However, the use of symmetry is not always valid. In the present study, the —particularly in wind turbine main bearings, where the bearing is typically tilted to promote uniform load distribution, leading to sector-dependent variations in lubrication dynamics (Loriemi et al., 2021).

The present research was conducted in collaboration with a wind turbine manufacturer to investigate lubrication behavior in a full-scale, grease-lubricated, double-row tapered roller bearing (TRB), installed in a wind turbine with a bore diameter of 1780 mm, is tilted by TRB installed as the main bearing in a direct-drive wind turbine. The bearing under study features a structural tilt of 5° towards the Main-Frame Side (MFS) w.r.t relative to the vertical axis. As a result, each sector of the bearing experiences different loading and lubrication conditions. To reliably capture the underlying physics, it is essential to investigate the behavior of the grease-lubricated double-row TRB in detail under varying, a configuration specifically implemented to improve load distribution. A comprehensive CFD model was developed using the open-source platform OpenFOAM® to simulate the multiphase grease-air interactions within the bearing under realistic operating conditions. All boundary conditions and operational parameters—including rotational speed, tilt, and grease fill levels—were defined based on specifications and guidance provided by the industrial partner, ensuring that the simulation closely reflects actual field conditions.

In the light of this, the primary objectives of this paper study are:

1. To develop a novel, full scale, multiphase, 3-D CFD model in OpenFOAM® environment for tilted double-row TRB.

2. To ~~investigate the behaviour of grease inside bearing under varying operating conditions.~~ predict grease distribution across the bearing geometry during rotation, including zones that may experience lubricant starvation over time.
3. To assess the effectiveness of different initial grease fill rates under realistic gravitational, and tilt conditions—information that can directly support maintenance planning and design of relubrication strategies.
4. To evaluate seal pressure under various conditions to assess the risk of grease leakage, which is a key concern in operational reliability.

The remainder of this paper is organized as follows:

Section 2 outlines the methodology adopted for the development of the CFD model. This includes the creation of the computational mesh, definition of boundary patches and conditions, selection of an appropriate multiphase solver, and the implementation of realistic operating parameters. Section 3 presents the simulation results and discussion, focusing on grease distribution across the bearing under various fill ratios, lubricant fluxes, and seal pressure evaluation. Finally, Section 4 concludes the study by summarizing the key findings and highlighting their implications for bearing design and maintenance in wind turbine applications.

2 CFD Model Development

2.1 Geometry of Double-Row TRB

The development of CFD model for the 41513219¹ double-row TRB started from the detailed study of its geometry. The main components of the bearing are rollers, cage, seal, inner raceway, and outer raceway. The 3-D CAD model of the bearing is shown in ~~the~~-Fig. 1a-(a) and the main components are highlighted in the section view of the bearing as shown in Fig. 1b(b). Each row consists of 65 identical sectors making a total of 130 similar sectors. The roller was ~~scale~~-scaled down by a factor of 0.98 ~~with respect to about~~ its center of gravity to ~~create clearance between~~ increase the clearance between the roller and raceways. This adjustment facilitated the creation of a more uniform and well-shaped mesh near the wall boundaries, thereby avoiding extreme aspect ratios and highly skewed cells (Maccioni et al., 2025). The key geometric specifications of the bearing are listed in Table 1.

2.2 Meshing of Double-Row TRB

2.2.1 Meshing of Half Sector

~~The bearing exhibits geometric symmetry and a periodic structure, which greatly facilitate the meshing process for the entire model. A systematic approach to initiate the meshing process was to first generate the mesh for a fraction of the entire domain—specifically, half of a single representative sector. The mesh of the entire bearing was then generated by systematically~~

¹This number represents the bearing reference code.




Figure 1. 41513219 double-row TRB (a) 3-D CAD model (b) Section view.

Table 1. Key geometric parameters of the bearing.

Parameter	Value
Type	Double-Row TRB
Outer Diameter	1780 mm
Bore Diameter	1370 mm
Pitch Diameter	1566 mm
Width (total)	276 mm
Mean Diameter of Roller	68 mm
<u>Length of Roller</u>	<u>63 mm</u>
Number of Rollers (total)	130
<u>Contact Angle (α)</u>	<u>45°</u>

~~rotating the mesh was generated using the blockMesh utility in OpenFOAM®. Since the bearing contains 65 rollers in each row, it comprises 65 identical sectors. Initially, the mesh was created for a half-sector mesh around the bearing axis. This method simplifies the meshing process by making use of the bearing's repeating pattern, which not only reduces complexity in the initial setup but also makes the overall workflow more manageable.~~

195 ~~The half-sector. This half-sector~~ was divided into ~~7 partitions at seven partitions along~~ the lateral side (Fig. 2(a)), while the front ~~side face~~ was segmented into 23 parts ~~with specific pattern as shown in following a specific pattern~~ (Fig. 2(b)). This pattern was consistently applied across all ~~7 lateral partitions of the half sector. It enabled the creation of seven lateral partitions, enabling the creation of a~~ high-quality structured mesh ~~exploiting the blockMesh utility in OpenFOAM®~~. Hexahedral blocks

were ~~created to ensure maximum numerical accuracy~~ employed to ensure high numerical accuracy (Maccioni et al., 2023b), with each block ~~consist of 8 vertices and its width spanning~~ consisting of eight vertices and spanning the width between adjacent partitions. ~~There were A total of 123 blocks created in this half-sector~~ hexahedral blocks were constructed for this half-sector.




Figure 2. Mesh of the half sector (a) Lateral view (b) Front view.

2.2.2 Meshing of Full Bearing

The creation of ~~the~~ mesh for the entire bearing presented ~~a significant challenge. The symmetry and periodic nature of the bearing were utilized to generate the mesh for the entire model.~~ significant challenges. The first major issue stemmed from the fact that the bearing consisted of 65 sectors—an odd number. As a result, a simple mirroring approach was not viable, since mirroring would produce an even number of sectors (e.g., 64), leaving the 65th sector unaccounted for. Creating the final sector manually and attempting to stitch it to the existing mesh carried a high risk of misalignment at the interface, potentially compromising mesh quality and numerical accuracy.

The second challenge was related to the scale and complexity of the bearing. Due to the large number of cells involved—on the order of millions—it was impractical to manually define all vertices, blocks, and arc segments directly in OpenFOAM[®] using the blockMeshDict file. OpenFOAM[®] does not automatically generate vertices; each one must be explicitly declared. To address both of these issues, a custom MATLAB[®] script was developed to parametrize the geometry and automate the generation of vertices, blocks, and arcs. This approach ensured consistency, accuracy, and scalability in the mesh generation process.

The previously created half-sector mesh served as the reference, which was ~~systematically~~ rotated through 360° around the bearing axis (x -axis) to construct the complete bearing mesh. The rotation was performed in the y - z plane using a standard rotation matrix as shown in Eq. 1.

$$\mathbf{R}_x = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \alpha & -\sin \alpha \\ 0 & \sin \alpha & \cos \alpha \end{bmatrix} \quad (1)$$

220 In this context, α represents the rotation applied to each vertex of the half-sector mesh. Since each bearing row consists of 65 identical sectors, the angular width of each sector is:

$$\alpha = \frac{360^\circ}{65} = 5.53^\circ \quad (2)$$

Each vertex is represented by a 3-D coordinate vector as:

$$\mathbf{v} = \begin{bmatrix} x \\ y \\ z \end{bmatrix} \quad (3)$$

225 ~~A MATLAB® script was developed to implement this logic, which parametrically generated the vertices, blocks, arcs, and patches for the entire bearing.~~ The script first created the second half of the initial sector by mirroring the z -coordinates of the original vertices with respect to the x - y plane, while keeping the x and y coordinates unchanged. This resulted in two adjacent half-sectors forming one complete sector within the same row, symmetrically reflected across the x - y plane.

To complete a full 360° rotation and generate the mesh for the entire bearing, the coordinates of each vertex of this sector
 230 were rotated by 5.53° in successive steps around the bearing axis in the y - z plane. For the second sector, the vertex coordinates from the first sector were rotated by 5.53° . For the third sector, the output coordinates from the second sector were again rotated by the same angle, and so on. This recursive approach ensured that each sector was generated based on the immediately preceding one, simulating a cumulative rotation through the full circular geometry. However, certain vertices lying along the boundaries between adjacent sectors were common across sectors due to their symmetry. It is important to note that
 235 OpenFOAM® treats vertices with different names as distinct, even if they occupy the same spatial location. This behavior can result in mesh discontinuities at sector interfaces. To preserve mesh continuity and avoid duplicate nodes at shared locations, the script reused these boundary vertices from the previous sector instead of creating new ones. This transformation was implemented via matrix-vector multiplication, as shown below:

$$\mathbf{v}_j^{(k)} = \begin{cases} \mathbf{v}_j^{(k-1)}, & \text{if } \mathbf{v}_j^{(k)} \text{ is a shared vertex from sector } k-1 \\ \mathbf{R}_x(\alpha) \cdot \mathbf{v}_j^{(k-1)}, & \text{otherwise} \end{cases} \quad (4)$$

240 Each transformation was executed in the script using a nested `for` loop, which iterated over all sectors, thereby constructing the complete mesh for 65 sectors within a single bearing row.

The bearing consists of two rows that are mirror images of each other. ~~The symmetry were~~ This symmetry was used to create the second row. To use mirror utility, `stl` files were created in order to keep the patches for the second row as well. The first row was then mirrored through symmetry. This automated and parametric approach enabled the generation of a high-resolution, structured hexahedral mesh for the full double-row tapered roller bearing geometry. The total cell count reached approximately 12.5 million. The grid for the full geometry is demonstrated in Figs. 3 and 4.




Figure 3. Grid visualization of patches Rollers, and Cages.




Figure 4. Grid visualization of patches InnerRing, InletOutlet, and OuterRing.

2.2.3 Patches of the Modelled Bearing

The ~~division of mesh into different regions can be done~~ mesh was divided into multiple regions by defining patches. ~~Patch is the combination~~ Patches are collection of boundary faces that ~~defines a specific region inside~~ represent specific regions within computational domain. ~~Different~~ Appropriate Boundary Conditions (BCs) ~~are~~ were then applied to these patches according to the physical conditions. In this study, the entire mesh of the double-row TRB was divided into several patches as shown in Fig. 5(a).




Figure 5. (a) Patches corresponding to bearing components. Velocity BCs applied to each patch are: cyclicAMI (InletOutlet), movingWallVelocity (Cage_R), conicalWallVelocity (Roller_R), rotatingWallVelocity (OuterRing), conicalWallVelocity (Roller_L), movingWallVelocity (Cage_L). (b) Additional patches defined for imposing pressure BCs. Velocity BCs for these patches are: zeroGradient (PRESSURE), fixedValue (WALLS), cyclicAMI (AMI).

Each roller in the left and right rows was defined as a separate patch. The red color shows the rollers in left row while the green color shows the rollers in right row. Right rollers in the left row are shown in red, while those in the right row are shown in green. The right and left cages are shown displayed in blue and brown colors respectively, respectively. The 'InletOutlet' patch is shown in purple, the 'InnerRing' in yellow, while the 'OuterRing' is shown in depicted as transparent. Three additional patches—namely, AMI, PRESSURE, and WALLS—were defined to ensure appropriate pressure boundary conditions within fluid domain (Fig. 5 (b)). These patches were superimposed on the outer surface of the 'InletOutlet' patch using mergeMeshes utility in OpenFOAM®.

2.2.4 Key Parameters of Mesh Quality

The mesh created for the full bearing was further check for its quality. The utility named checkMesh in OpenFOAM® used for this purpose. The key parameters of mesh quality are listed in Table 2. Aspect ratio of the mesh is the ratio of longest side of the cell aspect ratio—defined as the ratio of the longest to the shortest side of the cell. For this mesh, max aspect ratio a cell—had a maximum value of 13.968 was acceptable, which is considered acceptable for a complex geometry such as a large-size bearing; values exceeding 20 may lead to interpolation errors and numerical instability. Skewness of the cell is the measure of how much the cell deviates from ideal shape. A value of more than 4 creates numerical errors during simulation. Non-orthogonality is the measure of angle between the normal of face and vector connecting the center of neighbouring cell. If the maximum non-orthogonality is more than 70°, it will cause instability in simulation. The face volume ratio is the measure

of the difference of volumes of adjacent cells. Abrupt changes in the volume of cells in the mesh leads to numerical errors. The value close to 1 shows an excellent mesh quality (OpenFOAM® Foundation, 2024). The key parameters of mesh quality for half sector and full bearing models are listed in Tables 2 and 3 respectively. The mesh developed for bearing, all these values were in acceptable range as witnessed from Table 2.

Table 2. Key parameters of mesh quality of half sector.

Parameter	Value
Points	13891995 556,378
Faces	38814880 151,985
Internal Faces	35907560 135,409
Cells	47,899
Max Cell Openness	6.45338e-16
Max Aspect Ratio	7.915
Max Skewness	2.3730
Average Non-orthogonality	24.625
Average Face Volume Ratio	0.926

Table 3. Key parameters of mesh quality for full bearing.

Parameter	Value
Points	13,891,995
Faces	38,814,880
Internal Faces	35,907,560
Roller Faces (each)	6864 6,864
Cage Faces (each)	400010 400,010
Inner Raceway Faces	629460 629,460
Outer Raceway Faces	464880 464,880
InletOutlet Faces	120640 120,640
Cells	12453740 12,453,740
Max Cell Openness	5.34177e-16
Max Aspect Ratio	13.968
Max Skewness	2.37913
Average Non-orthogonality	24.1692
Average Face Volume Ratio	0.926

2.3 Governing Equations

2.3.1 CFD Governing Equations

275 Two fundamental laws of conservation were solved in this study i.e. law of conservation of mass (Continuity equation) and law of conservation momentum (Navier-Stokes equation). The fluid domain was considered as isothermal, therefore, energy equation was not solved in the model. Continuity equation for incompressible flow is shown as Eq. 5 and in expanded form in Eq. 6.

$$\nabla \cdot \mathbf{u} = 0 \quad (5)$$

280
$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} = 0 \quad (6)$$

where $\mathbf{u}$ is the velocity vector. Navier-Stokes equation for incompressible and non-Newtonian fluid is shown as Eq. 7

$$\rho \left(\frac{\partial \mathbf{u}}{\partial t} + (\mathbf{u} \cdot \nabla) \mathbf{u} \right) = -\nabla p + \nabla \cdot \boldsymbol{\tau} + \rho \mathbf{g} + \mathbf{F} \quad (7)$$

where ρ is the fluid density, $\mathbf{u}$ is the velocity vector, $\boldsymbol{\tau}$ is the stress tensor (includes pressure and viscous stress), $\rho \mathbf{g}$ represents body forces like gravity, $\mathbf{F}$ includes additional external forces.

285 **2.3.2 Volume of Fluid Model**

~~The fluid domain studied in this study was~~ In this study, the interaction between grease and air inside the bearing is modeled using the Volume of Fluid (VoF) ~~model was used to capture interface between these two immiscible fluid phases. This model is useful for multiphase simulation ensuring smooth transition of different properties across the interface. The volume fraction of grease and air must be equal to 1 satisfying the balance Eq. 8.~~

290 $\alpha_{\text{grease}} + \alpha_{\text{air}} = 1$

where approach implemented in OpenFOAM®. This method is particularly suitable for tracking the interface between the two immiscible phases—grease and air—while preserving volume conservation and capturing interface dynamics.

The volume fractions of grease (α_{grease} is volume fraction of grease and) and air (α_{air} is volume fraction of air. If the fluid in cell is only grease, then α_{grease} is equal to 1, and if it is only air, then α_{grease} is equal to 0. The weighted average equation in the

295 VoF method for density is given by:-

$$\rho_{\text{avg}} = \alpha_{\text{grease}} \cdot \rho_{\text{grease}} + (1 - \alpha_{\text{grease}}) \cdot \rho_{\text{air}}$$

) satisfy the relation:

$$\alpha_{\text{grease}} + \alpha_{\text{air}} = 1 \quad (8)$$

Other properties can be calculated using a similar approach and are used to compute phase-averaged properties such as density, for example:

$$\rho_{\text{avg}} = \alpha_{\text{grease}} \cdot \rho_{\text{grease}} + \alpha_{\text{air}} \cdot \rho_{\text{air}} \quad (9)$$

This formulation enables smooth interpolation of physical properties across the grease–air interface and is critical for resolving free surface evolution under tilt and rotation effects in the bearing cavity.

2.3.3 Kinematics of TRB

The kinematics of key components i.e., rollers, cage, inner, and outer raceways play important role in the CFD modelling of TRB. In kinematics of TRB, ~~cone~~ contact angle (α), roller mean diameter (d_R), pitch radius ($D_p/2$), and rotational directions of shaft speed (ω_S), roller speed (ω_R), and cage speed (ω_C) play significant role.

~~Cone~~ Contact angle (α) is the angle between the bearing axis and roller axis. In TRBs, all the rollers axes intersect the bearing axis at one common point. This point is called apex point. This design ensures the pure rolling motion of rollers, and uniform distribution of radial and axial loads. For double-row TRB, two apex points opposite to each other are present, each for its respective row. ~~This design ensures the pure rolling motion of rollers, and uniform distribution of radial and axial loads.~~ Equations 10 and 11 show that the rotational speed of cage (ω_C) and rollers (ω_R) can be expressed in terms of these geometric parameters (d_R , D_p , and α) and shaft rotational speed ω_S (Maccioni et al., 2023a).

$$\omega_C = \omega_S \cdot \frac{1}{2} \left(1 - \frac{d_R}{D_p} \cos \alpha \right) \quad (10)$$

$$\omega_R = \omega_S \cdot \frac{1}{2} \left\{ \frac{D_p}{d_R} \left[1 - \left(\frac{d_R}{D_p} \cos \alpha \right)^2 \right] \right\} \quad (11)$$

ω_S is considered the input velocity. Inner raceway rotates with the same velocity as ω_S while the outer raceway is stationary.

2.3.4 Lubrication Model

In this study, grease is used as a lubricant. Grease is a non-Newtonian fluid exhibiting complex behaviour under varying shear rates. At low shear rates, the viscosity of grease is high and behaves as solid upto its yield point. At high shear rates, viscosity decreases and grease manages to flow. This behaviour is called shear thinning. This behaviour can be witnessed from the experimental data for the grease used in this study as shown in Fig. 6a(a).

~~Herschel-Bulkley model was used to accurately describe this complex rheological behaviour of grease. This~~ In the present study, grease is modelled as a homogeneous non-Newtonian fluid using the Herschel–Bulkley formulation, which captures its

325 [shear-thinning and yield stress behavior \(Perez, 2004\)](#). This simplification allows us to focus on the global flow and distribution characteristics of grease within the bearing. The Herschel–Bulkley model is represented as Eq. 12;

$$\tau = \tau_y + K\dot{\gamma}^n \tag{12}$$

where τ is the shear stress, τ_y is the yield stress, K is the consistency index, $\dot{\gamma}$ is the shear rate, n is the flow behaviour index. τ_y , K , and n were determined from experimental data using the concept of curve fitting. MATLAB[®] script was developed in
 330 which sum of squared errors method was implemented to calculate these parameters. Experimental data and calculated data were in strong agreement with each other as shown in Fig. 6**b**(b).




Figure 6. Illustrating shear thinning behaviour of the grease (at 25 °C) used in this study (a) Experimental data (b) Curve-fitted data.

Some important physical properties of the grease used in this study are listed in Table 4.

Table 4. Properties of grease at 25 °C.

Property	Unit	Value
Density	kgm ⁻³	930
Kinematic viscosity	m ² s ⁻¹	0.0016
Yield Stress	Pa	210.1345
Consistency index	Pas ⁿ	31.5743
Flow index (n)	-	0.6626
NLGI grade	-	1

2.4 Boundary Conditions (BCs)

The interaction of fluid with the boundaries of domain in CFD analysis is defined by BCs. Therefore, ~~appropriated~~ appropriate BCs play significant role in accurately replicating the physical conditions in CFD environment. In this paper, the most appropriate BCs for velocity, relative pressure, and grease volume fraction were applied to respective patches as shown in Table 5.

Table 5. Boundary Conditions (BCs) applied.

Patch	U[m/s]	p[Pa]	p_rgh[Pa]	$\alpha[-]$
RollerL[1-65]	conicalWallVelocity	zeroGradient	zeroGradient	zeroGradient
RollerR[1-65]	conicalWallVelocity	zeroGradient	zeroGradient	zeroGradient
InnerRing	rotatingWallVelocity	zeroGradient	zeroGradient	zeroGradient
OuterRing	rotatingWallVelocity	zeroGradient	zeroGradient	zeroGradient
Cage_L	movingWallVelocity	zeroGradient	zeroGradient	zeroGradient
Cage_R	movingWallVelocity	zeroGradient	zeroGradient	zeroGradient
InletOutlet	cyclicAMI	cyclicAMI	cyclicAMI	cyclicAMI
AMI	cyclicAMI	cyclicAMI	cyclicAMI	cyclicAMI
PRESSURE	zeroGradient	fixedValue	fixedValue	inletOutlet
WALLS	fixedValue	zeroGradient	zeroGradient	zeroGradient

Rigid Mesh Motion (RMM) model was implemented to ensure the mesh rotation around bearing axis as single, undeformable entity. In our case, the mesh rotational speed was set to the same rotational speed as that of the cage. Therefore, movingWallVelocity BC was applied to cage to ensure zero relative velocity (no slip) between walls of cage and mesh. The rotatingWallVelocity BC was applied to inner ring and outer ring. Inner ring was rotated around a fixed axis (bearing axis) with the same rotational speed as that of shaft, whereas, outer ring was set as stationary. ~~The~~ In the 360° model, the cage was divided into two separate patches corresponding to both the rows of the bearing, and the boundary conditions were applied separately to each. The inner ring and outer ring were each treated as single continuous patches covering both rows of the bearing, and their respective boundary conditions were imposed uniformly over the entire surfaces. The conical rollers exhibit combined motion i.e., spinning about their own axis (dynamic axis) and rotating around bearing axis (fixed axis). To replicate this complex combination of motion, a new custom BC, named conicalWallVelocity was applied to each roller in both the rows, as their own axes of rotation were unique. The zeroGradient BCs corresponded to the conditions where the respective variables were not changing in perpendicular direction to the boundary faces. Non-conformal faces with different mesh structures were connected via cyclicAMI (Arbitrary Mesh Interface) BC. Gravitational effects are significant and are taken into account in this study. Since the bearing is tilted, the components of gravitational acceleration are resolved accordingly and applied to the bearing.

2.5 Solver Setup

In this study, the case was considered as multiphase, incompressible, laminar, and isothermal. The flow velocities involved in target domain are significantly lower than speed of soound, therefore grease and air phases were treated as incompressible. The most appropriate solver available in OpenFOAM® is interFoam for solving these conditions. This solver use VoF model to solve multiphase flows. Therefore, it was used in our study. The numerical stability, convergence, and good simulation speed were ensured by limiting the Courant number (Co) to less than 1. First order implicit Euler scheme was used for time discretization, whereas Gauss theorem was used for gradient calculation.

3 Simulated Operating Conditions

2.1 Simulated Operating Conditions

In this study, the grease filling ratio within the bearing was varied, while keeping the rotational speed and other ~~conditions the same. These operating conditions are listed~~ operating conditions constant. It is important to note that when the bearing is initially installed in the wind turbine, it is fully flooded with grease. However, during operation, grease continuously exits through the outlet ports. Although a re-lubrication pump supplies fresh grease to the bearing, the grease filling ratio remains below 50% of the total volume for most of the operational period. Therefore, the selected grease fill ratios were provided by the industrial partner, reflecting practical operating scenarios. These conditions are summarized in Table 6. Simulations were performed The rotational speed chosen corresponds to the rated speed of the wind turbine. All simulations were carried out for one full rotation of the cage due to computational resource limitations, utilizing 24 cores of a High-Performance Computing (HPC) cluster.

Table 6. Simulated operating conditions.

Simulation	Shaft rotational speed (rpm)	Grease filling ratio
1	17.5	45 %
2	17.5	35 %
3	17.5	21 %

The grease filling ratio for Simulation 3 (21% of the bearing volume) is considered the most critical condition, as it represents the lowest practical grease level. This level lies just below the outlet port, beyond which the grease volume cannot further decrease due to the port's positioning.

To gain further insight in understanding the behaviour of grease within the bearing, additional simulation was performed to examine the grease settling behaviour after the bearing rotation stops following operation. The simulation was carried out for operating conditions i.e. 45 % filling ratio, 0 rpm, and a temperature of 40 °C. The grease distribution after one complete rotation of cage was taken from the results of simulation 1. At this point, the bearing was brought to a stop (0 rpm), and

the grease temperature was maintained at 40 °C. The system was then monitored to observe the redistribution of grease as it gradually settled back toward its pre-rotation state. These operating conditions were designed to replicate a real-world scenario, such as a wind turbine shutdown, to assess how long it would take for the grease to migrate back to the lower region of the bearing under gravity-driven effects.

3 Results and Discussion

3.1 Grease Distribution

In this study, the grease filling ratios were kept below 50% of the total volume of the bearing's lubricating chamber to better represent critical operating conditions. The total volume of bearing's lubricating chamber is $0.0347001\text{--}0.035\text{ m}^3$. Figure 7 depicts the respective grease filling ratios for the three simulations. Simulation 3 employs the lowest filling ratio—21 % of the total volume (Fig. 7c)—which represents the most critical condition. It shows the initial grease level positioned just below the outlet ports within the lubricating chamber.




Figure 7. Grease filling ratios (a) 45 % (b) 35 % (c) 21 % of the total volume of bearing's lubricating chamber (images were captured as viewed from MFS).

The grease distribution inside the bearing after one complete rotation of bearing is shown in Fig. 8. As observed in Fig. 8, the upper region of the bearing exhibits signs of grease starvation, with noticeably less lubricant compared to the lower region for all the three grease filling ratios. This phenomenon is attributed mainly due to the influence of gravity.

The disparity in grease distribution is further illustrated in Fig. 9, which provides a clearer comparison between the top and bottom sections for the three simulations. For 45 % grease filling ratio (Fig. 9a(a)), the wetted volume of the upper part of the bearing is $0.004365\text{--}0.004\text{ m}^3$, whereas the lower part has a wetted volume of $0.01148\text{--}0.011\text{ m}^3$ — approximately 41 % greater




Figure 8. Grease distribution after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratios.

than that of the upper region. For 35 % grease filling ratio (Fig. 9b(b)), the wetted volume of the upper part of the bearing is $0.00311593 \pm 0.003 \text{ m}^3$, whereas the lower part has a wetted volume of $0.00885667 \pm 0.009 \text{ m}^3$ — approximately 36 % greater than that of the upper region. For 21 % grease filling ratio (Fig. 9c(c)), the wetted volume of the upper part of the bearing is $0.00133971 \pm 0.001 \text{ m}^3$, whereas the lower part has a wetted volume of $0.00575628 \pm 0.006 \text{ m}^3$ — approximately 25.6 % greater than that of the upper region.

The tilt of the bearing also influences the grease distribution behavior. To analyze this effect, the two rows of the bearing were separated, and the corresponding grease distribution was captured for each filling ratio as shown in Fig. 10. The total volume of the lubrication chamber for each row is $0.0174 \pm 0.017 \text{ m}^3$. After one complete rotation of cage, the wetted volume in the MFS row is $0.008645 \pm 0.009 \text{ m}^3$, whereas the hub side (HS) row has a wetted volume of $0.007203 \pm 0.007 \text{ m}^3$ for 45 % grease filling ratio (Fig. 10(a)). This indicates that the MFS row retains approximately 8.5 % more grease than the HS row. For 35 % ratio, the wetted volume in the MFS row is $0.00667421 \pm 0.007 \text{ m}^3$, whereas the hub side (HS) row has a wetted volume of $0.00530031 \pm 0.005 \text{ m}^3$ indicating approximately 7.9 % more grease in the MFS row (Fig. 10(b)). Similarly for 21 % grease filling ratio, the difference between the wetted volume in MFS and HS row is 6.35 % (Fig. 10(c)). The results of grease distribution by volume (m^3) are summarized in Table 7.

Figure 11 illustrates the asymmetric distribution of grease over time. Initially, both rows exhibit equal grease occupancy. However, once rotation begins, the grease volume in the MFS row (i.e., the row toward which the bearing is tilted) gradually increases, accompanied by a corresponding decrease in the HS row. This behavior can be attributed to the influence of centrifugal forces, which drive the grease radially outward. Due to the bearing tilt, this outward flow is biased toward the MFS row, resulting in a pressure build-up in that region. An interesting phenomenon of grease redistribution begins to occur after certain period of time. As the pressure in the MFS row increases, a sufficient pressure gradient is established between the two




Figure 9. Illustration of comparison of grease distribution in top and bottom part of the bearing after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratios.

415 rows. This gradient drives the grease back toward the HS row, counteracting the centrifugal bias. Eventually, a steady state is




Figure 10. Illustration of grease distribution in MFS and HS row after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratios.

reached in which a dynamic equilibrium exists between the centrifugal-driven flow and the pressure-induced backflow. At this stage, the net grease flow between the rows becomes negligible and the grease distribution ~~stabilizes~~stabilizes.

Illustration of asymmetrical grease occupancy as a percentage of lubrication chamber volume of each row w.r.t time (a) 45 % (b) 35 % (c) 21 % grease filling ratio

Figure 12 illustrates the temporal evolution of the grease film angle (θ) for three different grease filling ratios. The angles are measured with respect to the bottommost part of the bearing (i.e., $\theta = 0^\circ$), and represent the extent to which the grease progresses toward the topmost region ($\theta = 180^\circ$) under rotation. The initial grease levels in the rotating direction (positive x -axis) are approximately 82° , 62° , and 36° for the 45 %, 35 %, and 21 % filling ratios, respectively. These values reflect the initial angular spread of the grease before rotation begins.

Figure 12a(a) presents the grease film evolution on the MFS inner raceway. It is evident that, for all three filling ratios, the grease film progresses up to the topmost region of the bearing. However, the time required to reach this position varies with the filling ratio, with higher ratios achieving full coverage more rapidly. The corresponding distribution on the HS inner raceway is shown in Fig. 12b(b). In this case, the 45 % and 35 % filling ratios allow the grease film to reach the top region, similar to the MFS side. However, for the 21 % filling ratio, the grease front diminishes significantly and fails to reach the upper portion, indicating a thinning film and potentially inadequate lubrication in this area.

Table 7. Summary of grease distribution by volume (m³).

Simulation	Initial grease volume (m ³)	Grease volume (m ³) in top part after rotation	Grease volume (m ³) in bottom part after rotation	Grease volume (m ³) in MFS row after rotation	Grease volume (m ³) in HS row after rotation
1	0.016	0.004	0.011	0.009	0.007
2	0.012	0.003	0.009	0.007	0.005
3	0.007	0.001	0.006	0.004	0.003

Figure 12c(c) shows the grease progression on the MFS outer raceway. Only the 45 % filling ratio provides sufficient grease volume to reach the topmost section. For the 35 % and 21 % cases, the upper region remains starved. This behavior can be attributed to the fact that the outer raceway is stationary and, therefore, does not contribute to the centrifugal transport of grease. As a result, the grease tends to remain with the rotating inner raceway and rollers, limiting its migration toward the outer raceway—especially under low grease volumes. Finally, Figure 12d(d) illustrates the HS outer raceway. In this case, none of the three filling ratios succeed in delivering grease to the top region, leaving it starved throughout the simulation. This consistent starvation across all cases emphasizes the asymmetric grease distribution resulting from the bearing’s tilt and the centrifugal-biased flow towards the MFS side.

It is important to note that in cases where the grease fails to reach the topmost region, the limited amount of grease causes the front to gradually disappear over time. After a certain point, the grease becomes too sparse to form a continuous layer, instead

breaking into small dispersed droplets. As a result, it is not possible to extract a well-defined angle of progression beyond this stage. Therefore, data beyond this point were excluded from the graph, as no coherent front exists to track angular progression reliably.




Figure 11. Illustration of asymmetrical grease occupancy as a percentage of lubrication chamber volume of each row w.r.t time (a) 45 % (b) 35 % (c) 21 % grease filling ratios.

3.2 Fluxes

Figures 13 and 14 illustrate the velocity fields in cross-sectional slices taken from planes perpendicular to the bearing axis for the MFS and HS rows, respectively. It is evident that the velocity of the fluid varies between the speeds of the cage and the rollers throughout the domain, except in regions adjacent to the inner and outer raceways, where the fluid adheres to the no-slip boundary condition. Additionally, higher fluid velocities are observed near the roller surfaces, emphasizing the critical role of the rollers-squeezing effect in promoting fluid motion within the bearing.

The pumping effect induced by the rollers, resulting from their tapered geometry, is illustrated in Figs. 15 and 16 corresponding to the MFS and HS rows, respectively. Due to this geometry, one side of each roller exhibits outward-axial-velocity axial velocity towards the bearing bore, while the opposite-side-shows-inward-axial-velocity other side shows axial velocity away from bearing bore. This asymmetric velocity distribution contributes to the axial transport of lubricant within the bearing. Specifically, on-in Fig. 15 which shows the MFS side, negative axial velocity indicates outward-flow, whereas-on flow away from bearing bore, whereas positive axial velocity represents flow towards bearing bore. On the HS side, it-corresponds to-inward-flow. Conversely, the sign convention is opposite Fig. 16, where positive axial velocity represents inward-flow-on the-MFS-side-and-outward-flow-on-the-HS-side flow away from bearing bore, while negative axial velocity represents flow towards bearing bore. This bidirectional flow pattern highlights the role of tapered rollers (pumping effect) in driving lubricant circulation across the bearing rows.




Figure 12. Illustration of the temporal distribution of the grease within the range of $0^\circ \leq \theta \leq 180^\circ$ (a) MFS inner raceway (b) HS inner raceway (c) MFS outer raceway (d) HS outer raceway.

3.3 Pressure Fields

The pressure field developed due to grease flow over the roller surfaces and inner raceway is illustrated in Fig. 17. Higher pressure regions are observed in areas with greater lubricant accumulation which is evident from Fig. 17a that for 45 % grease filling ratio (Fig. 17(a)), the pressure developed inside the bearing is higher as compared to 35 % and 21 % filling ratios (Figs. 17b(b) and 17e(c) respectively). Notably, steep pressure gradients occur near the contact interfaces between the rollers and raceways, which can be attributed to the squeezing effect of the lubricant in these narrow gaps. Similar pressure trends profiles were found by Maccioni et al. (2023a) in their study.




Figure 13. Illustration of velocity fields in MFS row after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratio-ratios.




Figure 14. Illustration of velocity fields in HS row after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratio-ratios.

The pressure distribution on the bearing seals is of particular importance, as it directly affects the potential of lubricant leakage. Figure 18 presents the pressure profiles on both the MFS and HS seals for the three grease filling ratios. The left column corresponds to the MFS seal, while the right column shows the HS seal. It is evident that the pressure on the seals is




Figure 15. Illustration of axial velocity fields in MFS row after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratios




Figure 16. Illustration of axial velocity fields in HS row after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratio

470 highest for the 45 % grease filling ratio (Fig. 18(a)), followed by 35 % and 21 % (Figs. 18(b) and 18(c) respectively), indicating that increased grease volume leads to greater sealing pressure and potentially a higher risk of leakage.




Figure 17. Illustration of pressure fields in rollers and inner raceway after one rotation of cage (steep pressure gradients near the contact surfaces) (a) 45 % (b) 35 % (c) 21 % grease filling ratios.




Figure 18. Illustration of pressure fields in MFS and HS seals after one rotation of cage (a) 45 % (b) 35 % (c) 21 % grease filling ratios.




Figure 19. Illustration of grease settling behaviour for 45 % filling ratio at 40 °C (a) top part (b) bottom part.




Figure 20. Illustration of grease settling behaviour for 45 % filling ratio at 40 °C w.r.t time.

3.4 Grease Settling Behaviour

To gain further insight in understanding the behavior of grease within the bearing, further study was conducted to evaluate the time required for the grease to settle. Another important aspect of the lubrication phenomenon inside the bearing is the settling behavior of grease after the bearing rotation stops. The simulation was carried out for operating conditions i.e. 45 % filling ratio, 0 rpm, and a temperature of 40 °C. stops rotating. To investigate this, a dedicated simulation was performed following the operational scenario described in subsection 2.1.

The grease distribution after one complete rotation of cage was taken from the results of simulation 1. At this point, the bearing was brought to a stop (0 rpm), and the grease temperature was maintained at 40 °C. The system was then monitored to observe the redistribution of grease as it gradually settled back toward its pre-rotation state. These operating conditions were designed to replicate a real-world scenario, such as a wind turbine shutdown, to assess how long it would take for the grease to migrate back to the lower region of the bearing under gravity-driven effects. The grease distribution across the top and bottom sections of the bearing after 40 seconds is illustrated in Fig. 19, and the temporal evolution of the settling process is presented in Fig. 20. It is observed that approximately 98 % of the grease volume settled back to the lower region of the bearing within 40 seconds.

4 Conclusions

The primary objective of this study was to develop a full-scale CFD model of a tilted 41513219 double-row TRB to analyze in detail the behavior of a non-Newtonian lubricant—specifically, grease—under various operating conditions. An extensive three-dimensional hexahedral mesh of the entire bearing geometry was generated in OpenFOAM® using a parametric approach implemented through a custom MATLAB® script. The final mesh comprised approximately 12.5 million cells. A VoF model was employed to accurately capture the interface between grease and air. The complex rheological characteristics of the grease were modeled using the Herschel–Bulkley formulation.

The developed CFD model provided in detail the successfully captured key lubrication characteristics by simulating the bearing behavior at three different grease filling ratios. Using this model, detailed analyses A detailed analysis of grease distribution, pressure fields, and velocity profiles were conducted, within the bearing enabled the identification of critical zones prone to grease starvation. Grease fluxes were investigated, revealing both a pumping effect and a squeezing action near the roller ends. Seal pressures were also evaluated to assess the potential risk of grease leakage.

Lubricant behavior within the bearing is significantly influenced by gravitational and tilting effects. The upper region of the bearing exhibits noticeable grease starvation compared to the lower region due to gravitational settling. Additionally, the tilt toward the main MFS results in greater grease accumulation in the MFS row relative to the HS row.

In this study, simulations were conducted for varying grease filling ratios. The developed model can also be extended to simulate different operating conditions, such as variations in rotational speed and grease rheological properties. Overall, the developed model provides a robust framework for analyzing lubrication behavior in large-scale double-row tapered-roller bearings-TRBs and serves as a valuable tool for optimizing lubrication system design. A state of the art test rig is in the

505 developing stage which will further enhance the depth of understanding regarding lubrication physics involved in [large-size](#)
double-row TRBs ~~in large sizes~~.

Author contributions. Conceptualization, M.I.K., L.M., F.C.; methodology, M.I.K.; software, M.I.K., L.M.; validation, M.I.K.; formal analysis, M.I.K.; investigation, M.I.K.; resources, F.C.; data curation, M.I.K.; writing—original draft preparation, M.I.K.; writing—review and editing, M.I.K., L.M., F.C.; visualization, M.I.K.; supervision, L.M., F.C.; project administration, F.C.; funding acquisition, F.C. All authors
510 have read and agreed to the published version of the manuscript.

Competing interests. The authors declare that they have no conflict of interest.

Financial support. This research was funded by PNRR DM117 I52B23000570003.

References

- Aamer, S., Sadeghi, F., Russell, T., Peterson, W., Meinel, A., and Grillenberger, H.: Lubrication, flow visualization, and multiphase CFD modeling of ball bearing cage, *Tribology Transactions*, 65, 1088–1098, <https://doi.org/10.1080/10402004.2022.2123420>, 2022.
- Arya, U., Sadeghi, F., Aamer, S., Meinel, A., and Grillenberger, H.: In Situ Visualization and Analysis of Oil Starvation in Ball Bearing Cages, *Tribology Transactions*, 66, 965–978, <https://doi.org/10.1080/10402004.2023.2253867>, 2023.
- Bercea, I., Cretu, S., and Nélías, D.: Analysis of double-row tapered roller bearings, Part I-Model, *Tribology transactions*, 46, 228–239, 2003.
- Chen, H., Liang, H., Wang, W., and Zhang, S.: Investigation on the oil transfer behaviors and the air-oil interfacial flow patterns in a ball bearing under different capillary conditions, *Friction*, 11, 228–245, 2023.
- Concli, F., Schaefer, C. T., and Bohnert, C.: Innovative meshing strategies for bearing lubrication simulations, *Lubricants*, 8, 46, <https://doi.org/10.3390/lubricants8040046>, 2020.
- Crouchez-Pillot, A. and Morvan, H. P.: CFD simulation of an aeroengine bearing chamber using an enhanced volume of fluid (VOF) method: An evaluation using adaptive meshing, in: *Turbo Expo: Power for Land, Sea, and Air*, vol. 45738, p. V05CT16A033, American Society of Mechanical Engineers, 2014.
- Deng, S., Zhao, G., Qian, D., Jiang, S., and Hua, L.: Investigation of oil–air flow and temperature for high-speed ball bearings by combining nonlinear dynamic and computational fluid dynamics models, *Journal of Tribology*, 144, 071 204, 2022.
- Feldermann, A., Fischer, D., Neumann, S., and Jacobs, G.: Determination of hydraulic losses in radial cylindrical roller bearings using CFD simulations, *Tribology International*, 113, 245–251, <https://doi.org/10.1016/j.triboint.2017.03.020>, 2017.
- Gao, P., Tang, W., Cui, Y., Wang, Y., Mo, G., and Yin, J.: Theoretical and Experimental Investigation on Thermal Characteristics of Railway Double-Row Tapered Roller Bearing, *Energies*, 15, <https://doi.org/10.3390/en15124217>, 2022a.
- Gao, W., Zhang, S., Li, X., and Liu, Z.: Investigation on the drag effect of a rolling element confined in the cavity of a cylindrical roller bearing, *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 236, 777–785, <https://doi.org/10.1177/13506501211026063>, 2022b.
- Gonda, A., Großberndt, D., Sauer, B., and Schwarze, H.: Experimental and numerical investigations of hydraulic losses in rolling bearings under practice-oriented conditions (Experimentelle und numerische untersuchungen der hydraulischen Verluste in Wälzlager unter praxisrelevanten Bedingungen), *Tribol. Schmier*, 65, 7–13, 2018.
- Gonda, A., Sauer, B., Großberndt, D., and Schwarze, H.: Experimental and numerical investigations of hydraulic losses in fully and partially fluted, tapered roller bearings [experimentelle und numerische untersuchungen der hydraulischen verluste in voll-und teilgefluteten kegelrollenlagern], *VDI Berichte*, 2348, 97–106, 2019.
- Hart, E., Turnbull, A., Feuchtwang, J., McMillan, D., Golysheva, E., and Elliott, R.: Wind turbine main-bearing loading and wind field characteristics, *Wind Energy*, 22, 1534–1547, <https://doi.org/10.1002/we.2386>, 2019.
- Hart, E., Clarke, B., Nicholas, G., Kazemi Amiri, A., Stirling, J., Carroll, J., Dwyer-Joyce, R., McDonald, A., and Long, H.: A review of wind turbine main bearings: design, operation, modelling, damage mechanisms and fault detection, *Wind Energy Science*, 5, 105–124, <https://doi.org/10.5194/wes-5-105-2020>, 2020.
- Hoeprich, M. R.: Grease Performance in Tapered Roller Bearings, in: *World Tribology Congress*, vol. 42029, pp. 189–190, <https://doi.org/10.1115/WTC2005-64352>, 2005.
- Hong, S.-W. and Tong, V.-C.: Rolling-element bearing modeling: A review, *International Journal of Precision Engineering and Manufacturing*, 17, 1729–1749, 2016.

- 550 Hu, J., Wu, W., Wu, M., and Yuan, S.: Numerical investigation of the air–oil two-phase flow inside an oil-jet lubricated ball bearing, *International Journal of Heat and Mass Transfer*, 68, 85–93, <https://doi.org/10.1016/j.ijheatmasstransfer.2013.09.013>, 2014.
- Intergovernmental Panel on Climate Change: Climate Change 2022: Mitigation of Climate Change. Contribution of Working Group III to the Sixth Assessment Report of the Intergovernmental Panel on Climate Change, https://sdgs.un.org/sites/default/files/2023-01/IPCC_AR6_WGIII_FullReport.pdf, accessed: 2025-04-28, 2022.
- 555 Ishaq Khan, M., Maccioni, L., and Concli, F.: Trends in Lubrication Research on Tapered Roller Bearings: A Review by Bearing Type and Size, Lubricant, and Study Approach, *Lubricants*, 13, <https://doi.org/10.3390/lubricants13050204>, 2025.
- Kaymaz, E., Duman, S., and Guvenc, U.: Optimal power flow solution with stochastic wind power using the Lévy coyote optimization algorithm, *Neural Computing and Applications*, 33, 6775–6804, 2021.
- Keller, J., Sheng, S., Cotrell, J., and Greco, A.: Wind Turbine Drivetrain Reliability Collaborative Workshop: A Recap, 2016.
- 560 Khonsari, M. M. and Booser, E. R.: *Applied Tribology: Bearing Design and Lubrication*, John Wiley & Sons, Hoboken, NJ, 2017.
- Li, M., Lu, F., Bai, X., Zhu, W., and Zhu, R.: Heat-flow coupling variation in double-row tapered-roller bearings during the loss of lubrication process, *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 236, 7500–7510, <https://doi.org/10.1177/09544062221075185>, 2022.
- Liebrecht, J., Si, X., Sauer, B., and Schwarze, H.: Untersuchungen von hydraulischen Verlusten an Kegelrollenlagern, *Tribologie und Schmierungstechnik*, 62, 14–21, 2015.
- 565 Liebrecht, J., Si, X., Sauer, B., and Schwarze, H.: Berücksichtigung des Größeninflusses bei der Berechnung der Plansch- und Schleppverluste an Wälzlagern, *Tribologie und Schmierungstechnik*, 64, 46–52, 2017.
- Liu, J.: Analysis of tapered roller bearings considering high speed and combined loading, <https://doi.org/10.1115/1.3452933>, 1976.
- Loriemi, A., Jacobs, G., Reisch, S., Bosse, D., and Schröder, T.: Experimental and simulation-based analysis of asymmetrical spherical roller bearings as main bearings for wind turbines, *Forschung im Ingenieurwesen*, 85, 189–197, <https://doi.org/10.1007/s10010-021-00462-1>, 2021.
- 570 Maccioni, L. and Concli, F.: Computational fluid dynamics applied to lubricated mechanical components: Review of the approaches to simulate gears, bearings, and pumps, *Applied Sciences*, 10, 8810, <https://doi.org/10.3390/app10248810>, 2020.
- Maccioni, L., Chernoray, V. G., Bohnert, C., and Concli, F.: Particle Image Velocimetry measurements inside a tapered roller bearing with an outer ring made of sapphire: Design and operation of an innovative test rig, *Tribology International*, 165, 107313, <https://doi.org/10.1016/j.triboint.2021.107313>, 2022a.
- 575 Maccioni, L., Chernoray, V. G., Mastrone, M. N., Bohnert, C., and Concli, F.: Study of the impact of aeration on the lubricant behavior in a tapered roller bearing: Innovative numerical modelling and validation via particle image velocimetry, *Tribology International*, 165, 107301, <https://doi.org/10.1016/j.triboint.2021.107301>, 2022b.
- 580 Maccioni, L., Chernoray, V. G., and Concli, F.: Fluxes in a full-flooded lubricated tapered roller bearing: particle image velocimetry measurements and computational fluid dynamics simulations, *Tribology International*, 188, 108824, <https://doi.org/10.1016/j.triboint.2023.108824>, 2023a.
- Maccioni, L., Rüth, L., Koch, O., and Concli, F.: Load-Independent Power Losses of Fully Flooded Lubricated Tapered Roller Bearings: Numerical and Experimental Investigation of the Effect of Operating Temperature and Housing Wall Distances, *Tribology Transactions*, 66, 1078–1094, <https://doi.org/10.1080/10402004.2023.2254957>, 2023b.
- 585

- Maccioni, L., Chernoray, V. G., and Concli, F.: Investigating lubricant behavior in a partially flooded tapered roller bearing: Validation of a multiphase CFD solver for aerated oil sump via particle image velocimetry studies and high-speed camera acquisitions, *Tribology International*, 201, 110 274, <https://doi.org/h10.1016/j.triboint.2024.110274>, 2025.
- Mang, T. and Dresel, W.: *Lubricants and Lubrication*, 2nd ed., Wiley-VCH, Weinheim, Germany, 2007.
- 590 Manjunath, M., Hausner, S., Heine, A., De Baets, P., and Fauconnier, D.: Electrical impedance spectroscopy for precise film thickness assessment in line contacts, *Lubricants*, 12, 51, <https://doi.org/10.3390/lubricants12020051>, 2024.
- Marchesse, Y., Changenet, C., and Ville, F.: Drag power loss investigation in cylindrical roller bearings using CFD approach, *Tribology Transactions*, 62, 403–411, <https://doi.org/10.1080/10402004.2018.1565009>, 2019.
- Niemann, G. and Winter, H.: *Gears in General, Spur Gears – Fundamentals, Spur Gear Drives, Machine Elements*, Springer, Berlin/Heidelberg, Germany, 2002.
- 595 OpenFOAM® Foundation: OpenFOAM®: The Open Source CFD Toolbox, OpenFOAM Foundation Ltd., <https://www.openfoam.org/>, 2024.
- Perez, J. M.: *Lubrication Fundamentals*, CRC Press, Boca Raton, FL, 2004.
- Raju, K., Veettil, M. P., Ray, S., and Shi, F.: Needle roller bearing lubricant flow CFD simulations, Tech. rep., SAE Technical Paper, 2013.
- Ren, X., Xiao, Y., He, F., and Gozgor, G.: The contagion of extreme risks between fossil and green energy markets: evidence from China, *Quantitative Finance*, 24, 627–642, 2024.
- 600 Russell, T., Sadeghi, F., Peterson, W., Aamer, S., and Arya, U.: A novel test rig for the investigation of ball bearing cage friction, *Tribology Transactions*, 64, 943–955, <https://doi.org/10.1080/10402004.2021.1953657>, 2021.
- Sadeghi, F., Arya, U., Aamer, S., and Meinel, A.: A review of computational fluid dynamics approaches used to investigate lubrication of rolling element bearings, *Journal of Tribology*, 146, 100 801, <https://doi.org/10.1115/1.4065663>, 2024.
- 605 Santhosh, R., Hee, J. L., Simmons, K., Johnson, G., Hann, D., and Walsh, M.: Experimental investigation of oil shedding from an aero-engine ball bearing at moderate speeds, in: *Turbo expo: power for land, sea, and air*, vol. 50923, p. V07AT34A018, American Society of Mechanical Engineers, <https://doi.org/10.1115/GT2017-63815>, 2017.
- Sun, Q. G., Wang, Y. F., Wang, Y., Niu, P., and Wang, X. S.: Numerical study on rolling bearing temperature field under the oil-air lubrication, *Applied Mechanics and Materials*, 487, 580–584, 2014.
- 610 Terwey, J. and Mendelin, J.: Design-to-cost for TRB-TRB wind turbine main bearing systems, *Forschung im Ingenieurwesen*, 89, 18, 2025.
- Tong, V.-C. and Hong, S.-W.: Characteristics of tapered roller bearing subjected to combined radial and moment loads, *International journal of precision engineering and manufacturing-green technology*, 1, 323–328, <https://doi.org/10.1007/s40684-014-0040-1>, 2014.
- Versteeg, H. K.: *An introduction to computational fluid dynamics the finite volume method*, 2/E, Pearson Education India, 2007.
- Wen, Y. and Oshima, S.: Oil flow simulation based on CFD for reducing agitation torque of ball bearings, *SAE International Journal of Passenger Cars-Mechanical Systems*, 7, 1385–1391, <https://doi.org/10.4271/2014-01-2850>, 2014.
- 615 Wu, W., Hu, C., Hu, J., and Yuan, S.: Jet cooling for rolling bearings: Flow visualization and temperature distribution, *Applied Thermal Engineering*, 105, 217–224, <https://doi.org/10.1016/j.applthermaleng.2016.05.147>, 2016.
- Zhang, S.-w.: Green tribology: Fundamentals and future development, *Friction*, 1, 186–194, 2013.
- Zhu, W., Zhu, R., Tang, X., Lu, F., Bai, X., Wu, X., and Li, F.: CFD-based analysis of oil and gas two-phase flow characteristics in double-row tapered roller bearings with different rib structures, *Applied Sciences*, 12, 1156, <https://doi.org/10.3390/app12031156>, 2022.
- 620