Fast ~~blockage~~ models for blockage and gravity-wave effects on wind-farm power ~~prediction~~output

Koen Devesse[1] and Johan Meyers[1]

[1]Department of Mechanical Engineering, KU Leuven, Leuven, Belgium

Correspondence: Koen Devesse (koen.devesse@kuleuven.be)

Abstract. Large offshore wind farms can trigger atmospheric gravity waves, with the associated hydrostatic blockage effect impacting their energy yield. Unfortunately, to date no tools exist that can model this wind-farm gravity-wave interaction and blockage at a computational cost that is not drastically higher than conventional engineering wake models. To address this, this paper ~~applies insights from~~ develops ways of speeding up atmospheric perturbation models (APMs) by an order of magnitude by applying insights from the recently proposed two-scale momentum (2SM) theory ~~to an atmospheric perturbation model (APM), thereby significantly speeding up the latter.~~ (Nishino and Dunstan, J. Fluid Mech., vol. 894, 2020, A2). This leads to two different models, with one using pre-computed farm-level coefficients to compute the turbine forces and power output, while the other relies on repeated wake model evaluations. The core 2SM hypothesis of scale separation and both developed models are validated using a prior LES dataset of a large rectangular wind farm. Both fast 2SM–APMs perform well, predicting blockage-corrected farm power at a computational cost that is only a factor ~~40~~ 35 slower than a standalone wake model.

1 Introduction

As offshore wind turbines and farms continue to grow in both size and installed capacity, they reach the point where they form an obstacle to the entire atmospheric boundary layer (ABL) ~~. In~~ (Bleeg et al., 2018). Large Eddy Simulation (LES) studies have shown that in conventionally neutral boundary layers (CNBLs), where a neutral ABL is topped by a capping inversion and a stratified upper atmosphere, ~~they~~ wind farms can trigger gravity waves, creating upstream pressure gradients and blockage effects ~~that impact their performance (Bleeg et al., 2018; Allaerts and Meyers, 2017, 2018; Centurelli et al., 2021; Lanzilao and Meyers, 202~~ ~~. As offshore wind turbines and farms continue to grow in size and capacity,~~ (Allaerts and Meyers, 2017, 2018; Centurelli et al., 2021; Lanzi . As these mesoscale effects affect turbine power output, they are becoming more important to farm operation and planning.

Currently, conventional engineering tools rely on the superposition of individual turbine effects, thereby implicitly assuming that their aggregate effect is not larger than the sum of its parts (Porté-Agel et al., 2020). These *wake models* (WMs) remain widely used because of their low computational cost, which makes them well-suited for farm planning, control, and annual energy production estimates. In contrast, computational fluid dynamics (CFD) methods like Reynolds-averaged Navier-Stokes (RANS), ~~large-eddy simulations (LES)~~LES, or mesoscale climate models are able to capture most of the relevant flow phenomena. However, their high cost prevents them from being widely used for fast farm power predictions (Meyers et al., 2022).

Installing and operating the next generation of offshore wind farms will therefore require new models that can simulate ~~atmospheric flow dynamics~~the generation of blockage and gravity waves, while keeping the computational cost orders of magnitude below conventional CFD methods. One promising recently developed tool that fits these requirements is the atmospheric perturbation model (APM) (Allaerts and Meyers, 2019; Devesse et al., 2024a; Stipa et al., 2024a). Building on earlier work by Smith (2010), this model simulates the large-scale wind-farm atmosphere interaction explicitly, while coupling to conventional wake models ~~for fast farm power predictions. However, it still has to repeatedly solve linear differential equations, resulting in a relatively high computational cost~~ to account for turbine-scale flow effects. In order to capture the local inter-farm feedback effects between the turbine forces and the mesoscale flow, the governing system of equations is solved repeatedly in a fixed-point iteration. This constitutes the main cost of the model, which is low compared to conventional CFD tools but relatively high compared to standard wake models (several hundred to a thousand times slower, or approximately one to five minutes on a standard laptop per simulation) (Devesse et al., 2024b).

One way to further simplify and speed up the modeling of wind-farm atmosphere interactions is the two-scale momentum (2SM) framework introduced by Nishino and Dunstan (2020). At its core, this approach assumes a separation between the turbine- and farm-scale flows. As a result of this hypothesis, variations in farm power output due to mesoscale effects are fully determined by the associated changes in the average velocity over the farm. Based on high-fidelity LES results, this hypothesis has been confirmed for large wind farms in idealized conditions (Kirby et al., 2022, 2025).

Other recent studies have proposed wind farm models relying on the ~~same idea~~ similar ideas of scale separation. van der Laan et al. (2023) and Stipa et al. (2024c) proposed actuator-farm models for RANS and LES, respectively, allowing these methods to simulate wind farms without resolving the turbine-scale flow. Similarly, Du et al. (2025) developed a wind-farm parametrization for mesoscale weather models, which due to their kilometer-scale resolution cannot represent individual turbines, based on matching the average velocity in the farm between the mesoscale model and a wake model. However, since these studies are not as explicit in their theoretical treatment of this scale separation, we will refer to the overall idea as the two-scale momentum approach, following Nishino and Dunstan (2020).

~~The goal of the current paper is to combine~~ Our goal is to develop fast models for predicting wind-farm power output that account for blockage and gravity wave effects. To that end, the 2SM ~~and APM~~ framework can be useful, as it implies that flow solvers simulating the farm-scale flow do not have to resolve the turbine-scale flow. This would allow for coarser grid resolutions and reduced computational costs. However, even when using coarser grids, conventional CFD tools are still multiple orders of magnitude slower than engineering wake models (Ouro et al., 2025). In contrast, the APM already uses a coarse resolution, while its main cost lies in capturing the local feedback effects between the turbine forces and the mesoscale flow. Therefore, we focus on combining the 2SM and APM approaches, leveraging insights from the former to speed up and simplify the latter. ~~Since~~

Since, according to the 2SM hypothesis~~states that~~, a farm's power output only depends on the average velocity in the farm, the APM may neglect ~~the variations~~ local changes in the turbine force distribution within the farm induced by gravity wave effects. Instead, this force distribution can be scaled uniformly over the farm to match the total farm force as predicted by 2SM theory. Due to the linear nature of the APM, this transforms the model's governing equations into a system of scalar equations,

drastically lowering its computational cost. We use this to develop two versions of the sped-up APM, one which uses farm thrust and power coefficients to model the farm, following earlier 2SM studies, and one which couples directly to a standard wake model. Both models are validated using the LES dataset of a large wind farm operating in idealized CNBL conditions from Lanzilao and Meyers (2024).

The remainder of this paper is outlined as follows. Section 2 provides an overview of 2SM theory, and demonstrates its core hypothesis using the LES results of Lanzilao and Meyers (2024). Section 3 then introduces the APM's governing equations and how they are solved. Combining these two, section 4 shows how a 2SM–APM can cheaply calculate a farm's power output if its farm-level thrust and power coefficients are known. Building on this, section 5 develops an alternative method that couples the farm-averaged APM output directly to a wake model, thereby eliminating the need for these farm coefficients but requiring repeated wake model evaluations. Finally, section 6 gives an overview of the results and an outlook for future research.

2 Two-scale Momentum Theory

Recently, Kirby et al. (2025) demonstrated that the 2SM theory developed by Nishino and Dunstan (2020) can be used to simplify the interaction between mesoscale atmospheric flows and wind farm operation. The core hypothesis of 2SM theory is a separation of internal and external effects and the associated spatial scales. Internal effects, such as turbine setpoints and wakes, determine the ratios of the individual turbine disk velocities S_k to the average streamwise velocity U_f in the farm region. External effects, such as large-scale momentum advection, entrainment above the farm, or gravity-wave-induced pressure gradients, act on the farm scale, and affect the average velocity within the farm U_f. The total farm power P_f can then be expressed as

$$P_f = C_p^* \frac{\rho U_f^3}{2} A_f, \quad C_p^* = \sum_{k=1}^{N_t} C'_{p,k} \frac{S_k^3}{U_f^3} \frac{A_k}{A_f}, \quad A_f = \sum_{k=1}^{N_t} A_k, \tag{1}$$

where ρ is the air density, A_f is the total rotor area of the farm turbines, C_p^* is the internal farm power coefficient, N_t is the number of turbines, and A_k and $C'_{p,k}$ are the turbine disk areas and disk-based power coefficients, respectively, with k indicating the turbine number.

Nishino and Dunstan (2020) make an analogous argument for the farm thrust, so that

$$F = C_T^* \frac{U_f^2}{2} A_f, \quad C_T^* = \sum_{k=1}^{N_t} C'_{T,k} \frac{S_k^2}{U_f^2} \frac{A_k}{A_f}, \tag{2}$$

where F is the total farm force (scaled with air density), C_T^* is the farm thrust coefficient, and $C'_{T,k}$ are the disk-based turbine thrust coefficients. Like C_p^*, the internal farm thrust coefficient C_T^* is assumed to only depend on the internal problem.

~~Earlier work by Kirby et al. (2025) has shown~~ Kirby et al. (2025) investigated this assumption using LES results of large wind farms with uniform turbine densities in below-rated conditions. They found that the internal power coefficient C_p^* as defined in equation (1) is a good heuristic for internal effects~~. The 2SM hypothesis~~ , and remained constant over cases with different mesoscale flow behavior. This then implies that C_p^* can be calculated using ~~neutral flow~~ small-scale simulations of

the same farm or engineering wake models, while the problem of including mesoscale stratification effects in farm power calculations is simplified to solving only the external problem, i.e. estimating U_f.

We demonstrate this by taking C_p^* from a neutral flow simulation, and U_f from different CNBL simulations with different meso-scale stratification effects, but the same farm layout ~~.~~ and geostrophic wind speed. We then estimate the power produced in the CNBL cases using equation 1, and compare it against the actual production. For this, we use the prior LES dataset from Lanzilao and Meyers (2024), which consists of 36 simulations of the same large wind farm ~~(Lanzilao and Meyers, 2023b)~~ in idealized steady CNBL conditions (Lanzilao and Meyers, 2023b), which was also used by Kirby et al. (2025). This farm has 160 10MW turbines, arranged ~~in a uniform staggered layout~~uniformly in a rectangular staggered layout, operating at below-rated conditions. Each simulation has a different combination of boundary layer heights H, capping inversion strengths $\Delta\theta$, and atmospheric lapse rates Γ. The different cases are identified with these parameters, so that $H500$-$\Delta\theta5$-$\Gamma4$ denotes the case with the precursor profile initialized with these values. For each boundary layer height, the dataset also includes ~~a truly neutral~~ simulations of a wind-farm ~~simulation~~in truly neutral flow and of a stand-alone turbine with $\Delta\theta = 5\mathrm{K}$ and $\Gamma = 4\mathrm{K/km}$. A detailed description of the LES setup and results is given by Lanzilao and Meyers (2024).

We calculate U_f as a straightforward average over the wind farm, so that

$$U_f = \frac{1}{H_f \Omega_f} \int_0^{H_f} \iint_{\Omega_f} u \mathrm{d}\Omega_f \mathrm{d}z, \tag{3}$$

where H_f is the height of the 2SM averaging volume, and Ω_f the planform area of the wind farm. We take Ω_f to be a rectangle around the farm edge, thereby including the outer edges of the turbine disks at the sides. We set the height H_f of the volume ~~over which the farm average is defined equal~~ to twice the turbine hub height z_h, as this corresponds to the setup of the APM (see section 4.1). This height is above the turbine tip height but below the ABL height for all the cases in the dataset of Lanzilao and Meyers (2024). ~~Note that this is not the same height as was used in previous~~ While some of the $H150$ cases have lower unperturbed ABL heights, strong vertical displacements of the capping inversions over the wind farm ensure that even there the ABL height is above the 2SM ~~studies (Nishino and Dunstan, 2020; Kirby et al., 2022, 2025), where consistently $H_f = 2.5z_h$. However, we believe the lower height yields better results, as it aligns more closely with the region relevant to turbine-scale flow. It also does not stick out into the free atmosphere for the cases with very shallow boundary layers, whereas the higher one does. This probably explains why we find C_p^* to be consistent across all cases, whereas Kirby et al. (2025) found that the farm coefficients change for the lowest capping inversions . Finally, we also use a slightly wider averaging volume to avoid leaving out parts of the disks at the edges of the farm~~control volume. The exact dimensions of the resulting control volume are listed in table 1. This simple approach is possible because the analyzed farm has a convex and uniform layout. More realistic farms might require a more complex horizontal averaging method such as the one proposed by van der Laan et al. (2023), where the wind speed is weighted by Gaussian distributions centered around the turbines. Alternatively, a farm could be split in two or more homogeneous regions. Further investigation of such approaches is beyond the scope of this study, and left as promising future work.

Table 1. Specification of the 2SM farm averaging volume for the cases of Lanzilao and Meyers (2024).

Dimension	Value
Height H_f	238 m
Length	14.85 km
Width	9.603 km




Figure 1. A comparison of farm power P_f as calculated by LES (x-axis) and equation 1 (y-axis) for all 36 CNBL cases from the dataset by Lanzilao and Meyers (2024), scaled with the power outputs of standalone turbine simulations P_0. The power coefficient C_p^* is calculated using a neutral flow simulation (i.e. case $H500$-$\Delta\theta0$-$\Gamma0$ from the same dataset).

To calculate C_p^*, we use the 3D time-averaged velocity fields of case $H500$-$\Delta\theta0$-$\Gamma0$. After averaging the streamwise velocity field to obtain U_f, we obtain C_p^* from equation 1. Subsequently, the farm power ~~for the other~~ outputs for the 36 CNBL cases are calculated by averaging their U_f and combining it with the prior C_p^* through equation 1. ~~The resulting power outputs are scaled with the power output of a standalone turbine P_0~~ In order to avoid issues with the power calculation in LES related to the used actuator-disk method and grid size ~~,~~ (Shapiro et al., 2019), the resulting power outputs are scaled with the power outputs P_0 of standalone turbines operating at the same inflow wind speeds, as was done by Lanzilao and Meyers (2024). The results are shown in figure 1. The root-mean square error (RMSE) on P_f is 1% of the farm installed capacity, ~~showing that under idealized conditions~~ which shows that a C_p^* value calculated from a neutral simulation remains applicable over a wide range of CNBL flows. We conclude that the 2SM assumption ~~yields good results~~holds under the idealized conditions tested here.




Figure 2. Schematic representation of the atmospheric perturbation model. Figure reproduced from D. Allaerts and J. Meyers, Sensitivity and feedback of wind-farm-induced gravity waves, Journal of Fluid Mechanics, 862, 990-1028 (2019).

3 Atmospheric Perturbation Model

If C_P^* and C_T^* are known, calculating the farm power output with the 2SM approach then comes down to finding the average farm velocity U_f. The APM is well-suited for this, as it is a fast model for mesoscale atmosphere–farm interaction. Therefore, this section presents a brief overview of the APM.

The APM is a simplified model, and treats the ABL as two layers of vertically averaged flow, separated by a pliant surface following the flow streamlines (Allaerts and Meyers, 2019). In each of these layers, the continuity and horizontal momentum equations are solved explicitly for the average velocities and layer thicknesses. The wind-farm forces are added in the momentum equations for the lower layer, also called the wind-farm layer, while only affecting the upper layer via interactions through the pliant surface. The resulting model structure is visualized in figure 2.

The main advantage of the APM is that the vertical averaging drastically lowers the computational cost of the model compared to conventional ~~simulation tools~~CFD or mesoscale simulations, since it essentially reduces the vertical resolution to the ABL height. The horizontal resolution is likewise reduced by applying a Gaussian filter with a kernel size of 1 km (Allaerts and Meyers, 2019; Devesse et al., 2024a).

Mathematically, the APM can be derived by applying these filtering and height-averaging operators to the flow. For example, the lower layer velocity is defined as (Devesse et al., 2024a)

$$\langle \widetilde{\boldsymbol{u}} \rangle_1 = \frac{1}{h_1} \int_0^{h_1} \iint_{L_x \times L_y} G_\ell(x - x', y - y') \boldsymbol{u}(x', y', z) \mathrm{d}x' \mathrm{d}y' \mathrm{d}z, \tag{4}$$

where~~the subscript~~ x, y and z, denote the streamwise, spanwise, and vertical coordinates, respectively, the subscript 1 indicates the lower layer, the angled brackets and tilde denote the height-averaging and filtering, respectively, $\boldsymbol{u}$ is the horizontal velocity vector, h_1 is the lower layer thickness, $L_x \times L_y$ is the APM domain size, and G_ℓ is a Gaussian kernel with a fixed filter length $\ell = 1\mathrm{km}$. The ~~flow is~~ pliant surface h_1 is defined as following the streamlines of the horizontally filtered flow, so that

(Allaerts and Meyers, 2019)

$$\widetilde{w}(x,y,z_1) = \widetilde{\boldsymbol{u}}(x,y,z_1)\cdot\nabla_h h_1, \tag{5}$$

where w is the vertical velocity component, and ∇_h is the horizontal del operator. The flow is then further linearized around a uniform background state, so that for the lower layer

$$\langle\widetilde{\boldsymbol{u}}\rangle_1 = \boldsymbol{U}_1 + \boldsymbol{u}_1', \quad h_1 = H_1 + \eta_1, \tag{6}$$

where $\boldsymbol{U}_1$ and H_1 are the unperturbed layer velocity and thickness in the absence of the wind farm, and $\boldsymbol{u}_1'$ and η_1 are the perturbations to this state. For the upper layer, the notation is analogous.

The governing equations of the model can then be found by applying the above operators to the incompressible Reynolds-averaged steady-state Navier-Stokes equations, and linearizing the result. Thorough descriptions of this procedure can be found in Allaerts and Meyers (2019) and Devesse et al. (2024a). The resulting set of equations is

$$\boldsymbol{U}_1\cdot\nabla_h\eta_1 + H_1\nabla_h\cdot\boldsymbol{u}_1' = 0, \tag{7}$$

$$\boldsymbol{U}_2\cdot\nabla_h\eta_2 + H_2\nabla_h\cdot\boldsymbol{u}_2' = 0, \tag{8}$$

$$\begin{aligned}\boldsymbol{U}_1\cdot\nabla_h\boldsymbol{u}_1' &= -\frac{1}{\rho}\nabla_h p' + f_c\mathbf{J}\cdot\boldsymbol{u}_1' \\ &\quad +\nu_{t,1}\nabla_h^2\boldsymbol{u}_1' + \frac{\mathbf{D}'}{H_1}\cdot\Delta_1^2\boldsymbol{u}' - \frac{\mathbf{C}'}{H_1}\cdot\boldsymbol{u}_1' - \frac{\boldsymbol{T}_{h3,1}-\boldsymbol{T}_{h3,0}}{H_1^2}\eta_1 \\ &\quad +\frac{\widetilde{\boldsymbol{f}}_{wf}+\widetilde{\Delta\boldsymbol{\tau}_{wf}}}{H_1+\eta_1} + \nabla_h\cdot\langle\boldsymbol{\tau}_{d,hh}\rangle_1,\end{aligned} \tag{9}$$

$$\begin{aligned}\boldsymbol{U}_2\cdot\nabla_h\boldsymbol{u}_2' &= -\frac{1}{\rho}\nabla_h p' + f_c\mathbf{J}\cdot\boldsymbol{u}_2' + \nu_{t,2}\nabla_h^2\boldsymbol{u}_2' - \frac{\mathbf{D}'}{H_2}\cdot\Delta_1^2\boldsymbol{u}' + \frac{\boldsymbol{T}_{h3,1}}{H_2^2}\eta_2 \\ &\quad -\frac{\widetilde{\Delta\boldsymbol{\tau}_{wf}}}{H_2+\eta_2},\end{aligned} \tag{10}$$

where the subscript h indicates horizontal vector components, p' is the pressure perturbation induced by gravity waves, ρ is the air density, f_c is the Coriolis parameter, $\mathbf{J}$ is the two-dimensional rotation dyadic, and ν_t are height-averaged eddy viscosities. Furthermore, $\boldsymbol{T}_{h3,0}$ and $\boldsymbol{T}_{h3,1}$ are the unperturbed turbulent shear stresses at the ground and the layer interface, respectively, and $\mathbf{C}'$ and $\mathbf{D}'$ are the Jacobians of these stresses to the layer velocities. Finally, $\boldsymbol{f}_{wf}$, $\Delta\boldsymbol{\tau}_{wf}$, and $\langle\boldsymbol{\tau}_{d,hh}\rangle_1$ are the perturbing effects of the wind farm, with $\boldsymbol{f}_{wf}$ denoting the turbine forces (scaled with air density), $\Delta\boldsymbol{\tau}_{wf}$ representing the shear stresses between the layers due to the added turbulence intensity caused by the farm, and $\langle\boldsymbol{\tau}_{d,hh}\rangle_1$ denoting dispersive stresses due to turbine-scale flow heterogeneity. For the sake of simplicity, the latter two are not included in this study.

The pressure perturbation in the ABL p' is caused by the gravity waves on the capping inversion and in the free atmosphere. These waves are themselves triggered by the displacement of the capping inversion $\eta_t = \eta_1 + \eta_2$. Their pressure feedback can be related to this displacement in Fourier space, so that ~~(Smith, 2010)~~ (Gill, 1982; Smith, 2010)

$$\frac{p'}{\rho} = g'\eta_t + \mathcal{F}^{-1}(\Phi) * \eta_t, \tag{11}$$

where g' is the reduced gravity in the capping inversion, $\mathcal{F}^{-1}$ denotes an inverse Fourier transform, and $*$ denotes a convolution. Continuing, Φ are the stratification coefficients, which determine the pressure feedback of the internal gravity waves in the free atmosphere. For uniform barotropic free atmospheres, these coefficients are calculated in Fourier space as ~~(Smith, 2010)~~ (Allaerts and Meyers, 2019)

$$\Phi = \frac{\mathrm{i}\left(N_g^2 - \Omega^2\right)}{m} \tag{12}$$

where $N_g = \sqrt{\frac{g}{\theta}\frac{\mathrm{d}\theta}{\mathrm{d}z}}$ is the Brunt-Väisälä frequency in the free atmosphere, and Ω is the intrinsic wave frequency. The vertical wavenumber m is given by the dispersion relation ~~(Gill, 1982)~~(Smith, 1980):

$$m^2 = \left(k^2 + l^2\right)\left(\frac{N_g^2}{\Omega^2} - 1\right), \tag{13}$$

where the sign of m has to be chosen to ensure that the perturbation dies out with height if $m^2 < 0$, or that energy radiates outwards if $m^2 > 0$.

The grid spacing of the APM is significantly larger than the individual turbine diameters. Therefore, the turbine forces are considered to be point forces before they are filtered onto the numerical grid using the same filter as in equation 4, so that the total force is simply a sum of Gaussians (Allaerts and Meyers, 2019):

$$\widetilde{\boldsymbol{f}}_{wf} = \sum_{k}^{N_t} G_{\ell,k}\boldsymbol{f}_k, \tag{14}$$

where each $G_{\ell,k}$ is a Gaussian kernel centered around turbine k, and the turbine thrusts f_k are (Allaerts and Meyers, 2019)

$$\boldsymbol{f}_k = \frac{1}{2}C'_{T,k}A_k S_k^2 \boldsymbol{e}_k, \tag{15}$$

where S_k and $\boldsymbol{e}_k$ are the turbine disk velocities and orientations, respectively~~. These turbine-level conditions depend on the APMstate, so that throughout the farm there is a two-way coupling between the turbine forces and the mesoscale flow. Past studies incorporated this coupling by calculating~~ , and $C'_{T,k}$ can be evaluated using S_k ~~with a wake model, and modifying~~ from the turbine thrust coefficient curve. Because the APM's resolution is too low to resolve the turbine-scale flow, these quantities are calculated using a wake model. To capture the dependence of the turbine forces on the local mesoscale flow, past studies developed ways to calculate the background velocity used by the wake model ~~'s background velocity to incorporate the mesoscale velocity fluctuations across the farm (Allaerts and Meyers, 2019; Stipa et al., 2024a; Devesse et al., 2024a, b).~~

~~The goal of this work is to define a faster farm-averaged coupling method based on 2SM theory.~~ based on the APM state (Allaerts and Meyers, 2019; Stipa et al., 2024a; Devesse et al., 2024a, b).

~~To incorporate~~ Since the pressure feedback of the internal gravity waves is mostly easily expressed in Fourier space, the system of equations 7-~~10~~ 11 is solved with a ~~Fourier-Galerkin~~ Fourier–Galerkin method. All terms in equations 7-10 except the turbine forces $\widetilde{\boldsymbol{f}}_{wf}$ then decouple per wavenumber, so that for a given $\widetilde{\boldsymbol{f}}_{wf}$ the system can be easily solved through matrix inversion. The turbine forces are included through a fixed-point iteration, where at each step the linear APM equations are solved for a given forcing. The resulting APM state is used to infer a background velocity for the wake model, which is then used to re-calculate the turbine forces ~~$\widetilde{\boldsymbol{f}}_{wf}$ are then re-calculated based on the APM state , and the~~ $\boldsymbol{f}_k$. This process is repeated until convergence. For details, see Devesse et al. (2024a).

The main numerical costs of the classical APM lie in solving equations 7-11 and re-calculating the wake model background velocity at each step of the fixed point iteration (Devesse et al., 2024b). These repeated calculations were needed to resolve the local coupling between the mesoscale APM state $(\boldsymbol{u}_1', \eta_1, p')$ and the turbine forces. However, 2SM theory allows us to neglect this local coupling, and consider a farm-averaged approach instead. This is the focus of the following sections.

4 Combining 2SM and APM

The 2SM approach simplifies the turbine-scale problem by relating the turbine forces and power outputs to only the average velocity in the farm through C_P^* and C_T^*. The most straightforward way of combining this with the APM is then to use the APM as the external model to find U_f, while using C_T^* and C_p^* to represent the turbine forces in the APM. This section focuses on developing such coupling and on leveraging the simplifications of 2SM theory to speed up the APM.

The goal of this section is use the APM to solve the external problem as cheaply as possible. Therefore, we treat the farm coefficients C_P^* and C_T^* as known inputs for now. However, their computation still represents an additional cost, associated with calculating the farm-averaged velocity in a prior (neutral) wake-model simulation. This will be addressed in section 5.2, using insights from the methods developed in this section.

We will build up the combination of the 2SM and APM approaches step by step. First, section 4.1 discusses the differences between the mathematical averaging operators used by 2SM theory and in the derivation of the APM, and bridges the gap between them. Then, section 4.2 sets up a simplified version of the APM focused on finding U_f, thereby leveraging the insights of 2SM theory to speed up the model. Finally, section 4.3 validates the developed 2SM–APM with the same LES dataset from Lanzilao and Meyers (2024) that was used in section 2, and investigates the use of wake models to calculate C_P^* and C_T^*.

4.1 Relating the average APM and 2SM velocities

Combining the 2SM and APM approaches requires us to relate the average farm velocity used in the 2SM equations to the average lower-layer APM velocity within the farm. ~~The former is defined~~ We defined the former as a straightforward average




Figure 3. Sketch of the farm control volume (black) and lower APM layer (red) for a rectangular farm. Note that in contrast to the 2SM farm control volume, the upper boundary of the APM layer is not rigid, as it follows the streamlines.

over the wind farm, so that

$$U_f = \frac{1}{H_f \Omega_f} \int_0^{H_f} \iint_{\Omega_f} u \mathrm{d}\Omega_f \mathrm{d}z, \tag{3}$$

where H_f is the height of the 2SM averaging volume, and Ω_f the planform area of the wind farm. As noted in section 2, modeling wind farms with irregular turbine layouts may require more complex horizontal averaging operators. However, this does not affect the following discussion conceptually.

In contrast, the APM predicts a horizontally filtered, height-averaged velocity field:

$$\langle \widetilde{u} \rangle_1 = \frac{1}{H_1 + \eta_1} \int_0^{H_1+\eta_1} \iint_{L_x \times L_y} G_\ell(x - x', y - y') u(x', y', z) \mathrm{d}x' \mathrm{d}y' \mathrm{d}z. \tag{4}$$

Averaging the APM variables over the farm can therefore only be done horizontally, so that

$$\overline{\langle \widetilde{u} \rangle}_1 = \frac{1}{\Omega_f} \iint_{\Omega_f} \langle \widetilde{u} \rangle_1 \mathrm{d}\Omega_f, \quad \overline{u}_1' = \frac{1}{\Omega_f} \iint_{\Omega_f} u_1' \mathrm{d}\Omega_f, \tag{16}$$

where the bars indicate ~~farm-averaging for APM variables~~horizontally averaging over the farm.

It's clear that the averages defined by equations 3 and 16 are not equivalent. Since the internal 2SM problem has to remain constant, the volume over which the farm average is defined should be independent of the mesoscale perturbation. However, the layer interface in the APM follows the flow streamlines, and its vertical displacement η_1 is part of the model state. This results in two different control volumes, as sketched in figure 3. Moreover, the APM velocity is filtered horizontally before being averaged, while the 2SM velocity is not.

In this work, we neglect the filtering effects, thus presuming

$$\frac{1}{\Omega_f} \iint_{\Omega_f} \langle \widetilde{u} \rangle_1 \mathrm{d}\Omega_f \approx \frac{1}{\Omega_f} \iint_{\Omega_f} \langle u \rangle_1 \mathrm{d}\Omega_f. \tag{17}$$

Relating the 2SM and APM averages then only requires accounting for the discrepancy in the control volumes. Choosing $H_f = H_1$ makes these volumes as similar as possible, so that the remaining difference is solely due to the streamline displacement η_1.

~~By then~~ The velocity in this region depends on the relative strength of the turbulent entrainment and gravity-wave-induced pressure gradients. Here, we take the simplest possible approach by assuming that the average velocity perturbation in the part of the APM layer above the 2SM volume scales with the velocity deficit within it, ~~we find~~ so that

$$(H_1+_1)'_1 \frac{1}{\overline{\eta}_1} \int_{H_1}^{H_1+\overline{\eta}_1} (\overline{u}-U_0)\mathrm{d}z \approx (H_1+\frac{\alpha}{H_1} \int_0^{H_1} (\overline{u}-U_0)\mathrm{d}z = \alpha_1) u'_f, \tag{18}$$

where U_0 is the unperturbed velocity profile, α is a tuning parameter between 0 (no ~~perturbation above the 2SM volume) and~~velocity deficit in the region $H_1 < z < H_1 + \overline{\eta}_1$) and 1 (perfectly mixed APM layer), and u'_f is the 2SM-farm-averaged velocity deficit:

$$u'_f = U_f - \int_0^{H_1} U_0 \mathrm{d}z$$

$$= U_f - U_1. \tag{19}$$

Taking the vertical integral up to $H_1 + \overline{\eta}_1$, we then find

$$(H_1 + \overline{\eta}_1)\overline{u}'_1 \approx (H_1 + \alpha\overline{\eta}_1)u'_f. \tag{20}$$

The 2SM-farm-averaged velocity can then be calculated from the APM state as

$$u'_f = \overline{u}'_1 \frac{H_1 + \overline{\eta}_1}{H_1 + \alpha\overline{\eta}_1}, \quad U_f = U_1 + \overline{u}'_1 \frac{H_1 + \overline{\eta}_1}{H_1 + \alpha\overline{\eta}_1}. \tag{21}$$

We tune α using the NBL case $H500$-$\Delta\theta0$-$\Gamma0$ from the dataset of Lanzilao and Meyers (2024). We calculate ~~APM states~~the APM state (u'_1, η_1) directly from the LES data by horizontally filtering the ~~flow fields~~time-averaged flow field, advecting a set of points to find the ~~height of the pliant surface between the APM layers~~displacement of the APM layer η_1, and height-averaging the flow. A detailed description of this procedure can be found in Devesse et al. (2024a). By relating the LES-based APM ~~states~~ state set up this way to the U_f calculated directly from the LES using equation 3, we find~~that $\alpha = 0.14$ gives good results.~~ $\alpha = 0.16$. Note that this basic approach does not capture the significant differences in velocity profiles between NBL, CNBL, and realistic flows, and is instead chosen for its simplicity.

4.2 Basic 2SM–APM coupling

We now focus on a fast 2SM–APM variant that will require solving the APM equations 7–~~10~~ 11 only once, rather than at every iteration, thereby significantly speeding up the model.

4.2.1 ~~Derivation~~

We begin by simplifying the notation. We can write the APM as a set of linear operators that transform the turbine forces to an APM state, so that

$$u_1' = \mathcal{A}_u\left(\frac{\boldsymbol{f}}{h_1}\frac{\boldsymbol{f}_{wf}}{h_1}\right), \quad \eta_1 = \mathcal{A}_\eta\left(\frac{\boldsymbol{f}}{h_1}\frac{\boldsymbol{f}_{wf}}{h_1}\right), \quad p' = \mathcal{A}_p\left(\frac{\boldsymbol{f}}{h_1}\frac{\boldsymbol{f}_{wf}}{h_1}\right), \tag{22}$$

where $\mathcal{A}_u$, $\mathcal{A}_\eta$, and $\mathcal{A}_p$ are linear operators that follow from the APM equations 7–11, and ~~$\boldsymbol{f}$~~ $\boldsymbol{f}_{wf}$ is the turbine force. Note that this assumes that the direct turbine forces are the only perturbing forcing in the ABL. A more general approach would have to include the dispersive stresses and the increase in momentum flux as well. However, this does not change the following derivation conceptually.

When using the APM with conventional wake model coupling methods, one of the largest computational costs is applying these operators $\mathcal{A}$, which involves a large linear system solve, at each step of the fixed-point iteration (Devesse et al., 2024b). In the classical APM, this iteration is needed because at each point in space, the local height-averaged farm force depends on the local velocity and layer thickness. ~~However, these local variables~~ While these local values impact individual turbine performance, they are not relevant to the 2SM approach, as it only requires the average velocity over the farm to calculate the farm power output. Since the goal of the 2SM–APM is to compute this ~~quantity~~ farm-averaged velocity as cheaply as possible, including ~~these~~ local variations is an unnecessary cost. Therefore, we will assume that the distribution of the force in space, normalized by the total force $F/\overline{h}_1$, is independent of the APM state $(\boldsymbol{u}_1', \eta_1, p')$, so that

$$\frac{\boldsymbol{f}}{h_1}\frac{\boldsymbol{f}_{wf}}{h_1} \approx \boldsymbol{\Pi}_f \frac{F}{H_1 + \overline{\eta}_1}, \tag{23}$$

where $\boldsymbol{\Pi}_f$ is the geometric footprint of the height-averaged force, and F is the total farm thrust (see eq. 2). If this footprint is indeed independent of the APM state, the model is reduced to a set of scalar equations:

$$\overline{u}_1' = a_u \frac{F}{H_1 + \overline{\eta}_1}, \quad \overline{\eta}_1 = a_\eta \frac{F}{H_1 + \overline{\eta}_1}, \tag{24}$$

where the coefficients a_u and a_η can be pre-computed:

$$a_u = \frac{1}{\Omega_f}\iint_{\Omega_f} \mathcal{A}_u\left(\boldsymbol{\Pi}_f\right) \mathrm{d}\Omega_f, \quad a_\eta = \frac{1}{\Omega_f}\iint_{\Omega_f} \mathcal{A}_\eta\left(\boldsymbol{\Pi}_f\right) \mathrm{d}\Omega_f. \tag{25}$$

We then arrive at a closed system of equations by computing the farm force F with equation 2, while relating U_f to the average APM perturbations using equation 21:

$$F = C_T^* \frac{U_f^2}{2} A_f, \tag{2}$$

$$U_f = U_1 + \overline{u}_1' \frac{H_1 + \overline{\eta}_1}{H_1 + \alpha\overline{\eta}_1}. \tag{21}$$

The linear system of equations 7–~~10~~ 11 now has to be inverted only once when calculating a_u and a_η~~, which greatly decreases the computational~~ . This effectively reduces the cost of the model to a single step of the fixed-point iteration used by the classical APM, while still incorporating the overall feedback between the turbine forces and blockage effects.

The closer the footprint $\mathbf{\Pi}_f$ ~~can bechosen freely. In this work~~is to the actual normalized force distribution, the more accurate we expect the coefficients a_u and a_η to be. However, this actual footprint is not known *a priori*. Instead, we use ~~the footprint of the farm forces obtained with~~ a standalone wake model ~~through~~ to estimate the footprint cheaply. The wake model can predict the turbine disk velocities S_k, which can be combined with equations 14–15 ~~and scaled with the total farm force~~to find the farm forcing, so that

$$\widetilde{\mathbf{\Pi}}_f = \sum_k^{N_t} C'_{T,k} A_k S_k^2 G_{\ell,k}/F \frac{\sum_k^{N_t} \left(C'_{T,k,WM} A_k S_{k,WM}^2 \boldsymbol{e}_x \right)}{\sum_k^{N_t} \left(C'_{T,k,WM} A_k S_{k,WM}^2 \right)}, \tag{26}$$

where the ~~$C'_{T,k}$, S_k, $\boldsymbol{e}_k$, and F~~ subscript *WM* indicates the variables are calculated using a standalone wake model. This approximates the footprint of a farm in neutral conditions at a low computational cost.

Including additional wind-farm perturbing forces, such as the induced dispersive and turbulent stresses, can be done by following the same steps as above. Since the APM operators are linear, the responses to different inputs can simply be summed up. If the perturbing forces scale with $F/\overline{h}_1$, as can be assumed for the dispersive stresses, this results in a modification of $\mathbf{\Pi}_f$ when calculating a_u and a_η. However, including perturbing forces that scale differently, like the turbulent momentum flux in the upper layer, requires calculating additional coefficients for the scalar system of equations. We leave these complications to future work.

We briefly discuss how this 2SM–APM coupling relates to the coupling methods between the APM and underlying wake models developed in previous work. The most similar conventional method is the velocity matching (VM) approach developed by Devesse et al. (2024a), which calculates a background velocity that ensures that the wake model and the APM predict the same mesoscale velocity field at each point in the farm. This 2SM coupling imposes the same condition, but only on a farm average, so that the average farm velocity is the same in the internal and external problems (Nishino and Dunstan, 2020). Therefore, the 2SM–APM coupling can be seen as the VM method with just one degree of freedom for the background velocity.

4.3 Comparison to LES

To test the 2SM–APM approach, we validate the model with the CNBL LES results of Lanzilao and Meyers (2024) that were used in ~~the previous sections~~section 2. Like before, the farm coefficients are calculated using the neutral $H500$-$C0$-$G0$ case, which results in $C_T^* = 1.15$ and $C_p^* = 0.92$. This ensures that any errors introduced will come from the 2SM–APM coupling, and not from the estimation of the farm coefficients. The unperturbed background APM state is based on the precursor simulation driving each of the wind-farm simulations. We leave out the $H150$ cases, since the three-layer APM can not handle very shallow upper layer heights H_2 for the time being (Devesse et al., 2024a).

The numerical setup is the same as described in Devesse et al. (2024a). As discussed in the previous section, the APM operators $\mathcal{A}$ are solved using a Fourier-Galerkin method. To prevent the perturbations recycling through the periodic boundaries




Figure 4. A comparison of farm power P_f as calculated by LES and the fast 2SM–APM model for 27 different CNBL cases from Lanzilao and Meyers (2024). The footprint of the height-averaged turbine forces is assumed to be constant, so that the linear system of APM equations only has to be solved once. The axes are normalized with the power output of a standalone turbine P_0.

imposed by this method, we use the very large domain length of $L_x = 10\,000\text{km}$ in the streamwise direction. In the spanwise direction, we take $L_y = 30\text{km}$ in order to follow the LES results as closely as possible. The grid resolution is half of the horizontal filter length, so that $\Delta x = \Delta y = 500\text{m}$.

The ~~results~~ resulting predictions for the farm power P_f are shown in ~~figure 4~~ figures 4 and 5, and the corresponding error statistics are listed in table 2. The fast 2SM–APM seems to perform well overall~~. The general trend is clear, and the global bias is fairly small~~, with the general trend being clearly visible. The root-mean square error (RMSE) across all analyzed cases is ~~4.7P_0~~ 4.8P_0 (where P_0 is the power output of an isolated turbine), or ~~2.9~~3% of the farm's installed capacity. ~~This error~~ As shown in table 2, this RMSE is mostly due to the variance in the model errors, as the mean bias is comparatively small. Looking at figure 5, there seems to be no consistent relation between the model error and the varying atmospheric parameters H, $\Delta\Theta$, or Γ. Instead, figure 4 shows that there is a small but consistent positive bias, and that the scatter on the model's predictions is larger at lower farm power outputs, i.e. for cases with stronger blockage effects. ~~Furthermore, the model achieved the desired low computational cost,with each calculation taking roughly 2.7 seconds on a standard laptop, approximately 40 times longer than a wake model evaluation for the same farm .~~

To investigate the model's performance further, figure 6 shows ~~the velocity deficit~~velocity deficits u_1' as predicted by the fast 2SM–APM model ~~, compared~~ for three different cases, and compares them to LES results. The ~~model's accurate prediction~~ three cases are H500-$\Delta\theta$5-Γ4 (left), H1000-$\Delta\theta$2-Γ1 (middle), and H300-$\Delta\theta$8-Γ1 (right), which are the cases where the model performs best, median, and worst, respectively. In general, accurate predictions of the average velocity ~~is~~ are in part due to a cancellation of errors, as ~~it~~ the model over- and underpredicts the velocity at the front and back of the farm, respectively. ~~However, this is~~ While the model predicts the wrong location for the resonant lee waves for some of the H300 cases, as can bee seen in figure 6 (right), this has no consistent impact on its prediction of P_f. These errors in the local velocity profiles are




Figure 5. The farm power P_f as calculated by LES (black, □) and the fast 2SM–APM model (blue, ○) for the different cases from the dataset by Lanzilao and Meyers (2024). All values are normalized by the power output of a standalone turbine P_0. The dashed lines separate the cases with different ABL heights.

Table 2. The root-mean square (RMSE), mean, and standard deviation (STD) of the error on farm power P_f of all the models analyzed in the current paper for the LES dataset from Lanzilao and Meyers (2024). The "Section" column lists which sections of the paper describe the various models. All values are scaled with the power output of a standalone turbine. Note that ~~these~~ the three error metrics are related, as $\text{RMSE}^2 = \text{Mean}^2 + \text{STD}^2$.

Model	Section	RMSE [-]	Mean error [-]	Error STD [-]
U_f from LES, C_T^*, C_p^* from NBL LES	2	1.6	0.8	1.4
2SM–APM, C_T^*, C_p^* from NBL LES	~~4.7~~ 4.2	4.8	~~2.3~~ 2.5	4.1
2SM–APM, C_T^*, C_p^* from WM	~~6.0~~ 4.3.1	~~4.9~~ 5.9	-4.8	3.5
Farm-averaged PB	~~5.2~~ 5.2	~~3.5~~ 4.5	~~3.8~~ -2.8	3.5
Standalone WM	4.3.1	5.2	-1.1	5.1

not due to the 2SM simplifications, as earlier conventional versions of the APM have similar ~~errors~~ behavior (Devesse et al., 2024a). Improving the farm's parametrization by eg. including dispersive and turbulent stresses may improve this, but is out of the scope of this paper.

Lastly, we discuss the computational cost of the 2SM–APM. As desired, the model achieves a relatively low computational cost, with each calculation taking roughly 1.3 CPU seconds on a Intel Xeon Platinum 8360Y 2.4GHz CPU. This is only approximately 35 times longer than a wake model evaluation for the same farm, and drastically faster than the conventional APM with local coupling (Devesse et al., 2024b). The main computational gains are achieved by eliminating the costs of




Figure 6. Lower-layer velocity deficit through the center of the farm as predicted by LES (black) and the fast 2SM–APM (blue, orange) for the ~~case~~ cases H500-$\Delta\theta$5-Γ~~4.~~ 4 (left), H1000-$\Delta\theta$2-Γ1 (middle), and H300-$\Delta\theta$8-Γ1 (right). The dotted lines denote the wind farm region. The blue and orange lines showing the 2SM–APM predictions were obtained with C_T^* values calculated using LES and a wake model, respectively.

re-calculating the turbine forces and of repeatedly solving the APM equations (7–11). While the former cost is shifted to the calculation of the farm coefficients C_T^* and C_p^*, as discussed in the next section, the latter is fully removed.

4.3.1 Using a wake model to compute C_T^* and C_p^*

~~This section briefly demonstrates~~ When using the 2SM–APM in practical settings, it is not feasible to rely on LES to calculate the farm thrust and power coefficients C_p^* and C_T^*, as these simulations are too expensive. Therefore, this section aims to briefly demonstrate how a basic wake model can be used to calculate ~~the farm thrust and power coefficients , and how this affects the model's performance.~~ these coefficients instead of LES. We merely wish to show that this approach is conceptually possible and point out some potential issues, and do not attempt to minimize its computational cost.

In essence, the process is the same as before, i.e. the standalone wake model is used to estimate U_f, P_f, and F for a given farm, so that C_p^* and C_T^* can be calculated using equations 1 and 2. ~~These can then by used by the~~ As shown in section 2, the resulting coefficients capture the turbine-scale flow characteristics, and are valid across a range of atmospheric conditions as long as the turbine setpoints and wake shapes remain the same. Once they are calculated, the 2SM–APM can use them to predict the farm power output in different ~~atmospheric~~ mesoscale flow conditions.

To calculate the farm power and thrust, we use a Gaussian wake model (Bastankhah and Porté-Agel, 2014) with the wake merging method of Lanzilao and Meyers (2021) and the turbulence-intensity model of Niayifar and Porté-Agel (2016). The wake model is not tuned, and is run with the parameters reported by the above authors. The turbines are mirrored to account for ground effects~~.~~, as this significantly reduces the error on the predicted power output and farm-averaged velocity. This conflicts with the results from Bastankhah and Porté-Agel (2014), who found that mirroring the turbines had little effect on the WM's predictions. This difference with the original papers might be because we use a turbine type with a higher ratio of D/z_h, leading to the rotors being relatively closer to the ground.

Accurately calculating U_f with a wake model requires more modeling effort than P_f and F (Devesse et al., 2024a). Since wake models typically only need to estimate the velocity at downstream turbine locations, they are not always optimized for velocity estimations in the near-wake and induction regions. If not properly accounted for, this can lead to large errors in the average velocity predictions. Therefore, we follow Devesse et al. (2024a) and include a turbine-induction model when estimating U_f (Troldborg and Meyer Forsting, 2017).

The farm-averaged velocity U_f is calculated by evaluating the wake model on a dense, evenly spaced grid over the whole 2SM averaging volume. This brute-force approach is computationally expensive, and a more efficient placement of the evaluation points would likely improve on it. However, as this section simply aims to demonstrate that this type of wake-model coupling can be done in principle, we leave further ~~investigations~~ optimizations of how to ~~best~~ estimate U_f to future work.

The resulting C_T^* and C_p^* are 1.05 and 0.79, respectively. Both values are lower than those calculated from the neutral LES (1.15 and 0.92). This is mostly due to an error on U_f, as even with an induction model the farm-averaged velocity is overestimated (Devesse et al., 2024a).

With these coefficients, we now repeat the earlier validation using the LES dataset from Lanzilao and Meyers (2024). Figure 7 and table 2 show the resulting farm power predictions and error statistics, respectively, for both the 2SM–APM and the standalone wake model. Using the wake model to calculate C_T^* and C_p^* leads to a higher errors, mainly due to the consistent negative bias. Interestingly, the standalone wake model has a similar RMSE as the 2SM–APM despite not capturing any of the power variations in the dataset, mostly because its mean error is very small. In comparison, the 2SM–APM have a higher bias, but a significantly lower variance.

To investigate ~~the model behavior~~ further, figure 6 shows the velocity perturbations predicted by the 2SM–APM. As a result of the lower C_T^* value, the model predicts smaller u_1' than before, leading to higher U_f. However, this is counteracted by the lower C_p^*, so that the resulting farm power predictions have a consistent negative bias.

The above discussion shows that in principle wake models can serve the role of a prior CFD simulation in determining C_T^* and C_p^*, but that this requires the wake model to accurately represent the flow in the induction and near-wake regions. The associated computational cost can be significantly reduced by future research, as we have made no attempts to minimize it. Furthermore, constructing lookup tables for C_T^* and C_p^* as a function of wind speed and wake model inputs would allow this upfront cost to be shared by many 2SM–APM cases when performing eg. multiyear AEP estimates. Finally, the coefficients could potentially also be inferred directly from operational data. Instead of investigating these approaches further, the following section develops a second version of the 2SM–APM which directly couples to a wake model, eliminating the need for an explicit calculation of C_T^* and C_p^*.

5 Direct wake model coupling

The previous section treated C_T^* and C_p^* as known inputs from a prior simulation or wake model, and focused on improving the APM's cost and performance. However, calculating these coefficients with a wake model places requirements on said wake model's performance, and comes at a potentially significant computational cost. Therefore, we now apply the constant-footprint




Figure 7. A comparison of farm power P_f as calculated by LES (x-axis), the fast 2SM–APM model (orange circles), and a standalone wake model (black crosses) for 27 different CNBL cases from Lanzilao and Meyers (2024). The farm coefficients C_T^* and C_p^* used by the 2AM–APM are calculated using the wake model. The axes are normalized with the power output of a standalone turbine P_0, as calculated using LES (horizontal) and the wake model (vertical).

technique developed in the previous section to the pressure-based (PB) wake model coupling developed by Stipa et al. (2024a), resulting in a blockage-corrected model for farm power that does not require the explicit calculation of C_T^* and C_p^*.

This section first briefly derives the pressure-based wake model coupling technique. Afterwards, it applies the techniques developed in the previous section to eliminate the repeated APM operators. The resulting model is again validated using the dataset CNBL simulations of Lanzilao and Meyers (2024).

5.1 Derivation of the pressure-based coupling method

This section derives the equations for the pressure-based coupling method developed by Stipa et al. (2024a), by interpreting the APM as a correction model for CNBL effects. A similar but less thorough derivation has been made before by Devesse et al. (2024b). A graphical representation of the coupling and the derivation is given in figure 8, and an overview of the shorthand notations for the different operators used is given in

A wake model estimates the turbine-scale velocity field $\boldsymbol{u}_{micro}$ by superposing turbine wake functions on a given background velocity $\boldsymbol{U}_b$, so that

$$\boldsymbol{u}_{micro} = \mathrm{WM}(\boldsymbol{U}_b), \tag{27}$$

where WM is the wake model operator.

The background velocity $\boldsymbol{U}_b$ is defined as being the velocity field that will result in the correct $\boldsymbol{u}_{micro}$ when the wakes are superimposed on it. In the absence of blockage and gravity-wave effects, this is simply the unperturbed velocity in the absence of the wind farm, so that $\langle \widetilde{\boldsymbol{U}_b} \rangle_1 = \boldsymbol{U}_1$. In contrast, when coupling a wake model to the APM, $\boldsymbol{U}_b$ has to ensure that horizontally




Figure 8. A conceptual sketch of the pressure-based coupling method developed by Stipa et al. (2024a). We argue that the APM velocity perturbation can be split up into wake and pressure components, and that the latter can serve as the change in background velocity for the wake model due to blockage and gravity-wave effects. Figure based on Stipa et al., The multi-scale coupled model: a new framework capturing wind farm–atmosphere interaction and global blockage effects, Wind Energy Science, 9(5), 1123-1152 (2024).

Table 3. Overview of the shorthand notations for the different operators used in this paper, the sets of equations they represent, and the variables that serve as their in- and outputs.

Operator	Equations	Input	Output
$\mathcal{A}_u, \mathcal{A}_\eta, \mathcal{A}_p$	7–11	$\boldsymbol{f}_{wf}/h_1$	u_1', η_1, p'
$\mathcal{A}_u^n$	35–36	$\boldsymbol{f}_{wf}/h_1$	$u_{1,w}'$
$\mathcal{A}_u^c$	38–40	$\boldsymbol{f}_{wf}/h_1$	$u_{1,c}'$
$\mathcal{A}_{u,p}^c$	38–39	p'	$u_{1,c}'$

filtering and height-averaging the turbine-scale velocity field results in the APM velocity, so that

$$\langle \widetilde{\mathrm{WM}(\boldsymbol{U}_b)} \rangle_1 = \boldsymbol{U}_1 + \boldsymbol{u}_1'. \tag{28}$$

435 Devesse et al. (2024a) call this the *velocity matching* (VM) equation. This condition gives ~~in~~ an implicit equation for $\boldsymbol{U}_b$, and is related to using the pre-computed farm coefficients C_T^* and C_p^* when simplifying the APM–WM coupling using two-scale

momentum theory, as discussed in the previous section. Similar to computing these farm coefficients, solving the VM equation for $\boldsymbol{U}_b$ is relatively expensive (Devesse et al., 2024b).

In order to find a computationally cheaper way to estimate $\boldsymbol{U}_b$, we decompose the filtered, height-averaged wake model operator into a wake and a correction component, so that

$$\langle \widetilde{\mathrm{WM}(\boldsymbol{U}_b)} \rangle_1 = \boldsymbol{U}_1 + \boldsymbol{u}'_{1,w} + \boldsymbol{u}'_{1,c}. \tag{29}$$

where the wake component $\boldsymbol{u}'_{1,w}$ is the filtered and height-averaged velocity deficit corresponding to the turbine wakes, as predicted by the wake model, and the correction component $\boldsymbol{u}'_{1,c}$ accounts for ~~changes in the background velocity due to blockage.~~ the remainder of the total velocity perturbation $\boldsymbol{u}'_1$. This splitting is shown conceptually on the right-hand side of figure 8. For sufficiently small flow perturbations, we can ~~new assume~~ then assume that subtracting the wake component $\boldsymbol{u}'_{1,w}$ from the above equation corresponds to not applying the wake model operator WM, so that

$$\langle \widetilde{\boldsymbol{U}_b} \rangle_1 = \boldsymbol{U}_1 + \boldsymbol{u}'_{1,c}. \tag{30}$$

We can therefore interpret the correction component $\boldsymbol{u}'_{1,c}$ as representing the changes in the background velocity which we are trying to estimate.

~~Further using equation~~ Instead of deriving an expression for ~~28, the correction to the background velocity~~ $\boldsymbol{u}'_{1,c}$ ~~can then be found for a given~~ directly, we will derive it as the difference between the APM state $\boldsymbol{u}'_1$ ~~as~~ and the wake component $\boldsymbol{u}'_{1,w}$. Using equation 28, we find

$$\boldsymbol{u}'_{1,c} = \boldsymbol{u}'_1 - \boldsymbol{u}'_{1,w}. \tag{31}$$

Therefore, the next step is to estimate $\boldsymbol{u}'_{1,w}$, i.e. the part of the APM velocity perturbation that corresponds to the wake deficit predicted by the wake model. Rather than obtaining this by averaging over the microscale velocity predicted by the wake model, we aim at finding an APM operator that allows us to make a faster direct estimation of $\boldsymbol{u}'_{1,w}$. Since conventional standalone wake models are designed to estimate the response of a neutral atmosphere to turbine forcing, we can reasonably take

$$\boldsymbol{u}'_{1,w} = \mathcal{A}^n_u \left(\frac{\boldsymbol{f}}{h_1} \frac{\boldsymbol{f}_{wf}}{h_1} \right), \tag{32}$$

where $\mathcal{A}^n_u$ is the APM operator for neutral conditions. The component $\boldsymbol{u}'_{1,c}$ can then be seen as a correction to neutral flow due to blockage effects, and is defined as

$$\boldsymbol{u}'_{1,c} = \mathcal{A}^c_u \left(\frac{\boldsymbol{f}}{h_1} \frac{\boldsymbol{f}_{wf}}{h_1} \right), \tag{33}$$

where $\mathcal{A}^c_u$ is the APM operator for the difference between CNBL and neutral flow:

$$\mathcal{A}^c_u = \mathcal{A}_u - \mathcal{A}^n_u. \tag{34}$$

If this correction operator $\mathcal{A}_u^c$ is known, it can be used to directly predict $u'_{1,c}$ (and correspondingly U_b), without explicitly solving the velocity matching equation. To find $\mathcal{A}_u^c$, we first construct the neutral APM operator $\mathcal{A}_u^n$, since they are related through the above equation.

To find the neutral APM operator $\mathcal{A}_u^n$, we re-derive the APM for neutral flow. Doing so, the continuity and momentum equations remain unaltered. The only equation that changes is the pressure closure equation. In the absence of gravity waves, the pressure perturbations triggered by the farm are solely due to hydrodynamic effects, which are small compared to the buoyancy effects at typical wind farm length scales. This is demonstrated by the LES data of Lanzilao and Meyers (2024), where the pressure perturbations in the neutral cases are negligible compared to the CNBL simulations. Therefore, we take $p'_n = 0$.

We then easily find the model for the neutral component as equations 7–11 without the pressure term. For the sake of brevity, we only write the equations for the lower layer:

$$\boldsymbol{U}_1 \cdot \nabla_h \eta_{1,n} + H_1 \nabla_h \cdot \boldsymbol{u}'_{1,n} = 0, \tag{35}$$

$$\begin{aligned} \boldsymbol{U}_1 \cdot \nabla_h \boldsymbol{u}'_{1,n} \quad = \quad & f_c \mathbf{J} \cdot \boldsymbol{u}'_{1,n} + \nu_{t,1} \nabla_h^2 \boldsymbol{u}'_{1,n} \\ & + \frac{\mathbf{D}'}{H_1} \cdot \Delta_1^2 \boldsymbol{u}'_n - \frac{\mathbf{C}'}{H_1} \cdot \boldsymbol{u}'_{1,n} - \frac{\boldsymbol{T}_{h3,1} - \boldsymbol{T}_{h3,0}}{H_1^2} \eta_{1,n} \\ & + \frac{\widetilde{\boldsymbol{f}}}{H_1 + \eta_{1,n}} \frac{\widetilde{\boldsymbol{f}}_{wf}}{H_1 + \eta_{1,n}}, \end{aligned} \tag{36}$$

$$p'_n = 0. \tag{37}$$

The equations for the correction operator $\mathcal{A}_u^c$ can then be found by simply substracting the above equations for the neutral model from the original APM continuity and momentum equations. Doing this results in

$$\boldsymbol{U}_1 \cdot \nabla_h \eta_{1,c} + H_1 \nabla_h \cdot \boldsymbol{u}'_{1,c} = 0, \tag{38}$$

$$\begin{aligned} \boldsymbol{U}_1 \cdot \nabla_h \boldsymbol{u}'_{1,c} \quad = \quad & f_c \mathbf{J} \cdot \boldsymbol{u}'_{1,c} + \nu_{t,1} \nabla_h^2 \boldsymbol{u}'_{1,c} \\ & + \frac{\mathbf{D}'}{H_1} \cdot \Delta_1^2 \boldsymbol{u}'_c - \frac{\mathbf{C}'}{H_1} \cdot \boldsymbol{u}'_{1,c} - \frac{\boldsymbol{T}_{h3,1} - \boldsymbol{T}_{h3,0}}{H_1^2} \eta_{1,c} \\ & - \frac{1}{\rho} \nabla_h p'_c, \end{aligned} \tag{39}$$

$$p'_c = p' = \mathcal{A}_p \left(\frac{\boldsymbol{f}}{h_1} \right), \tag{40}$$

where we again only write the lower-layer equations for the sake of brevity. Note that for a given forcing $\boldsymbol{f}/h_1$, the pressure perturbation p' follows from equation 22 (based on the original APM operator $\mathcal{A}_p$), and is an input to equations 38–39.

We again define a simplified notation that expresses $\boldsymbol{u}'_{1,c}$ as the solution of the above system of equations:

$$\begin{aligned}\boldsymbol{u}'_{1,c} &= \mathcal{A}^c_{u,P}(p') \\ &= \mathcal{A}^c_{u,P}\left(\mathcal{A}_p\left(\frac{\boldsymbol{f}}{h_1}\frac{\boldsymbol{f}_{wf}}{h_1}\right)\right),\end{aligned} \tag{41}$$

where the operator $\mathcal{A}^c_{u,P}$ represents the solution operator of equations 38–39 given p' as an input. Note that $\mathcal{A}^c_{u,P}(\mathcal{A}_p)$ thus defines $\mathcal{A}^c_u$ (eq. 34).

Finally, we have thus arrived at a closed system of equations, as through equation 41 we can calculate the change in background velocity for a given forcing ~~$\boldsymbol{f}/h_1$~~$\boldsymbol{f}_{wf}/h_1$. This allows us to again employ a fixed-point iteration, where ~~$\boldsymbol{f}$~~ $\boldsymbol{f}_{wf}$ is calculated using the wake model, and the corresponding changes in h_1 and $\boldsymbol{u}_{1,c}$ are calculated using $\mathcal{A}_\eta$ and $\mathcal{A}^c_{u,P}(\mathcal{A}_p)$, respectively. The wake model then re-calculates the forces with the updated background velocity. This process is repeated until convergence.

The only remaining issue is that the input to the wake model requires a turbine-scale background velocity that is not height-averaged. The pressure-based coupling method therefore constructs a local background velocity for the wake model based on $\boldsymbol{u}'_{1,c}$ (Stipa et al., 2024a). Following the linearization of the APM, we write this background velocity $\boldsymbol{U}_b$ as the sum of the unperturbed velocity profile in the absence of the farm $\boldsymbol{U}_0$ and a perturbation around it, so that

$$\boldsymbol{U}_b(x,y,z) = \boldsymbol{U}_0(z) + \boldsymbol{u}_b(x,y) f_b(z), \tag{42}$$

where $\langle \boldsymbol{U}_0 \rangle_1 = \boldsymbol{U}_1$, and f_b is a shape function (we typically use a logarithmic function). The perturbation to the background velocity is then found by matching the height-averaged $u'_{1,c}$, so that

$$\boldsymbol{u}_b = \boldsymbol{u}'_{1,c}\left[\frac{1}{H_1+\eta_1}\int_0^{H_1+\eta_1} f_b \mathrm{d}z\right]^{-1}. \tag{43}$$

Stipa et al. (2024a) did not include the background component of the continuity equations (eq. 38) in their original coupling. However, the above derivation of the method shows that the whole APM operator should be split. These continuity equations add a parabolic behavior to the correction operator $\mathcal{A}^c_{u,P}$, so that the periodic boundary conditions imposed by the Fourier–Galerkin spectral method used to solve the original APM equations become inappropriate. However, since the closure equation for the internal gravity waves (eqs. 11–12) is not a part of the correction operator, we are free to use other numerical methods. Therefore, we solve equations 38–39 with a simple first-order explicit Euler marching scheme, with as inlet boundary conditions $\boldsymbol{u}'_{1,c}, \boldsymbol{u}'_{2,c}, \eta_{1,c}, \eta_{2,c} = 0$~~. To simplify this~~, which correspond to there being no pressure-induced change in background velocity at the inlet. For these conditions to be valid, the inlet should be placed far enough upstream of the farm so that $p' \approx 0$, which for realistic atmospheric conditions is typically less than 100 km (Smith, 2024). As a result, the operator $\mathcal{A}^c_{u,P}$ can use far smaller grid sizes than the periodic boundary conditions required of the conventional APM. Finally, in order to simplify the marching solver, we neglect ~~Coriolis effects and~~ the horizontal eddy viscosity, ~~and assume $V_1 = V_2 = 0$~~so that there are no second-order derivatives in the equations.

5.2 Farm-level pressure-based APM-WM coupling

We now apply the farm-averaging approach developed in the previous section to the PB coupling method. As discussed above, the background component of the APM velocity perturbation is given by

$$\boldsymbol{u}'_{1,c} = \mathcal{A}^c_{u,P}\left(\mathcal{A}_p\left(\frac{\boldsymbol{f}}{H_1+\eta_1}\,\frac{\boldsymbol{f}_{wf}}{H_1+\eta_1}\right)\right). \tag{41}$$

By plugging in the constant footprint (eq. 23), we find that the average streamwise correction component is

$$\overline{u}'_{1,c} = a_{u,c}\frac{F}{H+\overline{\eta}_1}\,\frac{F}{H_1+\overline{\eta}_1}, \tag{44}$$

where the coefficient can be calculated as

$$a_{u,c} = \frac{1}{\Omega_f}\iint_{\Omega_f}\mathcal{A}^c_{u,P}\left(\mathcal{A}_p\left(\mathbf{\Pi}_f\right)\right)\mathrm{d}\Omega_f. \tag{45}$$

The average layer displacement $\overline{\eta}_1$ can be found through equation 24, as in the basic 2SM–APM.

Following the pressure-based coupling approach, we now use this $\overline{u}'_{1,c}$ to directly correct the background wind speed in a wake model. Since the above results only hold on a farm average, we assume a constant background over the farm:

$$U_b(z) = U_0(z) + \overline{u}_b f_b(z), \tag{46}$$

where the average background velocity scale $\overline{u}_b$ is found by matching $\overline{u}'_{1,c}$:

$$\overline{u}_b = \overline{u}'_{1,c}\left[\frac{1}{H_1+\overline{\eta}_1}\int_0^{H_1+\overline{\eta}_1} f_b\mathrm{d}z\right]^{-1}. \tag{47}$$

The wake model can then be used to calculate F and P_f, closing the system of equations:

$$F = \sum_k^{N_t}\frac{1}{2}C'_{T,k}S_k^2A_k, \tag{48}$$

$$P_f = \sum_k^{N_t}\frac{1}{2}\rho C'_{p,k}S_k^3A_k, \tag{49}$$

where the turbine coefficients and disk velocities are calculated using a wake model with the background velocity defined in equation 46.

We solve the final system of equations (44, 24, 48, 49) using a fixed-point iteration solver with a relaxation factor of 0.7, as is done for the classical APM and the 2SM–APM developed in the previous section.




Figure 9. Farm power as calculated by LES (x-axis) and wake model (y-axis), both standalone (black crosses) and with farm-average pressure-based blockage coupling (green circles). The axes are normalized with the power output of a standalone turbine P_0, as calculated using LES (horizontal) and the wake model (vertical).

The advantages of this approach compared to the 2SM–APM coupling derived in the previous section are similar to the advantages of PB coupling compared to the VM method. It places no requirements on the wake model, and does not need to calculate C_T^* and C_p^*. ~~While this~~ Its main disadvantage is that it requires an additional solver for the operator $\mathcal{A}^c_{u,P}$, corresponding to equations 38–39. However, since it can use a simple first-order marching scheme and a relatively small grid, this solver is straightforward to implement and cheap to run. Finally, we emphasize that while this coupling no longer explicitly uses any of the results from 2SM theory, it implicitly makes the same assumption that farm power calculations only need the average wind speed within a farm.

5.2.1 Comparison to LES

We again validate this approach using the LES cases from the dataset by Lanzilao and Meyers (2024) used throughout this work. The numerical setup for the $\mathcal{A}_p$ operator is the same as in section 4.3. The correction operator $\mathcal{A}^c_{u,P}$ can use a smaller numerical domain, since its solver does not require periodic boundary conditions. Here, we use the same spanwise $L_y = 30\text{km}$ as before, but take a shorter streamwise $L_x = 43\text{km}$, placing the solver's inlet at the same upstream distance of the farm as the LES, i.e. 18km. We use the same wake model as in section 4.3.1.

The results are shown in figure 9, and the error statistics are listed in table 2. The general trend is visible, despite some scatter and a consistent negative bias. Overall, the wake model and the farm-level PB coupled model have the same RMSE on power of ~~$5.2P_0$~~$4.5P_0$, or ~~3.3~~2.8% of the farm's installed capacity, with the farm-averaged PB model having a lower error variance but larger bias. The computational cost is the same as before, as the pressure component operator and wake model evaluations have a negligible cost.




Figure 10. Difference between farm power in CNBL and NBL conditions as calculated by LES (x-axis) and wake model with farm-average pressure-based blockage coupling (y-axis). The axes are normalized with the power output of a standalone turbine P_0, as calculated using LES (horizontal) and the wake model (vertical).

As shown above, the pressure-based coupling can be derived as a correction to an NBL base state. With that in mind, figure 10 shows the difference in farm power between the coupled and standalone wake model, compared to the farm power differences between the CNBL and the neutral LES reference simulation, i.e. $H500$-$\Delta\theta 0$-$\Gamma 0$. It's clear that the farm-average coupling performs decently in the role of a blockage-correction model, as it captures the overall trend despite a consistent bias. The error on this power difference is similar to the error on the farm powers shown in figure 9, which indicates that the farm-averaged PB model's bias is mostly due to an overprediction of blockage losses.

6 Conclusions

Two-scale momentum (2SM) theory offers ~~an interesting~~ a new way of including mesoscale effects in wind farm power predictions. Using results from Lanzilao and Meyers (2024), its core hypothesis of scale separation between the turbine- and farm-scale flows was validated for steady-state idealized CNBL conditions. Building on that, this paper developed two ways to combine it with an atmospheric perturbation model (APM) to speed up farm power calculations. This speed-up is possible because according to the 2SM hypothesis, only the average velocity within a farm U_f is needed to compute the farm's force and power output. Since local fluctuations in the turbine forcing are therefore not relevant, the spatial distribution of the forces is assumed to be constant and independent of the APM state. Combined with the linearity of the APM, this transforms the APM's governing equations into a system of algebraic equations, which are trivial to solve numerically.

The first version of the 2SM–APM uses the APM as a mesoscale model to obtain the average velocity within the farm, and uses the 2SM farm coefficients C_T^* and C_p^* to calculate the turbine forces and power output. This basic coupling method is similar to the velocity matching method developed in by Devesse et al. (2024a), as it matches the average farm velocity

between the meso- and turbine scales. ~~It performs well, and predicts the farm power in CNBL conditions accurately forknown~~In a validation campaign using the LES results from Lanzilao and Meyers (2024), its RMSE on farm power was only 3% of the installed capacity when using LES-based values for C_T^* and C_p^*. Furthermore, we addressed the model's reliance on accurately knowing these coefficients by showing how they could in principle be calculated using a standard wake model.

The second model developed in this paper avoids the explicit use of C_T^* and C_p^* by coupling directly to a wake model. To this end, it applies the farm-averaging approach to the pressure-based wake model coupling method of Stipa et al. (2024a). Based on a rigorous derivation of this method, we show that it can also be interpreted as a model to correct neutral flow results for CNBL effects. The model performs ~~well in this role~~similar to the first model, and can predict the effects of blockage and gravity waves on farm power, albeit with a consistent bias.

Both ~~models presented here~~ the 2SM–APM model and the farm-averaged pressure-based approach have a similar accuracy and computational cost. Which of them is preferable largely depends on the trade-off between efficiently calculating the farm coefficients C_T^* and C_p^* for the former, and solving additional equations for the latter. This investigation is left as future work.

Both models achieve a lower variance in the error on their power predictions compared to a standalone wake model, at the cost of introducing a larger bias. Tuning the underlying wake models could ~~address~~ compensate for this, as both the wake spreading coefficients and the ~~farm-averaged~~ farm power and thrust coefficients~~can be optimized~~ C_T^* and C_p^* can be modified. The low computational cost of the models allows this tuning to directly incorporate large operational datasets. We believe this is a promising area of further research that will facilitate the model's adoption by the wind energy industry and community.

As powerful as the tools offered by the 2SM approach are, it remains unclear how valid the underlying assumptions are outside of the idealized conditions they have been tested in. So far, they have only been validated using LES of infinite farms (Kirby et al., 2022) and farms operating in horizontally homogeneous background conditions with uniform turbine layouts (Kirby et al., 2025). Future work should investigate whether the farm coefficients remain constant under realistic and transient atmospheric conditions, and how to account for irregular turbine spacing and operating setpoints.

Code availability. The models developed in this paper have been implemented in the open-source code WAYVE (Devesse et al., 2023). A repository containing the LES data used in this paper, post-processed to be used directly as input for WAYVE, can be found at https://gitlab.kuleuven.be/TFSO-software/wayve-validation.

Author contributions. KD and JM jointly derived the 2SM–APM couplings and set up the validation studies. KD performed code implementations and carried out the simulations. KD and JM jointly wrote the manuscript.

Competing interests. One of the (co-)authors is a member of the editorial board of Wind Energy Science. The authors have no other competing interests to declare.

Acknowledgements. The authors thank Frederik Aerts for insightful discussions on combining the 2SM and APM approaches. This research has been supported by the Energy Transition Fund of the Belgian Federal Public Service for Economy, SMEs, and Energy (FOD Economie, K.M.O., Middenstand en Energie), by the European Union Horizon Europe Framework programme (HORIZON-CL5-2021-D3-03-04) under grant agreement no. 101084205, and by Project Cloud4Wake, funded by Vlaamse Agentschap Innoveren & Ondernemen (VLAIO) under the Blue Cluster cSBO programme (Contract number HBC.2022.0549)

References

Allaerts, D. and Meyers, J.: Boundary-layer development and gravity waves in conventionally neutral wind farms, Journal of Fluid Mechanics, 814, 95–130, https://doi.org/10.1017/jfm.2017.11, 2017.

Allaerts, D. and Meyers, J.: Gravity Waves and Wind-Farm Efficiency in Neutral and Stable Conditions, Boundary-Layer Meteorology, 166, 269–299, https://doi.org/10.1007/s10546-017-0307-5, 2018.

Allaerts, D. and Meyers, J.: Sensitivity and feedback of wind-farm-induced gravity waves, Journal of Fluid Mechanics, 862, 990–1028, https://doi.org/10.1017/jfm.2018.969, 2019.

Bastankhah, M. and Porté-Agel, F.: A new analytical model for wind-turbine wakes, Renewable Energy, 70, 116–123, https://doi.org/10.1016/j.renene.2014.01.002, 2014.

Bleeg, J., Purcell, M., Ruisi, R., and Traiger, E.: Wind farm blockage and the consequences of neglecting its impact on energy production, Energies, 11, https://doi.org/10.3390/en11061609, 2018.

Centurelli, G., Vollmer, L., Schmidt, J., Dörenkämper, M., Schröder, M., Lukassen, L. J., and Peinke, J.: Evaluating Global Blockage engineering parametrizations with LES, Journal of Physics: Conference Series, 1934, 012 021, https://doi.org/10.1088/1742-6596/1934/1/012021, 2021.

Devesse, K., Lanzilao, L., Allaerts, D., Jamaer, S., and Meyers, J.: Wind-fArm gravitY-waVe and blockagE code, https://doi.org/10.48804/XMNVVY, 2023.

Devesse, K., Lanzilao, L., and Meyers, J.: A meso–micro atmospheric perturbation model for wind farm blockage, Journal of Fluid Mechanics, 998, A63, https://doi.org/10.1017/jfm.2024.868, 2024a.

Devesse, K., Stipa, S., Brinkerhoff, J., Allaerts, D., and Meyers, J.: Comparing methods for coupling wake models to an atmospheric perturbation model in WAYVE, Journal of Physics: Conference Series, 2767, 092 079, https://doi.org/10.1088/1742-6596/2767/9/092079, 2024b.

Du, B., Ge, M., Li, X., and Liu, Y.: A Meso-Microscale Coupled Wind Farm Parameterization, Boundary-Layer Meteorology, 191, 35, https://doi.org/10.1007/s10546-025-00928-7, 2025.

Gill, A. E.: Atmosphere-Ocean Dynamics, International geophysics series 30, Academic Press, San Diego, USA, ISBN 0122835204, 1982.

Kirby, A., Nishino, T., and Dunstan, T. D.: Two-scale interaction of wake and blockage effects in large wind farms, Journal of Fluid Mechanics, 953, 1–28, https://doi.org/10.1017/jfm.2022.979, 2022.

Kirby, A., Nishino, T., Lanzilao, L., Dunstan, T. D., and Meyers, J.: Turbine- and farm-scale power losses in wind farms: an alternative to wake and farm blockage losses, Wind Energy Science, 10, 435–450, https://doi.org/10.5194/wes-10-435-2025, 2025.

Lanzilao, L. and Meyers, J.: Set-point optimization in wind farms to mitigate effects of flow blockage induced by atmospheric gravity waves, Wind Energy Science, 6, 247–271, https://doi.org/https://doi.org/10.5194/wes-6-247-2021, 2021.

Lanzilao, L. and Meyers, J.: Effects of self-induced gravity waves on finite wind-farm operations using a large-eddy simulation framework, Journal of Physics: Conference Series, 2265, https://doi.org/10.1088/1742-6596/2265/2/022043, 2022.

Lanzilao, L. and Meyers, J.: An Improved Fringe-Region Technique for the Representation of Gravity Waves in Large Eddy Simulation with Application to Wind Farms, Boundary-Layer Meteorology, 186, 567–593, https://doi.org/10.1007/s10546-022-00772-z, 2023a.

Lanzilao, L. and Meyers, J.: A reference database of wind-farm large-eddy simulations for parametrizing effects of blockage and gravity waves, https://doi.org/10.48804/L45LTT, 2023b.

Lanzilao, L. and Meyers, J.: A parametric large-eddy simulation study of wind-farm blockage and gravity waves in conventionally neutral boundary layers, Journal of Fluid Mechanics, 979, A54, https://doi.org/10.1017/jfm.2023.1088, 2024.

Maas, O.: From gigawatt to multi-gigawatt wind farms: wake effects, energy budgets and inertial gravity waves investigated by large-eddy simulations, Wind Energy Science, 8, 535–556, https://doi.org/10.5194/wes-8-535-2023, 2023a.

Maas, O.: Large-eddy simulation of a 15 GW wind farm: Flow effects, energy budgets and comparison with wake models, Frontiers in Mechanical Engineering, 9, 1–23, https://doi.org/10.3389/fmech.2023.1108180, 2023b.

Meyers, J., Bottasso, C., Dykes, K., Fleming, P., Gebraad, P., Giebel, G., Göçmen, T., and van Wingerden, J.-W.: Wind farm flow control: prospects and challenges, Wind Energy Science, 7, 2271–2306, https://doi.org/10.5194/wes-7-2271-2022, 2022.

Niayifar, A. and Porté-Agel, F.: Analytical Modeling of Wind Farms: A New Approach for Power Prediction, Energies, 9, 741, https://doi.org/10.3390/en9090741, 2016.

Nishino, T. and Dunstan, T. D.: Two-scale momentum theory for time-dependent modelling of large wind farms, Journal of Fluid Mechanics, 894, https://doi.org/10.1017/jfm.2020.252, 2020.

Ouro, P., Ghobrial, M., Ali, K., and Stallard, T.: Numerical modelling of offshore wind-farm cluster wakes, Renewable and Sustainable Energy Reviews, 215, 115 526, https://doi.org/10.1016/j.rser.2025.115526, 2025.

Porté-Agel, F., Bastankhah, M., and Shamsoddin, S.: Wind-Turbine and Wind-Farm Flows: A Review, Boundary-Layer Meteorology, 174, 1–59, https://doi.org/10.1007/s10546-019-00473-0, 2020.

Shapiro, C. R., Gayme, D. F., and Meneveau, C.: Filtered actuator disks : Theory and application to wind turbine models in large eddy simulation, Wind Energy, pp. 1414–1420, https://doi.org/10.1002/we.2376, 2019.

Smith, R. B.: Linear theory of stratified hydrostatic flow past an isolated mountain., Tellus, 32, 348–364, https://doi.org/10.3402/tellusa.v32i4.10590, 1980.

Smith, R. B.: Gravity wave effects on wind farm efficiency, Wind Energy, 13, 449–458, https://doi.org/10.1002/we.366, 2010.

Smith, R. B.: The wind farm pressure field, Wind Energy Science, 9, 253–261, https://doi.org/10.5194/wes-9-253-2024, 2024.

Stipa, S., Ajay, A., Allaerts, D., and Brinkerhoff, J.: The multi-scale coupled model: a new framework capturing wind farm-atmosphere interaction and global blockage effects, Wind Energy Science, 9, 1123–1152, https://doi.org/10.5194/wes-9-1123-2024, 2024a.

Stipa, S., Ajay, A., Allaerts, D., and Brinkerhoff, J.: TOSCA – an open-source, finite-volume, large-eddy simulation (LES) environment for wind farm flows, Wind Energy Science, 9, 297–320, https://doi.org/10.5194/wes-9-297-2024, 2024b.

Stipa, S., Ajay, A., and Brinkerhoff, J.: The actuator farm model for large eddy simulation (LES) of wind-farm-induced atmospheric gravity waves and farm–farm interaction, Wind Energy Science, 9, 2301–2332, https://doi.org/10.5194/wes-9-2301-2024, 2024c.

Troldborg, N. and Meyer Forsting, A. R.: A simple model of the wind turbine induction zone derived from numerical simulations, Wind Energy, 20, 2011–2020, https://doi.org/10.1002/we.2137, 2017.

van der Laan, M. P., García-Santiago, O., Kelly, M., Meyer Forsting, A., Dubreuil-Boisclair, C., Sponheim Seim, K., Imberger, M., Peña, A., Sørensen, N. N., and Réthoré, P.-e.: A new RANS-based wind farm parameterization and inflow model for wind farm cluster modeling, Wind Energy Science, 8, 819–848, https://doi.org/10.5194/wes-8-819-2023, 2023.