



Unsteady airfoil aerodynamics in attached flow: From unsteady thin-airfoil theory to wind turbine implementation

Ang Li¹, Mac Gaunaa¹, and Georg Raimund Pirrung¹

¹Department of Wind and Energy Systems, Technical University of Denmark, Frederiksborgvej 399, 4000 Roskilde, Denmark

Correspondence: Ang Li (angl@dtu.dk)

Abstract. Attached-flow unsteady aerodynamics form the foundation of the dynamic stall models used in wind turbine aerodynamic and aeroelastic codes. These conditions are particularly important over the outboard blade region, which dominates power production and aerodynamic loading. In this region, the angle of attack and relative velocity are unsteady while the flow remains predominantly attached. A complete engineering model for unsteady airfoil aerodynamic loads combines several distinct elements, including airfoil polar lookup, attached-flow shed wake memory, non-circulatory loads, consistent definitions of force magnitude and direction, and, subsequently, separated-flow dynamics. Although the underlying theory is classical, to the authors' knowledge, existing descriptions do not provide a complete and internally consistent route for implementing these attached-flow contributions in wind turbine aerodynamic solvers. This work addresses this gap by focusing on the attached-flow component and presenting all attached-flow contributions in the form of lift, drag, and moment coefficients for implementation in generalized lifting-line methods, including blade-element momentum (BEM), lifting-line (LL), and actuator-line (AL) methods. The formulation is designed for combination with 2-D airfoil polars obtained from measurements or computational fluid dynamics (CFD). Starting from the classical dimensional loads of unsteady thin-airfoil theory, the circulatory and non-circulatory contributions are derived in coefficient form, and the implications of the associated modeling choices are clarified. In particular, the shed wake memory is formulated using the downwash velocity rather than the angle of attack as the aerodynamic state variable. Because the 2-D theory is classical, verification focuses on its rotor-level implementation. The coned straight blade case provides a cross-method benchmark and quantifies the errors in rotor-integrated thrust and power caused by omitting three required contributions that are often omitted. Among these, the lift direction projection contribution has the largest influence on power. Omitting the mid-chord heaving acceleration contribution eliminates the non-circulatory normal force cancellation and produces a thrust error. The zero-onset flow vertical-axis wind turbine (VAWT) case verifies that, in the ideal thin-airfoil limit, all circulatory and non-circulatory contributions cancel, resulting in zero total rotor torque.

1 Introduction

For modern wind turbines, both the relative velocity and angle of attack at a blade section can be unsteady even when the local flow remains attached. Such conditions are common, especially for the outboard blade region that dominates power production and aerodynamic loading for horizontal-axis wind turbines (HAWTs). The effects described by the attached-flow part of dynamic stall models are particularly relevant for large rotors with highly coned or deflected blades, where sectional



unsteady aerodynamic modeling can be important even under steady operating conditions (Li et al., 2022). In vertical-axis wind turbines (VAWTs), both the relative velocity and the angle of attack vary continuously with the azimuth position of the blades. Dynamic stall models in wind turbine aeroelastic codes contain several distinct modeling elements: airfoil polar lookup, shed wake memory in attached flow, non-circulatory loads, the definition of force magnitude and direction, and finally separated flow dynamics that are typically built on the attached flow formulation. The present work focuses on the attached-flow component and formulates the circulatory and non-circulatory loads as force and moment coefficients that can be combined with 2-D airfoil polars from measurements or computational fluid dynamics (CFD) simulations. When the formulation is embedded in a dynamic stall model, the attached-flow formulation provides the basis on which the separated-flow dynamics are subsequently introduced, while the separated-flow aerodynamic loads themselves remain outside the scope of the present work. The airfoil polar provides the quasi-steady lift magnitude, profile drag, and pitching moment at the effective angle of attack. The attached-flow model accounts for the effect of the shed wake memory and specifies how the resulting circulatory force is resolved into lift and drag relative to a local reference flow direction. Different reference directions change the lift and drag decomposition, but not the underlying aerodynamic force vector when the projection is treated consistently. The non-circulatory terms of the model provide additional force and moment contributions associated with the inertia of the fluid accelerated by the airfoil motion. These contributions are commonly referred to as added-mass or apparent-mass effects and arise naturally as the non-circulatory part of classical unsteady thin-airfoil theory. They may equivalently be interpreted as the potential-flow reaction forces generated by accelerating the fluid surrounding a body.

Although the underlying theory is classical and individual elements of the formulation have appeared in previous studies, to the authors' knowledge, the wind turbine aerodynamics literature still lacks a complete, internally consistent, and implementation ready description. The present work addresses this documentation gap by presenting a complete coefficient formulation that specifies how the circulatory lag state, airfoil polar lookup, force projection, and non-circulatory terms are combined consistently and without double counting.

The circulatory force magnitude and the memory effect of the shed wake follow classical unsteady thin-airfoil theory, as represented by Wagner's indicial response and Theodorsen's frequency-domain formulation (Theodorsen, 1935; Jones, 1938, 1940). The tangential force contribution required to determine the resulting force direction follows the classical leading edge suction treatment of Garrick (1936) and its generalized thin-airfoil formulation by Gaunaa (2010). The non-circulatory loads also follow from unsteady thin-airfoil potential flow theory, including its extension to time-varying inflow velocity (Garrick, 1936; Greenberg, 1947).

The engineering model considered here is based on the model documented by Hansen et al. (2004), commonly known as the Risø model and termed the Hansen-Gaunaa-Madsen (HGM) model in Branlard and Jonkman (2019), a name subsequently used in the OpenFAST literature (Branlard et al., 2022). For the low Mach numbers relevant to wind turbine applications, Hansen et al. (2004) specialised the Beddoes-Leishman dynamic stall model (Leishman and Beddoes, 1986, 1989) to incompressible aerodynamics by replacing the compressible impulsive response with non-circulatory added-mass loads. The HGM model also excludes leading edge separation and the associated leading edge vortex dynamics.



60 The general thin-airfoil formulation of Gaunaa (2010) was subsequently interpreted for implementation in attached-flow
 dynamic stall models in the manuscript by Bæk et al., reproduced in Appendix E of Bæk (2011). Of particular relevance here
 is Appendix A of that manuscript, authored by Gaunaa, which discusses the three-quarter-chord downwash governing the
 circulatory response and the role of the selected reference flow direction in defining lift and drag. Subsequent work further
 developed this incompressible Beddoes-Leishman type dynamic stall model for HAWC2 (Bergami and Gaunaa, 2012; Pirrung
 65 and Gaunaa, 2018). Related formulations are used in several widely used wind turbine aeroelastic simulation tools, including
 OpenFAST UAMod=4 (Branlard et al., 2022), the incompressible Beddoes-Leishman model in Bladed (DNV, 2025), and the
 ATEFlap model (Bergami and Gaunaa, 2012) as implemented in QBlade (Marten, 2020). Related formulations of incompress-
 ible attached-flow unsteady aerodynamics have also been applied in typical section aeroelastic models (Stäblein et al., 2017;
 Verdonck and Hach, 2026). Although these implementations are based on the same underlying model family, their descriptions
 70 differ in the definition of the circulatory lag state, the non-circulatory terms retained, and the conventions used to express the
 resulting force and moment coefficients.

In the original formulation, some terms of the underlying attached-flow theory were deliberately not retained in the engineer-
 ing model, as they were considered of minor importance for the operating conditions and predominantly planar and relatively
 stiff HAWT rotors targeted at the time. Indeed, Hansen et al. (2004) and Bæk (2011) derived the complete non-circulatory
 75 formulation before neglecting several contributions, such as the mid-chord heaving acceleration, in the reduced engineering
 model. As the model has subsequently been applied to more flexible and increasingly non-planar rotors, including highly coned
 or deflected configurations (Li et al., 2022), and to other concepts such as VAWTs (Pirrung and Gaunaa, 2018), the importance
 of contributions neglected in the original engineering model has become more apparent. This provides part of the motivation
 for the present work, which aims to provide the complete attached-flow framework together with a detailed specification of its
 80 inputs, force and moment definitions, reference directions, and implementation.

Two aspects of the implementation require particular attention. The first is the state variable used for the circulatory lag. The
 present formulation expresses the circulatory lag using downwash-based states rather than angle-of-attack states. A deficit-state
 representation is used that, when embedded in the full dynamic stall model, allows the generation of new wake memory to be
 progressively reduced as flow separation develops. The second aspect is the complete set of non-circulatory force and moment
 85 terms required when the formulation is written directly in terms of lift, drag, and quarter-chord pitching moment coefficients.
 These terms must also be transformed consistently into the selected lift and drag directions.

The model is applicable in all generalized lifting-line methods: aerodynamic models that discretize the blade into sections
 and use 2-D airfoil data, including blade-element momentum (BEM), lifting-line (LL), and actuator-line (AL) methods. These
 methods combine an outer 3-D rotor and wake problem with an inner 2-D airfoil model at each blade section. In simplified
 90 implementations, the inner 2-D model is often reduced to a direct airfoil-polar lookup using the flow at a single aerodynamic
 calculation point. Careful analysis of the thin-airfoil framework, however, shows that the flow angle at a single point is not,
 by itself, sufficient to predict the unsteady attached flow forces correctly (Bæk, 2011; Bergami and Gaunaa, 2012; Pirrung and
 Gaunaa, 2018; Li et al., 2022). The local flow angles at both the quarter- and three-quarter-chord points are required. These
 angles are generally different because the effective torsional rate causes the local flow angle to vary along the chord. They



95 must therefore be determined from the flow at the aerodynamic calculation point together with the effective torsional rate. For horizontal-axis wind turbines (HAWTs) with out-of-plane blade geometry and for VAWTs, inconsistent treatment of the non-circulatory loads or neglect of the effective torsional rate can produce erroneous loads (Pirrung and Gaunaa, 2018; Li et al., 2022).

100 The classical 2-D sectional responses underlying the formulation have been extensively studied in previous work (Hansen et al., 2004; Gaunaa, 2010; Bæk, 2011; Bergami and Gaunaa, 2012; Bergami et al., 2015). Verification therefore focuses on its implementation in rotor aerodynamic solvers, where the blade kinematics must be consistently coupled to the sectional aerodynamic model and the resulting loads transformed back to the rotor system. The present work uses two complementary rotor-level cases. The coned straight-blade case provides a cross-method numerical benchmark and quantifies the errors caused by omitting required force projection and non-circulatory contributions. The zero-onset VAWT case provides an analytical
105 consistency test building on previous studies of the circulatory torque balance and non-circulatory normal force cancellation (Pirrung and Gaunaa, 2018; Li et al., 2022). The present work extends these analyses by considering all circulatory and non-circulatory contributions and demonstrates that the complete formulation results in zero total aerodynamic torque when using ideal zero profile-drag airfoil data.

110 The derivation starts from the classical sectional normal force, tangential force, and pitching moment and proceeds through chord-axis coefficients. The final formulation gives lift and drag coefficients in the selected flow direction and the pitching moment coefficient about the quarter-chord point. The remainder of the paper derives the coefficient equations in Sect. 2, examines the two rotor-level cases in Sect. 3, and concludes in Sect. 4.

2 Methodology: from classical sectional loads to engineering coefficients

115 This section derives an implementation-ready coefficient formulation of unsteady thin-airfoil theory for coupling the inner 2-D airfoil model to generalized lifting-line methods. Classical unsteady thin-airfoil theory provides the sectional loads in terms of dimensional normal force, tangential force, and pitching moment, whereas 2-D airfoil polars used in engineering aerodynamic models are conventionally given in terms of lift, drag, and moment coefficients. The derivation therefore first converts the classical sectional loads to coefficient form, re-references the pitching moment to the quarter-chord point, and formulates the shed wake memory in state-space form. The second part develops the practical formulation required to combine these results
120 consistently with a 2-D airfoil polar. It couples the outer blade and wake model to the inner 2-D airfoil model, specifies the circulatory force magnitude and direction, introduces the airfoil polar lookup, and projects the force contributions into lift and drag relative to a local reference flow direction. The resulting contributions are then assembled into the total lift, drag, and pitching moment coefficients.



2.1 Classical dimensional unsteady thin-airfoil theory

125 The classical formulation considers incompressible 2-D potential flow under the small-angle assumptions of thin-airfoil theory (Theodorsen, 1935; Garrick, 1936; Øye, 1981; Gaunaa, 2010). Airfoil-specific viscous effects are introduced later through coupling with a steady 2-D airfoil polar.

The flow and airfoil coordinate systems and the positive directions used in the derivation are shown in Fig. 1. The coordinate system and sign conventions follow Li et al. (2022). Throughout this work, c denotes the chord length and $b = c/2$ the half-chord length. The chordwise coordinate is denoted by ξ and is measured from the mid-chord point, with $\xi = -b$ at the leading edge and $\xi = b$ at the trailing edge. The pitch axis is located at $\xi = ab$, where a is its dimensionless position relative to the mid-chord point. The motion of the airfoil is described by the translational displacements x and y , parallel and normal to the undisturbed flow direction, respectively, and by the pitching angle θ , which describes the torsional motion.




Figure 1. Definitions of the flow and airfoil coordinate systems and positive directions used in the derivation of unsteady 2-D thin-airfoil theory. Adapted from Li et al. (2022) with permission.

The relative streamwise velocity is defined as

135
$$U = V - \dot{x}, \quad (1)$$

where V is the constant streamwise flow velocity.

The classical literature on unsteady thin-airfoil theory adopts the simplifying assumption that the influence of the shed wake at any chordwise position is evaluated as if the airfoil and the shed wake lie along a straight line, with the shed vorticity convected downstream relative to the airfoil at the streamwise velocity $U(t)$. The theory is developed by enforcing the Neumann boundary condition, corresponding to no flow through the airfoil, together with the Kutta condition, which removes the pressure singularity at the trailing edge. The unsteady Bernoulli equation is then used to evaluate the local pressure difference, which is integrated to obtain the sectional aerodynamic loads. Because of the leading edge singularity in the thin-airfoil theory, the associated leading edge suction force must be included to obtain the correct tangential load (Garrick, 1936; Gaunaa, 2010). The suction force may be interpreted as the limiting physical suction force as the airfoil thickness tends to zero (Gaunaa, 2010). Its inclusion recovers zero drag in the steady inviscid limit, consistent with d'Alembert's paradox.

Within this framework, the input to the unsteady thin-airfoil model is the relative streamwise velocity $U(t)$ together with the onset downwash distribution $w(\xi, t)$, which is the undisturbed relative onset velocity component normal to the airfoil chord.



In this framework, at each instant in time, the onset downwash varies linearly along the chord, as shown explicitly in Eq. (13). The downwash distribution can therefore be characterized by its value at one chordwise location and its chordwise slope, which is set by the effective torsional rate $\dot{\theta}$. For use in generalized lifting-line models, the unsteady 2-D airfoil formulation may therefore be interpreted as an input–output machine. It maps the time histories of the relative flow magnitude U and the chordwise-linear onset downwash to the corresponding time histories of the integral sectional loads, expressed below as the normal force, tangential force, and pitching moment. This input–output interpretation follows the discussion of the normal-velocity boundary condition in Appendix E of Bæk (2011).

Differentiation of Eq. (1) gives

$$\dot{U} = -\ddot{x}. \quad (2)$$

The formulation assumes a positive relative streamwise speed, $U > 0$. Under the small-angle assumptions of thin-airfoil theory, the mid-chord heaving acceleration normal to the airfoil is

$$\ddot{\epsilon} = \ddot{x}\theta + \ddot{y} + ab\ddot{\theta}. \quad (3)$$

The onset downwash at the three-quarter-chord point is approximated as

$$w_{3/4} = U\theta - \dot{y} + \left(\frac{1}{2} - a\right)b\dot{\theta}. \quad (4)$$

The individual circulatory and non-circulatory contributions are identified from the dimensional loads. The normal force N acts perpendicular to the chord and is positive from the pressure side towards the suction side. The tangential force T acts along the chord and is positive towards the leading edge. The pitching moment M_a is taken about the pitch axis at $\xi = ab$ and is positive in the nose-up direction.

For harmonic motion at constant U , the effect of the shed wake is represented by Theodorsen’s function $C(k)$. Writing a harmonic downwash quantity as $w(t) = \text{Re}\{\hat{w}e^{i\omega t}\}$, where the hat denotes the complex harmonic amplitude, the frequency-domain relation between the equivalent wake-lagged downwash and the three-quarter-chord onset downwash is

$$\hat{w}_E = C(k)\hat{w}_{3/4}, \quad (5)$$

where $k = \omega b/U$ is the reduced frequency.

In time domain simulations, w_E is obtained from the indicial response states introduced in Sect. 2.3. It is an equivalent wake-lagged downwash used for determining the integrated circulatory loading in the model and should not be interpreted as a real physical wake-induced velocity evaluated at a particular chordwise position.

For the uncambered airfoil considered here, using w_E and the mid-chord heaving acceleration defined in Eq. (3), the dimensional unsteady thin-airfoil loads per unit span obtained from the general formulation given in Appendix B of Gaunaa (2010)



can be written in the present notation as

$$N = \underbrace{2\pi\rho b U w_E}_{N_{\text{circ}}} + \underbrace{\pi\rho b^2 (U\dot{\theta} - \ddot{\epsilon})}_{N_{\text{NC}}}, \quad (6)$$

$$\begin{aligned} T &= 2\pi\rho b \left(w_E - \frac{b}{2}\dot{\theta} \right)^2 \\ &= \underbrace{2\pi\rho b w_E^2 - 2\pi\rho b^2 w_E \dot{\theta}}_{T_{\text{suction circ}}} + \underbrace{\frac{1}{2}\pi\rho b^3 \dot{\theta}^2}_{T_{\text{NC}}^{\dot{\theta}^2}}, \end{aligned} \quad (7)$$

$$M_a = \underbrace{2\pi\rho b^2 \left(a + \frac{1}{2} \right) U w_E + \pi\rho b^3 a (U\dot{\theta} - \ddot{\epsilon})}_{M_{a,\text{circ}}} - \underbrace{\frac{1}{2}\pi\rho b^3 U \dot{\theta} - \frac{1}{8}\pi\rho b^4 \ddot{\theta}}_{M_{a,\text{NC}}}. \quad (8)$$

180 The non-circulatory normal force consists of the mid-chord heaving acceleration and torsional-rate contributions

$$N_{\text{NC}}^{\text{acc}} = -\pi\rho b^2 \ddot{\epsilon}, \quad (9)$$

$$N_{\text{NC}}^{\text{tor}} = \pi\rho b^2 U \dot{\theta}. \quad (10)$$

For airfoil polars, the pitching moment is generally provided about the quarter-chord point. The reference for the thin-airfoil pitching moment is therefore transferred from the pitch axis at $\xi = ab$ to the quarter-chord point at $\xi = -b/2$:

$$185 \quad M_{1/4}^{\text{thin}} = M_a - \left(a + \frac{1}{2} \right) b N. \quad (11)$$

Substitution of the normal force and pitching moment cancels the circulatory contribution exactly and gives

$$M_{1/4}^{\text{thin}} = -\frac{c}{4} N_{\text{NC}}^{\text{acc}} - \frac{c}{2} N_{\text{NC}}^{\text{tor}} - \frac{1}{8} \pi \rho b^4 \ddot{\theta}. \quad (12)$$

Thus, for the uncambered thin-airfoil considered here, the quarter-chord pitching moment contains only non-circulatory contributions.

190 2.1.1 Physical interpretation of the non-circulatory terms

The physical meaning of the non-circulatory terms can be clarified by considering the chordwise distribution of the onset downwash. For an arbitrary chordwise position ξ , the small-angle rigid-airfoil kinematics give

$$w(\xi, t) = U\theta - \dot{y} + (\xi - ab)\dot{\theta} = w_{1/2}(t) + \xi\dot{\theta}(t), \quad (13)$$

195 where $w_{1/2} = U\theta - \dot{y} - ab\dot{\theta}$ is the onset downwash at the mid-chord point. Equation (13) shows that $\dot{\theta}$ determines the linear variation of the downwash along the chord.

Differentiating Eq. (13) gives

$$\dot{w}(\xi, t) = \dot{w}_{1/2}(t) + \xi\ddot{\theta}(t). \quad (14)$$



Using $\dot{U} = -\ddot{x}$ from Eq. (2) and the definition of $\ddot{\epsilon}$ in Eq. (3), the rate of change of the mid-chord downwash is

$$\dot{w}_{1/2} = U\dot{\theta} - \ddot{\epsilon}. \quad (15)$$

200 The combination of the two terms in the non-circulatory normal force can therefore be interpreted as the rate of change of the mid-chord downwash. The term $-\ddot{\epsilon}$ represents the contribution from the mid-chord kinematic acceleration normal to the airfoil, whereas $U\dot{\theta}$ results from the changing projection of the streamwise relative flow as the airfoil rotates. Although $U\dot{\theta}$ is uniform along the chord in $\dot{w}$, the same torsional rate $\dot{\theta}$ simultaneously determines the linear chordwise variation of w through Eq. (13).

205 The torsional-rate-squared contribution $T_{NC}^{\dot{\theta}^2}$ is a non-circulatory tangential load associated with the linear variation of downwash along the chord produced by $\dot{\theta}$.

The physical interpretation of the non-circulatory quarter-chord moment can be made more transparent by rewriting Eq. (12) as

$$M_{1/4,NC} = -\frac{c}{4}N_{NC} - \frac{c}{4}N_{NC}^{\text{tor}} - \frac{1}{8}\pi\rho b^4\ddot{\theta}. \quad (16)$$

210 The first term corresponds to placing the total non-circulatory normal force at the mid-chord point. The second term is an additional moment associated with the linear variation of downwash along the chord caused by the torsional rate. The final term is associated with the torsional acceleration $\ddot{\theta}$. For pure rotation about the mid-chord, $\ddot{\theta}$ produces opposite normal accelerations on the leading- and trailing-edge sides, giving no resultant normal force but a non-zero pitching moment.

2.2 Thin-airfoil loads in coefficient form

215 The dynamic pressure and characteristic time for the flow to travel one half-chord are

$$q = \frac{1}{2}\rho U^2, \quad (17)$$

$$T_0 = \frac{b}{U} = \frac{c}{2U}. \quad (18)$$

The equivalent angle of attack associated with the wake-lagged downwash is defined as

$$\alpha_E = \frac{w_E}{U}. \quad (19)$$

220 The equivalent angle of attack is a calculated quantity that governs the circulatory-force magnitude and should not be interpreted as an actual local flow angle at the three-quarter-chord point.

Non-dimensionalisation of Eq. (6) gives the normal force coefficient

$$C_N = \frac{N}{qc} = 2\pi\alpha_E + C_{N,NC}, \quad (20)$$

where the non-circulatory contribution is

$$225 \quad C_{N,NC} = C_{N,NC}^{\text{acc}} + C_{N,NC}^{\text{tor}}, \quad (21)$$



with

$$C_{N,NC}^{\text{acc}} = -\pi T_0 \frac{\ddot{\epsilon}}{\bar{U}}, \quad (22)$$

$$C_{N,NC}^{\text{tor}} = \pi T_0 \dot{\theta}. \quad (23)$$

Non-dimensionalisation of Eq. (7) gives the tangential force coefficient

$$230 \quad C_T = \frac{T}{qc} = \underbrace{2\pi\alpha_E^2 - 2\pi T_0 \dot{\theta} \alpha_E}_{C_{T,circ}^{\text{suction}}} + \underbrace{\frac{1}{2}\pi (T_0 \dot{\theta})^2}_{C_{T,NC}^{\dot{\theta}^2}}. \quad (24)$$

The full non-circulatory pitching moment coefficient about the quarter-chord point is

$$\begin{aligned} C_{m,NC}^{\text{full}} &\equiv \frac{M_{1/4}^{\text{thin}}}{qc^2} = \frac{1}{4}\pi T_0 \frac{\ddot{\epsilon}}{\bar{U}} - \frac{1}{2}\pi T_0 \dot{\theta} - \frac{1}{16}\pi T_0^2 \ddot{\theta} \\ &= -\frac{1}{4}C_{N,NC}^{\text{acc}} - \frac{1}{2}C_{N,NC}^{\text{tor}} - \frac{1}{16}\pi T_0^2 \ddot{\theta}. \end{aligned} \quad (25)$$

2.3 Shed wake memory in state-space form

235 The frequency-domain shed wake relation in Eq. (5) is represented in the time domain through an exponential approximation of an indicial response. For an approximation with n_w exponential terms, the response function is written as

$$\phi(s) = 1 - \sum_{i=1}^{n_w} A_i e^{-\beta_i s}. \quad (26)$$

The non-dimensional convective time, which measures the distance travelled by the wake in units of the half-chords, is defined as

$$s = \frac{2}{c} \int_0^t U(t') dt'. \quad (27)$$

240 Because $T_0 = c/(2U)$, the rate of change of the convective time is $ds/dt = 1/T_0$.

Two- and three-term approximations are commonly used in practice. For example, the two-term approximation of Wagner's thin-airfoil impulsive response by Jones (1938, 1940) uses $n_w = 2$, with $A_1 = 0.165$, $A_2 = 0.335$, $\beta_1 = 0.0455$, and $\beta_2 = 0.3$. More general impulsive response functions that account for effects of airfoil thickness and shape have also been developed (Bergami et al., 2013).

245 The following equations are first written in terms of the geometric three-quarter-chord downwash,

$$w_{3/4} = U\alpha_{3/4}, \quad (28)$$

and the equivalent wake-lagged downwash,

$$w_E = U\alpha_E. \quad (29)$$



Here, α_E is the equivalent angle of attack. The treatment of cambered airfoils is introduced later through a zero-lift-shifted
 250 downwash.

A direct representation of the attached-flow wake memory in terms of downwash is given by Bæk (2011) and Pirrung and Gaunaa (2018). The equivalent wake-lagged downwash governing the circulatory response is

$$w_E = \left(1 - \sum_{i=1}^{n_w} A_i\right) w_{3/4} + \sum_{i=1}^{n_w} x_i^w. \quad (30)$$

Each state x_i^w represents one component of the wake-induced memory and satisfies

$$255 \quad \dot{x}_i^w + \frac{\beta_i}{T_0} x_i^w = \frac{\beta_i A_i}{T_0} w_{3/4}. \quad (31)$$

Starting from the downwash-state formulation, Hansen et al. (2004) introduce an equivalent formulation in terms of angle-of-attack states. The corresponding angle state z_i is defined by

$$x_i^w = U z_i. \quad (32)$$

Substitution of Eq. (32) into Eq. (30), followed by division by U and use of Eqs. (28) and (29), gives

$$260 \quad \alpha_E = \left(1 - \sum_{i=1}^{n_w} A_i\right) \alpha_{3/4} + \sum_{i=1}^{n_w} z_i. \quad (33)$$

In this angle-state formulation, α_E is not shifted by the zero-lift angle α_0 . Differentiating Eq. (32) and substituting the result into Eq. (31) give

$$\dot{z}_i + \left(\frac{\beta_i}{T_0} + \frac{\dot{U}}{U}\right) z_i = \frac{\beta_i A_i}{T_0} \alpha_{3/4}. \quad (34)$$

For time-varying U , the angle-state formulation requires the additional term $\dot{U}/U$, whereas the downwash-state formulation
 265 does not.

The direct downwash-state and angle-state forms are mathematically equivalent when the velocity-rate term and the initial conditions are treated consistently.

A deficit-state formulation is useful when embedding the attached-flow model in a dynamic stall model, because it separates the decay of stored wake memory from the new contribution to the attached-flow lag. The formulation introduced by Pirrung
 270 and Gaunaa (2018) uses the three-quarter-chord onset downwash $w_{3/4} = U \alpha_{3/4}$ as input and does not explicitly account for the airfoil zero-lift angle. Following Bæk (2011) and Pirrung et al. (2017), the present formulation instead uses the downwash relative to the zero-lift condition as input:

$$\tilde{w}_{3/4} = U (\alpha_{3/4} - \alpha_0) = w_{3/4} - U \alpha_0. \quad (35)$$

Here, α_0 is the zero-lift angle of the 2-D airfoil polar, and the tilde denotes an onset-downwash quantity measured relative to
 275 the zero-lift condition. The consistency of this shift for time-varying U is demonstrated in Appendix B1.



When the direct downwash-state equations are formulated using $\tilde{w}_{3/4}$, the deficit states are defined as

$$r_i^w = A_i \tilde{w}_{3/4} - x_i^w. \quad (36)$$

The corresponding zero-lift-shifted equivalent wake-lagged downwash is

$$\tilde{w}_E = \tilde{w}_{3/4} - \sum_{i=1}^{n_w} r_i^w. \quad (37)$$

280 The equivalent angle of attack is then recovered as

$$\alpha_E = \alpha_0 + \frac{\tilde{w}_E}{U}. \quad (38)$$

Differentiating Eq. (36) and using Eq. (31) gives the attached-flow deficit-state equation

$$\dot{r}_i^w + \frac{\beta_i}{T_0} r_i^w = A_i \dot{\tilde{w}}_{3/4}. \quad (39)$$

In this form, $\beta_i r_i^w / T_0$ describes the decay of stored wake memory, whereas $A_i \dot{\tilde{w}}_{3/4}$ represents the new contribution to the
 285 wake-memory. Together with Eqs. (37) and (38), Eq. (39) is equivalent to the direct downwash-state formulation.

When the deficit-state formulation is embedded in a full dynamic stall model, a scaling of the newly generated wake memory term with the separation state has been shown to provide a reasonable engineering treatment for issues arising during rapid angle-of-attack variations, such as those encountered in vertical-axis wind turbine (VAWT) applications (Pirrung and Gaunaa, 2018). The corresponding extension and its time-discrete implementation are described in Appendix B.

290 The preceding subsections provide the classical sectional loads in the chordwise normal and tangential directions together with the attached-flow shed wake memory. Because the normal and tangential directions are fixed relative to the airfoil chord, this chord-based force representation is unambiguous. For coupling with the 2-D airfoil polar and with the broader dynamic stall formulation, it is convenient to express the sectional forces in terms of lift and drag. The 2-D airfoil polar is conventionally provided in lift and drag coefficients, and the separation related terms in the full dynamic stall model are also formulated in
 295 terms of lift and drag. Unlike the chord-based normal and tangential components, however, lift and drag must be defined relative to a local reference flow direction. Specifying this reference direction is therefore a key, yet often overlooked, aspect of a consistent generalized lifting-line formulation. The following subsections develop this formulation by relating the blade and wake model to the 2-D section, interpreting the circulatory force, coupling the unsteady formulation with the airfoil polar, and projecting the resulting force contributions relative to the selected flow direction.

300 2.4 Coupling to the blade and wake model

In generalized lifting-line methods, including BEM, LL, and AL, the outer 3-D rotor and wake problem combines the onset flow, blade motion, and induced velocity to determine the local relative velocity vector at each aerodynamic calculation point. This velocity vector is projected onto the 2-D airfoil section plane and supplied as the external flow to the inner 2-D airfoil problem (Li et al., 2022). Following the input–output machine interpretation introduced in Sect. 2.1, the outer flow solution



305 and sectional kinematics together provide the relative flow and kinematic histories required by the inner 2-D model, including
 the information needed to determine the chordwise downwash distribution and its time variation. The inner model combines
 the 2-D airfoil polar with the non-circulatory force and moment contributions derived in the present work and the attached-flow
 indicial wake memory. The indicial wake memory is included only where the shed wake dynamics are not represented by the
 outer rotor and wake model. The projected flow defines the relative streamwise velocity U and the angle of attack α_χ at the
 310 calculation point.

Let χ denote the location of the aerodynamic calculation point as a fraction of the chord measured from the leading edge,
 with $\chi = 0$ at the leading edge and $\chi = 1$ at the trailing edge. The velocity relative to the airfoil due to its translational motion
 is uniform over the chord. The treatment of the trailed wake induced velocity supplied by the outer 3-D wake model, hereafter
 referred to as induction, depends on the method used. In BEM and conventional LL and AL implementations, this induction
 315 is evaluated at a single aerodynamic calculation point and is therefore treated as uniform over the chord when coupled to the
 inner 2-D airfoil model. Multi-point LL formulations may instead provide the induction at more than one chordwise location,
 for example at the quarter- and three-quarter-chord points in Gaunaa et al. (2026), thereby retaining its chordwise variation.

Following Hansen et al. (2004), variations in the incoming flow, including gusts, are treated as instantaneous changes over
 the entire airfoil section. For the instantaneous sectional relative flow velocity, changes due to translational airfoil motion
 320 and variations in the incoming flow therefore need not be distinguished at the sectional aerodynamic level. The accuracy of
 this approximation for unsteady inflow was investigated by Buhl et al. (2005), and its application in aeroelastic wind turbine
 simulations is discussed further by Li et al. (2022). In contrast, the effective torsional rate $\dot{\theta}$ is treated separately because it
 induces a linear variation along the chord in the velocity component normal to the airfoil and, consequently, in the local angle
 of attack. This kinematic variation in the 2-D airfoil model is independent of the treatment of the outer trailed wake induced
 325 velocity.

For a wind turbine blade section, the effective torsional rate may result from prescribed blade pitching, blade torsional
 deformation, or the projection of the rotor angular velocity onto the 2-D airfoil section plane, as occurs for coned HAWTs
 and VAWTs (Pirring and Gaunaa, 2018; Li et al., 2022, 2025). The aerodynamic formulation depends only on the resulting
 effective torsional rate and does not distinguish between its origins.

330 For a rigid airfoil section, the effective torsional rate causes the normal velocity, and hence the local angle of attack, to vary
 linearly along the chord. The angles of attack at the quarter-chord and three-quarter-chord points are therefore reconstructed as

$$\alpha_{1/4} = \alpha_\chi + \left(\frac{1}{4} - \chi\right) \frac{c\dot{\theta}}{U}, \quad (40)$$

$$\alpha_{3/4} = \alpha_\chi + \left(\frac{3}{4} - \chi\right) \frac{c\dot{\theta}}{U}. \quad (41)$$

Their difference is independent of the location of the aerodynamic calculation point:

335 $\alpha_{3/4} - \alpha_{1/4} = \frac{b\dot{\theta}}{U} = T_0\dot{\theta}. \quad (42)$



For example, in the aerodynamic module of HAWC2, the aerodynamic calculation point is located at the three-quarter-chord point (Larsen and Hansen, 2007). Therefore,

$$\alpha_\chi = \alpha_{3/4}, \quad (43)$$

$$\alpha_{1/4} = \alpha_{3/4} - T_0 \dot{\theta}. \quad (44)$$

340 The mid-chord heaving acceleration $\ddot{e}$ represents the kinematic contribution from airfoil section motion to the time variation of the relative flow normal to the airfoil chord at mid-chord. In an aeroelastic model, the kinematic contribution can arise from structural deformation and rigid body rotor motion. The chord-normal relative velocity may also vary as the blade moves through a spatially and temporally varying flow field, including gusts and turbulence.¹ The kinematic contributions from the blade and rotor motion must nevertheless be included consistently. It is important to notice that the contributions from the
 345 projection of the centripetal acceleration due to rotation of a deflected or coned rotor into the airfoil section must be included in this term. An extreme case in this respect occurs for VAWTs, where the projection of the centripetal acceleration onto the airfoil normal direction can be significant.

The treatment of the shed wake memory depends on the outer aerodynamic model. In BEM models, the outer induction model based on momentum theory does not explicitly model the shed wake from the blades. The attached flow indicial states
 350 are therefore used to represent the local 2-D shed wake memory and determine $\tilde{w}_E$ and α_E . Conversely, when a lifting-line (LL) or actuator-line (AL) solver explicitly resolves the shed wake induction in the outer wake or flow solution, this contribution is already included in the local relative velocity and therefore in $\alpha_{3/4}$ supplied to the 2-D airfoil model. To avoid double counting, the attached flow indicial states are then omitted by setting $\alpha_E = \alpha_{3/4}$.

2.5 Circulatory force magnitude and direction

355 First, the general relation between the chord-based normal and tangential forces and the lift and drag components is introduced. Let $\Delta\alpha_r$ denote the signed angle between the onset-flow direction and a selected reference flow direction. The angle between the chord and the selected reference flow direction is then $\alpha_r = \theta + \Delta\alpha_r$, as illustrated in Fig. 2.

The chord-axis force coefficients are transformed to lift and drag relative to this direction according to

$$C_{l,r} = C_N \cos \alpha_r + C_T \sin \alpha_r, \quad (45)$$

$$360 \quad C_{d,r} = C_N \sin \alpha_r - C_T \cos \alpha_r. \quad (46)$$

Under the small-angle approximation used in classical thin-airfoil theory,

$$C_{l,r} \approx C_N, \quad (47)$$

$$C_{d,r} \approx C_N \alpha_r - C_T. \quad (48)$$

¹In the present implementation of the HAWC2 aerodynamic module, the contribution from temporal variation of the chord-normal relative velocity to the non-circulatory mid-chord acceleration term is neglected.




Figure 2. Projection of the normal and tangential force components into lift and drag defined relative to a selected flow direction. The selected direction differs from the onset-flow direction by $\Delta\alpha_r$, such that $\alpha_r = \theta + \Delta\alpha_r$. Adapted from Li et al. (2022) with permission.

The circulatory force relations developed below retain the small-angle approximation of classical thin-airfoil theory. The non-circulatory normal and tangential force contributions are later projected using the full trigonometric relations in Eqs. (45) and (46). The pitching moment is defined about the quarter-chord point and is unchanged by the force rotation.

Analysis of the unsteady thin airfoil equations identifies distinct roles for the three-quarter-chord and quarter-chord flow quantities (Øye, 1981; Gaunaa, 2010; Bæk, 2011; Bergami and Gaunaa, 2012). The three-quarter-chord quantity governs the circulatory lift magnitude, while the quarter-chord flow direction provides a natural reference direction for resolving the circulatory force into lift and drag (Øye, 1981; Bæk, 2011; Li et al., 2022).

The zero-lift-shifted three-quarter-chord downwash $\tilde{w}_{3/4}$ is the input to the 2-D shed wake model in the present formulation. The indicial response states account for the history of this input and determine the zero-lift-shifted equivalent wake-lagged downwash $\tilde{w}_E$, from which the effective angle α_E is recovered. The three-quarter-chord angle $\alpha_{3/4}$ defines the quasi-steady target of the circulatory response, while α_E represents the response after accounting for the shed wake memory. In classical linear thin-airfoil theory for a symmetric airfoil, the corresponding circulatory normal force coefficient is

$$C_{N,\text{circ}} = 2\pi\alpha_E. \quad (49)$$

Thus, α_E determines the circulatory lift magnitude.

The geometric quarter-chord flow direction $\alpha_{1/4}$ has a different role in the circulatory force decomposition. Applying Eq. (48) to the circulatory normal and tangential force contributions gives the circulatory drag coefficient resolved relative to a reference direction α_r :

$$\begin{aligned} C_{d,\text{circ},r} &\approx C_{N,\text{circ}}\alpha_r - C_{T,\text{circ}}^{\text{suction}} \\ &= 2\pi\alpha_E \left(\alpha_r - \alpha_E + T_0\dot{\theta} \right). \end{aligned} \quad (50)$$

Using the relation $\alpha_{1/4} = \alpha_{3/4} - T_0\dot{\theta}$ from Eq. (42), Eq. (50) can be rewritten as

$$C_{d,\text{circ},r} \approx 2\pi\alpha_E \left[\left(\alpha_{3/4} - \alpha_E \right) + \left(\alpha_r - \alpha_{1/4} \right) \right]. \quad (51)$$



The first term in Eq. (51) is the induced drag associated with the shed-wake memory, defined as

$$C_{d,\text{ind}} \equiv 2\pi\alpha_E (\alpha_{3/4} - \alpha_E). \quad (52)$$

The second term arises solely from the choice of reference direction. The angular offset from the quarter-chord flow direction is $\Delta\alpha \equiv \alpha_r - \alpha_{1/4}$, the corresponding reference direction contribution is denoted by $C_d^{\Delta\alpha} \equiv 2\pi\alpha_E \Delta\alpha$. The circulatory drag can then be written as

$$C_{d,\text{circ},r} \approx C_{d,\text{ind}} + C_d^{\Delta\alpha}. \quad (53)$$

When $\alpha_r = \alpha_{1/4}$, we have $C_d^{\Delta\alpha} = 0$, so that the circulatory drag resolved relative to the quarter-chord flow direction is $C_{d,\text{circ},1/4} = C_{d,\text{ind}}$. A related derivation for the circulatory drag resolved relative to different local flow directions is given in Appendix A.2 of the manuscript reproduced in Appendix E of Bæk (2011).

In the quasi-steady limit, $\alpha_E = \alpha_{3/4}$, and hence $C_{d,\text{ind}} = 0$. The integrated circulatory normal force and leading edge suction therefore produce zero drag when resolved relative to the quarter-chord flow direction. This property motivates the use of $\alpha_{1/4}$ as a natural reference direction for the circulatory lift and drag.

Under unsteady conditions, the shed wake memory causes α_E to differ from $\alpha_{3/4}$. The integrated circulatory force then has a non-zero drag component when resolved relative to $\alpha_{1/4}$. The direction of the circulatory force is identified as the direction for which its drag component vanishes. Its angle relative to the chord is denoted by $\alpha_{\text{circ},\text{dir}}$. Setting Eq. (51) to zero gives

$$\alpha_{\text{circ},\text{dir}} = \alpha_{1/4} - (\alpha_{3/4} - \alpha_E) = \alpha_E - T_0 \dot{\theta}. \quad (54)$$

The shed wake lag $\alpha_{3/4} - \alpha_E$ therefore shifts the circulatory-force direction away from the geometric quarter-chord flow direction.

2.6 Coupling with the 2-D airfoil polar

In the classical thin-airfoil formulation, the circulatory lift magnitude is governed by the effective angle of attack α_E through a linear flat plate relation with a lift-curve slope of 2π . To represent the aerodynamic characteristics of a real airfoil, this linear relation is replaced by a 2-D airfoil polar obtained from measurements or CFD simulations (Hansen et al., 2004).

The polar is evaluated at α_E and provides

$$C_{l,\text{circ}}^{\text{dyn}} \equiv C_l^{\text{polar}}(\alpha_E), \quad (55)$$

$$C_d^{\text{profile}} \equiv C_d^{\text{polar}}(\alpha_E), \quad (56)$$

$$C_m^{\text{profile}} \equiv C_m^{\text{polar}}(\alpha_E). \quad (57)$$

Here, the superscript dyn denotes the unsteady circulatory lift response, and $C_{l,\text{circ}}^{\text{dyn}}$ is obtained by evaluating the polar at the wake-lagged effective angle α_E .

In the present formulation, the polar lookup provides the circulatory lift magnitude, profile drag, and quarter-chord pitching moment. The airfoil polar accounts for the effects of airfoil camber and viscosity on these quantities. The non-circulatory loads and the induced drag associated with the unsteady 2-D shed wake are added separately.



415 Following previous formulations (Hansen et al., 2004; Bæk, 2011; Bergami and Gaunaa, 2012), the corresponding 2-D shed wake-induced drag is calculated as

$$C_{d,ind} = C_{l,circ}^{dyn} \left(\alpha_{3/4} - \alpha_E \right). \quad (58)$$

2.6.1 Circulatory force projection relative to the calculation point flow direction

When lift and drag are defined relative to the local flow direction at the aerodynamic calculation point χ , the reference direction
 420 defined in Sect. 2.5 is $\alpha_r = \alpha_\chi$. Using the circulatory lift magnitude from the 2-D airfoil polar in Eq. (55), the circulatory drag in Eq. (53) becomes

$$C_{d,circ,\chi} \approx C_{d,ind} + C_{l,circ}^{dyn} \left(\chi - \frac{1}{4} \right) \frac{c\dot{\theta}}{U}. \quad (59)$$

When the reference direction is the quarter-chord flow direction, $\chi = 1/4$, the second term in Eq. (59) vanishes, and the circulatory drag reduces to $C_{d,ind}$.

425 When the reference direction is the three-quarter-chord flow direction, as in HAWC2 (Madsen et al., 2020), $\chi = 3/4$. Lift and drag are then defined relative to the local flow direction at the three-quarter-chord point. Equation (59) becomes

$$C_{d,circ,3/4} \approx C_{d,ind} + C_{l,circ}^{dyn} T_0 \dot{\theta}. \quad (60)$$

Although the two reference directions lead to different lift and drag decompositions, they describe the same aerodynamic force when the corresponding projection is implemented consistently.

430 For the three-quarter-chord reference direction, $\Delta\alpha = T_0 \dot{\theta}$. The corresponding reference direction contribution to drag is therefore

$$C_d^{\Delta\alpha} = C_{l,circ}^{dyn} T_0 \dot{\theta}. \quad (61)$$

Both $C_d^{\Delta\alpha}$ and $C_{d,ind}$ are circulatory contributions and are distinct from the non-circulatory tangential force contribution $C_{T,NC}^{\dot{\theta}^2}$ in Eq. (24), which is quadratic in the torsional rate.

435 2.7 Final implementation form

This section assembles the coefficient equations using the conventions of HAWC2 version 13.2. The aerodynamic calculation point is at the three-quarter chord ($\chi = 3/4$), and lift and drag are defined relative to the local flow direction at that point.

For each blade section, a local sectional coordinate system S is defined following the HAWC2 convention. Its origin is located at the airfoil mid-chord point, the sectional x -axis lies along the chord and is positive from the trailing edge towards the leading edge, and the sectional y -axis is normal to the chord and positive from the pressure side towards the suction side. The
 440 sectional z -axis completes the right-handed coordinate system. The orientation of the sectional coordinate system follows the instantaneous blade geometry, such that prebend, blade deflection, twist, and torsional deformation are included. Translational and rotational kinematic quantities provided by the structural solver are transformed to the sectional coordinate system.



For each blade section, the outer rotor and wake solver combines the incoming flow, induced velocity, and blade motion, then
 445 projects the relative velocity onto the airfoil plane to determine U and $\alpha_{3/4}$. Variations in incoming flow, including turbulence,
 therefore enter the circulatory model through the histories of these quantities. The effective torsional rate $\dot{\theta}$ and mid-chord
 heaving acceleration $\ddot{e}$ are obtained from blade kinematics, while contributions from temporal variations of the incoming flow
 are omitted in the present implementation and left for future work.

For the HAWC2 implementation, the structural kinematics are evaluated at the three-quarter-chord point. Denoting the
 450 acceleration component normal to the airfoil section by $a_{3/4,y}^S$, the mid-chord heaving acceleration is

$$\ddot{e} = a_{3/4,y}^S + \frac{c}{4}\dot{\omega}_z^S + \frac{c}{4}\omega_x^S\omega_y^S \approx a_{3/4,y}^S + \frac{c}{4}\dot{\omega}_z^S. \quad (62)$$

In the present HAWC2 implementation, the approximated form in Eq. (62) is used. The three-dimensional quadratic rotational
 contribution associated with the point transformation is neglected.

The effective torsional rate $\dot{\theta}$ is correspondingly the angular velocity component about the sectional z -axis. For the present
 455 choice $\chi = 3/4$, $\alpha_\chi = \alpha_{3/4}$. The corresponding zero-lift-shifted downwash $\tilde{w}_{3/4} = U(\alpha_{3/4} - \alpha_0)$ is used to update the time-
 domain 2-D shed wake states described in Sect. 2.3, which determine $\tilde{w}_E$ and consequently the effective angle of attack
 $\alpha_E = \alpha_0 + \tilde{w}_E/U$.

With these quantities, the total lift coefficient is

$$C_{l,3/4}^{\text{tot}} = C_{l,\text{circ}}^{\text{dyn}} + C_{N,\text{NC}} \cos \alpha_{3/4} + C_{T,\text{NC}}^{\dot{\theta}^2} \sin \alpha_{3/4}. \quad (63)$$

460 Here, $C_{l,\text{circ}}^{\text{dyn}}$ is obtained by evaluating the airfoil polar at α_E using Eq. (55). The non-circulatory coefficients $C_{N,\text{NC}}$ and $C_{T,\text{NC}}^{\dot{\theta}^2}$
 are given by Eqs. (21) and (24), respectively, and their lift components follow from the projection in Eq. (45).

The total drag coefficient is

$$C_{d,3/4}^{\text{tot}} = C_d^{\text{profile}} + C_{d,\text{ind}} + C_d^{\Delta\alpha} + C_{N,\text{NC}} \sin \alpha_{3/4} - C_{T,\text{NC}}^{\dot{\theta}^2} \cos \alpha_{3/4}. \quad (64)$$

Here, C_d^{profile} is obtained from the airfoil polar at α_E using Eq. (56), and the 2-D induced drag due to shed wake, $C_{d,\text{ind}}$, is
 465 defined in Eq. (58). The direction projection contribution $C_d^{\Delta\alpha}$ is defined in Eq. (61). The non-circulatory drag components are
 obtained from the projection of the non-circulatory normal and tangential forces, using Eq. (46).

The full non-circulatory quarter-chord pitching moment is given by Eq. (25) and is repeated here for completeness:

$$\begin{aligned} C_{m,\text{NC}}^{\text{full}} &= \frac{1}{4}\pi T_0 \frac{\ddot{e}}{U} - \frac{1}{2}\pi T_0 \dot{\theta} - \frac{1}{16}\pi T_0^2 \ddot{\theta} \\ &= -\frac{1}{4}C_{N,\text{NC}}^{\text{acc}} - \frac{1}{2}C_{N,\text{NC}}^{\text{tor}} - \frac{1}{16}\pi T_0^2 \ddot{\theta}. \end{aligned} \quad (65)$$

In HAWC2 version 13.2, only the final term, which is proportional to the torsional acceleration $\ddot{\theta}$, is neglected. Accordingly,
 470 the total quarter-chord pitching moment coefficient is calculated from the remaining non-circulatory pitching moment $C_{m,\text{NC}}$:

$$C_{m,1/4}^{\text{tot}} = C_m^{\text{profile}} + C_{m,\text{NC}}, \quad (66)$$



where C_m^{profile} is obtained from the airfoil polar at α_E using Eq. (57).

Because the non-circulatory added mass terms depend directly on the acceleration of the blade section, explicit aeroelastic
475 coupling can become numerically unstable. In HAWC2 version 13.2, the mid-chord heaving acceleration from the converged
blade kinematics at the previous time step is used, which is therefore kept fixed during the aeroelastic iterations. An alternative
is to include the aerodynamic added mass in the blade structural mass matrix.

The force application point is a separate choice from the aerodynamic calculation point and the reference direction for lift and
drag. In the HAWC2 implementation, the sectional force is applied at the three-quarter-chord point, whereas the aerodynamic
480 pitching moment in Eq. (66) is defined about the quarter-chord point. After conversion to dimensional sectional loads, static
equivalence is preserved by transferring the moment according to

$$\mathbf{M}_{3/4}^{\text{tot}} = \mathbf{M}_{1/4}^{\text{tot}} + (\mathbf{r}_{1/4} - \mathbf{r}_{3/4}) \times \mathbf{F}, \quad (67)$$

where $\mathbf{F}$ is the dimensional sectional aerodynamic force. The moment transfer term acts about the local spanwise axis and
therefore contributes directly to the blade torsional moment. For a straight blade lying in the rotor plane, it contributes only to
485 the blade torsional moment. Coning, prebend, or other out-of-plane geometry tilts the local spanwise axis, causing part of the
transferred moment to project onto the rotor axis and contribute to the aerodynamic rotor torque.

Algorithm 1 summarizes the resulting attached-flow update within an iterative aeroelastic simulation using a BEM aerody-
namic model, following the conventions and implementation details used in the HAWC2 code. Quantities required from the
previous time step remain fixed during the iterations of the new time step, while the current flow and sectional kinematics are
490 updated in each iteration.

A reference implementation of the attached flow formulation is provided with this work (Li, 2026). The accompanying
package includes HAWC2 comparison cases for a pitching airfoil and a harmonically pitching coned blade. These cases provide
a direct check that the reference implementation closely reproduces the corresponding HAWC2 results. The coned blade case
additionally illustrates how 3-D rotor and blade kinematics are projected into the sectional model inputs. The package also
495 serves as a practical reference for readers developing their own implementations.

2.7.1 Practical interpretation of sectional coefficients

The sectional coefficients require careful interpretation when the relative velocity is small or when lift and drag are defined
relative to the three-quarter-chord flow direction. At small relative velocities, the dynamic pressure becomes small and the
non-circulatory lift coefficients can therefore become very large, while the associated dimensional forces remain bounded
500 and physically meaningful (Larsen and Hansen, 2007). The drag coefficient may also become negative because the selected
reference direction changes the decomposition of the sectional force into lift and drag. Such coefficient values do not neces-
sarily indicate an incorrect aerodynamic force, and the corresponding dimensional force components should therefore also be
examined.



Algorithm 1 Evaluation of the sectional attached-flow aerodynamic model within an iterative aeroelastic simulation using a BEM aerodynamic model

```
for each time step  $t_{n+1}$  do  
  for each aeroelastic iteration do  
    for each blade section do  
      if this is the first iteration at  $t_{n+1}$  then  
        Save the converged aerodynamic state variables from the previous time step  $t_n$  for use in all iterations at this time step.  
      end if  
  
      Part I: Construct the input to the sectional 2-D model.  
  
      Obtain the current blade section kinematics from the structural solver.  
      Obtain the local inflow velocity, including shear and turbulence.  
      Determine the relative flow velocity from the inflow, induced velocity, and blade motion, project into the sectional coordinate system  $S$ .  
      Determine  $U$  and  $\alpha_{3/4}$  from the relative flow velocity components in the airfoil plane.  
      Determine torsional rate  $\dot{\theta}$  from the sectional kinematics and compute mid-chord heaving acceleration  $\ddot{e}$  from Eq. (62).  
  
      Part II: Evaluate the unsteady sectional 2-D model.  
  
      Evaluate the non-circulatory terms using  $\ddot{e}_n$  from the previous time step and  $\dot{\theta}$  from the current time step.  
      Compute  $\tilde{w}_{3/4} = U(\alpha_{3/4} - \alpha_0)$  and update the shed-wake states using Eq. (B29) with  $f_{\text{scale}} = 1$ .  
      Compute  $\tilde{w}_E$  and  $\alpha_E$  using Eq. (B31) and evaluate the airfoil polar at  $\alpha_E$  using Eqs. (55) to (57).  
      Compute  $C_{d,\text{ind}}$  and  $C_d^{\Delta\alpha}$  using Eqs. (58) and (61).  
      Assemble  $C_{l,3/4}^{\text{tot}}$ ,  $C_{d,3/4}^{\text{tot}}$ , and  $C_{m,1/4}^{\text{tot}}$  using Eqs. (63), (64), and (66).  
  
      Part III: Return the sectional aerodynamic output to the rotor model.  
  
      Convert the coefficients to dimensional sectional loads, then transfer to the selected reference point, and supply them to the structural solver.  
    end for  
  end for  
end for
```



3 Rotor-level implementation benchmark and verification cases

505 The classical sectional pitching and heaving responses have been documented and verified in previous formulations of the attached-flow model (Hansen et al., 2004; Gaunaa, 2010; Bergami and Gaunaa, 2012; Bergami et al., 2015). The purpose of the following cases is therefore not to revalidate the underlying 2-D theory. Likewise, validation of the outer 3-D rotor and wake models is beyond the scope of the present study. Instead, the focus is the coupling between the outer 3-D rotor problem and the inner 2-D sectional aerodynamic model.

510 When modeling wind turbines using generalized lifting-line methods, the 3-D rotor flow and blade kinematics must be projected into the sectional coordinate system to provide the flow and kinematic quantities required by the 2-D model. The resulting sectional loads must subsequently be transformed back to the rotor system. Coned blade configurations provide a particularly useful test of this coupling because, even under steady rotor operation, projecting the rotor kinematics into the sectional system introduces torsional rate and acceleration terms. Omitting such terms therefore results in an incomplete
 515 coupling of the 3-D rotor kinematics to the 2-D sectional model.

The two rotor-level cases are used for different verification purposes. The coned straight blade case provides a cross-method benchmark of the coupling between the 3-D rotor kinematics and the 2-D sectional aerodynamic model, and assesses how omitting selected terms changes the predicted rotor-integrated thrust and power. The zero-onset VAWT case provides an analytical consistency test by extending the studies of Pirrung and Gaunaa (2018) and Li et al. (2022) to include all circulatory
 520 and non-circulatory contributions in the ideal thin-airfoil limit. The resulting torque contributions are shown to cancel, giving zero total aerodynamic torque.

3.1 Coned straight blade case

The coned straight blade case provides a controlled rotor-level test of the coupling between the 3-D rotor kinematics and the unsteady 2-D airfoil model. At non-zero cone angles, effective sectional torsional rate and acceleration contributions arise even
 525 under steady operating conditions, allowing their influence on the predicted rotor loads to be isolated and quantified.

The effective sectional torsional rate $\dot{\theta}$ accounts for the variation in local flow angle along the chord and is used to determine the flow angles at the three-quarter- and quarter-chord points from the flow evaluated at a single aerodynamic calculation point.² Li et al. (2022) examined its influence primarily through comparisons of sectional blade loads. These comparisons are not repeated here; instead, the present analysis considers rotor-integrated quantities over a wide range of cone angles.

530 The blade element momentum (BEM), lifting-line (LL), and computational fluid dynamics (CFD) calculations provide a rotor-level numerical benchmark across aerodynamic solvers of increasing fidelity. In addition, three BEM calculations are performed, each omitting selected non-circulatory terms from the complete formulation.

²This procedure is referred to as the *one-point correction* by Li et al. (2022).



3.1.1 Test configuration and objective

The present study builds on the comparison used in Li et al. (2022), but uses an updated straight bladed configuration based on the IEA 10 MW reference wind turbine (Bortolotti et al., 2019) and a different operating condition. All CFD, LL, and BEM results presented here are obtained from new calculations. The blade geometry is prescribed in all simulations, elastic blade deformations are not included, and the blade pitch angle is set to zero.

The rotor tilt is first removed. The prebend and sweep of the reference blade are then removed so that the half-chord line is straight. The baseline rotor radius is $R_0 = 99.555$ m, including the hub radius $r_{\text{hub}} = 2.8$ m. Coned rotors are generated by rotating each blade about its root connection to the hub, with the cone angle κ ranging from -30° to 30° , where positive cone angles denote upwind coning.

The rotor thrust and power coefficients are normalized using the projected rotor area

$$A_{\text{proj}}(\kappa) = \pi [r_{\text{hub}} + (R_0 - r_{\text{hub}}) \cos \kappa]^2. \quad (68)$$

The rotor thrust and power coefficients are calculated from the rotor-integrated thrust and power, T_{rot} and P_{rot} , respectively, and are defined as

$$C_{T,\text{rot}} = \frac{T_{\text{rot}}}{\frac{1}{2} \rho U_0^2 A_{\text{proj}}(\kappa)}, \quad (69)$$

$$C_{P,\text{rot}} = \frac{P_{\text{rot}}}{\frac{1}{2} \rho U_0^3 A_{\text{proj}}(\kappa)}. \quad (70)$$

The rotor operates in uniform inflow with no wind shear or yaw misalignment. The wind speed is $U_0 = 8 \text{ m s}^{-1}$, and the rotational speed is fixed at $\Omega = 0.72322 \text{ rad s}^{-1}$. For the baseline rotor with radius R_0 , the tip-speed ratio is $\lambda_0 = \Omega R_0 / U_0 = 9$. Fully turbulent airfoil polars obtained from 2-D CFD calculations are used consistently in the LL and BEM simulations.

The high-fidelity reference calculations are performed using EllipSys3D, a pressure-based incompressible three-dimensional computational fluid dynamics (CFD) solver (Michelsen, 1992, 1994; Sørensen, 1995). The solver uses a finite volume discretization of the Reynolds-averaged Navier–Stokes (RANS) equations. The flow is assumed fully turbulent and modeled using the $k-\omega$ shear stress transport (SST) turbulence model (Menter, 1994). Body-fitted, wall-resolved meshes are used following the numerical setup described by Li et al. (2022).

The LL calculations are performed using the free-wake vortex solver MIRAS (Ramos-García et al., 2016) coupled to HAWC2 for the prescribed blade geometry and rigid-body sectional kinematics. The whole turbine is assumed to be stiff, and no elastic blade deformation is included. MIRAS evaluates the 3-D induced velocity at the quarter-chord point as part of the outer 3-D free-wake problem. HAWC2 evaluates the rotational and structural kinematic velocities at the three-quarter-chord point and combines them with the MIRAS induced velocity. The relative flow direction at the three-quarter-chord point is used to define lift and drag.

The BEM calculations are performed using the HAWC2 BEM module. Within this module, the sectional relative velocity and the reference direction for lift and drag are evaluated at the three-quarter-chord point. The induction from the momentum theory is determined at the blade element level and is assumed constant along the chord.



565 For a straight blade with a cone angle κ , projecting the rotor angular velocity into the airfoil section results in an effective sectional torsional rate

$$\dot{\theta} = -\Omega \sin \kappa. \quad (71)$$

According to Eq. (42), this torsional rate produces a variation in the flow direction along the chord. The small chordwise variation in the relative velocity magnitude is neglected, as justified numerically by Li et al. (2022).

570 For the present steady operating condition, the 2-D shed wake-induced drag vanishes, so $C_{d,\text{ind}} = 0$. For the steady coned straight blade configuration, the heaving acceleration and torsional-rate contributions to $C_{N,\text{NC}}$ in Eq. (21) cancel (Li et al., 2022). The general drag formulation in Eq. (64) reduces to

$$C_{d,3/4}^{\text{tot}} = C_d^{\text{profile}} + C_d^{\Delta\alpha} - C_{T,\text{NC}}^{\dot{\theta}^2} \cos \alpha_{3/4}. \quad (72)$$

The CFD results are compared with LL and BEM results obtained using the complete formulation. Three additional BEM
 575 calculations quantify the changes caused by omitting individual contributions from the complete formulation. The first omits the direction projection contribution $C_d^{\Delta\alpha}$. The second omits the torsional-rate-squared tangential force contribution $C_{T,\text{NC}}^{\dot{\theta}^2}$. The third omits both the non-circulatory normal force contribution associated with the mid-chord heaving acceleration, $C_{N,\text{NC}}^{\text{acc}}$, and its corresponding quarter-chord moment contribution in Eq. (25).

3.1.2 Results and discussion

580 Figure 3 compares the rotor thrust and power coefficients obtained using CFD, LL, and BEM over the investigated range of cone angles.




Figure 3. Rotor-integrated (a) thrust coefficient $C_{T,\text{rot}}$ and (b) power coefficient $C_{P,\text{rot}}$ as functions of cone angle for EllipSys3D CFD, MIRAS LL, and the HAWC2 BEM formulation. The LL and BEM calculations use fully turbulent airfoil polars.

The three aerodynamic methods predict similar overall trends, with closer agreement for thrust than for power. The thrust coefficient reaches a maximum at a slightly negative cone angle and then decreases as the cone angle increases. The LL and



BEM results remain similar, while CFD generally predicts higher thrust coefficients. The power coefficient also increases
 585 and then decreases as the cone angle increases from -30° to 30° . CFD predicts its maximum power at a cone angle of
 approximately 5° , whereas BEM and LL reach their maximum values at approximately 10° and 20° , respectively.

Figure 4 compares the complete BEM formulation with the three incomplete variants.




Figure 4. Effect of omitting individual contributions on the rotor-integrated (a) thrust coefficient $C_{T,rot}$ and (b) power coefficient $C_{P,rot}$. The omitted contributions are the direction projection term $C_d^{\Delta\alpha}$, the non-circulatory torsional-rate-squared tangential force $C_{T,NC}^{\hat{\theta}^2}$, and the mid-chord heaving acceleration force and its associated moment.

Omitting the direction projection contribution has little influence on thrust but changes the predicted power by approximately
 4% at $\kappa = \pm 10^\circ$, which is significant. This omission neglects the change in force direction associated with the chordwise
 590 variation in angle of attack while retaining the force magnitude determined from the three-quarter-chord aerodynamic state.
 The resulting difference primarily affects the tangential loading and rotor-integrated power, whereas its influence on the axial
 loading and rotor-integrated thrust is smaller, as analysed by Li et al. (2022).

The torsional-rate-squared tangential force has a negligible influence on both thrust and power for the present case. By con-
 trast, omitting the mid-chord heaving acceleration contribution primarily affects thrust. The thrust difference is approximately
 595 1.5% at $\kappa = \pm 10^\circ$ and increases to about 4.5% at $\kappa = \pm 30^\circ$, whereas the corresponding power difference remains below
 approximately 1.1%.

For the steady coned blade, the heaving acceleration and torsional-rate contributions to the non-circulatory normal force
 cancel. Omitting the heaving acceleration contribution leaves the torsional-rate contribution unbalanced, producing a spurious
 non-circulatory normal force and therefore a larger change in thrust. At zero cone angle, the effective torsional rate vanishes,
 600 so the complete formulation and all three incomplete variants give identical results.



3.2 Zero-onset VAWT: complete torque cancellation in the ideal thin-airfoil limit

3.2.1 Test configuration and objective

The configuration follows the zero-onset-flow vertical-axis wind turbine (VAWT) case considered by Pirrung and Gaunaa (2018) and Li et al. (2022). Each blade is represented by an ideal two-dimensional airfoil section moving on a circular path of
 605 radius R with constant angular velocity Ω and zero onset flow velocity.

Following Pirrung and Gaunaa (2018), the blade is mounted at the half-chord point. Let β denote the constant mounting angle between the airfoil chord and the local rotor-tangential direction, with the sign convention chosen consistently with the sectional angle of attack. Because the onset flow is zero, the relative flow at the half-chord mounting point is rotor-tangential and the section therefore experiences a constant angle of attack set by β . The relative flow observed in the blade-fixed frame is
 610 consequently steady.

Although the mounting angle is constant, the circular blade motion produces an effective torsional rate and a centripetal acceleration in the sectional thin-airfoil kinematics. The effective torsional rate introduced below is not the time derivative of the constant mounting angle β , but results from the rotation of the local relative-flow direction as the blade moves around the circular path.

615 Viscous profile drag and the steady airfoil pitching moment are neglected, while the non-circulatory pitching moment predicted by the thin-airfoil formulation is retained. The purpose of the test is to verify that, in the ideal small-angle thin-airfoil limit, the complete circulatory and non-circulatory contributions produce zero net aerodynamic rotor torque.

3.2.2 Complete torque balance

For the zero-onset circular motion, the magnitude of the relative flow at the half-chord mounting point is

$$620 \quad U = \Omega R. \quad (73)$$

Note that the component of the relative velocity along the chord is $\Omega R \cos \beta$.

The local relative-flow direction rotates with angular velocity Ω , giving the effective torsional rate

$$\dot{\theta} = -\Omega, \quad \ddot{\theta} = 0. \quad (74)$$

The mid-chord acceleration is centripetal. Its component normal to the chord is

$$625 \quad \ddot{e} = -\Omega^2 R \cos \beta \approx -\Omega^2 R. \quad (75)$$

The circulatory torque is zero when the circulatory force direction is treated consistently (Pirrung and Gaunaa, 2018):

$$Q_{\text{circ}} = 0. \quad (76)$$

It remains to establish the non-circulatory torque balance. The cancellation of the non-circulatory normal force contributions identified by Li et al. (2022) is first rederived using the notation of the present formulation. Substitution of Eqs. (73), (74), and



630 (75) into Eqs. (22) and (23), with $T_0 = b/U$, gives

$$C_{N,NC}^{\text{acc}} = \pi \frac{b}{R}, \quad (77)$$

$$C_{N,NC}^{\text{tor}} = -\pi \frac{b}{R}. \quad (78)$$

Hence,

$$C_{N,NC} = C_{N,NC}^{\text{acc}} + C_{N,NC}^{\text{tor}} = 0. \quad (79)$$

635 Since $\ddot{\theta} = 0$, substitution of Eqs. (77) and (78) into Eq. (25) gives

$$C_{m,NC} = -\frac{1}{4}C_{N,NC}^{\text{acc}} - \frac{1}{2}C_{N,NC}^{\text{tor}} = \frac{\pi b}{4R}. \quad (80)$$

Using $T_0 = b/U$ together with Eqs. (73) and (74), the torsional-rate-squared contribution in Eq. (24) becomes

$$C_{T,NC}^{\dot{\theta}^2} = \frac{1}{2}\pi \left(T_0 \dot{\theta}\right)^2 = \frac{1}{2}\pi \left(\frac{b}{R}\right)^2. \quad (81)$$

Using $c = 2b$ and the dynamic pressure defined in Eq. (17), the dimensional non-circulatory quarter-chord moment per unit
 640 span and tangential force per unit span are

$$M_{NC} = qc^2 C_{m,NC} = \frac{q\pi b^3}{R}, \quad (82)$$

$$T_{NC}^{\dot{\theta}^2} = qc C_{T,NC}^{\dot{\theta}^2} = \frac{q\pi b^3}{R^2}. \quad (83)$$

The tangential force acts along the airfoil chord, which is inclined by β relative to the rotor tangential direction.

With the present force sign convention, the corresponding non-circulatory rotor torque is

$$\begin{aligned} Q_{NC} &= M_{NC} + RT_{NC,rot}^{\dot{\theta}^2} \\ &= \frac{q\pi b^3}{R} - R \frac{q\pi b^3}{R^2} \cos \beta \\ 645 \quad &= \frac{q\pi b^3}{R} (1 - \cos \beta) \approx 0. \end{aligned} \quad (84)$$

The rotor torque generated by the non-circulatory torsional-rate-squared tangential force is therefore canceled by the non-circulatory pitching moment under the small-angle thin-airfoil formulation.

Combining the circulatory and non-circulatory contributions gives

$$Q_{\text{tot}} = Q_{\text{circ}} + Q_{NC} = 0. \quad (85)$$

650 This completes the zero-torque balance for all circulatory and non-circulatory contributions in the ideal small-angle thin-airfoil limit.

The cancellation also provides a sensitive implementation check: omitting or inconsistently treating contributions that balance one another can leave a spurious residual torque. One possible consequence is the non-physical prediction of positive aerodynamic power at zero onset flow reported by Pirrung and Gaunaa (2018).



655 4 Conclusions and future work

The present work revisits classical unsteady thin-airfoil theory and derives a consistent coefficient formulation for generalized lifting-line methods, including blade-element momentum (BEM), lifting-line (LL), and actuator-line (AL) methods. These methods combine an outer 3-D rotor and wake problem with an inner 2-D airfoil model at each blade section. The inner 2-D airfoil model can be viewed as an input–output machine. The outer 3-D flow solution and sectional kinematics provide the relative flow and kinematic histories required by the model, which maps them to the corresponding sectional force and moment. Starting from the dimensional sectional loads, the derivation traces the circulatory and non-circulatory contributions through conversion to coefficient form, coupling with the 2-D airfoil polar, and projection into the selected lift and drag directions.

The zero-lift-shifted three-quarter-chord onset downwash is used to update the shed wake states, which determine the wake-lagged effective angle of attack and therefore the circulatory force magnitude. The circulatory force direction and the corresponding decomposition into lift and drag are discussed in detail. This distinction clarifies the physical meaning of the different flow angles and their roles in the sectional force calculation. The formulation also clarifies how the classical attached flow contributions are combined with a 2-D airfoil polar without double counting. The airfoil polar supplies the circulatory lift, profile drag, and pitching moment, while the 2-D shed wake-induced drag, direction projection contribution, and non-circulatory force and moment contributions are added separately. The downwash-based deficit-state formulation avoids the separate velocity-rate term required by the angle-state formulation. Its wake-memory scaling allows the new contribution to the attached-flow lag to be progressively reduced in dynamic stall models as the flow separates, while the stored state continues to decay.

The coned straight blade calculations show that omitting individual contributions from the complete formulation affects rotor-integrated thrust and power differently. Building on previous work, the zero-onset VAWT analysis is extended to include all circulatory and non-circulatory thin-airfoil contributions and shows that their total torque contributions cancel exactly in the ideal thin-airfoil limit. Omitting individual contributions from the complete formulation can break this cancellation and may even lead to positive aerodynamic power production under zero-onset flow.

Future work should examine how the individual aerodynamic contributions described here should be treated when the attached flow formulation is embedded in a full dynamic stall model. In particular, as the flow becomes fully separated, the circulatory attached flow dynamics may be suppressed while non-circulatory force and moment contributions are retained. It should be assessed whether all of these contributions, particularly the torsional rate contribution, remain applicable at very large angles of attack or whether they should be modified or disabled. This question is relevant to wind turbines in stand-still conditions and may improve the modeling of stall-induced vibrations. Future work should also address a fully consistent treatment of turbulent inflow.

Code and data availability. A compact MATLAB reference implementation of the attached flow formulation, together with the HAWC2 comparison cases, reference HAWC2 results, and corresponding comparison scripts, is available (Li, 2026). The 2-D airfoil data used in this article were generated using fully turbulent 2-D RANS computations (Bortolotti et al., 2019).



Appendix A: Nomenclature

A1 Roman-letter variables used in the present work

Symbol	Description
a	dimensionless pitch-axis position relative to the mid-chord point, with the pitch axis at $\xi = ab$
A_i	amplitude of the i -th exponential term in the Wagner-function approximation
b, c	half-chord and chord lengths, with $b = c/2$
$C(k), k$	Theodorsen function and reduced frequency, with $k = \omega b/U$
C_N, C_T	sectional normal and tangential force coefficients
C_l, C_d, C_m	sectional lift, drag, and pitching-moment coefficients
$C_{T,rot}, C_{P,rot}$	rotor-integrated thrust and power coefficients
f_{scale}, f_{sep}	scaling factor for the new state increment and lagged dynamic separation-point position
$\mathbf{F}$	dimensional sectional aerodynamic force vector
$M, \mathbf{M}$	pitching moment per unit span; dimensional sectional aerodynamic moment vector
N, T, L	normal force, tangential force, and lift per unit span, respectively
q	dynamic pressure, $q = \rho U^2/2$
Q	aerodynamic torque per unit span about the rotor center
R, R_0, r_{hub}	circular-path radius for a VAWT; baseline rotor radius for a HAWT; hub radius
$\mathbf{r}$	position vector of the sectional load/moment reference point
s	non-dimensional convective time measured in half-chords
t	physical time
T_0	half-chord convection time, $T_0 = b/U$
T_{rot}, P_{rot}	rotor-integrated thrust and power
U, U_0, V	sectional relative streamwise velocity, onset wind speed, and constant streamwise flow velocity
w	onset downwash distribution normal to the airfoil chord
$w_{3/4}, w_E$	three-quarter-chord onset downwash and equivalent wake-lagged downwash
$\tilde{w}_{3/4}, \tilde{w}_E$	corresponding zero-lift-shifted downwash quantities
x, y	airfoil displacements parallel and normal to the undisturbed flow direction
x_i^w, r_i^w	direct downwash and downwash-deficit states
z_i	angle-of-attack state



A2 Greek-letter variables used in the present work

Symbol	Description
α_0	zero-lift angle of the 2-D airfoil polar
$\alpha_{1/4}, \alpha_{3/4}$	angles of attack at the quarter- and three-quarter-chord points
α_E	wake-lagged effective angle of attack
α_χ	angle of attack at aerodynamic calculation point χ
$\alpha_{\text{circ,dir}}$	force-direction angle corresponding to zero circulatory drag
α_r	angle of the reference direction used to define lift and drag
$\Delta\alpha_r$	signed angular difference between the onset-flow direction and the selected reference flow direction
β_i	decay coefficient of the i -th exponential term in the Wagner-function approximation
Γ	bound circulation
χ	chordwise location of the aerodynamic calculation point
Δs_n	increment in non-dimensional semi-chord time over time step n
Δt	time-step size
$\ddot{\epsilon}$	mid-chord heaving acceleration
κ	rotor cone angle
λ_0	baseline rotor tip-speed-ratio, $\lambda_0 = \Omega R_0 / U_0$
$\phi(s)$	Wagner indicial response function
ρ	air density
$\theta, \dot{\theta}, \ddot{\theta}$	pitching angle, effective torsional rate, and torsional acceleration
ξ	chordwise coordinate measured from the mid-chord point
ω	angular frequency of the harmonic motion; angular velocity of an airfoil section
$\dot{\omega}$	angular acceleration of an airfoil section
Ω	rotor rotational speed



690 A3 Subscripts used in the present work

Symbol	Description
$1/4, 3/4$	quarter- and three-quarter-chord points
$1/2$	mid-chord point
a	reference to the pitch axis at $\xi = ab$
χ	aerodynamic calculation point
E	equivalent wake-lagged quantity
circ	circulatory contribution
dec	decay coefficient
NC	non-circulatory contribution
ind	2-D shed wake-induced contribution
proj	projected rotor quantity
r	selected reference direction
rot	rotor-integrated quantity
i	state index
$n, n + 1$	discrete time step index

A4 Superscripts used in the present work

Symbol	Description
acc	contribution associated with mid-chord heaving acceleration
dyn	unsteady contribution evaluated at the effective angle of attack
full	full expression
S	quantity in the sectional coordinate systems
polar	quantity obtained directly from the 2-D airfoil polar
profile	profile contribution obtained from the 2-D airfoil polar
suction	leading edge suction contribution
thin	quantity obtained from classical thin-airfoil theory
tor	contribution associated with the effective torsional rate
tot	total contribution
$\dot{\theta}^2$	contribution proportional to the square of the effective torsional rate
$\Delta\alpha$	direction projection contribution



Appendix B: Indicial formulation: downwash and deficit states

This appendix explains the zero-lift offset applied to the downwash input and derives the time-discrete updates for the direct downwash-state formulation and the deficit-state formulation with wake-memory scaling. Following the indicial terminology of Hansen et al. (2004), each update consists of the decay of the previous state and a new increment. A direct downwash-based wake-lag formulation with the three-quarter-chord input referenced to the zero-lift angle is already present in the manuscript reproduced in Appendix E of Bæk (2011). The deficit-state formulation of Pirrung and Gaunaa (2018) uses the downwash as input and applies a scaling factor to the new contribution to the attached-flow lag. The present work applies this deficit-state treatment to the zero-lift-shifted downwash for a cambered airfoil, while the direct downwash-state formulation is included as an alternative attached-flow discretization for reference.

B1 Zero-lift offset in the downwash input

Pirrung and Gaunaa (2018) write the deficit-state update using the three-quarter-chord onset downwash

$$w_{3/4} = U\alpha_{3/4}. \quad (\text{B1})$$

The zero-lift offset associated with airfoil camber is not considered explicitly in that formulation. Following Bæk (2011); Pirrung et al. (2017), the input to the shed wake model is referenced to the zero-lift angle. In the present notation, this gives

$$\tilde{w}_{3/4} = U(\alpha_{3/4} - \alpha_0) = w_{3/4} - U\alpha_0. \quad (\text{B2})$$

The shed wake memory represents the delayed aerodynamic response associated with vorticity shed from the trailing edge as the bound circulation changes. For a cambered airfoil in the linear attached-flow range, the circulatory lift per unit span is

$$L_{\text{circ}} = \frac{1}{2}\rho U^2 c C_{l,\alpha} (\alpha_{3/4} - \alpha_0), \quad (\text{B3})$$

where $C_{l,\alpha}$ is the attached-flow lift-curve slope. Using the Kutta–Joukowski relation

$$L_{\text{circ}} = \rho U \Gamma, \quad (\text{B4})$$

the corresponding bound circulation is

$$\Gamma = \frac{1}{2} U c C_{l,\alpha} (\alpha_{3/4} - \alpha_0). \quad (\text{B5})$$

The bound circulation is therefore proportional to the zero-lift-shifted downwash,

$$\Gamma = \frac{1}{2} c C_{l,\alpha} \tilde{w}_{3/4}. \quad (\text{B6})$$

For the classical thin-airfoil lift-curve slope $C_{l,\alpha} = 2\pi$, this reduces to

$$\Gamma = \pi c \tilde{w}_{3/4}. \quad (\text{B7})$$



Thus, changes in $\tilde{w}_{3/4}$ correspond directly to changes in the bound circulation that generate the shed wake memory.

The zero-lift offset also ensures a consistent downwash input when U varies. Differentiating Eq. (B1) gives

$$\dot{w}_{3/4} = U\dot{\alpha}_{3/4} + \dot{U}\alpha_{3/4}. \quad (\text{B8})$$

Consider a case in which the three-quarter-chord angle of attack remains equal to the constant zero-lift angle α_0 while U varies. The corresponding conditions are

$$\alpha_{3/4} = \alpha_0, \quad (\text{B9a})$$

$$\dot{\alpha}_{3/4} = 0. \quad (\text{B9b})$$

Equation (B8) then gives

$$\dot{w}_{3/4} = \dot{U}\alpha_0. \quad (\text{B10})$$

The unshifted onset downwash would therefore produce a new contribution to the attached-flow lag when U varies, even though the attached circulatory lift and bound circulation are zero.

For constant α_0 , differentiation of Eq. (B2) gives

$$\dot{\tilde{w}}_{3/4} = U\dot{\alpha}_{3/4} + \dot{U}(\alpha_{3/4} - \alpha_0). \quad (\text{B11})$$

Under the zero-lift conditions in Eq. (B9), this gives

$$\dot{\tilde{w}}_{3/4} = 0, \quad (\text{B12})$$

independently of changes in U .

Because f_{scale} scales the generation of new deficit, the deficit-state update uses $\tilde{w}_{3/4}$, which is proportional to the bound circulation. The zero-lift-shifted downwash $\tilde{w}_{3/4}$ is used in the wake memory update, and the effective angle α_E is recovered before the airfoil polar is evaluated.

B2 Non-dimensional semi-chord time and decay coefficient

The non-dimensional semi-chord time s in Eq. (27) measures the distance travelled by the wake in half-chords. Differentiation with respect to physical time gives

$$\frac{ds}{dt} = \frac{2U(t)}{c} = \frac{1}{T_0(t)}. \quad (\text{B13})$$

Integrating Eq. (B13) from t_n to t_{n+1} gives the exact increment in non-dimensional time

$$\Delta s_n = s_{n+1} - s_n = \int_{t_n}^{t_{n+1}} \frac{dt}{T_0(t)} = \frac{2}{c} \int_{t_n}^{t_{n+1}} U(t) dt. \quad (\text{B14})$$



In the HAWC2 implementation, this increment is approximated using the relative velocity at the end of the time step (Pirring and Gaunaa, 2018):

$$745 \quad \Delta s_n = \frac{2U_{n+1}\Delta t_n}{c}. \quad (\text{B15})$$

The decay coefficient follows from the homogeneous deficit-state equation in non-dimensional time:

$$\frac{dr_i^w}{ds} + \beta_i r_i^w = 0. \quad (\text{B16})$$

Its exact solution over one time step is

$$r_{i,n+1}^w = C_{\text{dec},i,n} r_{i,n}^w, \quad (\text{B17a})$$

$$750 \quad C_{\text{dec},i,n} = \exp(-\beta_i \Delta s_n). \quad (\text{B17b})$$

For $\beta_i > 0$ and $\Delta s_n \geq 0$, the decay coefficient $C_{\text{dec},i,n}$ is the fraction of the stored state retained during the time step.

B3 Direct downwash-state update

Using $ds/dt = T_0^{-1}$, the direct state equation for the zero-lift-shifted downwash becomes

$$\frac{dx_i^w}{ds} + \beta_i x_i^w = \beta_i A_i \tilde{w}_{3/4}. \quad (\text{B18})$$

755 Here and below, $i = 1, \dots, n_w$. Multiplication by $e^{\beta_i s}$ and integration over one time step give the indicial update

$$x_{i,n+1}^w = C_{\text{dec},i,n} x_{i,n}^w + \beta_i A_i \int_{s_n}^{s_{n+1}} e^{-\beta_i(s_{n+1}-\sigma)} \tilde{w}_{3/4}(\sigma) d\sigma. \quad (\text{B19})$$

Following the terminology of Hansen et al. (2004), the first term is the decayed previous state and the integral term is the new increment. Assuming that $\tilde{w}_{3/4}$ is piecewise constant over the time step and evaluating it at the end of the step give

$$x_{i,n+1}^w = C_{\text{dec},i,n} x_{i,n}^w + A_i (1 - C_{\text{dec},i,n}) \tilde{w}_{3/4,n+1}. \quad (\text{B20})$$

760 The zero-lift-shifted equivalent wake-lagged downwash and the corresponding effective angle of attack are then

$$\tilde{w}_{E,n+1} = \left(1 - \sum_{i=1}^{n_w} A_i\right) \tilde{w}_{3/4,n+1} + \sum_{i=1}^{n_w} x_{i,n+1}^w, \quad (\text{B21})$$

$$\alpha_{E,n+1} = \alpha_0 + \frac{\tilde{w}_{E,n+1}}{U_{n+1}}. \quad (\text{B22})$$

B4 Deficit-state update with wake-memory scaling

The deficit-state formulation introduced in Sect. 2.3 describes the attached-flow wake-memory dynamics according to Eq. (39).

765 For the zero-lift-shifted downwash, the deficit state is defined as

$$r_i^w = A_i \tilde{w}_{3/4} - x_i^w. \quad (\text{B23})$$



Using $ds/dt = T_0^{-1}$, Eq. (39) can be written in non-dimensional time as

$$\frac{dr_i^w}{ds} + \beta_i r_i^w = A_i \frac{d\tilde{w}_{3/4}}{ds}. \quad (\text{B24})$$

When this formulation is embedded in the full dynamic stall model, the separation state scales the generation of new attached-
 770 flow wake memory as the flow separates (Pirring and Gaunaa, 2018). Specifically, the scaling function f_{scale} multiplies the
 new contribution to the attached-flow lag:

$$\dot{r}_i^w + \frac{\beta_i}{T_0} r_i^w = A_i f_{\text{scale}} \dot{\tilde{w}}_{3/4}. \quad (\text{B25})$$

The term $\beta_i r_i^w / T_0$ describes the decay of the stored state, whereas $A_i f_{\text{scale}} \dot{\tilde{w}}_{3/4}$ describes the scaled generation of new
 attached-flow wake memory.

775 In the discrete HAWC2 dynamic stall coupling, the scaling factor used to calculate the aerodynamic states at time t is
 evaluated using the converged dynamic separation-point position from the previous time step:

$$f_{\text{scale}}(t) = f_{\text{sep}}(t - \Delta t). \quad (\text{B26})$$

Here, $f_{\text{sep}} = 1$ represents fully attached flow, whereas $f_{\text{sep}} = 0$ represents fully separated flow.

For fully attached flow, $f_{\text{scale}} = 1$, and Eq. (B25) reduces to the attached-flow deficit-state equation, Eq. (39). As separation
 780 develops and f_{scale} decreases, the generation of new wake memory is progressively reduced, while the stored state continues
 to decay with its original time scale. For fully separated flow, $f_{\text{scale}} = 0$, so no new wake-memory contribution is generated.

Using $ds/dt = T_0^{-1}$, Eq. (B25) becomes

$$\frac{dr_i^w}{ds} + \beta_i r_i^w = A_i f_{\text{scale}} \frac{d\tilde{w}_{3/4}}{ds}. \quad (\text{B27})$$

Assuming that $\tilde{w}_{3/4}$ varies linearly in non-dimensional time over the step and that $f_{\text{scale},n}$ remains constant, integration of
 785 Eq. (B27) gives the indicial update

$$r_{i,n+1}^w = C_{\text{dec},i,n} r_{i,n}^w + f_{\text{scale},n} \frac{A_i}{\beta_i} \frac{1 - C_{\text{dec},i,n}}{\Delta s_n} (\tilde{w}_{3/4,n+1} - \tilde{w}_{3/4,n}). \quad (\text{B28})$$

The first term is the decayed previous state, and the second term is the scaled new increment.

Using the end-of-step approximation for the non-dimensional time increment in Eq. (B15), the update becomes

$$r_{i,n+1}^w = C_{\text{dec},i,n} r_{i,n}^w + f_{\text{scale},n} \frac{A_i}{\beta_i} \frac{T_{0,n+1}}{\Delta t_n} (1 - C_{\text{dec},i,n}) (\tilde{w}_{3/4,n+1} - \tilde{w}_{3/4,n}). \quad (\text{B29})$$

790 The zero-lift-shifted equivalent wake-lagged downwash and the corresponding effective angle of attack are then

$$\tilde{w}_{E,n+1} = \tilde{w}_{3/4,n+1} - \sum_{i=1}^{n_w} r_{i,n+1}^w, \quad (\text{B30})$$

$$\alpha_{E,n+1} = \alpha_0 + \frac{\tilde{w}_{E,n+1}}{U_{n+1}} = \alpha_{3/4,n+1} - \frac{1}{U_{n+1}} \sum_{i=1}^{n_w} r_{i,n+1}^w. \quad (\text{B31})$$

The zero-lift offset therefore modifies the downwash input used to advance the wake-lag states, while α_E remains the effective
 angle supplied to the airfoil polar.



795 *Author contributions.* This work builds on previous research by MG, GRP, and AL on the incompressible Beddoes–Leishman type dynamic
stall model and its implementation in HAWC2. The complete attached flow formulation was described by AL, with contributions from
MG and GRP. The interpretation of classical unsteady thin-airfoil theory and its coupling with airfoil polars for wind turbine applications
were primarily developed by MG, with contributions from GRP and AL. The deficit-state formulation and its HAWC2 implementation were
primarily developed by GRP and MG, with contributions from AL. The zero-onset VAWT case was derived by AL, with contributions from
800 MG and GRP. AL performed the numerical studies using CFD, lifting-line, and BEM models. AL post-processed and discussed the numerical
results, with contributions from MG and GRP. All authors contributed to the conclusions. Future work directions were primarily proposed
by GRP, with contributions from MG and AL. AL wrote the original draft. All authors contributed to reviewing and revising the manuscript
and approved the final manuscript.

Competing interests. DTU Wind and Energy Systems develops and distributes the Navier–Stokes solver EllipSys3D on commercial and
805 academic terms. DTU Wind and Energy Systems also develops, supports and distributes HAWC2 on commercial terms, and HAWC2 is
available free of charge for educational and academic research purposes.

Acknowledgements. The authors gratefully acknowledge David Marten of QBlade.org Consulting for valuable discussions on this topic. The
authors would like to thank Frederik Zahle of DTU Wind and Energy Systems for his contributions to establishing the fully scripted mesh
generation and post-processing workflows for the Navier–Stokes simulations in EllipSys3D. Computational and data resources were provided
810 by the Sophia HPC Cluster at DTU (Technical University of Denmark, 2019). Earlier versions of this paper were revised iteratively with the
assistance of AI tools, including OpenAI’s ChatGPT (GPT-5.5 and GPT-5.6). These tools were used by the authors to generate suggestions
for improving language and wording based on author-prepared drafts that were developed and updated throughout the preparation of the
paper. The paper underwent multiple rounds of revision by the authors, with AI-generated suggestions being selectively incorporated and
extensively modified.



815 References

- Bæk, P.: Unsteady Flow Modeling and Experimental Verification of Active Flow Control Concepts for Wind Turbine Blades, Ph.D. thesis, Technical University of Denmark, Department of Wind Energy, Roskilde, Denmark, 2011.
- Bergami, L. and Gaunaa, M.: ATEFlap Aerodynamic Model, a dynamic stall model including the effects of trailing edge flap deflection, Tech. Rep. Risø-R-1792(EN), Risø DTU, National Laboratory for Sustainable Energy, Roskilde, Denmark, ISBN 978-87-550-3934-6,
 820 2012.
- Bergami, L., Gaunaa, M., and Heinz, J. C.: Indicial lift response function: an empirical relation for finite-thickness airfoils, and effects on aeroelastic simulations, *Wind Energy*, 16, 681–693, <https://doi.org/10.1002/we.1516>, 2013.
- Bergami, L., Riziotis, V. A., and Gaunaa, M.: Aerodynamic response of an airfoil section undergoing pitch motion and trailing edge flap deflection: a comparison of simulation methods, *Wind Energy*, 18, 1273–1290, <https://doi.org/10.1002/we.1759>, 2015.
- 825 Bortolotti, P., Tarrés, H. C., Dykes, K., Merz, K., Sethuraman, L., Verelst, D., and Zahle, F.: IEA Wind TCP Task 37: Systems Engineering in Wind Energy – WP2.1 Reference Wind Turbines, Tech. Rep. NREL/TP-5000-73492, National Renewable Energy Laboratory (NREL), Golden, CO, USA, <https://doi.org/10.2172/1529216>, 2019.
- Branlard, E. and Jonkman, J.: Development Plan for the Aerodynamic Linearization in OpenFAST, https://github.com/OpenFAST/openfast/blob/main/docs/OtherSupporting/AeroDyn/AeroLin_2019-12.pdf, OpenFAST development document, 2019.
- 830 Branlard, E., Jonkman, B., Pirrung, G. R., Dixon, K., and Jonkman, J.: Dynamic inflow and unsteady aerodynamics models for modal and stability analyses in OpenFAST, *Journal of Physics: Conference Series*, 2265, 032 044, <https://doi.org/10.1088/1742-6596/2265/3/032044>, 2022.
- Buhl, T., Gaunaa, M., and Bak, C.: Potential load reduction using airfoils with variable trailing edge geometry, *Journal of Solar Energy Engineering*, 127, 503–516, <https://doi.org/10.1115/1.2037094>, 2005.
- 835 DNV: Bladed Theory Manual, DNV Services UK, 4.18 edn., 2025.
- Garrick, I. E.: Propulsion of a flapping and oscillating airfoil, Tech. Rep. NACA-TR-567, National Advisory Committee for Aeronautics, 1936.
- Gaunaa, M.: Unsteady two-dimensional potential-flow model for thin variable geometry airfoils, *Wind Energy*, 13, 167–192, <https://doi.org/10.1002/we.377>, 2010.
- 840 Gaunaa, M., Li, A., and Pirrung, G. R.: From thin airfoil theory to finite wings: consistent implementation of lifting-line-based models, *Journal of Physics: Conference Series*, 3224, 042 030, <https://doi.org/10.1088/1742-6596/3224/4/042030>, 2026.
- Greenberg, J. M.: Airfoil in Sinusoidal Motion in a Pulsating Stream, Tech. Rep. NACA-TN-1326, National Advisory Committee for Aeronautics, 1947.
- Hansen, M. H., Gaunaa, M., and Madsen, H. A.: A Beddoes-Leishman type dynamic stall model in state-space and indicial formulations,
 845 Tech. Rep. Risø-R-1354(EN), Risø National Laboratory, Roskilde, Denmark, ISBN 87-550-3090-4, 2004.
- Jones, R. T.: Operational treatment of the nonuniform-lift theory in airplane dynamics, Tech. Rep. NACA-TN-667, National Advisory Committee for Aeronautics, 1938.
- Jones, R. T.: The Unsteady Lift of a Wing of Finite Aspect Ratio, Tech. Rep. NACA-TR-681, National Advisory Committee for Aeronautics, 1940.
- 850 Larsen, T. J. and Hansen, A. M.: How 2 HAWC2, the user’s manual, Tech. Rep. Risø-R-1597(ver. 3-1)(EN), Risø National Laboratory, Roskilde, Denmark, ISBN 978-87-550-3583-6, 2007.



- Leishman, J. G. and Beddoes, T. S.: A generalised model for airfoil unsteady aerodynamic behaviour and dynamic stall using the indicial method, in: Proceedings of the 42nd Annual Forum of the American Helicopter Society, pp. 243–265, Washington, DC, USA, 1986.
- Leishman, J. G. and Beddoes, T. S.: A semi-empirical model for dynamic stall, *Journal of the American Helicopter Society*, 34, 3–17,
 855 <https://doi.org/10.4050/JAHS.34.3>, 1989.
- Li, A.: Code and HAWC2 comparison cases accompanying “Unsteady airfoil aerodynamics in attached flow: From unsteady thin-airfoil theory to wind turbine implementation”, <https://doi.org/10.5281/zenodo.22793702>, 2026.
- Li, A., Gaunaa, M., Pirrung, G. R., Meyer Forsting, A., and Horcas, S. G.: How should the lift and drag forces be calculated from 2-D airfoil data for dihedral or coned wind turbine blades?, *Wind Energy Science*, 7, 1341–1365, <https://doi.org/10.5194/wes-7-1341-2022>, 2022.
- 860 Li, A., Gaunaa, M., Pirrung, G. R., and Lønbæk, K.: Disentangling wake and projection effects in the aerodynamics of wind turbines with curved blades, *Wind Energy Science*, 10, 2299–2349, <https://doi.org/10.5194/wes-10-2299-2025>, 2025.
- Madsen, H. A., Larsen, T. J., Pirrung, G. R., Li, A., and Zahle, F.: Implementation of the blade element momentum model on a polar grid and its aeroelastic load impact, *Wind Energy Science*, 5, 1–27, <https://doi.org/10.5194/wes-5-1-2020>, 2020.
- Marten, D.: QBlade: a modern tool for the aeroelastic simulation of wind turbines, Ph.D. thesis, Technische Universität Berlin, Berlin,
 865 Germany, <https://doi.org/10.14279/depositon-10646>, 2020.
- Menter, F. R.: Two-equation eddy-viscosity turbulence models for engineering applications, *AIAA Journal*, 32, 1598–1605, <https://doi.org/10.2514/3.12149>, 1994.
- Michelsen, J. A.: Basis3D – a platform for development of multiblock PDE solvers, Tech. Rep. AFM 92-05, Technical University of Denmark, Department of Fluid Mechanics, Lyngby, Denmark, 1992.
- 870 Michelsen, J. A.: Block structured multigrid solution of 2D and 3D elliptic PDEs, Tech. Rep. AFM 94-06, Technical University of Denmark, Department of Fluid Mechanics, Lyngby, Denmark, 1994.
- Øye, S.: Stationary aerodynamic forces on a two-dimensional wing profile, Tech. Rep. AFM notat 81-05, Afdeling for Fluid Mekanik, Danmarks Tekniske Højskole, Lyngby, Denmark, 1981.
- Pirrung, G., Riziotis, V., Madsen, H. A., Hansen, M., and Kim, T.: Comparison of a coupled near and far wake model with a free wake vortex
 875 code, *Wind Energy Science*, 2, 15–33, <https://doi.org/10.5194/wes-2-15-2017>, 2017.
- Pirrung, G. R. and Gaunaa, M.: Dynamic stall model modifications to improve the modeling of vertical axis wind turbines, Tech. Rep. DTU Wind Energy E-0171, DTU Wind Energy, Roskilde, Denmark, ISBN 978-87-93549-39-5, 2018.
- Ramos-García, N., Sørensen, J. N., and Shen, W. Z.: Three-dimensional viscous-inviscid coupling method for wind turbine computations, *Wind Energy*, 19, 67–93, <https://doi.org/10.1002/we.1821>, 2016.
- 880 Sørensen, N. N.: General purpose flow solver applied to flow over hills, Tech. Rep. Risø-R-827(EN), Risø National Laboratory, Roskilde, Denmark, 1995.
- Stäblein, A. R., Hansen, M. H., and Pirrung, G.: Fundamental aeroelastic properties of a bend–twist coupled blade section, *Journal of Fluids and Structures*, 68, 72–89, <https://doi.org/10.1016/j.jfluidstructs.2016.10.010>, 2017.
- Technical University of Denmark: Sophia HPC Cluster, <https://doi.org/10.57940/afac-6m81>, 2019.
- 885 Theodorsen, T.: General theory of aerodynamic instability and the mechanism of flutter, Tech. Rep. NACA-TR-496, National Advisory Committee for Aeronautics, 1935.
- Verdonck, H. and Hach, O.: Edgewise instabilities of a wind turbine blade section in attached flow conditions, *Wind Energy Science Discussions*, <https://doi.org/10.5194/wes-2026-9>, preprint, in review, 2026.